



POE Switch

ASK-816GP1G1SFP



Overview

Our 16-port PoE switch delivers full PoE+ support across all 16 ports with a 260W total power budget, ensuring stable power for demanding devices. Designed for enterprise-grade connectivity, it features dual RJ45 and SFP uplinks that provide both flexible expansion and redundancy—making it ideal for critical security and surveillance applications.

Key Features

- 16 PoE+ Ports
- 260W Total Power Budget
- 1 RJ45 Uplink Ports
- 1 SFP Uplink Ports
- Durable Metal Housing
- Rack-Mountable Design
- 5-Year Warranty Included



Power Supply

Power Supply Mode	Mains on load
Voltage Range	AC 100~240V
Power Consumption	The device <15W, POE power supply <260W

Network Port Parameter

Network Port Parameter	1~16 Ports: 10/100Mbps Ethernet port, adaptive control
Uplink	1 SFP: 1.25Gbps and 10/100/1000Mbps RJ45
Transmission Distance	1~16 Ethernet Port: 0~100m 1 Ethernet Uplink Port: 0~100m 1 SFP: According to Fiber Optic Parameters
Transmission Media	1~16 Ethernet Port Cat5e/6 standard UTP cable, 1 SFP: LC interface
PoE Agreement / Standard	IEEE 802.3af Power over Ethernet, IEEE 802.3at Power over Ethernet Plus
PoE Power Supply Mode	End-span method
PoE Power Supply Wattage	Each port≤30W, Whole device<260W , Supports up to 16 PoE devices or 8 PoE+ devices = Total 260W.

Network Switch Specification

Network Standard	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab Gigabit 1000BASE-T, IEEE 802.3z Gigabit SX/LX IEEE 802.3x flow control and back pressure
Swap Mode	Store-and-forward
Switch Capacity	40Gbps

Status Indicators

Power Indicator Light	One power light (green)
Optical Fiber Port Indicator	One fiber link indication light (green), Green light keeps on when the fiber port is well connected; Blinking when transceiver data
PoE Indicator	1~16 POE indicator light
PoE Network Port LED	1~16 port (green light on RJ45 jack) Keeps on when normally connected, Blinking when transceiver data

Protection Level

Surge Immunity	Level 3, executive standard: IEC61000-4-5
Electrostatic Protection	1a touch electric discharge: level 3, 1a Air discharge: level 3, Executive standard IEC61000-4-2

Operating Environment

Working Temperature	-10 °C~55 °C
Storage Temperature	-40 °C~85 °C
Humidity (non-congeal)	5~95%

Mechanical Attributes

Dimensions (L×W×H)	330 x 205 x 44.5mm
Color	Black
Weight	3kg

Protection Level

Mean Time Between Failures (MTBF)	<50,000h
-----------------------------------	----------