



POE Switch

ASK-824GP1G1SFP



Overview

This 24-port PoE switch delivers full PoE+ support on all ports with a robust 320W total power budget, ensuring reliable and consistent power across connected devices. Designed specifically for large-scale surveillance deployments, it provides seamless integration into enterprise networks. The rack-mountable form factor offers easy installation and efficient space utilization, making it an ideal choice for mission-critical security environments.

Key Features

- 24 PoE+ Ports
- 320W Total Power Budget
- 1 RJ45 Uplink Port
- 1 SFP Uplink Port
- Durable Metal Housing
- Rack-Mountable Design
- 5-Year Warranty Included



SPECIFICATIONS | ASK-824GP1G1SFP

Power Supply

Power Supply Mode	Mains on load
Voltage Range	AC 100~240V
Power Consumption	The device <15W, POE power supply <320W

Network Port Parameter

Network Port Parameter	1~24 Ports: 10/100/1000Mbps Ethernet port, adaptive control
Uplink	1 SFP: 1.25Gbps and 10/100/1000Mbps RJ45
Transmission Distance	1~24 Ethernet Port: 0~100m, 1 Ethernet Uplink Port 0~100m, 2 SFP: According to Fiber Optic Parameters
Transmission Media	1~24 Ethernet Port: Cat5e/6 standard UTP cable, 1 SFP: LC interface
PoE Agreement / Standard	IEEE 802.3af Power over Ethernet, IEEE 802.3at Power over Ethernet Plus
PoE Power Supply Mode	End-span method
PoE Power Supply Wattage	Each port ≤ 30W, whole device <320W. Supports up to 24 PoE devices or 10 PoE+ devices = Total 320W.

Network Switch Specification

Network Standard	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab Gigabit 1000BASE-T IEEE 802.3z Gigabit SX/LX, IEEE 802.3x flow control and back pressure
Swap Mode	Store-and-forward
Switch Capacity	56Gbps

Status Indicators

Power Indicator Light	One power light (green)
Optical Fiber Port Indicator	One fiber link indication light (green), Green light keeps on when the fiber port is well connected; Blinking when transceiver data
Uplink Port	LED (Green): On, port is link on; Off, port is link down:
PoE Indicator	1~24 POE indicator light
PoE Network Port LED	1~24 port (green light on RJ45 jack) Keeps on when normally connected, Blinking when transceiver data

Protection Level

Surge Immunity	Level 3, executive standard: IEC61000-4-5
Electrostatic Protection	1a touch electric discharge: level 3 1a Air discharge: level 3 Executive standard IEC61000-4-2

Operating Environment

Working Temperature	-10 ° C~55 ° C
Storage Temperature	-40 ° C~85 ° C
Humidity (non-congeal)	5~95%

Mechanical Attributes

Dimensions (L×W×H)	442mm×224mm×44.5mm
Color	Black
Weight	4.5kg

Protection Level

Mean Time Between Failures (MTBF)	<50000h
-----------------------------------	---------



AEROSKOP W.L.L

info@aeroskop.com

www.aeroskop.com

MIDDLE EAST & AFRICA

Umm Al Hassam, Bahrain

+973 77992203

EUROPE

ul. Hoża 86 lok. 410, 00-682 Warszawa

+48 732 082 387

*Product specifications and availability are subject to change without notice.