

AEROSKOP–RHINO

Storage Server

Surveillance–Grade Storage with the Strength of a Rhino
Built for Surveillance. Powered by Linux Secured by Design



Overview

The Aeroskop Rhino Storage Server redefines reliability and performance in surveillance storage infrastructure. Strong and resilient as its namesake, Rhino is built to endure the harshest conditions, protect your critical data, and operate around the clock without compromise. Designed specifically for demanding video surveillance applications, Rhino combines High-grade hardware design with an intelligent dual-platform architecture, providing robust performance, high fault tolerance and unmatched data security.



Hybrid OS – Windows + Linux Integration.

- Native support for both Windows and Linux environments in a single server.
- Isolated layers for enhanced performance, system stability, and data protection.



Software–Defined Storage with OpenZFS and RAID–Z .

- No reliance on hardware RAID–cards , removes single points of failure.
- RAID–Z1 / Z2 / Z3 configurations provide 1, 2, or 3 disk failure protection.



Key Advantages:

- Self–Healing Architecture: Automatically detects and repairs corrupted data.
- Bitrot Protection: Prevents data corruption with end–to–end checksumming.
- Data Integrity by Design: Every read/write operation is verified.



Why Choose Aeroskop Rhino?

- Robust and ready for continuous operation.
- Dual–platform architecture for flexibility.
- Fault Tolerance: Bitrot protection, self–healing, and RAID ensure high reliability.
- Hot–swappable enterprise–grade drives.
- Redundant power supply and cooling.
- Supports high bit–rate multi–camera streams upto 250–350 Cameras.
- Optimized for real–time video preview and playback



CPU

1 OR 2 X INTEL XEON SILVER 4410Y 12 CORE (24 C TOTAL) , 2.0 GHZ, 30 MB L3 CACHE

MEMORY

64 GB DDR5 ECC RAM , MAXIMUM 4 TB

CHASIS

2U 19" RACK MOUNT WITH 12 X 3.5" HDD BAY SATA/SAS , 650MM (D) X 437.5MM (W)X 88 MM (H)

INTERNAL STORAGE

HDD: SATA / SAS

240 TERABYTE RAW CAPACITY , CAN BE TAILORED TO PROJECT NEEDS

HDD CATEGORY : ENTERPRISE OR SURVEILLANCE

MAXIMUM NO HDD = 12 HOT SWAPABLE

SSD: 2X 1000 GB SATA III SSD (FOR OS AND VMS) ZFS MIRROR

HDD REDUNDANCE

Linux OpenZFS software-defined storage with RAID-Z architecture, offering functional equivalents to hardware RAID

Hardware RAID CARD option Available

PSU

DUAL HOT- PLUG REDUNDANT POWER SUPPLY (1+1) 800 WATTS EACH

NETWORKING

2 X 10 GBASE-T PORT (ONBOARD BACK PANEL)

1X1 Gbps RJ45, 1RJ45 IPMI LAN PORT FOR MANAGEMENT

BACK PANNEL I/O PORTS

2 x USB 3.0 ports, 1 x VGA port ,1 UID button w/ LED

ON BOARD EXPANSION SLOTS

5 X PCIe 5.0 ,16 X slots & 1 X PCIe 5.0 ,8 X slot

1 M-key (PCIe5.0 x4); support 22110/2280 form factor

2 MCIO (PCIe5.0 x8)

3 OCuLink (PCIe3.0 x4 or 4 SATA 6Gb/s) [PCH]

REMOTE MANAGEMENT

IPMI (Intelligent Platform Management Interface)

WARRANTY

COMPREHENSIVE WARRANTY COVERAGE FOR ALL HARDWARE COMPONENTS

5-YEAR COMPREHENSIVE WARRANTY ON POWER SUPPLY

5-YEAR WARRANTY ON HARD DISK

ALL HARDWARE: "KEEP YOUR HARDWARE WARRANTY"



AEROSKOP W.L.L

✉ info@aeroskop.com

🌐 www.aeroskop.com

MIDDLE EAST & AFRICA

📍 Umm Al Hassam, Bahrain

☎ +973 77992203

EUROPE

📍 ul. Hoża 86 lok. 410, 00-682 Warszawa

☎ +48 732 082 387

*Product specifications and availability are subject to change without notice.