



Programming in Prolog

Part - 2



Loops

- Prolog does not support loops, so 'for', 'while', 'do-while' does not work in Prolog
- Still we can achieve same via *recursion*
- For example:

loop(0).

loop(N) :- N > 0, write(N), nl, S is N-1, loop(S).

- The above logic will simulate 'for' loop logic

Loops (contd..)

- Another way to achieve looping is via '**repeat**' built-in predicate
- For example:

correct_num(5).

correct_num(10).

predict_num(Input) :- write("Game: Guess a number"), nl, repeat, write("Your input?"), nl,

read(Input), correct_num(Input), write("Correct!!!"), nl.

Lists

- In Prolog, list is a common data-structure
- Example list:

[apples, bananas, oranges, pears, mangos].

- With the help of “ | ” (bar) operator, Prolog splits any given list into two parts
 - Head: First element of the list (CAR: Contents of the Address part of the Register)
 - Tail: All remaining elements of list (CDR: Contents of the Decrement part of the Register; not the second element or last element)
- For example:

[apples, bananas, oranges, pears, mangos] = [H | T]

H = apples.

T = [bananas, oranges, pears, mangos].

Lists (contd..)

- Prolog has built-in predicate *'length/2'* which will calculate the length of a list
- Example:

length([a, b, c], L). # L = 3

- The following code will simulate *'length/2'* built-in predicate

size([], 0). # size of empty list is 0

size([_ | T], N) :- size(T, N1), N is N1+1. # increment N till Tail becomes

NULL

Lists (contd)..

- Membership: Checking whether a given element is member of a list or not
- Logic:

is_member(X, [X|_]).

is_member(X, [_ | T]) :- is_member(X, T).

- 'X' is a member of given list,
 - If X is head of the list
 - Or, Iterate through list till X becomes the head of the list
- If 'X' present then query will evaluated True otherwise False

Lists (contd)..

- Union: Combining two lists to make a new third list
- Logic:

list_append([], L, L).

list_append([H | T], L2, [H | R]) :- list_append(T, L2, R).

- First copy second list as Tail to new list
- One by one, add elements of first list to Head of new list in reverse order
- Prolog has 'append/3' built-in predicate which will do the same

Lists (contd..)

- Reversing a list
- Logic:

reverse_it([], []).

reverse_it([H | T], L) :- reverse_it(T, L2), list_append(L2, [H], L).

- 'append/3' will add elements of second list to Tail of new list
- To reverse a list, add each element of first list to second list one at a time, and then append the two lists to new list

Exercise

- Write a Prolog program to remove duplicates from a given list
- Write a Prolog program to perform intersection between two lists

Further Reading

- Controlling backtracking through '**cut (!)**' operator
- Negation As Failure (NAF)
- Usage of Accumulators

References

- <https://discretemathisfun.wordpress.com/2009/12/07/looping-using-prolog/>
- <https://stackoverflow.com/questions/29857372/how-to-go-back-to-repeat-in-prolog>
- <https://www.javatpoint.com/looping-until-a-condition-is-satisfied>
- https://www.doc.gold.ac.uk/~mas02gw/prolog_tutorial/prologpages/lists.html
- <https://en.wikibooks.org/wiki/Prolog/Lists>
- <https://www.cs.toronto.edu/~hojjat/384w10/PrologTutorial2.pdf>