

一、判断下列语句或程序段的对错。（“×”表示错，“√”表示对）（10分）

- |   |            |
|---|------------|
| (1) int x=0,y=x;                            | (        ) |
| (2) #define SIZE 10<br>int a[SIZE/2][SIZE]; | (        ) |
| (3) char *str;<br>str="c\test";             | (        ) |
| (4) register int n;<br>scanf("%d",&n);      | (        ) |
| (5) int x, *px=&x;<br>float *p=px;          | (        ) |
| (6) int (*pa)[8],a[6][8];<br>pa=*a++;       | (        ) |
| (7) int x, *px;<br>*px=&x;                  | (        ) |
| (8) int **pp,a[6][8];<br>pp=a;              | (        ) |
| (9) float xyz.1=3;                          | (        ) |
| (10) int x='\x78';                          | (        ) |

一、判断下列语句或程序的对错。（“×”表示错，“√”表示对）（10分）

- |  |            |
|--|------------|
| 1 float x15=.234e+12;                              | (        ) |
| 2 #define N = 50;<br>int a[N]                      | (        ) |
| 3 char str[]=" hust cse!"<br>printf( "%s" ,str+5); | (        ) |
| 4 int x,*p=x;                                      | (        ) |
| 5 char str[4]=" HUST" ;                            | (        ) |
| 6 float data[]={0,1,2,3,4};                        | (        ) |
| 7 int x = '\a7' ;                                  | (        ) |
| 8 int xyz_1=2;                                     | (        ) |
| 9 int x = (018 == 'A' ) ;                          | (        ) |
| 10 int(*p)[20],a[2][20];<br>p=a+1;                 | (        ) |

一、判断下列语句或程序段的对错。（“×”表示错，“√”表示对）（10 分）

- |  |     |
|--|-----|
| (1) char ch='55';                                      | ( ) |
| (2) unsinged int a=b=c=5;                              | ( ) |
| (3) int a=2,*p; p=&a;<br>printf("%d", *&a);            | ( ) |
| (4) int a[5][5], (*p)[5];<br>p=&a[0][0];               | ( ) |
| (5) char a='a',c;<br>c=a++;                            | ( ) |
| (6) int n; scanf("%d",&n);<br>int a[n];                | ( ) |
| (7) int a[10],*p;<br>p=a+2;                            | ( ) |
| (8) int a,b;<br>scanf("%d,%f",a,b);                    | ( ) |
| (9) float a=1,*b=&a,*c=&b;                             | ( ) |
| (10) char str[]={ "World" };<br>printf("%c",*(str+2)); | ( ) |

二、判断下列语句或程序的对错。（“x”表示错，“√”表示对）（10 分）

- |                                     |     |
|-------------------------------------|-----|
| 11 float x= '1' ;                   | ( ) |
| 12 #define N 50;<br>int a[N]        | ( ) |
| 13 printf( "%f\n" , (40, 50, 60));  | ( ) |
| 14 int x[100];<br>float *p;<br>p=x; | ( ) |
| 15 char str[20] ;<br>str=" HUST" ;  | ( ) |
| 16 int data[4]={0, 1, 2, 3, 4} ;    | ( ) |
| 17 int x = '\x56' ;                 | ( ) |
| 18 int xyz_1=2;                     | ( ) |
| 19 int x = (013 == 'A' ) ;          | ( ) |
| 10 float *p, a[2][3];<br>p=*a++;    | ( ) |

