Thus A'^2/A^2 would be the ratio of the "measured in motion" to the "measured at rest" energy of a given light complex, if the volume of a light complex were the same, whether measured in K or in k. But this is not the case. If l, m, n are the direction-cosines of the wave-normals of the light in the stationary system, no energy passes through the surface elements of a spherical surface moving with the velocity of light:—

$$(x - lct)^2 + (y - mct)^2 + (z - nct)^2 = R^2.$$

We may therefore say that this surface permanently encloses the same light complex. We inquire as to the quantity of energy enclosed by this surface, viewed in system k, that is, as to the energy of the light complex relatively to the system k.

The spherical surface—viewed in the moving system—is an ellipsoidal surface, the equation for which, at the time $\tau = 0$, is

$$(\beta \xi - l\beta \xi v/c)^2 + (\eta - m\beta \xi v/c)^2 + (\zeta - n\beta \xi v/c)^2 = R^2$$

If S is the volume of the sphere, and S' that of this ellipsoid, then by a simple calculation

$$\frac{S'}{S} = \frac{\sqrt{1 - v^2/c^2}}{1 - \cos\phi \cdot v/c}.$$

Thus, if we call the light energy enclosed by this surface E when it is measured in the stationary system, and E' when measured in the moving system, we obtain

$$\frac{E'}{E} = \frac{{A'}^2 S'}{A^2 S} = \frac{1 - \cos \phi \cdot v/c}{\sqrt{1 - v^2/c^2}},$$

and this formula, when $\phi = 0$, simplifies into

$$\frac{\mathrm{E'}}{\mathrm{E}} = \sqrt{\frac{1 - v/c}{1 + v/c}}.$$

It is remarkable that the energy and the frequency of a light complex vary with the state of motion of the observer in accordance with the same law.

Now let the co-ordinate plane $\xi=0$ be a perfectly reflecting surface, at which the plane waves considered in § 7 are reflected. We seek for the pressure of light exerted on the reflecting surface, and for the direction, frequency, and intensity of the light after reflexion.

Let the incidental light be defined by the quantities A, $\cos \phi$, ν (referred to system K). Viewed from k the corresponding quantities are

$$A' = A \frac{1 - \cos \phi \cdot v/c}{\sqrt{1 - v^2/c^2}},$$