

CS supplement (1 page)

Same workshop — technical track

Name: _____ Image: 7109 7225 7149

A. Vocabulary (*one sentence each*)

Lexical / Jaccard agreement: _____

TF-IDF cosine: _____

SBERT cosine: _____

min_pairwise_semantic: _____

semantic_agreement_tier: _____

B. Min vs mean (three models → three pairs per field)

	Mean pairwise	Min pairwise
Formula	average of 3 pair scores	smallest of 3
Asks	“Mostly similar?”	“ Every pair similar?”
Risk	One dissenting pair averaged away	Can fail on paraphrase (7225 time)

7225: lighting/scene/background = high min; time = low min → **4/5** auto-trust, not 5/5.

Image gate: count fields **high** or **absent**; default **4/5** (strict), or **2/5** for demos.

Why **min** for automation? _____

When is min **too** strict? _____

C. Run it (*laptop + repo*)

```
python3 classroom_demo/compare_model_agreement.py \  
  --csv classroom_demo/coyote_metadata_comparison.csv \  
  --species-hint coyote \  
  --output /tmp/workshop_report.json \  
  --limit 20 --no-sbert
```

In JSON → **assessments** → your image → compare **field_results** and **semantic_trust** to the educator rubric.

Which fields would SBERT likely upgrade from partial → high? _____

D. Pipeline sketch

[image] → [3 VLMs] → [???] → [trust / review queue]

What belongs in [???] besides “pick the longest answer”?

Note: **best_model** in metrics CSV is consensus-heuristic, not ground-truth accuracy.

Educator handout: *practitioner_<image>_2page.md* · Full print doc: *worksheet_pdf_full.md*