

Table 1: Calculation time with the values of the contrast function  $\phi$  (Eq. (12)): They are the averages over 10 runs at the 10th layer (approximation) and the 720th layer (convergence) in LMICA (the normal one and the one without the mapping phase). In addition, those of 10 iterations in MaxKurt (approximately corresponding to  $L = 10 \times 72 = 720$ ) are shown. They were calculated in Intel 2.8GHz CPU.

	LMICA	LMICA without mapping	MaxKurt (10 iterations)
10th layer	22sec (4.91)	9.5sec (4.6)	
720th layer	1600sec (4.57)	670sec (4.57)	940sec (4.57)

of quite high-dimensional data space, such as the text mining. In addition, we are trying to find out the pre-whitening method suitable for LMICA. Some normalization techniques in the local-ICA phase may be promising.

## References

- [1] C. Jutten and J. Herault. Blind separation of sources (part I): An adaptive algorithm based on neuromimetic architecture. *Signal Processing*, 24(1):1–10, jul 1991.
- [2] P. Comon. Independent component analysis - a new concept? *Signal Processing*, 36:287–314, 1994.
- [3] A. J. Bell and T. J. Sejnowski. An information-maximization approach to blind separation and blind deconvolution. *Neural Computation*, 7:1129–1159, 1995.
- [4] J.-F. Cardoso and Beate Laheld. Equivariant adaptive source separation. *IEEE Transactions on Signal Processing*, 44(12):3017–3030, dec 1996.
- [5] A. Hyvärinen and E. Oja. A fast fixed-point algorithm for independent component analysis. *Neural Computation*, 9(7):1483–1492, 1997.
- [6] A. Hyvärinen. Fast and robust fixed-point algorithms for independent component analysis. *IEEE Transactions on Neural Networks*, 10(3):626–634, 1999.
- [7] Jean-François Cardoso and Antoine Souloumiac. Blind beamforming for non Gaussian signals. *IEE Proceedings-F*, 140(6):362–370, dec 1993.
- [8] Jean-François Cardoso. High-order contrasts for independent component analysis. *Neural Computation*, 11(1):157–192, jan 1999.
- [9] Yoshitatsu Matsuda and Kazunori Yamaguchi. Linear multilayer ica algorithm integrating small local modules. In *Proceedings of ICA2003*, pages 403–408, Nara, Japan, 2003.
- [10] Yoshitatsu Matsuda and Kazunori Yamaguchi. Linear multilayer independent component analysis using stochastic gradient algorithm. In *Independent Component Analysis and Blind source separation - ICA2004*, volume 3195 of *LNCS*, pages 303–310, Granada, Spain, sep 2004. Springer-Verlag.
- [11] Yoshitatsu Matsuda and Kazunori Yamaguchi. Global mapping analysis: stochastic approximation for multidimensional scaling. *International Journal of Neural Systems*, 11(5):419–426, 2001.
- [12] Yoshitatsu Matsuda and Kazunori Yamaguchi. An efficient MDS-based topographic mapping algorithm. *Neurocomputing*, 2005. in press.
- [13] A. J. Bell and T. J. Sejnowski. The "independent components" of natural scenes are edge filters. *Vision Research*, 37(23):3327–3338, dec 1997.
- [14] J. H. van Hateren and A. van der Schaaf. Independent component filters of natural images compared with simple cells in primary visual cortex. *Proceedings of the Royal Society of London: B*, 265:359–366, 1998.