



Table 8: An example where the nested attention hybrid model outperforms the non-nested model.

## 6 Conclusions

We have introduced a novel hybrid neural model with two nested levels of attention: word-level and character-level. The model addresses the unique challenges of the grammatical error correction task and achieves the best reported results on the CoNLL-14 benchmark among fully neural systems. Our nested attention hybrid model deeply combines the strengths of word and character level information in all components of an end-to-end neural model: the encoder, the attention layers, and the decoder. This enables it to correct both global word-level and local character-level errors in a unified way. The new architecture contributes substantial improvement in correction of confusions among rare or orthographically similar words compared to word-level sequence-to-sequence and non-nested hybrid models.

## Acknowledgements

We would like to thank the ACL reviewers for their insightful suggestions, Victoria Zayats for her help with reproducing the baseline word-level NMT system and Yu Shi, Daxin Jiang and Michael Zeng for the helpful discussions.

## References

Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. 2015. Neural machine translation by jointly learning to align and translate. In *Proceedings of ICLR*.

Chris Brockett, William B Dolan, and Michael Gamon. 2006. Correcting ESL errors using phrasal SMT techniques. In *Proceedings of the 21st International*

*Conference on Computational Linguistics and the 44th annual meeting of the Association for Computational Linguistics*. pages 249–256.

Christian Buck, Kenneth Heafield, and Bas Van Ooyen. 2014. N-gram counts and language models from the Common Crawl. In *LREC*.

Kyunghyun Cho, Bart van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. 2014. Learning phrase representations using RNN encoder-decoder for statistical machine translation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Sébastien Jean Kyunghyun Cho, Roland Memisevic, and Yoshua Bengio. 2015. On using very large target vocabulary for neural machine translation. In *Proceedings of ACL*.

Shamil Chollampatt, Kaveh Taghipour, and Hwee Tou Ng. 2016. Neural network translation models for grammatical error correction. In *Proceedings of IJCAI*.

Daniel Dahlmeier, Hwee Tou Ng, and Siew Mei Wu. 2013. Building a large annotated corpus of learner English: The NUS corpus of learner English. In *Proceedings of the Eighth Workshop on Innovative Use of NLP for Building Educational Applications*. pages 22–31.

Jianfeng Gao, Xiaolong(Shiao-Long) Li, Daniel Micol, Chris Quirk, and Xu Sun. 2010. A large scale ranker-based system for search query spelling correction. In *The 23rd International Conference on Computational Linguistics*.

Richard HR Hahnloser, Rahul Sarpeshkar, Misha A Mahowald, Rodney J Douglas, and H Sebastian Seung. 2000. Digital selection and analogue amplification coexist in a cortex-inspired silicon circuit. *Nature* 405(6789):947–951.

Marcin Junczys-Dowmunt and Roman Grundkiewicz. 2016. Phrase-based machine translation is state-of-the-art for automatic grammatical error correction. In *EMNLP*.

Lingpeng Kong, Chris Alberti, Daniel Andor, Ivan Bogatyy, and David Weiss. 2017. Dragnn: A transition-based framework for dynamically connected neural networks.

Jason Lee, Kyunghyun Cho, and Thomas Hofmann. 2017. Fully character-level neural machine translation without explicit segmentation. *TACL* 5.

Minh-Thang Luong and Christopher D. Manning. 2016. Achieving open vocabulary neural machine translation with hybrid word-character models. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*.