

Table 5: Average PSNR and SSIM results on BSD100 for super-resolution.

	PSNR								
	SRCNN	NBSRF	CSCN	CSC	TSE	ARFL+	RED10	RED20	RED30
$s = 2$	31.36	31.30	31.54	31.27	31.18	31.35	31.85	31.95	31.99
$s = 3$	28.41	28.36	28.58	28.31	28.30	28.36	28.79	28.90	28.93
$s = 4$	26.90	26.88	27.11	26.83	26.85	26.86	27.25	27.35	27.40
	SSIM								
	SRCNN	NBSRF	CSCN	CSC	TSE	ARFL+	RED10	RED20	RED30
$s = 2$	0.8879	0.8876	0.8908	0.8876	0.8855	0.8885	0.8953	0.8969	0.8974
$s = 3$	0.7863	0.7856	0.7910	0.7853	0.7843	0.7851	0.7975	0.7993	0.7994
$s = 4$	0.7103	0.7110	0.7191	0.7101	0.7108	0.7091	0.7238	0.7268	0.7290

comparing to the case in which using separate models for denoising and super-resolution. This may due to the fact that the network has to fit much more complex mappings. Except that CSCN works slightly better on Set14 super-resolution with scales 3 and 4, our network still beats the existing methods, showing that our network works much better in image denoising and super-resolution even using only one single model to deal with complex corruption.

Table 6: Average PSNR and SSIM results for image denoising using a single 30-layer network.

	Set5				Set14				BSD200			
	$s = 2$	$s = 3$	$s = 4$		$s = 2$	$s = 3$	$s = 4$		$s = 2$	$s = 3$	$s = 4$	
PSNR	34.49	29.09	26.75	25.20	33.38	27.88	25.69	24.36	34.49	29.09	26.75	25.20
SSIM	0.9368	0.8414	0.7710	0.7157	0.9280	0.7980	0.7119	0.6544	0.9368	0.8414	0.7710	0.7157

Table 7: Average PSNR and SSIM results for image super-resolution using a single 30-layer network.

	Set5			Set14			BSD100		
	$s = 2$	$s = 3$	$s = 4$	$s = 2$	$s = 3$	$s = 4$	$s = 2$	$s = 3$	$s = 4$
PSNR	37.56	33.70	31.33	32.81	29.50	27.72	31.96	28.88	27.35
SSIM	0.9595	0.9222	0.8847	0.9135	0.8334	0.7698	0.8972	0.7993	0.7276

4 Conclusions

In this paper we have proposed a deep encoding and decoding framework for image restoration. Convolution and deconvolution are combined, modeling the restoration problem by extracting primary image content and recovering details. More importantly, we propose to use skip connections, which helps on recovering clean images and tackles the optimization difficulty caused by gradient vanishing, and thus obtains performance gains when the network goes deeper. Experimental results and our analysis show that our network achieves better performance than state-of-the-art methods on image denoising and super-resolution.

This work was in part supported by Natural Science Foundation of China (Grants 61673204, 61273257, 61321491), Program for Distinguished Talents of Jiangsu Province, China (Grant 2013-XXRJ-018), Fundamental Research Funds for the Central Universities (Grant 020214380026), and Australian Research Council Future Fellowship (FT120100969). X.-J. Mao's contribution was made when visiting University of Adelaide. His visit was supported by the joint PhD program of China Scholarship Council.

References

- [1] H. C. Burger, C. J. Schuler, and S. Harmeling. Image denoising: Can plain neural networks compete with BM3D? In *Proc. IEEE Conf. Comp. Vis. Patt. Recogn.*, pages 2392–2399, 2012.
- [2] P. Chatterjee and P. Milanfar. Clustering-based denoising with locally learned dictionaries. *IEEE Trans. Image Process.*, 18(7):1438–1451, 2009.
- [3] F. Chen, L. Zhang, and H. Yu. External patch prior guided internal clustering for image denoising. In *Proc. IEEE Int. Conf. Comp. Vis.*, pages 603–611, 2015.
- [4] Z. Cui, H. Chang, S. Shan, B. Zhong, and X. Chen. Deep network cascade for image super-resolution. In *Proc. Eur. Conf. Comp. Vis.*, pages 49–64, 2014.
- [5] K. Dabov, A. Foi, V. Katkovnik, and K. O. Egiazarian. Image denoising by sparse 3-d transform-domain collaborative filtering. *IEEE Trans. Image Process.*, 16(8):2080–2095, 2007.