

PRACTICAL - 2

SUBMITTED BY: AIMAN SIDDIQUA - 2K18/MC/008

PASSENGER TABLE

Creating the table:

```
mysql> create table passenger (  
-> passenger_id int not null,  
-> first_name varchar(25),  
-> last_name varchar(25),  
-> phone_no varchar(10),  
-> primary key(passenger_id)  
-> );  
Query OK, 0 rows affected (0.15 sec)
```

```
mysql> describe passenger;  
+-----+-----+-----+-----+-----+-----+  
| Field      | Type      | Null | Key | Default | Extra |  
+-----+-----+-----+-----+-----+-----+  
| passenger_id | int(11)   | NO   | PRI | NULL    |       |  
| first_name   | varchar(25) | YES  |     | NULL    |       |  
| last_name    | varchar(25) | YES  |     | NULL    |       |  
| phone_no     | varchar(10) | YES  |     | NULL    |       |  
+-----+-----+-----+-----+-----+-----+  
4 rows in set (0.02 sec)
```

Inserting values into the table:

```
mysql> insert into passenger values(12008, 'Aiman', 'Siddiqua', 9876453828);  
Query OK, 1 row affected (0.13 sec)
```

Displaying the entire table:

```
mysql> select * from passenger;
```

| passenger_id | first_name | last_name | phone_no |
|--------------|------------|-----------|------------|
| 12008 | Aiman | Siddiqua | 9876453828 |
| 12009 | Akanksha | Dhayani | 8802391657 |
| 12010 | Aksht | Jain | 9716710426 |
| 12011 | Amogh | Diwan | 9818648313 |
| 12012 | Apoorva | Srivastav | 8806496492 |
| 12013 | Ansh | Aggarwal | 9173963819 |
| 12014 | Abhishek | Ralhan | 8764017589 |
| 12016 | Anikait | Gupta | 8371937492 |
| 12015 | Anirudh | Awasthi | 8163917391 |
| 12017 | Aryan | Bhardwaj | 9818163971 |

```
10 rows in set (0.12 sec)
```

TICKET TABLE

Creating the table :

```
mysql> create table ticket(
-> ticket_no int not null,
-> date date,
-> passenger_id int,
-> flight_no int
-> );
Query OK, 0 rows affected (0.12 sec)
```

```
mysql> describe ticket;
```

| Field | Type | Null | Key | Default | Extra |
|--------------|---------|------|-----|---------|-------|
| ticket_no | int(11) | NO | PRI | NULL | |
| date | date | YES | | NULL | |
| passenger_id | int(11) | YES | | NULL | |
| flight_no | int(11) | YES | | NULL | |

```
4 rows in set (0.00 sec)
```

Inserting values into the table:

```
mysql> insert into ticket values(2829, '2021-02-02', 12008, 961001);
Query OK, 1 row affected (0.00 sec)
```

Displaying the entire table:

```
mysql> select * from ticket;
+-----+-----+-----+-----+
| ticket_no | date       | passenger_id | flight_no |
+-----+-----+-----+-----+
| 2829      | 2021-02-02 | 12008        | 961001    |
| 2867      | 2021-02-08 | 12009        | 961003    |
| 2845      | 2021-02-05 | 12010        | 961001    |
| 2832      | 2021-02-11 | 12015        | 961007    |
| 2830      | 2021-03-07 | 12017        | 961003    |
| 2857      | 2021-04-17 | 12011        | 961007    |
| 2848      | 2021-03-22 | 12013        | 961004    |
| 2855      | 2021-02-26 | 12016        | 961001    |
| 2839      | 2021-04-01 | 12012        | 961007    |
| 2843      | 2021-03-30 | 12014        | 961003    |
+-----+-----+-----+-----+
10 rows in set (0.00 sec)
```

FLIGHT TABLE

Creating the table:

```
mysql> create table flight (
-> flight_no int not null,
-> source varchar(15),
-> destination varchar(15),
-> aircraft_type varchar(25),
-> route_id int,
-> primary key(flight_no)
-> );
Query OK, 0 rows affected (0.26 sec)
```

```
mysql> describe flight;
```

| Field | Type | Null | Key | Default | Extra |
|---------------|-------------|------|-----|---------|-------|
| flight_no | int(11) | NO | PRI | NULL | |
| source | varchar(15) | YES | | NULL | |
| destination | varchar(15) | YES | | NULL | |
| aircraft_type | varchar(25) | YES | | NULL | |
| route_id | int(11) | YES | | NULL | |

```
5 rows in set (0.00 sec)
```

Inserting values into the table:

```
mysql> insert into flight values(961003, 'Delhi', 'Goa', 'Boeing 747SP', 218);
Query OK, 1 row affected (0.00 sec)
```

Displaying the entire table:

```
mysql> select * from flight;
```

| flight_no | source | destination | aircraft_type | route_id |
|-----------|-----------|-------------|-------------------------|----------|
| 961003 | Delhi | Goa | Boeing 747SP | 218 |
| 961007 | Mumbai | Paris | Airbus A330-200 | 224 |
| 961001 | Bangalore | New York | Douglas DC-9-50 | 215 |
| 961004 | Kolkata | Chandigarh | Airbus A330-200 | 213 |
| 961006 | Delhi | Tokyo | Embraer E195-E2 | 227 |
| 961002 | Toronto | Chennai | Douglas DC-9-50 | 216 |
| 961009 | Agra | Raipur | Embraer E195-E2 | 221 |
| 961014 | Pune | Patna | Boeing 747SP | 229 |
| 961005 | Abu Dhabi | Mumbai | Airbus A330-200 | 219 |
| 961012 | Goa | Jaipur | McDonnell Douglas MD-90 | 211 |

```
10 rows in set (0.00 sec)
```

ROUTE TABLE

Creating the table:

```
mysql> create table route(
-> route_id int not null,
-> domestic_continental varchar(15),
-> tariff decimal,
-> fare_range decimal,
-> primary key(route_id))
```

```
-> );  
Query OK, 0 rows affected (0.11 sec)
```

```
mysql> describe route;  
+-----+-----+-----+-----+-----+-----+  
| Field                | Type          | Null | Key | Default | Extra |  
+-----+-----+-----+-----+-----+-----+  
| route_id             | int(11)       | NO   | PRI | NULL    |       |  
| domestic_continental | varchar(15)   | YES  |     | NULL    |       |  
| tariff               | decimal(10,0) | YES  |     | NULL    |       |  
| fare_range           | decimal(10,0) | YES  |     | NULL    |       |  
+-----+-----+-----+-----+-----+-----+  
4 rows in set (0.11 sec)
```

Inserting values into the table:

```
mysql> insert into route values(213, 'domestic', 301, 5000);  
Query OK, 1 row affected, 1 warning (0.02 sec)
```

Displaying the entire table:

```
mysql> select * from route;  
+-----+-----+-----+-----+  
| route_id | domestic_continental | tariff | fare_range |  
+-----+-----+-----+-----+  
| 213      | domestic             | 301    | 5000       |  
| 219      | continental          | 295    | 9300       |  
| 215      | continental          | 330    | 15700      |  
| 221      | domestic             | 282    | 6400       |  
| 218      | domestic             | 310    | 5900       |  
| 216      | continental          | 348    | 17800      |  
| 227      | continental          | 335    | 16200      |  
| 211      | domestic             | 275    | 4800       |  
| 224      | continental          | 316    | 17300      |  
| 229      | domestic             | 296    | 7300       |  
+-----+-----+-----+-----+  
10 rows in set (0.00 sec)
```

Entire Database:

```
mysql> use airline;
Database changed
mysql> show tables;
+-----+
| Tables_in_airline |
+-----+
| flight             |
| passenger          |
| route              |
| ticket             |
+-----+
4 rows in set (0.00 sec)
```