Assignment 11.3 Ai Assisted Coding

Name: Sandhi. Abhinay Reddy
Ht.no: 2303A51382

Batch: 06

Task 1:

Smart Contact Manager (Arrays & Linked Lists)

Scenario

SR University's student club requires a simple Contact Manager Application to store members' names and phone numbers. The system should support efficient addition, searching, and deletion of contacts.

Prompt:

Write a python program to Create a Contact Manager using list and linked list with add, search, and delete functions.

Code:







Output:



Explanation:

- In an array, adding at the end is fast, but inserting in the middle is slow because elements must shift.
- In a linked list, insertion is fast because no shifting is needed.
- Searching takes the same time in both (you must check each element).
- Deleting in an array is slower due to shifting elements.
- Linked list is better for frequent insertions and deletions.

Task 2:

Library Book Search System (Queues & Priority Queues) Scenario

The SRU Library manages book borrow requests. Students and faculty submit requests, but faculty requests must be prioritized over student requests.

Prompt:

Write a Python program for a library book request system.First, make a normal queue where requests are handled in the order they come.Then, make another version where faculty requests are given first priority over student requests.Include functions to add a request and remove a request.

Code:

```python
from collections import deque

# ===== NORMAL QUEUE IMPLEMENTATION =====
class BookRequest:
    """Represents a book request"""
    def __init__(self, request_id, requester_name, book_title):
        self.request_id = request_id
        self.requester_name = requester_name
        self.book_title = book_title

    def __str__(self):
        return f"ID: {self.request_id}, Requester: {self.requester_name}, Book: {self.book_title}"


class NormalQueue:
    """Simple FIFO queue for book requests"""
    def __init__(self):
        self.queue = deque()

    def add_request(self, request):
        """Add a request to the queue"""
        self.queue.append(request)
        print(f"Request added: {request}")

    def remove_request(self):
        """Remove and return the first request"""
        if not self.queue:
            print("Queue is empty!")
            return None
        request = self.queue.popleft()
        print(f"Request processed: {request}")
        return request

    def display_queue(self):
        """Display all requests in queue"""
        if not self.queue:
            print("Queue is empty!")
            return
        print("\n=== Normal Queue ===")
        for i, req in enumerate(self.queue, 1):
            print(f"{i}. {req}")

    def size(self):
        return len(self.queue)


# ===== PRIORITY QUEUE IMPLEMENTATION =====
class PriorityBookRequest:
    """Book request with priority (Faculty > Student)"""
    def __init__(self, request_id, requester_name, book_title, user_type):
        self.request_id = request_id
        self.requester_name = requester_name
        self.book_title = book_title
        self.user_type = user_type  # "Faculty" or "Student"

    def __str__(self):
        return f"ID: {self.request_id}, Requester: {self.requester_name} ({self.user_type}), Book: {self.book_title}"

    def get_priority(self):
        """Return priority (lower number = higher priority)"""
        if self.user_type.lower() == "faculty":
```

```python
class PriorityQueue:
    """Priority queue for book requests (Faculty first)"""
    def __init__(self):
        self.queue = []

    def add_request(self, request):
        """Add a request with priority sorting"""
        self.queue.append(request)
        self.queue.sort(key=lambda x: x.get_priority())
        print(f"Request added: {request}")

    def remove_request(self):
        """Remove and return the highest priority request"""
        if not self.queue:
            print("Queue is empty!")
            return None
        request = self.queue.pop(0)
        print(f"Request processed: {request}")
        return request

    def display_queue(self):
        """Display all requests in priority order"""
        if not self.queue:
            print("Queue is empty!")
            return
        print("\n=== Priority Queue ===")
        for i, req in enumerate(self.queue, 1):
            print(f"{i}. {req}")

    def size(self):
        return len(self.queue)


# ===== DEMO PROGRAM =====
if __name__ == "__main__":
    print("=" * 60)
    print("LIBRARY BOOK REQUEST SYSTEM")
    print("=" * 60)

    # ===== Normal Queue Demo =====
    print("\n--- NORMAL QUEUE (FIFO) ---")
    normal_q = NormalQueue()

    # Add requests
    normal_q.add_request(BookRequest(1, "Alice", "Python Programming"))
    normal_q.add_request(BookRequest(2, "Bob", "Data Science"))
    normal_q.add_request(BookRequest(3, "Charlie", "Web Development"))
    normal_q.add_request(BookRequest(4, "Diana", "Machine Learning"))

    normal_q.display_queue()
    print(f"Queue size: {normal_q.size()}")

    # Process requests
    print("\n--- Processing Requests (Normal Queue) ---")
    normal_q.remove_request()
    normal_q.remove_request()

    normal_q.display_queue()
    print(f"Queue size: {normal_q.size()}")

    # ===== Priority Queue Demo =====
```



```
class PriorityQueue:
    def display_queue(self):
        return
        print("\n=== Priority Queue ===")
        for i, req in enumerate(self.queue, 1):
            print(f"{i}. {req}")

    def size(self):
        return len(self.queue)


# ===== DEMO PROGRAM =====
if __name__ == "__main__":
    print("=" * 60)
    print("LIBRARY BOOK REQUEST SYSTEM")
    print("=" * 60)

    # ===== Normal Queue Demo =====
    print("\n--- NORMAL QUEUE (FIFO) ---")
    normal_q = NormalQueue()

    # Add requests
    normal_q.add_request(BookRequest(1, "Alice", "Python Programming"))
    normal_q.add_request(BookRequest(2, "Bob", "Data Science"))
    normal_q.add_request(BookRequest(3, "Charlie", "Web Development"))
    normal_q.add_request(BookRequest(4, "Diana", "Machine Learning"))

    normal_q.display_queue()
    print(f"Queue size: {normal_q.size()}")

    # Process requests
    print("\n--- Processing Requests (Normal Queue) ---")
    normal_q.remove_request()
    normal_q.remove_request()

    normal_q.display_queue()
    print(f"Queue size: {normal_q.size()}")

    # ===== Priority Queue Demo =====
    print("\n\n--- PRIORITY QUEUE (Faculty First) ---")
    priority_q = PriorityQueue()

    # Add requests (mixed faculty and student)
    priority_q.add_request(PriorityBookRequest(1, "Alice", "Python Programming", "Student"))
    priority_q.add_request(PriorityBookRequest(2, "Prof. Bob", "Data Science", "Faculty"))
    priority_q.add_request(PriorityBookRequest(3, "Charlie", "Web Development", "Student"))
    priority_q.add_request(PriorityBookRequest(4, "Prof. Diana", "Machine Learning", "Faculty"))
    priority_q.add_request(PriorityBookRequest(5, "Eve", "Databases", "Student"))

    priority_q.display_queue()
    print(f"Queue size: {priority_q.size()}")

    # Process requests
    print("\n--- Processing Requests (Priority Queue) ---")
    priority_q.remove_request()
    priority_q.remove_request()
    priority_q.remove_request()

    priority_q.display_queue()
    print(f"Queue size: {priority_q.size()}")
```

Output:

```
PS C:\AI Assistant Coding> & C:/Users/edula/AppData/Local/Microsoft/WindowsApps/python3.11.exe "c:/AI Assistant Coding/bug.py"

=== Priority Queue ===
1. ID: 3, Requester: Charlie (Student), Book: Web Development
2. ID: 5, Requester: Eve (Student), Book: Databases
Queue size: 2

============================================================
PS C:\AI Assistant Coding>
```

Explanation:

- Queue (FIFO) → First request comes, first served.(If a student requests first, they get the book first.)
- Priority Queue → Faculty requests are served before students, even if they come later.
- enqueue() → Adds a request to the system.
- dequeue() → Removes and processes the next request.

Task 3: Emergency Help Desk (Stack Implementation)

Scenario

SR University's IT Help Desk receives technical support tickets from students and staff.

While tickets are received sequentially, issue escalation follows a Last-In, First-Out (LIFO) approach.

Prompt:

Write a program of stack-based ticket system in Python with push, pop, peek, isEmpty, and isFull. Add five tickets and show how they are resolved using LIFO order.

Code:





Output:



Explanation:

The program uses a stack to manage help desk tickets.
A stack works in last in, first solved order.
When a new ticket is raised, it is added to the top.
When solving a ticket, the most recent one is handled first.
The program can also check if there are no tickets left or if the stack is full.

Task 4:

Hash Table

Objective

To implement a Hash Table and understand collision handling.

Prompt:

Write a Python program to create a Hash Table.
Add methods to insert, search, and delete data.
Handle collisions using chaining (store multiple values in a list at the same index).
Add comments to explain the code and show example usage.

Code:

```python
# ===== HASH TABLE WITH CHAINING COLLISION HANDLING =====

# Key-Value pair class for storing data
class KeyValuePair:
    """Represents a key-value pair in the hash table"""
    def __init__(self, key, value):
        self.key = key
        self.value = value

    def __str__(self):
        return f"{self.key}: {self.value}"


class HashTable:
    """
    Hash Table implementation using chaining to handle collisions.
    Chaining stores multiple key-value pairs that hash to the same index in a linked list.
    """

    def __init__(self, size=10):
        """
        Initialize the hash table
        Args:
            size (int): Number of buckets in the hash table
        """
        self.size = size
        # Create an array of empty lists (chains) for collision handling
        self.table = [[] for _ in range(size)]
        self.total_items = 0

    def _hash_function(self, key):
        """
        Hash function to determine the index for a given key
        Uses simple modulo operation: hash(key) % table_size

        Args:
            key: The key to hash

        Returns:
            int: Index in the hash table
        """
        # Convert key to string and sum ASCII values for different key types
        key_str = str(key)
        hash_value = sum(ord(char) for char in key_str)
        return hash_value % self.size

    def insert(self, key, value):
        """
        Insert a key-value pair into the hash table
        If key already exists, update its value
        If collision occurs, add to the chain (list) at that index

        Args:
            key: The key to insert
            value: The value associated with the key

        Returns:
            bool: True if insertion successful, False otherwise
        """
        # Get the hash index
        index = self._hash_function(key)
        chain = self.table[index]

        # Check if key already exists in the chain and update if found
        for i, pair in enumerate(chain):
            if pair.key == key:
```

```python
    def insert(self, key, value):
        # Check if key already exists in the chain and update if found
        for i, pair in enumerate(chain):
            if pair.key == key:
                chain[i].value = value
                print(f"✓ Updated: {key} = {value} (at index {index})")
                return True

        # If key not found, add new key-value pair to the chain
        chain.append(KeyValuePair(key, value))
        self.total_items += 1
        print(f"✓ Inserted: {key} = {value} (at index {index})")
        return True

    def search(self, key):
        """
        Search for a key in the hash table

        Args:
            key: The key to search for

        Returns:
            The value associated with the key, or None if not found
        """
        # Get the hash index
        index = self._hash_function(key)
        chain = self.table[index]

        # Search for the key in the chain
        for pair in chain:
            if pair.key == key:
                print(f"✓ Found: {key} = {pair.value} (at index {index})")
                return pair.value

        # Key not found
        print(f"✗ Key '{key}' not found in the hash table")
        return None

    def delete(self, key):
        """
        Delete a key-value pair from the hash table

        Args:
            key: The key to delete

        Returns:
            bool: True if deletion successful, False if key not found
        """
        # Get the hash index
        index = self._hash_function(key)
        chain = self.table[index]

        # Search for and remove the key from the chain
        for i, pair in enumerate(chain):
            if pair.key == key:
                deleted_pair = chain.pop(i)
                self.total_items -= 1
                print(f"✓ Deleted: {key} = {deleted_pair.value} (from index {index})")
                return True

        # Key not found
        print(f"✗ Key '{key}' not found in the hash table")
        return False

    def display(self):
```



Output:



Explanation:

- A Hash Table stores data using a key and value. • A hash function decides where to store the data.
- Sometimes two keys go to the same place. This is called a collision.
- To solve collisions, we use chaining, meaning we store multiple items in a list at the same index.
- The program should allow adding, finding, and removing data correctly.

Task 5:

Real-Time Application Challenge

Scenario

Design a Campus Resource Management System with the following features:

- Student Attendance Tracking
- Event Registration System
- Library Book Borrowing
- Bus Scheduling System
- Cafeteria Order Queue

Prompt:

Create a Campus Resource Management System in Python.For each feature (Attendance, Event Registration, Library, Bus Schedule, Cafeteria Orders), choose the best data structure

Code:




File Edit Selection
AI Assistant Coding
campus_resource_management.py
class EventRegistration:
def pending_count(self):
return len(self.queue)
def list_pending(self):
return list(self.queue)
# ---------- Library (dict/hash table) ----------
class Library:
"""Simple library using a dict for O(1) lookups by ISBN."""
def __init__(self):
# isbn -> {title, author, copies, borrowers(list)}
self.catalog = {}
def add_book(self, isbn, title, author, copies=1):
if isbn in self.catalog:
self.catalog[isbn]['copies'] += copies
print(f"Added {copies} more copy(ies) of {title} (ISBN: {isbn}).")
else:
self.catalog[isbn] = {
'title': title,
'author': author,
'copies': copies,
'borrowers': []
}
print(f"Added book: {title} (ISBN: {isbn}).")
def search(self, isbn):
return self.catalog.get(isbn)
def borrow_book(self, isbn, user_id):
book = self.catalog.get(isbn)
if not book:
print("Book not found.")
return False
if book['copies'] <= 0:
print("No copies available.")
return False
book['copies'] -= 1
book['borrowers'].append(user_id)
print(f"{user_id} borrowed {book['title']}")
return True
def return_book(self, isbn, user_id):
book = self.catalog.get(isbn)
if not book:
print("Book not found.")
return False
try:
book['borrowers'].remove(user_id)
except ValueError:
print("This user did not borrow the book.")
return False
book['copies'] += 1
print(f"{user_id} returned {book['title']}")
return True
def list_available(self):
return [(isbn, info['title'], info['copies']) for isbn, info in self.catalog.items()]
---------- Bus Schedule (route -> sorted list of times) ----------
BUG FIXING ASSISTANCE
it is not giving any output


File Edit Selection
AI Assistant Coding
campus_resource_management.py
# ---------- Demo ----------
if __name__ == '__main__':
print('='*60)
print('Campus Resource Management Demo')
print('='*60)
# Attendance demo
att = Attendance()
att.mark_present('S001')
att.mark_present('S002')
att.mark_present('S010')
print('Present list:', att.list_present())
print('Is S002 present?', att.is_present('S002'))
att.mark_absent('S002')
print('Present count:', att.present_count())
# Event registration demo
ev = EventRegistration()
ev.add_registration('A001', 'Alice')
ev.add_registration('A002', 'Bob')
ev.add_registration('A003', 'Charlie')
print('Pending registrations:', ev.list_pending())
ev.process_registration()
print('Pending count:', ev.pending_count())
# Library demo
lib = Library()
lib.add_book('978-0135166307', 'Clean Code', 'Robert C. Martin', copies=2)
lib.add_book('978-1491950296', 'Fluent Python', 'Luciano Ramalho', copies=1)
lib.borrow_book('978-0135166307', 'S001')
lib.borrow_book('978-0135166307', 'S003')
lib.borrow_book('978-0135166307', 'S004') # no copies left
print('Available books:', lib.list_available())
lib.return_book('978-0135166307', 'S001')
print('Available books after return:', lib.list_available())
# Bus schedule demo
bs = BusSchedule()
now = datetime.now()
bs.add_route_time('Route A', now + timedelta(minutes=5))
bs.add_route_time('Route A', now + timedelta(minutes=20))
bs.add_route_time('Route B', now + timedelta(minutes=2))
print('Next Route A bus:', bs.next_bus('Route A', current_time=now))
print('Route A schedule:', bs.list_route('Route A'))
# Cafeteria orders demo
caf = CafeteriaOrders()
caf.add_order('O001', 'S001', ['Coffee', 'Sandwich'], customer_type='Student')
caf.add_order('O002', 'F001', ['Salad'], customer_type='Faculty')
caf.add_order('O003', 'S002', ['Tea'], customer_type='Student')
caf.add_order('O004', 'F002', ['Pasta'], customer_type='Faculty')
print('Pending cafeteria orders:', caf.pending_count())
caf.serve_order()
caf.serve_order()
print('Pending orders after serving:', caf.pending_count())
print('\nDemo complete.')
BUG FIXING ASSISTANCE
it is not giving any output

Output:

```
PROBLEMS    OUTPUT    DEBUG CONSOLE    PORTS    TERMINAL    POSTMAN CONSOLE

PS C:\AI Assistant Coding> & C:/Users/edula/AppData/Local/Microsoft/WindowsApps/python3.11.exe "c:/AI Assistant Coding/bug.py"
Is empty: False
PS C:\AI Assistant Coding> & C:/Users/edula/AppData/Local/Microsoft/WindowsApps/python3.11.exe "c:/AI Assistant Coding/bug.py"
PS C:\AI Assistant Coding> & C:/Users/edula/AppData/Local/Microsoft/WindowsApps/python3.11.exe "c:/AI Assistant Coding/campus_resource_management.py"
============================================================
Campus Resource Management Demo
============================================================
Marked present: S001
Marked present: S002
Marked present: S010
Present list: ['S001', 'S002', 'S010']
Is S002 present? True
Marked absent: S002
Present count: 2
Registered: A001 - Alice
Registered: A002 - Bob
Registered: A003 - Charlie
Pending registrations: [('A001', 'Alice'), ('A002', 'Bob'), ('A003', 'Charlie')]
Processed registration: A001 - Alice
Pending count: 2
Added book: Clean Code (ISBN: 978-0135166307).
Added book: Fluent Python (ISBN: 978-1491950296).
S001 borrowed Clean Code
S003 borrowed Clean Code
No copies available.
Available books: [('978-0135166307', 'Clean Code', 0), ('978-1491950296', 'Fluent Python', 1)]
S001 returned Clean Code
Available books after return: [('978-0135166307', 'Clean Code', 1), ('978-1491950296', 'Fluent Python', 1)]
Added bus time for Route A: 2026-02-18 10:42:24.367227
Added bus time for Route A: 2026-02-18 10:57:24.367227
Added bus time for Route B: 2026-02-18 10:39:24.367227
Next Route A bus: 2026-02-18 10:42:24.367227
Route A schedule: [datetime.datetime(2026, 2, 18, 10, 42, 24, 367227), datetime.datetime(2026, 2, 18, 10, 57, 24, 367227)]
Order added: O001 (Student)
Order added: O002 (Faculty)
Order added: O003 (Student)
Order added: O004 (Faculty)
Pending cafeteria orders: 4
Serving order: O002 (Faculty)
Serving order: O004 (Faculty)
Pending orders after serving: 2

Demo complete.
PS C:\AI Assistant Coding>
```

Explanation:

Library Book Borrowing using a queue:

- The queue stores student names who request a book.
- When a student requests a book, we use enqueue() to add them to the queue.
- When a book becomes available, we use dequeue() to give it to the first student in line.
- This ensures fairness because the first requester gets the book first.