



**Data manipulation:
Data wrangling, aggregation, and
group operations.**

AAA-Python Edition



school of analytics

Plan

- 1- Hierarchical indexing
- 2- Combining and merging Data Sets
- 3- Reshaping and pivoting
- 4- Group by Mechanics
- 5- Data aggregation
- 6- Other aggregation operations



school of ai

1- Hierarchical indexing

Data Wrangling and hierarchical indexing

- Data wrangling** is the process of **cleaning** and **unifying messy** and **complex** data sets for **easy access** and **analysis**. (from: <https://www.datawatch.com/what-is-data-wrangling/>)
- Hierarchical indexing**: is the use of **multiple indexes** at different **levels**

```
1 # creating a Series with a hierarchical index
2 hind = [list("AAABBBCCCD"), ["i1", "i2", "i3"]*3 + ["i1"]]
3 ser1 = S(range(10), index= hind)
```

hind

i1, i2, i3 will be
In the level A

```
[['A', 'A', 'A', 'B', 'B', 'B', 'C', 'C', 'C', 'D'],
 ['i1', 'i2', 'i3', 'i1', 'i2', 'i3', 'i1', 'i2', 'i3', 'i1']]
```

ser1.index

level 1

level 2

```
MultiIndex(levels=[['A', 'B', 'C', 'D'], ['i1', 'i2', 'i3']],
            labels=[0, 0, 0, 1, 1, 1, 2, 2, 2, 3], [0, 1, 2, 0, 1, 2, 0, 1, 2, 0])
```

Indices of level 1

Indices of level 2

| | | |
|--------------|----|---|
| ser1 | | |
| A | i1 | 0 |
| | i2 | 1 |
| | i3 | 2 |
| B | i1 | 3 |
| | i2 | 4 |
| | i3 | 5 |
| C | i1 | 6 |
| | i2 | 7 |
| | i3 | 8 |
| D | i1 | 9 |
| dtype: int64 | | |



school of a

1- Hierarchical indexing

Reordering and sorting

- Reordering enables **interchanging the index levels** using the **swaplevel** method
- Sorting enables **sorting** the **data** by sorting **one level values**, using the **sort_index** method.

```
1 # naming the levels
2 ser1.index.names=["the_level0","the_level1"]
3 # rearranging the levels
4 ser1.swaplevel("the_level0","the_level1")
```

| the_level0 | the_level1 |
|------------|------------|
| A | i1 |
| B | i1 |
| C | i1 |
| D | i1 |
| A | i2 |
| B | i2 |
| C | i2 |
| A | i3 |
| B | i3 |
| C | i3 |

| | | |
|---|----|---|
| A | i1 | 0 |
| B | i1 | 3 |
| C | i1 | 6 |
| D | i1 | 9 |
| A | i2 | 1 |
| B | i2 | 4 |
| C | i2 | 7 |
| A | i3 | 2 |
| B | i3 | 5 |
| C | i3 | 8 |

dtype: int64

The hierarchy of the indexes changed

The hierarchy of the Indexes didn't change

The order of the data (so the indexes too) changed: **the_level1** index was **sorted**

| the_level1 | the_level0 |
|------------|------------|
| i1 | A |
| i2 | A |
| i3 | A |
| i1 | B |
| i2 | B |
| i3 | B |
| i1 | C |
| i2 | C |
| i3 | C |
| i1 | D |

dtype: int64

The order of the data (so the indexes too) remains the same

```
1 # sorting the values following the second level : level=1
2 ser1.sort_index(level=1)
```



school of a

1- Hierarchical indexing

Operations by level

df1

| | | colors | codes |
|-----------|--------|--------|-------------|
| Code_type | number | | |
| hex | 1 | green | #FF0000 |
| | 2 | blue | #0000FF |
| | 3 | red | #FF0000 |
| rgb | 1 | green | (0, 0, 255) |
| | 2 | blue | (0, 255, 0) |
| | 3 | red | (255, 0, 0) |

```
1 # summarising the columns values by "code_type"  
2 df1.sum(level="Code_type")
```

| | | colors | codes |
|-----------|--|--------------|-----------------------------------|
| Code_type | | | |
| hex | | greenbluered | #FF0000#0000FF#FF0000 |
| rgb | | greenbluered | (0, 0, 255, 0, 255, 0, 255, 0, 0) |

If sum was applied on number,
It would perform an addition instead
Of this concatenation

```
1 df1["value"] = [5, 7, 8, 10, 3, 1]  
2 # sort the df1 values according to the second index  
3 df1 = df1.sort_index(level=1)
```

[By Amina Delali]

df1

sorted

A new column
added

| | | colors | codes | value |
|-----------|--------|--------|-------------|-------|
| Code_type | number | | | |
| hex | 1 | green | #FF0000 | 5 |
| rgb | 1 | green | (0, 0, 255) | 7 |
| hex | 2 | blue | #0000FF | 8 |
| rgb | 2 | blue | (0, 255, 0) | 10 |
| hex | 3 | red | #FF0000 | 3 |
| rgb | 3 | red | (255, 0, 0) | 1 |



school of a

1- Hierarchical indexing

indexing

```
1 # creating a new DataFrame using df1 columns
2 df2 = df1.set_index(["colors", "codes"])
```

df2

| | | value |
|--------|-------------|-------|
| colors | codes | |
| green | #FF0000 | 5 |
| | (0, 0, 255) | 7 |
| blue | #0000FF | 8 |
| | (0, 255, 0) | 10 |
| red | #FF0000 | 3 |
| | (255, 0, 0) | 1 |

The previous df1 columns are now indexes

The indexes are converted into columns

| | colors | codes | value |
|---|--------|-------------|-------|
| 0 | green | #FF0000 | 5 |
| 1 | green | (0, 0, 255) | 10 |
| 2 | blue | #0000FF | 7 |
| 3 | blue | (0, 255, 0) | 3 |
| 4 | red | #FF0000 | 8 |
| 5 | red | (255, 0, 0) | 1 |

```
1 # the indexes are converted into columns
2 df2.reset_index()
```



school of ai

2- Combining and merging Data Sets

merge

```
1 # merging two dataframes df1 and df3, using the common values  
2 #in "colors" and "mycolors" columns  
3 pd.merge(df1,df3,left_on="colors",right_on="mycolors")
```

df1

| | colors | codes | value |
|-----------|--------|-------|----------------|
| Code_type | number | | |
| hex | 1 | green | #FF0000 5 |
| rgb | 1 | green | (0, 0, 255) 7 |
| hex | 2 | blue | #0000FF 8 |
| rgb | 2 | blue | (0, 255, 0) 10 |
| hex | 3 | red | #FF0000 3 |
| rgb | 3 | red | (255, 0, 0) 1 |

df3

| | codes | mycolors |
|---|-------|----------|
| 0 | G | green |
| 1 | B | blue |

Each row from **df1** with "green" value in "colors" column, will be combined with each row from **df3** with "green" value in "mycolors" column.

"red" rows weren't included

Both **df1** and **df2** have "codes" column, so "_x" and "_y" suffixes were added.

| | colors | codes_x | value | codes_y | mycolors |
|---|--------|-------------|-------|---------|----------|
| 0 | green | #FF0000 | 5 | G | green |
| 1 | green | (0, 0, 255) | 7 | G | green |
| 2 | blue | #0000FF | 8 | B | blue |
| 3 | blue | (0, 255, 0) | 10 | B | blue |



school of ai

2- Combining and merging Data Sets

merge

df1

```
4 pd.merge(df1,df3,left_on="colors",right_on="mycolors",suffixes=("_df1","_df3"),how="left")
```

Code_type number

| | | | | |
|-----|---|-------|-------------|----|
| hex | 1 | green | #FF0000 | 5 |
| rgb | 1 | green | (0, 0, 255) | 7 |
| hex | 2 | blue | #0000FF | 8 |
| rgb | 2 | blue | (0, 255, 0) | 10 |
| hex | 3 | red | #FF0000 | 3 |
| rgb | 3 | red | (255, 0, 0) | 1 |

df3

| | codes | mycolors |
|---|-------|----------|
| 0 | G | green |
| 1 | B | blue |

Specifying the argument **"how"** as **"left"**, all rows from **df1** were included (even if no matching value exists in **df3**)

| | colors | codes_df1 | value | codes_df3 | mycolors |
|---|--------|-------------|-------|-----------|----------|
| 0 | green | #FF0000 | 5 | G | green |
| 1 | green | (0, 0, 255) | 7 | G | green |
| 2 | blue | #0000FF | 8 | B | blue |
| 3 | blue | (0, 255, 0) | 10 | B | blue |
| 4 | red | #FF0000 | 3 | NaN | NaN |
| 5 | red | (255, 0, 0) | 1 | NaN | NaN |

The suffixes argument used to customize the suffixes added to columns with the same name



school of ai

2- Combining and merging Data Sets

merge

```
3 # using df3 indexes values as common values for merge
4 pd.merge(df11,df3,left_on="number", right_index=True)
```

df11

| | Code_type | number | colors | codes | value |
|---|-----------|--------|--------|-------------|-------|
| 0 | hex | 1 | green | #FF0000 | 5 |
| 1 | rgb | 1 | green | (0, 0, 255) | 7 |
| 2 | hex | 2 | blue | #0000FF | 8 |
| 3 | rgb | 2 | blue | (0, 255, 0) | 10 |
| 4 | hex | 3 | red | #FF0000 | 3 |
| 5 | rgb | 3 | red | (255, 0, 0) | 1 |

df3

| | codes | mycolors |
|---|-------|----------|
| 0 | G | green |
| 1 | B | blue |

Combining df11 and df3 by matching values from "number" column from df11, with Index values from df3

| | Code_type | number | colors | codes_x | value | codes_y | mycolors |
|---|-----------|--------|--------|-------------|-------|---------|----------|
| 0 | hex | 1 | green | #FF0000 | 5 | B | blue |
| 1 | rgb | 1 | green | (0, 0, 255) | 7 | B | blue |



school of a

2- Combining and merging Data Sets

join

```
df11.join(df3, lsuffix="_df11", rsuffix="_df3")
```

df11

| | Code_type | number | colors | codes | value |
|---|-----------|--------|--------|-------------|-------|
| 0 | hex | 1 | green | #FF0000 | 5 |
| 1 | rgb | 1 | green | (0, 0, 255) | 7 |
| 2 | hex | 2 | blue | #0000FF | 8 |
| 3 | rgb | 2 | blue | (0, 255, 0) | 10 |
| 4 | hex | 3 | red | #FF0000 | 3 |
| 5 | rgb | 3 | red | (255, 0, 0) | 1 |

df3

| | codes | mycolors |
|---|-------|----------|
| 0 | G | green |
| 1 | B | blue |

You have to specify the suffixes if the dataframes have columns with same names

The dataframes are combined by matching indexes values

By default all the values of df11 were added

| | Code_type | number | colors | codes_df11 | value | codes_df3 | mycolors |
|---|-----------|--------|--------|-------------|-------|-----------|----------|
| 0 | hex | 1 | green | #FF0000 | 5 | G | green |
| 1 | rgb | 1 | green | (0, 0, 255) | 7 | B | blue |
| 2 | hex | 2 | blue | #0000FF | 8 | NaN | NaN |
| 3 | rgb | 2 | blue | (0, 255, 0) | 10 | NaN | NaN |
| 4 | hex | 3 | red | #FF0000 | 3 | NaN | NaN |
| 5 | rgb | 3 | red | (255, 0, 0) | 1 | NaN | NaN |

[By Amina Delali]



school of a

2- Combining and merging Data Sets

concat

```
1 # concatenating ser11 and ser2 by concatenating the indexes
2 pd.concat([ser11,ser2])
```

ser11

| | |
|---|---|
| a | 0 |
| b | 1 |

dtype: int64

ser2

| | |
|---|---|
| c | 7 |
| d | 8 |
| e | 9 |

dtype: int64

| | |
|---|---|
| a | 0 |
| b | 1 |
| c | 7 |
| d | 8 |
| e | 9 |

dtype: int64

combine_first

```
ser3.combine_first(ser4)
```

ser3

| | |
|---|---|
| a | 0 |
| b | 1 |
| c | 2 |

dtype: int64

ser3 values
were chosen
over ser4
values

ser4

| | |
|---|---|
| a | 7 |
| b | 8 |
| d | 9 |

dtype: int64

| | |
|---|-----|
| a | 0.0 |
| b | 1.0 |
| c | 2.0 |
| d | 9.0 |

dtype: float64

ser3

| | |
|---|-----|
| a | NaN |
| b | 1.0 |
| c | 2.0 |

dtype: float64

In ser3, "a" corresponding
value == nan and in ser4
"a" corresponding value
is not null, so it was chosen

ser4

| | |
|---|---|
| a | 7 |
| b | 8 |
| d | 9 |

dtype: int64

| | |
|---|-----|
| a | 7.0 |
| b | 1.0 |
| c | 2.0 |
| d | 9.0 |

dtype: float64

[By Amina Delali]



school of ai

3- Reshaping and pivoting

stack & unstack

- **stack**: pivot **columns** label to **rows** indexes
- **unstack**: pivot **rows** indexes to **columns** labels

| | Code_type | number | colors | codes | value |
|---|-----------|--------|--------|-------------|-------|
| 0 | hex | 1 | green | #FF0000 | 5 |
| 1 | rgb | 1 | green | (0, 0, 255) | 7 |
| 2 | hex | 2 | blue | #0000FF | 8 |
| 3 | rgb | 2 | blue | (0, 255, 0) | 10 |
| 4 | hex | 3 | red | #FF0000 | 3 |
| 5 | rgb | 3 | red | (255, 0, 0) | 1 |

```
1 df11.stack()
```

```
0  Code_type      hex      1      green  #FF0000      5
   number      colors      codes      value
1  Code_type      rgb      1      green  (0, 0, 255)   7
   number      colors      codes      value
2  Code_type      hex      2      blue   #0000FF      8
   number      colors      codes      value
3  Code_type      rgb      2      blue   (0, 255, 0)  10
   number      colors      codes      value
4  Code_type      hex      3      red    #FF0000      3
   number      colors      codes      value
5  Code_type      rgb      3      red    (255, 0, 0)   1
   number      colors      codes      value
dtvpe: object
```

```
df11.stack().unstack()
```



school of a

3- Reshaping and pivoting

Pivot (long to wide)

```
1 df11.pivot(index="Code_type", columns="number", values="value")
```

| | Code_type | number | colors | codes | value |
|---|-----------|--------|--------|-------------|-------|
| 0 | hex | 1 | green | #FF0000 | 5 |
| 1 | rgb | 1 | green | (0, 0, 255) | 7 |
| 2 | hex | 2 | blue | #0000FF | 8 |
| 3 | rgb | 2 | blue | (0, 255, 0) | 10 |
| 4 | hex | 3 | red | #FF0000 | 3 |
| 5 | rgb | 3 | red | (255, 0, 0) | 1 |

3 unique values
3 columns

Only 2 unique
values for
Code_type

| | number | 1 | 2 | 3 |
|-----------|--------|---|----|---|
| Code_type | | | | |
| hex | | 5 | 8 | 3 |
| rgb | | 7 | 10 | 1 |

The values are obtained
from "value" by matching
"Code_type" and
"number" values

Melt (wide to long)

```
1 # melting all the columns in 2 columns "variable" and "value"  
2 pd.melt(df3)
```

df3

| | col1 | col2 |
|---|------|------|
| 0 | 1 | 2 |
| 1 | 3 | 4 |

| | variable | value |
|---|----------|-------|
| 0 | col1 | 1 |
| 1 | col1 | 3 |
| 2 | col2 | 2 |
| 3 | col2 | 4 |



school of ai

4- Group by Mechanics

groupby

```
1 # grouping values having same Code_type,  
2 # and applying on them sum method  
3 df11["value"].groupby(df11["Code_type"]).sum()
```

df11

| | Code_type | number | colors | codes | value |
|---|-----------|--------|--------|-------------|-------|
| 0 | hex | 1 | green | #FF0000 | 5 |
| 1 | rgb | 1 | green | (0, 0, 255) | 10 |
| 2 | hex | 2 | blue | #0000FF | 7 |
| 3 | rgb | 2 | blue | (0, 255, 0) | 3 |
| 4 | hex | 3 | red | #FF0000 | 8 |
| 5 | rgb | 3 | red | (255, 0, 0) | 1 |

$5 + 7 + 8 = 20$

Code_type
hex 20
rgb 14
Name: value, dtype: int64

```
1 # iterating over a group  
2 for i,j in df11["value"].groupby(df11["Code_type"]):  
3     print(i)  
4     print(j)
```

hex
0 5
2 7
4 8
Name: value, dtype: int64

rgb
1 10
3 3
5 1
Name: value, dtype: int64



school of a

4- Group by Mechanics

groupby

{'number': 'Gr1', 'value': 'Gr1', 'value2': 'Gr2', 'value3': 'Gr2'}

myDict

| | Code_type | number | colors | codes | value | value2 | value3 |
|---|-----------|--------|--------|-------------|-------|--------|--------|
| 0 | hex | 1 | green | #FF0000 | 5 | 10 | 1 |
| 1 | rgb | 1 | green | (0, 0, 255) | 10 | 11 | 1 |
| 2 | hex | 2 | blue | #0000FF | 7 | 12 | 1 |
| 3 | rgb | 2 | blue | (0, 255, 0) | 3 | 13 | 1 |
| 4 | hex | 3 | red | #FF0000 | 8 | 14 | 1 |
| 5 | rgb | 3 | red | (255, 0, 0) | 1 | 15 | 1 |

```
1 # grouping number and value values in Gr1
2 # and grouping colors and codes in Gr2
3 # then apply a sum on the grouped values
4 df11.groupby(myDict,axis=1).sum()
```

Gr1 values are summed together.
And Gr2 values are also summed together

| | Gr1 | Gr2 |
|---|-----|-----|
| 0 | 6 | 11 |
| 1 | 11 | 12 |
| 2 | 9 | 13 |
| 3 | 5 | 14 |
| 4 | 11 | 15 |
| 5 | 4 | 16 |



school of ai

5- Data aggregation

agg

```
1 my_group=df11["value"].groupby(df11["Code_type"])
2 # applying multiple aggregation operations on
3 my_group.agg(["sum","prod"])
```

Became an index

| | sum | prod |
|-----------|-----|------|
| Code_type | | |
| hex | 20 | 280 |
| rgb | 14 | 30 |

We could just write:
`groupby("Code_type")`

Columns kept columns

```
1 my_group2=df11.groupby(df11["Code_type"],as_index=False)
2 # "Code_type" is no longer an index, but a column
3 my_group2.mean()
```

Remains a column

| | Code_type | number | value | value2 | value3 |
|---|-----------|--------|----------|--------|--------|
| 0 | hex | 2.0 | 6.666667 | 12.0 | 1.0 |
| 1 | rgb | 2.0 | 4.666667 | 13.0 | 1.0 |



school of ai

6- Other aggregation operations

| | Code_type | number | colors | codes | value | value2 | value3 |
|---|-----------|--------|--------|-------------|-------|--------|--------|
| 0 | hex | 1 | green | #FF0000 | 5 | 10 | 2 |
| 1 | rgb | 1 | green | (0, 0, 255) | 10 | 11 | 31 |
| 2 | hex | 2 | blue | #0000FF | 7 | 12 | 62 |
| 3 | rgb | 2 | blue | (0, 255, 0) | 3 | 13 | 156 |
| 4 | hex | 3 | red | #FF0000 | 8 | 14 | 230 |
| 5 | rgb | 3 | red | (255, 0, 0) | 1 | 15 | 1000 |

The data values in “**value3**” column are grouped by intervals created by **cut**(same length) and **qcut** (same size)

cut & qcut

```
1 # grouping value3 by intervals of the same length
2 intervals=pd.cut(df11.value3,3)
3 my_group4= df11["value3"].groupby(intervals)
4 my_group4.count()
```

```
value3
(1.002, 334.667]      5
(334.667, 667.333]    0
(667.333, 1000.0]     1
Name: value3, dtype: int64
```

We see that the number values in each interval is different from the others

```
1 # grouping value3 by intervals of the same size
2 # same number of values in each interval
3 intervals=pd.qcut(df11.value3,3)
4 my_group5= df11["value3"].groupby(intervals)
5 my_group5.count()
```

```
value3
(1.999, 51.667]      2
(51.667, 180.667]    2
(180.667, 1000.0]    2
Name: value3, dtype: int64
```

We see that the number values in each interval are all the same == 2



school of ai

6- Other aggregation operations

crosstab

```
1 # for each value in column "number",  
2 # crosstab will calculate the frequencies  
3 # of each unique value in "colors"  
4  
5 pd.crosstab(df11.number, df11.colors)
```

For "number" value == 1,
corresponds: 2 values == green
and 0 value in blue and red in
"colors"

| colors | blue | green | red |
|--------|------|-------|-----|
| number | | | |
| 1 | 0 | 2 | 0 |
| 2 | 2 | 0 | 0 |
| 3 | 0 | 0 | 2 |

df11

| | Code_type | number | colors | codes | value | value2 | value3 |
|---|-----------|--------|--------|-------------|-------|--------|--------|
| 0 | hex | 1 | green | #FF0000 | 5 | 10 | 2 |
| 1 | rgb | 1 | green | (0, 0, 255) | 10 | 11 | 31 |
| 2 | hex | 2 | blue | #0000FF | 7 | 12 | 62 |
| 3 | rgb | 2 | blue | (0, 255, 0) | 3 | 13 | 156 |
| 4 | hex | 3 | red | #FF0000 | 8 | 14 | 230 |
| 5 | rgb | 3 | red | (255, 0, 0) | 1 | 15 | 1000 |



school of analytics

References

- Datawatch. What is data wrangling? On-line at <https://www.datawatch.com/what-is-data-wrangling/>. Accessed on 31-10-2018.
- Wes McKinney. Python for data analysis: Data wrangling with Pandas, NumPy, and IPython. O'Reilly Media, Inc, 2018.
- pydata.org. Pandas documentation. On-line at <https://pandas.pydata.org/>. Accessed on 19-10-2018.



Thank you!

FOR ALL YOUR TIME