

```
#include <stdio.h>
#include <stdlib.h>

#define MAX_STATES 10
#define MAX_TRANSITIONS 100

typedef struct {
    int state;
    int *epsilonTransitions;
    int epsilonCount;
} NFAStruct;

NFAStruct nfa[MAX_STATES];
int numStates;

void addEpsilonTransition(int fromState, int toState) {
    nfa[fromState].epsilonTransitions[nfa[fromState].epsilonCount++] = toState;
}

void computeEpsilonClosure(int state, int *closure, int *closureCount) {
    for (int i=0; i<*closureCount; i++) {
        if (closure[i] == state) {
            return;
        }
    }

    closure[(*closureCount)++] = state;

    for (int i=0; i<nfa[state].epsilonCount; i++) {
        computeEpsilonClosure(nfa[state].epsilonTransitions[i], closure,
closureCount);
    }
}

void printEpsilonClosure() {
    for (int i=0; i<numStates; i++) {
        int closure[MAX_STATES];
        int closureCount = 0;

        computeEpsilonClosure(i, closure, &closureCount);
        printf("Epsilon closure of state %d: { ", i);

        for (int j=0; j<closureCount; j++) {
            printf("%d ", closure[j]);
        }
        printf("}\n");
    }
}

int main() {
    printf("Enter number of states in the NFA: ");
    scanf("%d", &numStates);

    for (int i=0; i<numStates; i++) {
        nfa[i].state = i;
        nfa[i].epsilonTransitions = (int *)malloc(MAX_STATES * sizeof(int));
        nfa[i].epsilonCount = 0;
    }

    int numTransitions;

    printf("Enter number of epsilon transitions: ");
    scanf("%d", &numTransitions);

    printf("Enter transitions in format 'from to':\n");
```

```
    for (int i=0; i<numTransitions; i++) {
        int fromState, toState;
        scanf("%d %d", &fromState, &toState);
        addEpsilonTransition(fromState, toState);
    }

    printEpsilonClosure();

    for (int i=0; i<numStates; i++) {
        free(nfa[i].epsilonTransitions);
    }

    return 0;
}
```