Arch Linux

AISK

January, 2022

CONTENTS

Contents

1	Flas	sh USB	4			
	1.1	Download Arch ISO	4			
	1.2	USB Preparation	4			
	1.3	Flash ISO to USB	4			
	1.4	Boot Live Installer	4			
		1.4.1 Secure Boot	4			
		1.4.2 Boot	5			
2	Pre	Installation	6			
	2.1	Check Disk for bad sectors	6			
		2.1.1 Theory	6			
		2.1.2 Disk Info gathering	6			
		2.1.3 Check Disk for bad sectors	6			
3	Installation 8					
	3.1	ISO specific	8			
		3.1.1 Remove pcspkr	8			
		3.1.2 Connect to WiFi	8			
	3.2	Disk Partitioning	9			
		3.2.1 GPT UEFI	9			
	3.3	Mount FS	11			
	3.4	Install Arch	11			
	3.5	Customize settings	12			
		3.5.1 Time	12			
		3.5.2 Locales	12			
		3.5.3 Network	13			
	3.6	Install bootloader	13			
	3.7	Finish installation	13			
		3.7.1 Root Password	13			
		3.7.2 Finish installation	14			
4	Post-Installation 15					
	4.1	Disable pcspkr	15			
	4.2	Repository mirrors	15			

CONTENTS

5 GRUB			
	5.1	Configuration	16
	5.2	Colors	16
	5.3	Update	16
6	Ref	rences	17

1. Flash USB

1.1 Download Arch ISO

- 1. **Download Arch ISO from:** https://archlinux.org/download/
- 2. Verify Download:

```
user$ sha1sum <archlinux-YYYY.MM.DD-x86_64.iso>
```

1.2 USB Preparation

1. Create Partition Table

```
root# parted -s </dev/sdX> mktable gpt
```

2. Print change:

```
root# parted </dev/sdX> (p)rint [free]
```

1.3 Flash ISO to USB

- 1. Unmount any mounted FS on HARD DRIVE!
- 2. Flash to USB (/dev/sdX):

```
root# dd if=<./archlinux-YYYY.MM.DD-x86_64.iso> of=</dev/sdX>
[bs=4M | status=progress]
```

1.4 Boot Live Installer

1.4.1 Secure Boot

Make sure, that Secure Boot is Disabled!

1. During POST press Key to access BIOS/UEFI: BIOS/UEFI Menu Keys For All Vendors

- 2. Disable Secure Boot
- 3. Poweroff/Restart

1.4.2 Boot

- 1. Plug in Flashed USB
- 2. **During POST press Key to access Boot Menu:** Boot Menu Keys For All Vendors
- 3. Select USB entry.

2. Pre-Installation

2.1 Check Disk for bad sectors

2.1.1 Theory

- **Block:** group of sectors, every file must occupy at least 1 block. 0b file occupy whole block.
 - **512b** = good for lot of small files. More blocks = more metadata.
 - **4096b** = good for larger files, less metadata. Waste if there are small files.

2.1.2 Disk Info gathering

• Find disks (block devices):

```
user$ lsblk [-ap | -apf]
root# fdisk -l [/dev/sdX]
root# blkid
```

- Get raw disk info:
 - Disk size in bytes:

```
root# blockdev [-v] --getsize64 </dev/sdX[Y]>
```

- Disk block size in bytes:

```
root# blockdev [-v] --getbsz </dev/sdX[Y]>
```

- Check if disk is readonly (1 = ro, 0 = rw):

```
root# blockdev [-v] --getro </dev/sdX[Y]>
```

• See partitions:

```
root# parted </dev/sdX> (p)rint [free]
```

2.1.3 Check Disk for bad sectors

- 1. Unmount FS!
- 2. Check disk for bad blocks:

2. PRE-INSTALLATION

root# badblocks [-b 4096] [-w [-t 0xaa]] [-v] [-s]
</dev/sdX[Y]> | tee -a <0UTPUT_FILE>

3. Installation

3.1 ISO specific

3.1.1 Remove pcspkr

• Remove pcspkr module:

```
root# modprobe -r pcspkr
```

3.1.2 Connect to WiFi

```
1. Enable WiFi:
```

```
root# rfkill unblock wlan
```

2. Start services:

```
{\color{red}\textbf{root#}} \  \, \textbf{systemctl} \  \, \textbf{start wpa\_supplicant.service} \  \, \textbf{dhcpcd.service}
```

3. Configure WiFi:

```
File (/etc/wpa_supplicant/wpa_supplicant.conf):

ctrl_interface=/run/wpa_supplicant

update_config=1

country=<2-LETTER-ISO-CODE>

# WPA-PSK protected:

network={
    ssid="<ESSID>"
    scan_ssid=1 # Find hidden network
    key_mgmt=WPA-PSK
    psk="<PLAINTEXT-PASSWD>"
    #psk=<32byte-HEX-NUMBER>
    priority=1 # To which WiFi connect first
}

# WPA-EAP protected::
network={
```

```
ssid="<ESSID>"
           scan_ssid=1 # Find hidden network
          key_mgmt=WPA-EAP
           #eap=PEAP
           identity="<USERNAME>@<DOMAIN>"
           password="<PLAINTEXT-PASSWD>"
           #psk=<32byte-HEX-NUMBER>
           #ca_cert="/etc/cert/ca.pem"
           #phase1="peaplabel=0"
           phase2="auth=MSCHAPV2"
           priority=2 # To which WiFi connect first
   }
   # Unprotected:
   network={
       ssid="<ESSID>"
       scan_ssid=1 # Find hidden network
      key_mgmt=NONE
      priority=3 # To which WiFi connect first
   }
4. Connect to WiFi:
   root# wpa_supplicant -B -D wext -i <wlan0>
  -c </etc/wpa_supplicant/wpa_supplicant.conf>
```

3.2 Disk Partitioning

3.2.1 GPT UEFI

- 1. Get info about disks: See section 2.1.2.
- 2. Create GPT Partition Table

```
root# parted -s </dev/sdX> mktable gpt
```

- 3. Create Paritions:
 - (a) Enter cfdisk:

```
root# cfdisk </dev/sdX>
```

(b) Create EFI Partition (max 512MiB):

```
cfdisk> n
cfdisk> 512MiB
```

cfdisk> t

cfdisk> EFI System

```
(c) Create Root Partition:
       cfdisk> n
       cfdisk> (Enter)
   (d) Write Changes:
       cfdisk> W
       cfdisk> yes
   (e) Quit cfdisk:
       cfdisk> Q
4. Create filesystems:
   (a) Create FAT32 for EFI:
       root# mkfs.fat [-F 32] [-n "EFI"] </dev/sdX1>
   (b) Create Encrypted filesystem:
       i. Encrypt root partition:
          root# cryptsetup [--label "LUKS"] luksFormat </dev/sdX2>
          > YES
          > <PASSWORD>
          > <PASSWORD (VERIFY)>
       ii. Open Encrypted root partition:
          root# cryptsetup open --type luks </dev/sdX2> <luks_root>
          > <PASSWORD>
      iii. Create EXT4 for Root:
          root# mkfs.ext4 [-L "LUKS_ROOT"] </dev/mapper/luks_root>
5. OPTIONAL LUKS stuff:
    • Close LUKS:
       root# cryptsetup close <luks_root>
    • LUKS header:
      (a) See LUKS header:
          root# cryptsetup luksDump </dev/sdX2>
      (b) Make LUKS header backup:
          root# cryptsetup luksHeaderBackup </dev/sdX2>
          --header-backup-file <FILE>
      (c) Destroy LUKS header:
          root# cryptsetup luksErase </dev/sdX2>
      (d) restore LUKS header:
          root# cryptsetup luksHeaderRestore </dev/sdX2>
          --header-backup-file <FILE>
                           Page 10
```

3.3 Mount FS

1. Mount Root filesystem:

```
root# mount </dev/mapper/luks_root> </mnt/>
```

2. Create boot dir:

```
root# mkdir </mnt/boot/>
```

3. Mount boot partition:

```
root# mount </dev/sdX1> </mnt/boot/>
```

3.4 Install Arch

1. Check Mirrors:

```
root# cat /etc/pacman.d/mirrorlist
```

2. Download Arch:

This installs BASE packages, LINUX kernel and common LINUX-FIRMWARE for common hardware:

```
root# pacstrap </mnt/> base linux [linux-firmware]
```

3. Generate fstab:

```
root# genfstab -U </mnt/> >> /mnt/etc/fstab
```

- 4. Chroot into arch:
 - (a) Mount filesystems:

```
root# mount -t proc /proc/ </mnt/proc/>
root# mount --rbind /sys/ </mnt/sys/>
root# mount --make-rslave </mnt/sys/>
root# mount --rbind /dev/ </mnt/dev/>
root# mount --make-rslave </mnt/dev/>
```

(b) Chroot to root filesystem:

```
root# chroot </mnt/> /bin/bash
```

5. Set up DNS for chrooted environment:

```
[root#] echo "nameserver 1.1.1.1" > /etc/resolv.conf
```

- 6. Install packages:
 - Install vim:

```
[root#] [yes |] pacman -S vim
```

7. Add encrypted support to mkinitcpio:

File (/etc/mkinitcpio.conf):

```
HOOKS=(base udev autodetect modconf block encrypt filesystems keyboard fsck)
```

8. Recreate initramfs with encrypted support:

```
[root#] mkinitcpio -P
```

3.5 Customize settings

3.5.1 Time

1. Select timezone:

```
[root#] ln -sf </usr/share/zoneinfo/Europe/Copenhagen> /etc/localtime
```

2. Update HW clock (generate: /etc/adjtime):

```
[root#] hwclock --systohc
```

3.5.2 Locales

1. Select locales:

```
en_US.UTF-8 UTF-8
en_US ISO-8859-1
```

File (/etc/locale.gen):

2. Generate locales:

```
[root#] locale-gen
```

3. Set language:

```
File (/etc/locale.conf):
```

```
LANG=en_US.UTF-8
```

4. Set keyboard:

```
File (/etc/vconsole.conf):
```

KEYMAP=us

3.5.3 Network

1. Set hostname:

```
File (/etc/hostname): <hostname>
```

- 2. Install network packages:
 - Install WiFi control:

```
[root#] [yes |] pacman -S wpa_supplicant
```

• Install DHCP client:

```
[root#] [yes |] pacman -S dhcpcd
```

3.6 Install bootloader

1. Download packages:

```
[root#] [yes |] pacman -S efibootmgr grub
```

- 2. Make sure EFI partition is mounted! See section 3.3.
- 3. Install GRUB:

```
[root#] grub-install --target=x86_64-efi [--boot-directory=</boot/>]
--efi-directory=</boot/> --bootloader-id=<ArchLinux>
```

4. Find UUID of encrypted luks fs:

```
[root#] blkid | grep "crypto_LUKS"
```

5. Edit GRUB config for encryption: File (/etc/default/grub):

```
GRUB_CMDLINE_LINUX="cryptdevice=UUID=<UUID>:<luks_root> \
root=</dev/mapper/luks_root>"
```

6. Make/Update GRUB config file:

```
[root#] grub-mkconfig -o /boot/grub/grub.cfg
```

3.7 Finish installation

3.7.1 Root Password

1. Create root password:

```
[root#] passwd root
> <PASSWORD>
> <PASSWORD-VERIFY>
```

3.7.2 Finish installation

1. Exit chroot:

```
[root#] exit
```

2. Umount disk partitions:

```
root# umount -R </mnt/>
```

3. Reboot:

root# poweroff

4. Post-Installation

4.1 Disable pcspkr

1. Blacklist pcspkr module: File (/etc/modprobe.d/blacklist.conf): blacklist pcspkr

4.2 Repository mirrors

To be added

5. GRUB

- 5.1 Configuration
- 5.2 Colors
- 5.3 Update

6. References

- App list: https://wiki.archlinux.org/title/List_of_applications
- Boot Procedure: https://wiki.archlinux.org/title/Arch_boot_process
- Partition Optimal: Partitioning
- Booted from UEFI:

root# ls /sys/firmware/efi/efivars

WIKI