
aisquared

The AI Squared Team

Jan 11, 2023

DOCUMENTATION

1	Installation	3
1.1	aisquared	3
1.1.1	aisquared package	3
1.1.1.1	Module contents	3
1.1.1.2	Subpackages	3
2	Changelog	51
	Python Module Index	55
	Index	57



This package contains utilities to interact with the AI Squared technology stack, particularly with developing and deploying models to the AI Squared Platform or other applications developed through the AI Squared JavaScript SDK.

Current Production Version: 0.3.1

INSTALLATION

This package is available through [Pypi](#) and can be installed by running the following command:

```
pip install aisquared
```

Alternatively, the latest version of the software can be installed directly from GitHub using the following command:

```
pip install git+https://github.com/AISquaredInc/aisquared
```

1.1 aisquared

1.1.1 aisquared package

1.1.1.1 Module contents

This package contains utilities to interact with the AI Squared technology stack, particularly with developing and deploying models to the AI Squared Browser Extension or other applications developed through the AI Squared JavaScript SDK.

1.1.1.2 Subpackages

aisquared.base package

Module contents

The aisquared.base package contains both some basic objects that are used across the aisquared package backend and some objects which are designed to facilitate simple use cases of the technology.

Submodules

aisquared.base.BaseObject module

class aisquared.base.BaseObject.BaseObject

Bases: object

Base class used for all other classes within the aisquared package. This class is not meant to be used by any end user of this package, but is rather used throughout this package as a parent class.

to_dict() → dict

Get the object as a dictionary

to_json() → str

Return the object as a json string

aisquared.base.CustomObject module

class aisquared.base.CustomObject.CustomObject(*class_name: str, **kwargs*)

Bases: *BaseObject*

Custom class that allows the user to define custom classes for configuration

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.base.CustomObject(
    'MyClass',
    key1 = 'foo',
    key2 = 'bar'
)
>>> my_obj.to_dict()
{'className': 'MyClass', 'params': {'key1': 'foo', 'key2': 'bar'}}
```

to_dict() → dict

Get the object as a dictionary

aisquared.base.rendering module

Some allowed configuration parameters - not meant to be directly called by the end user

aisquared.base.stages module

Some allowed configuration parameters - not designed to be directly called by the user

aisquared.config package

Module contents

The aisquared.config subpackage contains utilities and objects for packaging aisquared configuration steps and models.

For in-depth examples of how to build out .air files using the utilities and classes in this library, please visit our GitHub repository at <https://github.com/AISquaredInc/airFiles>

Subpackages

aisquared.config.analytic package

Module contents

The aisquared.config.analytic subpackage contains objects for packaging individual analytics.

Submodules

aisquared.config.analytic.DeployedAnalytic module

class aisquared.config.analytic.DeployedAnalytic.**DeployedAnalytic**(url: str, input_type: str, secret: str = 'request', header: Optional[dict] = None)

Bases: *BaseObject*

Interaction with a remote analytic

Example usage:

```
>>> import aisquared
>>> analytic = aisquared.config.analytic.DeployedAnalytic(
    'analytic_url',
    'text'
)
>>> analytic.to_dict()
{'className': 'DeployedAnalytic',
 'params': {'url': 'analytic_url',
 'inputType': 'text',
 'secret': 'request',
 'header': None}}
```

property header

property input_type

property secret

to_dict() → dict

Get the object as a dictionary

property url

aisquared.config.analytic.DeployedModel module

```
class aisquared.config.analytic.DeployedModel.DeployedModel(url: str, input_type: str, secret: str =  
    'request', header: Optional[dict] =  
    None)
```

Bases: *BaseObject*

Interaction with a remote model

Example usage:

```
>>> import aisquared  
>>> analytic = aisquared.config.analytic.DeployedModel(  
    'model_url',  
    'text'  
)  
>>> analytic.to_dict()  
{'className': 'DeployedModel',  
 'params': {'url': 'model_url',  
 'inputType': 'text',  
 'secret': 'request',  
 'header': None}}
```

property header

property input_type

property secret

to_dict() → dict

Get the config object as a dictionary

property url

aisquared.config.analytic.LocalAnalytic module

```
class aisquared.config.analytic.LocalAnalytic.LocalAnalytic(path: str, input_type: str, all: bool =  
    False)
```

Bases: *BaseObject*

Interaction with an analytic (lookup table) saved to the local file system

Example usage:

```
>>> import aisquared  
>>> analytic = aisquared.config.analytic.LocalAnalytic(  
    'analytic_path',  
    'text'  
)  
>>> analytic.to_dict()  
{'className': 'LocalAnalytic',  
 'params': {'path': 'analytic_path',  
 'inputType': 'text',  
 'all': False}}
```

property all

property input_type

property path

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.analytic.LocalModel module

class aisquared.config.analytic.LocalModel.**LocalModel**(*path: str, input_type: str*)

Bases: *BaseObject*

Interaction with a model currently saved to the local file system

Example usage:

```
>>> import aisquared
>>> analytic = aisquared.config.analytic.LocalModel(
    'model_path',
    'text'
)
>>> analytic.to_dict()
{'className': 'LocalModel',
 'params': {'path': 'model_path',
            'inputType': 'text'}}
```

property input_type

property path

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.analytic.ReverseMLWorkflow module

class aisquared.config.analytic.ReverseMLWorkflow.**ReverseMLWorkflow**(*bucket: str, filename: str, column: str, input_type: str, period: Optional[int] = None, secret: str = ""*)

Bases: *BaseObject*

Interaction with a ReverseML CSV stored in S3

Example usage:

```
>>> import aisquared
>>> analytic = aisquared.config.analytic.ReverseMLWorkflow(
    'bucket_name',
    'file_name',
    'column_name',
    'text'
)
```

(continues on next page)

(continued from previous page)

```
>>> analytic.to_dict()
{'className': 'ReverseMLWorkflow',
 'params': {'bucket': 'bucket_name',
 'fileName': 'file_name',
 'inputType': 'text',
 'column': 'column_name',
 'period': None,
 'secret': ''}}
```

property bucket

property column

property filename

property input_type

property period

property secret

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.feedback package

Module contents

The `aisquared.config.feedback` subpackage contains objects for configuring feedback in aisquared models.

Submodules

aisquared.config.feedback.BinaryFeedback module

class `aisquared.config.feedback.BinaryFeedback`(*label_map: list*)

Bases: *BaseObject*

Feedback for binary classification

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.feedback.BinaryFeedback(['class1', 'class2'])
>>> my_obj.to_dict()
{'className': 'BinaryFeedback', 'params': {'labelMap': ['class1', 'class2']}}
```

property label_map

to_dict() → dict

Return the object as a dictionary

aisquared.config.feedback.ModelFeedback module

class aisquared.config.feedback.ModelFeedback.**ModelFeedback**

Bases: *BaseObject*

Feedback object for questions and answers for an individual model.

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.feedback.ModelFeedback()
>>> my_obj.add_question(
    'How is the model performing?',
    choices = ['very poorly', 'poorly', 'neutral', 'well', 'very well']
)
>>> my_obj.add_question(
    'Any additional feedback?',
    'text'
)
>>> my_obj.to_dict()
{'className': 'ModelFeedback',
 'params': {'questions': [{'question': 'How is the model performing?',
 'answerType': 'singleChoice',
 'choices': ['very poorly', 'poorly', 'neutral', 'well', 'very well']},
 {'question': 'Any additional feedback?', 'answerType': 'text'}]}}
```

add_question(*question: str, answer_type: str = 'singleChoice', choices: list = []*)

Add a question to be asked.

Parameters

- **question** (*str*) – The question to be asked.
- **answer_type** (*str (default 'singleChoice')*) – One of either ‘singleChoice’, ‘multiChoice’, or ‘text’
- **choices** (*list (default [])*) – The choices to be provided, if *answer_type* is ‘singleChoice’ or ‘multiChoice’

to_dict() → dict

Return the object as a dictionary

aisquared.config.feedback.MulticlassFeedback module

class aisquared.config.feedback.MulticlassFeedback.**MulticlassFeedback**(*label_map: list*)

Bases: *BaseObject*

Feedback for multiclass classification

Example Usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.feedback.MulticlassFeedback(['class1', 'class2',
↪ 'class3'])
>>> my_obj.to_dict()
```

(continues on next page)

(continued from previous page)

```
{'className': 'MulticlassFeedback',  
'params': {'labelMap': ['class1', 'class2', 'class3']}}
```

property `label_map`

to_dict() → dict

Return the object as a dictionary

aisquared.config.feedback.QualitativeFeedback module

class `aisquared.config.feedback.QualitativeFeedback.QualitativeFeedback`

Bases: `BaseObject`

Feedback object for questions and answers for individual predictions.

Example usage:

```
>>> import aisquared  
>>> my_obj = aisquared.config.feedback.QualitativeFeedback()  
>>> my_obj.add_question('Any additional feedback?', 'text')  
>>> my_obj.to_dict()  
{'className': 'QualitativeFeedback',  
'params': {'questions': [{'question': 'Any additional feedback?',  
'answerType': 'text'}]}}
```

add_question(*question: str, answer_type: str = 'singleChoice', choices: list = []*)

Add a question to be asked.

Parameters

- **question** (*str*) – The question to be asked.
- **answer_type** (*str* (default 'singleChoice')) – One of either 'singleChoice', 'multiChoice', or 'text'
- **choices** (*list* (default [])) – The choices to be provided, if *answer_type* is 'singleChoice' or 'multiChoice'

to_dict() → dict

Return the object as a dictionary

aisquared.config.feedback.RegressionFeedback module

class `aisquared.config.feedback.RegressionFeedback.RegressionFeedback`

Bases: `BaseObject`

Feedback for regression

Example usage:

```
>>> import aisquared  
>>> my_obj = aisquared.config.feedback.RegressionFeedback()  
>>> my_obj.to_dict()  
{'className': 'RegressionFeedback', 'params': {}}
```

to_dict() → dict

Return the object as a dictionary

aisquared.config.feedback.SimpleFeedback module

class aisquared.config.feedback.SimpleFeedback.**SimpleFeedback**

Bases: *BaseObject*

Simple thumbs-up/thumbs-down feedback for predictions

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.feedback.SimpleFeedback()
>>> my_obj.to_dict()
{'className': 'SimpleFeedback', 'params': {}}
```

to_dict() → dict

Return the object as a dictionary

aisquared.config.harvesting package

Module contents

The aisquared.config.harvesting subpackage contains objects for configuring harvesting of data.

Submodules

aisquared.config.harvesting.ImageHarvester module

class aisquared.config.harvesting.ImageHarvester.**ImageHarvester**(*how: str = 'all'*)

Bases: *BaseObject*

Object to harvest images

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.harvesting.ImageHarvester()
>>> my_obj.to_dict()
{'className': 'ImageHarvester', 'params': {'how': 'all'}}
```

property how

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.harvesting.InputHarvester module

```
class aisquared.config.harvesting.InputHarvester.InputHarvester(input_type: str = 'text',  
                                                                max_length: Optional[int] =  
                                                                None, features: Optional[list] =  
                                                                None)
```

Bases: *BaseObject*

Object to harvest user-input text

Example usage:

```
>>> import aisquared  
>>> my_obj = aisquared.config.harvesting.InputHarvester()  
>>> my_obj.to_dict()  
{'className': 'InputHarvester',  
 'params': {'inputType': 'text', 'maxLength': None, 'features': None}}
```

property features

property input_type

property max_length

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.harvesting.QueryParameterHarvester module

```
class aisquared.config.harvesting.QueryParameterHarvester.QueryParameterHarvester(query_keys:  
                                                                Union[str,  
                                                                list],  
                                                                url_locations:  
                                                                Union[str,  
                                                                list], at-  
                                                                tributes:  
                                                                Union[str,  
                                                                list])
```

Bases: *BaseObject*

Harvester for Query Parameters

Example usage:

```
>>> import aisquared  
>>> my_obj = aisquared.config.harvesting.QueryParameterHarvester(  
    'test_key',  
    'test_url',  
    'test_attribute'  
)  
>>> my_obj.to_dict()  
{'className': 'QueryParameterHarvester',  
 'params': {'queryKeys': ['test_key'],  
            'urlLocations': ['test_url'],  
            'attributes': ['test_attribute']}}
```


property attributes

property query_keys

to_dict() → dict

Get the configuration object as a dictionary

property url_locations

aisquared.config.harvesting.TextHarvester module

class aisquared.config.harvesting.TextHarvester.**TextHarvester**(*how: str = 'all', regex: Optional[str] = None, flags: str = 'gu', body_only: bool = False, keywords: Optional[Union[str, list]] = None, limit: Optional[int] = None*)

Bases: *BaseObject*

Object to harvest text

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.harvesting.TextHarvester(
    how = 'all',
    body_only = True
)
>>> my_obj.to_dict()
{'className': 'TextHarvester',
 'params': {'how': 'all',
 'regex': None,
 'flags': 'gu',
 'bodyOnly': True,
 'limit': None}}
```

property body_only

property flags

property how

property limit

property regex

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.postprocessing package

Module contents

The aisquared.config.postprocessing subpackage contains objects for configuring how predictions are postprocessed.

Submodules

aisquared.config.postprocessing.BinaryClassification module

```
class aisquared.config.postprocessing.BinaryClassification.BinaryClassification(label_map:  
                                                                    list,  
                                                                    threshold:  
                                                                    float = 0.5)
```

Bases: *BaseObject*

Postprocessing configuration object for binary classification

Example usage

```
>>> import aisquared  
>>> my_obj = aisquared.config.postprocessing.BinaryClassification(  
    ['class1', 'class2']  
)  
>>> my_obj.to_dict()  
{'className': 'BinaryClassification',  
 'params': {'labelMap': ['class1', 'class2'], 'threshold': 0.5}}
```

property label_map

property threshold

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.postprocessing.MulticlassClassification module

```
class aisquared.config.postprocessing.MulticlassClassification.MulticlassClassification(label_map:  
                                                                    list)
```

Bases: *BaseObject*

Postprocessing configuration object for multiclass classification

Example usage:

```
>>> import aisquared  
>>> my_obj = aisquared.config.postprocessing.MulticlassClassification(  
    ['class1', 'class2', 'class3']  
)  
>>> my_obj.to_dict()  
{'className': 'MulticlassClassification',  
 'params': {'labelMap': ['class1', 'class2', 'class3']}}
```

property **label_map**

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.postprocessing.ObjectDetection module

class aisquared.config.postprocessing.ObjectDetection.**ObjectDetection**(*label_map: list, threshold: float = 0.5*)

Bases: *BaseObject*

Postprocessing configuration object for object detection

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.postprocessing.ObjectDetection(
    ['class1', 'class2', 'class3']
)
>>> my_obj.to_dict()
{'className': 'ObjectDetection',
 'params': {'labelMap': ['class1', 'class2', 'class3'], 'threshold': 0.5}}
```

property **label_map**

property **threshold**

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.postprocessing.Regression module

class aisquared.config.postprocessing.Regression.**Regression**(*min: Optional[Union[int, float]] = None, max: Optional[Union[int, float]] = None, round: bool = False*)

Bases: *BaseObject*

Postprocessing configuration object for Regression

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.postprocessing.Regression(
    10,
    100
)
>>> my_obj.to_dict()
{'className': 'Regression', 'params': {'min': 10, 'max': 100, 'round': False}}
```

property **max**

property **min**

property **round**

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.preprocessing package

Module contents

The **aisquared.config.preprocessing** subpackage contains utilities to configure the preprocessing of data in the data pipeline. It contains

three separate subpackages, **aisquared.config.preprocessing.text**, **aisquared.config.preprocessing.image**, and **aisquared.config.preprocessing.tabular**, which configure the preprocessing of different types of data.

Subpackages

aisquared.config.preprocessing.image package

Module contents

The **aisquared.config.preprocessing.image** subpackage contains objects for configuring image preprocessing.

Submodules

aisquared.config.preprocessing.image.ImagePreprocessing module

class **aisquared.config.preprocessing.image.ImagePreprocessing.ImagePreprocessor** (*steps: Optional[list] = None*)

Bases: *BaseObject*

Preprocessor object for image data

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.image.ImagePreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.image.AddValue(255.0)
)
```

add_step(*step*)

Add a step to the preprocessor object

property **step_dict**

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.preprocessing.image.Steps module**class** aisquared.config.preprocessing.image.Steps.**AddValue**(value: Union[int, float])Bases: *BaseObject*

Preprocessing step to add a value to all pixels in an image

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.image.ImagePreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.image.AddValue(255.0)
)
```

to_dict() → dict

Get the configuration object as a dictionary

property value**class** aisquared.config.preprocessing.image.Steps.**ConvertToColor**(color: str)Bases: *BaseObject*

Preprocessing step to convert images to a color scheme

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.image.ImagePreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.image.ConvertToColor('RGB')
)
```

property color**to_dict()** → dict

Get the configuration object as a dictionary

class aisquared.config.preprocessing.image.Steps.**DivideValue**(value: Union[int, float])Bases: *BaseObject*

Preprocessing step to divide all pixels in an image by a value

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.image.ImagePreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.image.DivideValue(255.0)
)
```

to_dict() → dict

Get the configuration object as a dictionary

property value

class aisquared.config.preprocessing.image.Steps.**MultiplyValue**(value: Union[int, float])

Bases: *BaseObject*

Preprocessing step to multiply all pixels in an image by a value

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.image.ImagePreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.image.MultiplyValue(2.0)
)
```

to_dict() → dict

Get the configuration object as a dictionary

property value

class aisquared.config.preprocessing.image.Steps.**Resize**(size: list, method: str = 'bilinear',
preserve_aspect_ratio: bool = False)

Bases: *BaseObject*

Preprocessing step to resize an image

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.image.ImagePreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.image.Resize([100, 100])
)
```

property method

property preserve_aspect_ratio

property size

to_dict() → dict

Get the configuration object as a dictionary

class aisquared.config.preprocessing.image.Steps.**SubtractValue**(value: Union[int, float])

Bases: *BaseObject*

Preprocessing step to subtract a value from all pixels in an image

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.image.ImagePreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.image.SubtractValue(255.0)
)
```

to_dict() → dict

Get the configuration object as a dictionary

property value

aisquared.config.preprocessing.tabular package

Module contents

The aisquared.config.preprocessing.tabular subpackage contains objects for preprocessing tabular data.

Submodules

aisquared.config.preprocessing.tabular.Steps module

class aisquared.config.preprocessing.tabular.Steps.**DropColumn**(column: int)

Bases: *BaseObject*

Drop a column from tabular data

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.tabular.TabularPreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.tabular.DropColumn(
        3
    )
)
```

property column

to_dict() → dict

Get the configuration object as a dictionary

class aisquared.config.preprocessing.tabular.Steps.**MinMax**(mins: list, maxs: list, columns: Optional[list] = None)

Bases: *BaseObject*

Min-Max Scaling preprocessing step

Min-Max Scaling takes all associated columns and maps values relative to the minimum and maximum values of the training data.

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.tabular.TabularPreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.tabular.MinMax(
        [0, 1.1, 2],
        [0.2, 14, 18.3]
    )
)
```

property columns

property maxs

property mins

to_dict() → dict

Get the configuration object as a dictionary

class aisquared.config.preprocessing.tabular.Steps.**OneHot**(*column: int, values: list*)

Bases: *BaseObject*

One Hot encoding preprocessing step

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.tabular.TabularPreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.tabular.OneHot(
        6,
        ['one', 'two', 'three']
    )
)
```

property column

to_dict() → dict

Get the configuration object as a dictionary

property values

class aisquared.config.preprocessing.tabular.Steps.**ZScore**(*means: list, stds: list, columns: Optional[Union[int, list]] = None*)

Bases: *BaseObject*

Z-Score normalization preprocessing step

Z-Score normalization takes each supplied column value, subtracts that column's provided mean, and divides by the provided standard deviation.

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.tabular.TabularPreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.tabular.ZScore(
        [0, 1, 2],
        [0.2, 0.4, 0.6]
    )
)
```

property columns

property means

property stds

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.preprocessing.tabular.TabularPreprocessing module

class aisquared.config.preprocessing.tabular.TabularPreprocessing.**TabularPreprocessor**(*steps: Optional[list] = None*)

Bases: *BaseObject*

Preprocessor object for tabular data

Example usage:

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.tabular.TabularPreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.tabular.ZScore(
        [0, 1, 2],
        [0.2, 0.4, 0.6]
    )
)
```

add_step(*step*)

Add a step to the preprocessor object

to_dict()

Get the configuration object as a dictionary

aisquared.config.preprocessing.text package**Module contents**

The aisquared.config.preprocessing.text subpackage contains objects for preprocessing text data.

Submodules**aisquared.config.preprocessing.text.Steps module**

class aisquared.config.preprocessing.text.Steps.**ConvertToCase**(*lowercase: bool = True*)

Bases: *BaseObject*

Text preprocessing object to convert inputs to all lowercase or all uppercase

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.text.TextPreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.text.ConvertToCase()
)
```

property lowercase

to_dict() → dict

Get the configuration object as a dictionary

```
class aisquared.config.preprocessing.text.Steps.ConvertToVocabulary(vocabulary: dict,  
                                                                    start_character: int = 1,  
                                                                    oov_character: int = 2,  
                                                                    max_vocab: Optional[int]  
                                                                    = None)
```

Bases: *BaseObject*

Text preprocessing object to convert tokens to integer vocabularies

Example usage:

```
>>> import aisquared  
>>> preprocessor = aisquared.config.preprocessing.text.TextPreprocessor()  
>>> preprocessor.add_step(  
    aisquared.config.preprocessing.text.ConvertToVocabulary(  
        {  
            'test' : 3,  
            'vocabulary' : 4  
        }  
    )  
)
```

property max_vocab

property oov_character

property start_character

to_dict() → dict

Get the configuration object as a dictionary

property vocabulary

```
class aisquared.config.preprocessing.text.Steps.PadSequences(pad_character: int = 0, length: int =  
                                                             128, pad_location: str = 'post',  
                                                             truncate_location: str = 'post')
```

Bases: *BaseObject*

Text preprocessing object to pad sequences

Example usage:

```
>>> import aisquared  
>>> preprocessor = aisquared.config.preprocessing.text.TextPreprocessor()  
>>> preprocessor.add_step(  
    aisquared.config.preprocessing.text.PadSequences()  
)
```

property length

property pad_character

property pad_location

to_dict() → dict

Get the configuration object as a dictionary

property truncate_location

```
class aisquared.config.preprocessing.text.Steps.RemoveCharacters(remove_digits: bool = True,
                                                                remove_punctuation: bool =
                                                                True)
```

Bases: *BaseObject*

Preprocessing step to remove characters from text

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.text.TextPreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.text.RemoveCharacters()
)
```

property remove_digits

property remove_punctuation

to_dict() → dict

Get the configuration object as a dictionary

```
class aisquared.config.preprocessing.text.Steps.Tokenize(split_sentences: bool = False,
                                                           split_words: bool = True, token_pattern:
                                                           str = '\x08\\w\\w+\x08')
```

Bases: *BaseObject*

Preprocessing Step to tokenize text

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.text.TextPreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.text.Tokenize()
)
```

property split_sentences

property split_words

to_dict() → dict

Get the configuration object as a dictionary

property token_pattern

```
class aisquared.config.preprocessing.text.Steps.Trim
```

Bases: *BaseObject*

Text preprocessing class to trim whitespace from text

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.text.TextPreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.text.Trim()
)
```

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.preprocessing.text.TextPreprocessing module

class aisquared.config.preprocessing.text.TextPreprocessing.**TextPreprocessor**(*steps:*
Optional[list] = None)

Bases: *BaseObject*

Preprocessor object for natural language

Example usage:

```
>>> import aisquared
>>> preprocessor = aisquared.config.preprocessing.text.TextPreprocessor()
>>> preprocessor.add_step(
    aisquared.config.preprocessing.text.Tokenize()
)
```

add_step(*step*)

Add a step to the preprocessor object

property **step_dict**

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.rendering package

Module contents

The aisquared.config.rendering subpackage contains objects for configuring how rendering of predictions is to occur.

Submodules

aisquared.config.rendering.BarChartRendering module

```
class aisquared.config.rendering.BarChartRendering.BarChartRendering(label: str, id: str,
                                                                    chart_name: str,
                                                                    chart_colors: list,
                                                                    chart_labels: list,
                                                                    container_id: str,
                                                                    prediction_name_key: str,
                                                                    prediction_value_key: str,
                                                                    prediction_name_value:
                                                                    str, width: str = 'auto',
                                                                    height: str = 'auto',
                                                                    xOffset: str = '0', yOffset:
                                                                    str = '0')
```

Bases: *BaseObject*

Rendering class for rendering a Bar Chart

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.rendering.BarChartRendering(
    'my bar chart',
    'barChart1Label',
    'MyBarChart',
    ['red', 'blue'],
    ['label1', 'label2'],
    'my_container',
    'key',
    'value',
    'name'
)
>>> my_obj.to_dict()
{'className': 'BarChartRendering',
 'label': 'my bar chart',
 'params': {'id': 'barChart1Label',
            'chartName': 'MyBarChart',
            'chartColors': ['red', 'blue'],
            'chartLabels': ['label1', 'label2'],
            'containerId': 'my_container',
            'predictionNameKey': 'key',
            'predictionValueKey': 'value',
            'predictionNameValue': 'name',
            'width': 'auto',
            'height': 'auto',
            'xOffset': '0',
            'yOffset': '0'}}
```

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.rendering.ContainerRendering module

```
class aisquared.config.rendering.ContainerRendering.ContainerRendering(label: str, id: str,  
query_selector: str,  
width: str = 'auto',  
height: str = 'auto',  
display: str = 'flex',  
xOffset: str = '0',  
yOffset: str = '0',  
position: str = '',  
orientation: str =  
'column')
```

Bases: *BaseObject*

Rendering for a container

Example usage:

```
>>> import aisquared  
>>> my_obj = aisquared.config.rendering.ContainerRendering(  
    'my container',  
    'myContainerID',  
    "[data-id='tabpanel-general']"  
)  
>>> my_obj.to_dict()  
{'className': 'ContainerRendering',  
 'label': 'my container',  
 'params': {'id': 'myContainerID',  
 'width': 'auto',  
 'height': 'auto',  
 'display': 'flex',  
 'xOffset': '0',  
 'yOffset': '0',  
 'position': '',  
 'orientation': 'column',  
 'querySelector': "[data-id='tabpanel-general']"}}
```

property display

property height

property id

property label

property orientation

property position

property query_selector

to_dict() → dict

Get the configuration object as a dictionary

property width

property xOffset

property yOffset

aisquared.config.rendering.DashboardReplacementRendering module

```
class aisquared.config.rendering.DashboardReplacementRendering.DashboardReplacementRendering(anchor_selector: str,
where_replace: str,
label: str)
    """
    """
```

Bases: *BaseObject*

Rendering for dashboard replacement

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.rendering.DashboardReplacementRendering(
    'test_anchor_selector'
)
>>> my_obj.to_dict()
{'className': 'DashboardReplacementRendering',
 'label': '',
 'params': {'anchorSelector': 'test_anchor_selector', 'whereReplace': ''}}
```

property anchor_selector

property label

to_dict() → dict

Get the configuration object as a dictionary

property where_replace

aisquared.config.rendering.DocumentRendering module

```
class aisquared.config.rendering.DocumentRendering.DocumentRendering(prediction_key: str =
                                                                    'className', words:
                                                                    Optional[Union[list, dict,
                                                                    str]] = None, documents:
                                                                    Optional[Union[list, dict,
                                                                    str]] = None,
                                                                    include_probability: bool
                                                                    = False, probability_key:
                                                                    str = 'probability',
                                                                    underline_color: str =
                                                                    'blue', classes:
                                                                    Optional[list] = None,
                                                                    threshold_key:
                                                                    Optional[str] = None,
                                                                    threshold_value:
                                                                    Optional[Union[int,
                                                                    float]] = None)
```

Bases: *BaseObject*

Object which dictates how to render predictions on entire documents

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.rendering.DocumentRendering()
>>> my_obj.to_dict()
{'className': 'DocumentRendering',
 'params': {'predictionKey': 'className',
 'words': None,
 'documents': None,
 'includeProbability': False,
 'probabilityKey': 'probability',
 'underlineColor': 'blue',
 'classes': None,
 'thresholdKey': None,
 'thresholdValue': None}}
```

property classes

property documents

property include_probability

property prediction_key

property probability_key

property threshold_key

property threshold_value

to_dict() → dict

Get the configuration object as a dictionary

property underline_color

property words

aisquared.config.rendering.DoughnutChartRendering module

```

class aisquared.config.rendering.DoughnutChartRendering.DoughnutChartRendering(label: str, id:
    str,
    chart_name:
    str,
    chart_colors:
    list,
    chart_labels:
    list,
    container_id:
    str, predic-
    tion_name_key:
    str, predic-
    tion_value_key:
    str, predic-
    tion_name_value:
    str, dis-
    play_legend:
    bool,
    legend_icon:
    str, width: str =
    'auto',
    height: str =
    'auto',
    xOffset: str =
    '0', yOffset:
    str = '0')

```

Bases: [BaseObject](#)

Rendering class for rendering a Doughnut Chart

Example usage:

```

>>> import aisquared
>>> my_obj = aisquared.config.rendering.DoughnutChartRendering(
    'my doughnut chart',
    'MyDoughnutChartID',
    'MyDoughnutChart',
    ['red', 'blue'],
    ['label1', 'label2'],
    'my_countainer_id',
    'key',
    'value',
    'name',
    True,
    'circle'
)
>>> my_obj.to_dict()
{'className': 'DoughnutChartRendering',
 'label': 'my doughnut chart',
 'params': {'id': 'MyDoughnutChartID',
 'chartName': 'MyDoughnutChart',
 'chartColors': ['red', 'blue'],

```

(continues on next page)

(continued from previous page)

```
'chartLabels': ['label1', 'label2'],
'containerId': 'my_container_id',
'predictionNameKey': 'key',
'predictionValueKey': 'value',
'predictionNameValue': 'name',
'displayLegend': True,
'legendIcon': 'circle',
'width': 'auto',
'height': 'auto',
'xOffset': '0',
'yOffset': '0'}}
```

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.rendering.FilterRendering module

```
class aisquared.config.rendering.FilterRendering.FilterRendering(source: str, key: str, qualifier:
                                                                str, value: Union[list, str, int,
                                                                float])
```

Bases: *BaseObject*

Object which dictates how predictions are to be passed to downstream analytics

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.rendering.FilterRendering(
    'inputs',
    'key',
    'gt',
    0.2
)
>>> my_obj.to_dict()
{'className': 'FilterRendering',
 'params': {'source': 'inputs', 'key': 'key', 'qualifier': 'gt', 'value': 0.2}}
```

property key**property qualifier****property source****to_dict()** → dict

Get the configuration object as a dictionary

property value

aisquared.config.rendering.HTMLTagRendering module

```
class aisquared.config.rendering.HTMLTagRendering.HTMLTagRendering(label: str, id: str,
                                                                    container_id: str,
                                                                    html_content: str,
                                                                    extra_content_tag: str,
                                                                    injection_action: str,
                                                                    prediction_name_key: str,
                                                                    prediction_value_key: str,
                                                                    prediction_name_value: str,
                                                                    content: str = "")
```

Bases: *BaseObject*

Rendering for HTML tags

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.rendering.HTMLTagRendering(
    'my HTML tag',
    'MyHTMLTagRenderingID',
    'MyContainerID',
    '<p>Example Text</p>',
    'extra_tag',
    'append',
    'name_key',
    'value_key',
    'name_value'
)
>>> my_obj.to_dict()
{'className': 'HTMLTagRendering',
 'label': 'my HTML tag',
 'params': {'id': 'MyHTMLTagRenderingID',
            'containerId': 'MyContainerID',
            'htmlContent': '<p>Example Text</p>',
            'extraContentTag': 'extra_tag',
            'injectionAction': 'append',
            'predictionNameKey': 'name_key',
            'predictionValueKey': 'value_key',
            'predictionNameValue': 'name_value',
            'content': ''}}
```

to_dict() → dict

Return the configuration object as a dictionary

aisquared.config.rendering.ImageRendering module

```
class aisquared.config.rendering.ImageRendering.ImageRendering(color: str = 'blue', thickness: str =  
    '5px', placement: str =  
    'bottomleft', include_probability:  
    bool = False, badge_color: str =  
    'white', font_color: str = 'black',  
    font_size: str = '5px', classes:  
    Optional[list] = None,  
    threshold_key: Optional[str] =  
    None, threshold_value:  
    Optional[Union[int, float]] =  
    None)
```

Bases: *BaseObject*

Object which dictates how to render images

Example usage:

```
>>> import aisquared  
>>> my_obj = aisquared.config.rendering.ImageRendering()  
>>> my_obj.to_dict()  
{'className': 'ImageRendering',  
 'params': {'color': 'blue',  
 'thickness': '5px',  
 'placement': 'bottomleft',  
 'includeProbability': False,  
 'badgeColor': 'white',  
 'fontColor': 'black',  
 'fontSize': '5px',  
 'classes': None,  
 'thresholdKey': None,  
 'thresholdValue': None}}
```

property badge_color

property classes

property color

property font_color

property font_size

property include_probability

property placement

property thickness

property threshold_key

property threshold_value

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.rendering.LineChartRendering module

```
class aisquared.config.rendering.LineChartRendering.LineChartRendering(label: str, id: str,
                                                                    chart_name: str,
                                                                    chart_colors: list,
                                                                    chart_labels: list,
                                                                    container_id: str,
                                                                    prediction_name_key:
                                                                    str,
                                                                    prediction_value_key:
                                                                    str, predic-
                                                                    tion_name_value: str,
                                                                    width: str = 'auto',
                                                                    height: str = 'auto',
                                                                    xOffset: str = '0',
                                                                    yOffset: str = '0')
```

Bases: *BaseObject*

Rendering class for rendering a Line Chart

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.rendering.LineChartRendering(
    'my line chart',
    'MyLineChartID',
    'MyLineChart',
    ['red', 'blue'],
    ['label1', 'label2'],
    'MyContainerID',
    'name_key',
    'value_key',
    'name_value'
)
>>> my_obj.to_dict()
{'className': 'LineChartRendering',
 'label': 'my line chart',
 'params': {'id': 'MyLineChartID',
            'chartName': 'MyLineChart',
            'chartColors': ['red', 'blue'],
            'chartLabels': ['label1', 'label2'],
            'containerId': 'MyContainerID',
            'predictionNameKey': 'name_key',
            'predictionValueKey': 'value_key',
            'predictionNameValue': 'name_value',
            'width': 'auto',
            'height': 'auto',
            'xOffset': '0',
            'yOffset': '0'}}
```

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.rendering.ObjectRendering module

```
class aisquared.config.rendering.ObjectRendering.ObjectRendering(color: str = 'blue', thickness: str = '5px', placement: str = 'bottomleft', include_probability: bool = False, badge_color: str = 'white', font_color: str = 'black', font_size: str = '5px')
```

Bases: *BaseObject*

Object which dictates how to render object detection in images

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.rendering.ObjectRendering()
>>> my_obj.to_dict()
{'className': 'ObjectRendering',
 'params': {'color': 'blue',
 'thickness': '5px',
 'placement': 'bottomleft',
 'includeProbability': False,
 'badgeColor': 'white',
 'fontColor': 'black',
 'fontSize': '5px'}}
```

property badge_color

property color

property font_color

property font_size

property include_probability

property placement

property thickness

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.rendering.PieChartRendering module

```
class aisquared.config.rendering.PieChartRendering.PieChartRendering(label: str, id: str,
                                                                    chart_name: str,
                                                                    chart_colors: list,
                                                                    chart_labels: list,
                                                                    container_id: str,
                                                                    prediction_name_key: str,
                                                                    prediction_value_key: str,
                                                                    prediction_name_value:
                                                                    str, display_legend: bool,
                                                                    legend_icon: str, width:
                                                                    str = 'auto', height: str =
                                                                    'auto', xOffset: str = '0',
                                                                    yOffset: str = '0')
```

Bases: *BaseObject*

Rendering class for rendering a Pie Chart

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.rendering.PieChartRendering(
    'my pie chart',
    'MyPieChartID',
    'MyPieChart',
    ['red', 'blue'],
    ['label1', 'label2'],
    'my_container_id',
    'key',
    'value',
    'name',
    True,
    'circle'
)
>>> my_obj.to_dict()
{'className': 'PieChartRendering',
 'label': 'my pie chart',
 'params': {'id': 'MyPieChartID',
 'chartName': 'MyPieChart',
 'chartColors': ['red', 'blue'],
 'chartLabels': ['label1', 'label2'],
 'containerId': 'my_container_id',
 'predictionNameKey': 'key',
 'predictionValueKey': 'value',
 'predictionNameValue': 'name',
 'displayLegend': True,
 'legendIcon': 'circle',
 'width': 'auto',
 'height': 'auto',
 'xOffset': '0',
 'yOffset': '0'}}
```

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.rendering.SOSRendering module

class aisquared.config.rendering.SOSRendering.SOSRendering(*can_toggle: bool, label: str = ""*)

Bases: *BaseObject*

Rendering of an SOS dashboard

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.rendering.SOSRendering(True)
>>> my_obj.to_dict()
{'className': 'SOSRendering', 'label': '', 'params': {'canToggle': True}}
```

property can_toggle

property label

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.rendering.TableRendering module

class aisquared.config.rendering.TableRendering.TableRendering(*label: str, id: str, container_id: str, prediction_name_key: str, prediction_value_key: str, prediction_name_values: str, table_name: str = ""*)

Bases: *BaseObject*

Class for rendering tables

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.rendering.TableRendering(
    'my table',
    'MyTableID',
    'MyContainerID',
    'name_key',
    'value_key',
    'name_values'
)
>>> my_obj.to_dict()
{'className': 'TableRendering',
 'label': 'my table',
 'params': {'id': 'MyTableID',
            'containerId': 'MyContainerID',
            'predictionNameKey': 'name_key',
            'predictionValueKey': 'value_key',
            'predictionNameValues': 'name_values',
            'tableName': ''}}
```

to_dict() → dict

Get the configuration object as a dictionary

aisquared.config.rendering.WordRendering module

```
class aisquared.config.rendering.WordRendering.WordRendering(word_list: str = 'input', result_key:
Optional[str] = None, content_key:
Optional[str] = None, badge_shape:
str = 'star', badge_color: str = 'blue',
classes: Optional[list] = None,
threshold_key: Optional[str] =
None, threshold_value:
Optional[Union[int, float]] = None)
```

Bases: *BaseObject*

Object for rendering badges on individual words

Example usage:

```
>>> import aisquared
>>> my_obj = aisquared.config.rendering.WordRendering()
>>> my_obj.to_dict()
{'className': 'WordRendering',
'params': {'wordList': 'input',
'resultKey': None,
'contentKey': None,
'badgeShape': 'star',
'badgeColor': 'blue',
'classes': None,
'thresholdKey': None,
'thresholdValue': None}}
```

property badge_color

property badge_shape

property classes

property content_key

property result_key

property threshold_key

property threshold_value

to_dict() → dict

Get the configuration object as a dictionary

property word_list

Submodules

aisquared.config.GraphConfiguration module

```
class aisquared.config.GraphConfiguration.GraphConfiguration(name: str, stage: str =
    'experimental', version:
    Optional[int] = None, description:
    str = "", mlflow_uri: Optional[str] =
    None, mlflow_user: Optional[str] =
    None, mlflow_token: Optional[str] =
    None, owner: Optional[str] = None,
    url: str = '*', auto_run: bool =
    False)
```

Bases: [BaseObject](#)

Configuration object for deploying a set of processing steps and/or analytics as a dependency graph

add_node(step: [BaseObject](#), dependencies: Optional[Union[int, list]] = None) → int

Add a node to the configuration graph

Parameters

- **step** (*aisquared configuration step*) – The step to add
- **dependencies** (*int, list of int, or None*) – The ids of nodes which must be run before the added node

Returns

node_id – The integer id of the node that is added

Return type

int

property auto_run

compile(filename: Optional[str] = None, dtype: Optional[str] = None) → None

Compile the object into a '.air' file, which can then be dragged and dropped into applications using the AI Squared JavaScript SDK

Parameters

- **filename** (*path-like or None (default None)*) – Filename to compile to. If None, defaults to '{NAME}.air', where {NAME} is the name of the analytic
- **dtype** (*str or None (default None)*) – The datatype to use for the model weights when using a Keras model. If None, defaults to 'float32'

property description

get_filenames() → list

Get filenames for all models in the configuration

property mlflow_token

property mlflow_uri

property mlflow_user

property name

property owner

property stage

to_dict() → dict

Get the object as a dictionary

property url

property version

aisquared.config.ModelConfiguration module

```
class aisquared.config.ModelConfiguration.ModelConfiguration(name: str, harvesting_steps:
    Union[BaseObject, list],
    preprocessing_steps:
    Union[BaseObject, list], analytic:
    Union[BaseObject, list],
    postprocessing_steps:
    Union[BaseObject, list],
    rendering_steps: Union[BaseObject,
    list], feedback_steps:
    Optional[Union[BaseObject, list]] =
    None, stage: str = 'experimental',
    version: Optional[int] = None,
    description: str = "", mlflow_uri:
    Optional[str] = None, mlflow_user:
    Optional[str] = None, mlflow_token:
    Optional[str] = None, owner:
    Optional[str] = None, url: str = '*',
    auto_run: bool = False)
```

Bases: *BaseObject*

Configuration object for deploying a model or analytic

property analytic

property analytic_dict

property auto_run

compile(filename: Optional[str] = None, dtype: Optional[str] = None) → None

Compile the object into a '.air' file, which can then be dragged and dropped into applications using the AI Squared JavaScript SDK

Parameters

- **filename** (*path-like or None (default None)*) – Filename to compile to. If None, defaults to '{NAME}.air', where {NAME} is the name of the analytic
- **dtype** (*str or None (default None)*) – The datatype to use for the model weights. If None, defaults to 'float32'

property description

property feedback_dict

property `feedback_steps`

get_model_filenames() → list
Get filenames for all models in the configuration

property `harvester_dict`

property `harvesting_steps`

property `mlflow_token`

property `mlflow_uri`

property `mlflow_user`

property `name`

property `owner`

property `postprocessor_dict`

property `postprocessing_steps`

property `preprocessor_dict`

property `preprocessing_steps`

property `render_dict`

property `rendering_steps`

property `stage`

to_dict() → dict
Get the object as a dictionary

property `url`

property `version`

aisquared.logging package

Module contents

The `aisquared.logging` subpackage contains utilities for performing experiments within `aisquared`.

This functionality is inherited from MLFlow. Please see the MLFlow documentation at <https://mlflow.org>.

aisquared.platform package

Module contents

Utilities for interacting with the AI Squared Platform.

The primary class within this subpackage is the *AISquaredPlatformClient* class, which has the capabilities to interact with much of the functionality in the AI Squared platform. For more information about this class, please see its documentation.

Submodules

aisquared.platform.AISquaredPlatformClient module

exception aisquared.platform.AISquaredPlatformClient.AISquaredAPIException

Bases: Exception

class aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient

Bases: object

Client for interacting with the AI Squared platform programmatically

When using the client for the first time, it is important to run the `client.login()` method. When doing so, the client will ask for any required information interactively.

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> # If you have never logged in before, run the following code:
>>> client.login()
>>> # Test connection
>>> client.test_connection()
Connection successful
200
```

add_user_to_group(group_id, user_id)

Not yet implemented

property base_url: str

The base URL associated with the client

delete_model(id: str, port: int = 8080) → bool

Delete a model

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.delete_model('model_id')
True
```

Parameters

- **id** (str) – The ID for the model
- **port** (int (default 8080)) – The API port for the model

Returns

success – Whether the action was successful

Return type

bool

get_model(id: str, port: int = 8080) → dict

Retrieve a model configuration

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
```

(continues on next page)

(continued from previous page)

```
>>> client.get_model('model_id')
*JSON Response including model data and metadata*
```

Parameters

- **id** (*str*) – The ID for the model
- **port** (*int* (*default 8080*)) – The API port for the call

Returns

data – Metadata about the model coupled with the model's configuration information

Return type

dictionary

get_model_id_by_name(*model_name: str*) → *str*

Retrieve a model's ID using the name of the model

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.get_model_id_by_name('my_awesome_model')
*model_id*
```

Parameters

model_name (*str*) – The name of the model

Returns

model_id – The model's ID

Return type

str

get_user_id_by_name(*name: str*) → *str*

Get a user's ID from their display name

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.get_user_id_by_name('User Name')
*user_id*
```

Parameters

name (*str*) – The display name of the user

Returns

id – The ID of the user

Return type

str

get_user_usage_metrics(*user_id, port=8080*)

Not yet implemented

property headers

Headers used for authentication with the AI Squared Platform

list_group_users(*group_id: str, as_df: bool = True, port: int = 8083*) → Union[DataFrame, dict]

List users in a group

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.list_group_users('group_id')
*DataFrame with results*
```

Parameters

- **group_id** (*str*) – The ID for the group
- **as_df** (*bool (default True)*) – Whether to return the response as a pandas DataFrame
- **port** (*int (default 8083)*) – The API port to use

Returns

users – The response from the API

Return type

pandas DataFrame or dictionary

list_groups(*as_df: bool = True, port: int = 8083*) → Union[DataFrame, dict]

List all groups

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.list_groups()
*DataFrame with results*
```

Parameters

- **as_df** (*bool (default True)*) – Whether to return the result as a pandas DataFrame
- **port** (*int (default 8083)*) – The API port for the call

Returns

groups – The response from the API

Return type

pandas DataFrame or dictionary

list_model_feedback(*model_id, port=8080*)

Not yet implemented

list_model_prediction_feedback(*model_id*)

Not yet implemented

list_model_predictions(*model_id, port=8080*)

Not yet implemented

list_model_users(*id: str, as_df: bool = True, port: int = 8080*) → Union[DataFrame, dict]

List users for a model

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.list_model_users('model_id')
*DataFrame with results*
```

Parameters

- **id** (*str*) – The ID for the model
- **as_df** (*bool* (*default True*)) – Whether to return the response as a Pandas DataFrame
- **port** (*int* (*default 8080*)) – The API port for the call

Returns

model_users – The users for the model

Return type

pandas DataFrame or dictionary

list_models(*as_df: bool = True, port: int = 8080*) → Union[DataFrame, dict]

List models within the platform

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.list_models()
*DataFrame with results*
```

Parameters

- **as_df** (*bool* (*default True*)) – Whether to return the response as a pandas DataFrame
- **port** (*int* (*default 8080*)) – The API port for the call

Returns

models – The models

Return type

pandas DataFrame or dictionary

list_prediction_feedback(*prediction_id, port=8080*)

Not yet implemented

list_users(*as_df: bool = True, port: int = 8080*) → Union[DataFrame, dict]

List all users

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.list_users()
*DataFrame with results*
```

Parameters

- **as_df** (*bool* (*default True*)) – Whether to return the data as a Pandas DataFrame
- **port** (*int* (*default 8080*)) – The API port for the call

Returns

users – The response from the API

Return type

pandas DataFrame or dictionary

login(url: Optional[str] = None, port: int = 8080, username: Optional[str] = None, password: Optional[str] = None) → None

Log in to the platform programmatically. If no url, username, or password are provided, logs in interactively

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.login()
Enter URL: https://platform.squared.ai
Enter Username: your.email@your_domain.com
Enter Password: <hidden>
```

Parameters

- **url** (str or None (default None)) – The URL for the platform API
- **port** (int (default 8080)) – The API port for the call
- **username** (str or None (default None)) – The username
- **password** (str or None (default None)) – The password

property password: str

The password associated with the client

remove_user_from_group(group_id, user_id)

Not yet implemented

share_model_with_group(model_id, group_id, port=8083)

Not yet implemented

share_model_with_user(model_id: str, user_id: str, port: int = 8080) → bool

Share a model with a user

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.share_model_with_user('model_id', 'user_id')
True
```

Parameters

- **model_id** (str) – The ID for the model
- **user_id** (str) – The ID for the user
- **port** (int (default 8080)) – The API port for the call

Returns

success – Whether the action was successful

Return type

bool

test_connection(port: int = 8080) → int

Test whether there is a healthy connection to the platform

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.test_connection()
Connection successful
200
```

Parameters

port (*int* (default 8080)) – The API port for the call

Returns

status_code – The status code when checking the health API

Return type

int

property token: *str*

The token associated with the client

unshare_model_with_user(*model_id: str, user_id: str, port: int = 8080*) → *bool*

Unshare a model with a user

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.unshare_model_with_user('model_id', 'user_id')
True
```

Parameters

- **model_id** (*str*) – The ID for the model
- **user_id** (*str*) – The ID for the user
- **port** (*int* (default 8080)) – The API port for the call

Returns

success – Whether the action was successful

Return type

bool

upload_model(*model_file: str, port: int = 8081*) → *str*

Upload a model to the platform

```
>>> import aisquared
>>> client = aisquared.platform.AISquaredPlatformClient()
>>> client.upload_model('my_model_filename.air')
True
```

Parameters

- **model_file** (*path* or *path-like*) – The path to the model file
- **port** (*int* (default 8081)) – The API port to use

Returns

successful – Whether the action was successful

Return type

bool

property username: str

The username associated with the client

aisquared.serving package**Module contents**

The aisquared.serving package contains utilities to serve models to a local REST endpoint.

Here is an example of how to serve a simple keras model using these utilities:

```
>>> # Assume model is already trained and stored in memory as model
>>> from aisquared import serving
>>> serving.save_keras_model(model, 'my_model')
>>> serving.deploy_model(
    'my_model',
    'keras',
    additional_functions_file = '<optional file containing `preprocess` and
    ↳ `postprocess` functions, if applicable>'
)
App created successfully. Serving and awaiting requests
```

And to retrieve predictions from the model:

```
>>> # From a separate terminal, assume data is already loaded
>>> from aisquared import serving
>>> serving.get_remote_predictions(data) # Do not need to change host or port if
    ↳ predicting from the same machine
*predictions*
```

Submodules**aisquared.serving.deploy_model module**

`aisquared.serving.deploy_model.deploy_model(saved_model: str, model_type: str, host: str = '127.0.0.1', port: int = 2244, custom_objects: Optional[dict] = None, additional_functions_file: Optional[str] = None)`

Deploy a model to a Flask server on the specified host

Parameters

- **saved_model** (*Path-like*) – The path to the saved model directory or model file
- **model_type** (*str*) – The type of model
- **host** (*str* (*default* '127.0.0.1')) – The host to deploy to
- **port** (*int* (*default* 2244)) – The port to deploy to
- **custom_objects** (*dict* or *None* (*default* *None*)) – Any custom objects to load when using a MANN model

- **additional_functions_file** (*file-like or None (default None)*) – File name containing additional functions (which have to be named *preprocess* and *postprocess*, if created) that are used during the prediction process

`aisquared.serving.deploy_model.load_mann_model(model: str, custom_objects: dict)`

Load a MANN model with custom objects

aisquared.serving.get_remote_prediction module

`aisquared.serving.get_remote_prediction.get_remote_prediction(data: Union[dict, str, ndarray, list],
host: str = '127.0.0.1', port: int = 2244) → list`

Send data to use for prediction

Parameters

- **data** (*dict, str, np.ndarray, or list*) – The data to be predicted on
- **host** (*str (default '127.0.0.1')*) – The host to use
- **port** (*int (default '2244')*) – The port to use

Notes

- If data is a dictionary, it is expected to already be correctly formatted
- If data is a string, it is expected to already be correctly formatted

Returns

predictions – The predictions from the deployed model

Return type

list

aisquared.utils package

Module contents

Additional utilities to use with the *aisquared* package. These utilities currently consist of two functions, the *mimic_model* and *get_model* functions. They utilize functionality that exists in our open source package BeyondML to train teacher-student models

To see in-depth examples of how to use these functions, please visit our GitHub repository at <https://github.com/AISquaredInc/MimicModelExamples>

Submodules

aisquared.utils.utils module

`aisquared.utils.utils.get_model(model_type: str, input_shape: Union[int, tuple[int]], num_outputs: int, output_activation: str, size: str = 'small', vocab_size: Union[None, int] = None)`

Get a pre-configured model for different use cases

Parameters

- **model_type** (*str*) – Either ‘cv’, ‘nlp_embedding’, or ‘fc’, defining the model type
- **input_shape** (*int or tuple of int*) – The input shape to the model
- **num_outputs** (*int*) – The output shape of the model
- **output_activation** (*str or keras activation function*) – The activation of the final layer of the model
- **size** (*str (default 'small')*) – One of either ‘small’, ‘medium’, or ‘large’
- **vocab_size** (*str or None (default None)*) – Size of the vocab, if model_type is ‘nlp_embedding’

Returns

model – The model

Return type

TensorFlow Keras model

`aisquared.utils.utils.mimic_model(trained_model: BaseEstimator, nnet: Model, training_data: ndarray, test_data: ndarray, test_labels: ndarray, problem_type: str, loss: str, metrics: Union[str, list], optimizer: str, mimic_proba: bool = False, retention: float = 0.9, batch_size: int = 32, epochs: int = 100, starting_sparsification: int = 0, max_sparsification: int = 99, sparsification_rate: int = 5) → Model`

Train a sparse neural network to mimic a scikit-learn model

Parameters

- **trained_model** (*sklearn model*) – The model that is already trained
- **nnet** (*TensorFlow keras Model*) – The neural network to train to mimic the trained model
- **training_data** (*array or array-like*) – The input data that was used to train the trained model
- **test_data** (*array or array-like*) – The input data to be used for testing
- **test_labels** (*array or array-like*) – The output data used in testing
- **problem_type** (*str*) – The type of problem, either ‘classification’ or ‘regression’
- **loss** (*str or keras loss function*) – The loss to use
- **metrics** (*str, function or list of str, function*) – Metrics to measure
- **optimizer** (*str or keras optimizer*) – The optimizer to use
- **mimic_proba** (*bool (default False)*) – For classification, mimic the probability outputs

- **retention** (*float* (*default* 0.9)) – The retention of performance to allow further pruning
- **batch_size** (*int* (*default* 32)) – The batch size to use while training
- **epochs** (*int* (*default* 100)) – The number of epochs (if early stopping is not met beforehand)
- **starting_sparsification** (*int* (*default* 0)) – The starting model sparsification
- **max_sparsification** (*int* (*default* 99)) – The maximum sparsification to allow
- **sparsification_rate** (*int* (*default* 5)) – The sparsification rate when invoked

Returns

nnet – The trained model

Return type

TensorFlow keras Model

CHANGELOG

- **Version 0.1.3**

- Added *flags* parameter to *TextHarvester* using regular expression harvesting
- Deleted *model_feedback* parameter in *ModelConfiguration* object and included functionality in *feedback_steps* parameter
- Changed *format* parameter to *header* for both deployed analytics
- Added feedback and stages to *DocumentPredictor* and *ImagePredictor* objects
- Non-API changes for *ALLOWED_STAGES*
- Fixed bugs preventing Windows users from importing the package
- Updated *ModelConfiguration* to include *url* parameter
- Changed default tokenization string

- **Version 0.2.0**

- Moved preprocessing steps under subpackages for specific kinds of preprocessing steps
- Cleaned up documentation to render within programmatic access environments
- Added *aisquared.logging* subpackage
- **Created *InputHarvester***
 - * Allows for harvesting of input text, images, and tabular data
- Created the *aisquared.serving* subpackage, specifically the *deploy_model* and *get_remote_prediction* functions
- Created the *GraphConfiguration* class
- Added *auto-run* parameter to *ModelConfiguration* and *GraphConfiguration* classes
- **Created the *aisquared* CLI with the following commands:**
 - * *aisquared deploy*, which deploys a model locally
 - * *aisquared predict*, which predicts using a local JSON file
 - * *aisquared airfiles*, which contains the subcommands *list*, *delete*, *download*, and *upload*
- Changed all classes within *aisquared.config.analytic* to accept 'tabular' as an *input_type*
- Removed *aisquared.logging* and *aisquared.remote* from top-level imports
- Added *round* parameter to Regression postprocessor
- Removed *DocumentPredictor* and *ImagePredictor* classes

- Removed *ChainRendering* class
- Created *FilterRendering* class
- Altered *QUALIFIERS*
- Added advanced rendering parameters to rendering objects
- Removed *logging* and *remote* subpackages from top-level *aisquared* import
- **Version 0.2.1**
 - Added the *S3Connector* class to the *analytics* subpackage, which allows download of an analytic directly from S3
 - Updated the documentation and added the *docs* subdirectory for hosting the documentation on GitHub Pages
- **Version 0.2.2**
 - Fixed bug in *to_dict* method within *ObjectRendering* class
 - Fixed bug in name of *MultiplyValue* step
 - Fixed bug in datatype checking for text harvester
 - Added *body_only* parameter to *TextHarvester*
 - Added ‘underline’ to possible badges
 - Added *threshold_key* and *threshold_values* to relevant rendering classes
 - Added *Trim* text preprocessing class
 - Added *CustomObject* in the base package to allow for creation of custom classes
 - Added keyword harvesting capabilities
 - Added *utils* subpackage with capabilities to mimic a trained sklearn model
 - Small documentation changes
 - Changed the required imports for the package to streamline installation process, and created two installation options *aisquared* and *aisquared[full]*
- **Version 0.2.3**
 - Added functionality to add custom preprocessing and postprocessing functions to the model deployment pipeline
 - Added *all* parameter to *LocalAnalytic* class
 - Changed under-the-hood functionality of *mimic_model* function in line with updates to *BeyondML*
 - Altered the *ReverseMLWorkflow* analytic
 - Added the *BarChartRendering*, *ContainerRendering*, *DashboardReplacementRendering*, *DoughnutChartRendering*, *HTMLTagRendering*, *LineChartRendering*, *PieChartRendering*, *SOSRendering*, and *TableRendering* rendering classes
 - Added the *QueryParameterHarvester* harvester class
 - Added the *limit* parameter to the *TextHarvester* class
- **Version 0.3.0**
 - Added type hinting to documentation strings
 - Revamped documentation to use Sphinx

- **Version 0.3.1**
 - Changed Python type hints to allow for backwards compatibility with older versions of Python

PYTHON MODULE INDEX

a

aisquared, 3
aisquared.base, 3
aisquared.base.BaseObject, 3
aisquared.base.CustomObject, 4
aisquared.base.rendering, 4
aisquared.base.stages, 4
aisquared.config, 4
aisquared.config.analytic, 5
aisquared.config.analytic.DeployedAnalytic, 5
aisquared.config.analytic.DeployedModel, 6
aisquared.config.analytic.LocalAnalytic, 6
aisquared.config.analytic.LocalModel, 7
aisquared.config.analytic.ReverseMLWorkflow, 7
aisquared.config.feedback, 8
aisquared.config.feedback.BinaryFeedback, 8
aisquared.config.feedback.ModelFeedback, 9
aisquared.config.feedback.MulticlassFeedback, 9
aisquared.config.feedback.QualitativeFeedback, 10
aisquared.config.feedback.RegressionFeedback, 10
aisquared.config.feedback.SimpleFeedback, 11
aisquared.config.GraphConfiguration, 38
aisquared.config.harvesting, 11
aisquared.config.harvesting.ImageHarvester, 11
aisquared.config.harvesting.InputHarvester, 12
aisquared.config.harvesting.QueryParameterHarvester, 12
aisquared.config.harvesting.TextHarvester, 13
aisquared.config.ModelConfiguration, 39
aisquared.config.postprocessing, 14
aisquared.config.postprocessing.BinaryClassification, 14
aisquared.config.postprocessing.MulticlassClassification, 14
aisquared.config.postprocessing.ObjectDetection, 15
aisquared.config.postprocessing.Regression, 15
aisquared.config.preprocessing, 16
aisquared.config.preprocessing.image, 16
aisquared.config.preprocessing.image.ImagePreprocessing, 16
aisquared.config.preprocessing.image.Steps, 17
aisquared.config.preprocessing.tabular, 19
aisquared.config.preprocessing.tabular.Steps, 19
aisquared.config.preprocessing.tabular.TabularPreprocessing, 21
aisquared.config.preprocessing.text, 21
aisquared.config.preprocessing.text.Steps, 21
aisquared.config.preprocessing.text.TextPreprocessing, 24
aisquared.config.rendering, 24
aisquared.config.rendering.BarChartRendering, 24
aisquared.config.rendering.ContainerRendering, 26
aisquared.config.rendering.DashboardReplacementRendering, 27
aisquared.config.rendering.DocumentRendering, 27
aisquared.config.rendering.DoughnutChartRendering, 29
aisquared.config.rendering.FilterRendering, 30
aisquared.config.rendering.HTMLTagRendering, 31
aisquared.config.rendering.ImageRendering, 32
aisquared.config.rendering.LineChartRendering, 33
aisquared.config.rendering.ObjectRendering, 34
aisquared.config.rendering.PieChartRendering, 34
aisquared.config.rendering.SOSRendering, 36
aisquared.config.rendering.TableRendering, 36
aisquared.config.rendering.WordRendering, 37

`aisquared.logging`, [40](#)
`aisquared.platform`, [40](#)
`aisquared.platform.AISquaredPlatformClient`,
 [41](#)
`aisquared.serving`, [47](#)
`aisquared.serving.deploy_model`, [47](#)
`aisquared.serving.get_remote_prediction`, [48](#)
`aisquared.utils`, [48](#)
`aisquared.utils.utils`, [49](#)

INDEX

A

- `add_node()` (*aisquared.config.GraphConfiguration.GraphConfiguration* module), 38
- `add_question()` (*aisquared.config.feedback.ModelFeedback.ModelFeedback* module), 9
- `add_question()` (*aisquared.config.feedback.QualitativeFeedback.QualitativeFeedback* module), 10
- `add_step()` (*aisquared.config.preprocessing.image.ImagePreprocessing.ImagePreprocessor* module), 16
- `add_step()` (*aisquared.config.preprocessing.tabular.TabularPreprocessing.TabularPreprocessor* module), 21
- `add_step()` (*aisquared.config.preprocessing.text.TextPreprocessing.TextPreprocessor* module), 24
- `add_user_to_group()` (*aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient* module), 41
- `AddValue` (class in *aisquared.config.preprocessing.image.Steps*), 17
- `aisquared` module, 3
- `aisquared.base` module, 3
- `aisquared.base.BaseObject` module, 3
- `aisquared.base.CustomObject` module, 4
- `aisquared.base.rendering` module, 4
- `aisquared.base.stages` module, 4
- `aisquared.config` module, 4
- `aisquared.config.analytic` module, 5
- `aisquared.config.analytic.DeployedAnalytic` module, 5
- `aisquared.config.analytic.DeployedModel` module, 6
- `aisquared.config.analytic.LocalAnalytic` module, 6
- `aisquared.config.analytic.LocalModel` module, 7
- `aisquared.config.analytic.ReverseMLWorkflow` module, 7
- `aisquared.config.feedback` module, 8
- `aisquared.config.feedback.BinaryFeedback` module, 8
- `aisquared.config.feedback.ModelFeedback` module, 8
- `aisquared.config.feedback.MulticlassFeedback` module, 9
- `aisquared.config.feedback.QualitativeFeedback` module, 9
- `aisquared.config.feedback.RegressionFeedback` module, 10
- `aisquared.config.feedback.SimpleFeedback` module, 11
- `aisquared.config.GraphConfiguration` module, 38
- `aisquared.config.harvesting` module, 11
- `aisquared.config.harvesting.ImageHarvester` module, 11
- `aisquared.config.harvesting.InputHarvester` module, 12
- `aisquared.config.harvesting.QueryParameterHarvester` module, 12
- `aisquared.config.harvesting.TextHarvester` module, 13
- `aisquared.config.ModelConfiguration` module, 39
- `aisquared.config.postprocessing` module, 14
- `aisquared.config.postprocessing.BinaryClassification` module, 14
- `aisquared.config.postprocessing.MulticlassClassification` module, 14
- `aisquared.config.postprocessing.ObjectDetection` module, 15
- `aisquared.config.postprocessing.Regression` module, 15
- `aisquared.config.preprocessing` module, 16

```

aisquared.config.preprocessing.image
    module, 16
aisquared.config.preprocessing.image.ImagePreprocessing
    module, 16
aisquared.config.preprocessing.image.Steps
    module, 17
aisquared.config.preprocessing.tabular
    module, 19
aisquared.config.preprocessing.tabular.Steps
    module, 19
aisquared.config.preprocessing.tabular.TabularPreprocessing
    module, 21
aisquared.config.preprocessing.text
    module, 21
aisquared.config.preprocessing.text.Steps
    module, 21
aisquared.config.preprocessing.text.TextPreprocessing
    module, 24
aisquared.config.rendering
    module, 24
aisquared.config.rendering.BarChartRendering
    module, 24
aisquared.config.rendering.ContainerRendering
    module, 26
aisquared.config.rendering.DashboardReplacementRendering
    module, 27
aisquared.config.rendering.DocumentRendering
    module, 27
aisquared.config.rendering.DoughnutChartRendering
    module, 29
aisquared.config.rendering.FilterRendering
    module, 30
aisquared.config.rendering.HTMLTagRendering
    module, 31
aisquared.config.rendering.ImageRendering
    module, 32
aisquared.config.rendering.LineChartRendering
    module, 33
aisquared.config.rendering.ObjectRendering
    module, 34
aisquared.config.rendering.PieChartRendering
    module, 34
aisquared.config.rendering.SOSRendering
    module, 36
aisquared.config.rendering.TableRendering
    module, 36
aisquared.config.rendering.WordRendering
    module, 37
aisquared.logging
    module, 40
aisquared.platform
    module, 40
aisquared.platform.AISquaredPlatformClient
    module, 41
aisquared.serving
    module, 47
aisquared.serving.deploy_model
    module, 47
aisquared.serving.get_remote_prediction
    module, 48
aisquared.utils
    module, 48
aisquared.utils.utils
    module, 49
AISquaredAPIException, 41
AISquaredPlatformClient (class in
    aisquared.platform.AISquaredPlatformClient),
    41
all (aisquared.config.analytic.LocalAnalytic.LocalAnalytic
    property), 6
analytics (aisquared.config.ModelConfiguration.ModelConfiguration
    property), 39
analytic_dict (aisquared.config.ModelConfiguration.ModelConfiguration
    property), 39
anchor_selector (aisquared.config.rendering.DashboardReplacementRe
    property), 27
attributes (aisquared.config.harvesting.QueryParameterHarvester.Query
    property), 12
auto_run (aisquared.config.GraphConfiguration.GraphConfiguration
    property), 38
auto_run (aisquared.config.ModelConfiguration.ModelConfiguration
    property), 39
B
badge_color (aisquared.config.rendering.ImageRendering.ImageRenderin
    property), 32
badge_color (aisquared.config.rendering.ObjectRendering.ObjectRenderi
    property), 34
badge_color (aisquared.config.rendering.WordRendering.WordRendering
    property), 37
badge_shape (aisquared.config.rendering.WordRendering.WordRendering
    property), 37
BarChartRendering (class in
    aisquared.config.rendering.BarChartRendering),
    24
base_url (aisquared.platform.AISquaredPlatformClient.AISquaredPlatfor
    property), 41
BaseObject (class in aisquared.base.BaseObject), 3
BinaryClassification (class in
    aisquared.config.postprocessing.BinaryClassification),
    14
BinaryFeedback (class in
    aisquared.config.feedback.BinaryFeedback), 8
body_only (aisquared.config.harvesting.TextHarvester.TextHarvester
    property), 13
bucket (aisquared.config.analytic.ReverseMLWorkflow.ReverseMLWorkflo
    property), 8

```

C

[can_toggle](#) ([aisquared.config.rendering.SOSRendering.SOSRendering](#) property), 36
[classes](#) ([aisquared.config.rendering.DocumentRendering.DocumentRendering](#) property), 28
[classes](#) ([aisquared.config.rendering.ImageRendering.ImageRendering](#) property), 32
[classes](#) ([aisquared.config.rendering.WordRendering.WordRendering](#) property), 37
[color](#) ([aisquared.config.preprocessing.image.Steps.ConvertToColor](#) property), 17
[color](#) ([aisquared.config.rendering.ImageRendering.ImageRendering](#) property), 32
[color](#) ([aisquared.config.rendering.ObjectRendering.ObjectRendering](#) property), 34
[column](#) ([aisquared.config.analytic.ReverseMLWorkflow.ReverseMLWorkflow](#) property), 8
[column](#) ([aisquared.config.preprocessing.tabular.Steps.DropColumn](#) property), 19
[column](#) ([aisquared.config.preprocessing.tabular.Steps.OneHot](#) property), 20
[columns](#) ([aisquared.config.preprocessing.tabular.Steps.MinMax](#) property), 19
[columns](#) ([aisquared.config.preprocessing.tabular.Steps.ZScore](#) property), 20
[compile\(\)](#) ([aisquared.config.GraphConfiguration.GraphConfiguration](#) method), 38
[compile\(\)](#) ([aisquared.config.ModelConfiguration.ModelConfiguration](#) method), 39
[ContainerRendering](#) (class in [aisquared.config.rendering.ContainerRendering](#)), 26
[content_key](#) ([aisquared.config.rendering.WordRendering.WordRendering](#) property), 37
[ConvertToCase](#) (class in [aisquared.config.preprocessing.text.Steps](#)), 21
[ConvertToColor](#) (class in [aisquared.config.preprocessing.image.Steps](#)), 17
[ConvertToVocabulary](#) (class in [aisquared.config.preprocessing.text.Steps](#)), 22
[CustomObject](#) (class in [aisquared.base.CustomObject](#)), 4

D

[DashboardReplacementRendering](#) (class in [aisquared.config.rendering.DashboardReplacementRendering](#)), 27
[delete_model\(\)](#) ([aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient](#) method), 41
[deploy_model\(\)](#) (in module [aisquared.serving.deploy_model](#)), 47

[DeployedAnalytic](#) (class in [aisquared.config.analytic.DeployedAnalytic](#)), 5
[DeployedModel](#) (class in [aisquared.config.analytic.DeployedModel](#)), 6
[description](#) ([aisquared.config.GraphConfiguration.GraphConfiguration](#) property), 38
[description](#) ([aisquared.config.ModelConfiguration.ModelConfiguration](#) property), 39
[display](#) ([aisquared.config.rendering.ContainerRendering.ContainerRendering](#) property), 26
[DivideValue](#) (class in [aisquared.config.preprocessing.image.Steps](#)), 17
[DocumentRendering](#) (class in [aisquared.config.rendering.DocumentRendering](#)), 27
[documents](#) ([aisquared.config.rendering.DocumentRendering.DocumentRendering](#) property), 28
[DoughnutChartRendering](#) (class in [aisquared.config.rendering.DoughnutChartRendering](#)), 29
[DropColumn](#) (class in [aisquared.config.preprocessing.tabular.Steps](#)), 19
F
[features](#) ([aisquared.config.harvesting.InputHarvester.InputHarvester](#) property), 12
[feedback_dict](#) ([aisquared.config.ModelConfiguration.ModelConfiguration](#) property), 39
[feedback_steps](#) ([aisquared.config.ModelConfiguration.ModelConfiguration](#) property), 39
[filename](#) ([aisquared.config.analytic.ReverseMLWorkflow.ReverseMLWorkflow](#) property), 8
[FilterRendering](#) (class in [aisquared.config.rendering.FilterRendering](#)), 30
[flags](#) ([aisquared.config.harvesting.TextHarvester.TextHarvester](#) property), 13
[font_color](#) ([aisquared.config.rendering.ImageRendering.ImageRendering](#) property), 32
[font_color](#) ([aisquared.config.rendering.ObjectRendering.ObjectRendering](#) property), 34
[font_size](#) ([aisquared.config.rendering.ImageRendering.ImageRendering](#) property), 32
[font_size](#) ([aisquared.config.rendering.ObjectRendering.ObjectRendering](#) property), 34

G

[get_filenames\(\)](#) ([aisquared.config.GraphConfiguration.GraphConfiguration](#) method), 38
[get_model\(\)](#) ([aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient](#) method), 41
[get_model\(\)](#) (in module [aisquared.utils.utils](#)), 49

get_model_filenames() include_probability
(aisquared.config.ModelConfiguration.ModelConfiguration (aisquared.config.rendering.ImageRendering.ImageRendering
method), 40 property), 32
get_model_id_by_name() include_probability
(aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient (aisquared.config.rendering.ObjectRendering.ObjectRendering
method), 42 property), 34
get_remote_prediction() (in module input_type (aisquared.config.analytic.DeployedAnalytic.DeployedAnalytic
aisquared.serving.get_remote_prediction), property), 5
48 input_type (aisquared.config.analytic.DeployedModel.DeployedModel
property), 6
get_user_id_by_name() input_type (aisquared.config.analytic.LocalAnalytic.LocalAnalytic
(aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient (aisquared.config.analytic.LocalAnalytic
method), 42 property), 7
get_user_usage_metrics() input_type (aisquared.config.analytic.LocalModel.LocalModel
(aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient (aisquared.config.analytic.LocalModel.LocalModel
method), 42 property), 7
GraphConfiguration (class in input_type (aisquared.config.analytic.ReverseMLWorkflow.ReverseMLWorkflow
aisquared.config.GraphConfiguration), 38 property), 8
input_type (aisquared.config.harvesting.InputHarvester.InputHarvester
property), 12
H InputHarvester (class in
aisquared.config.harvesting.InputHarvester),
property), 12
harvester_dict (aisquared.config.ModelConfiguration.ModelConfiguration (aisquared.config.harvesting.InputHarvester),
property), 40
harvesting_steps (aisquared.config.ModelConfiguration.ModelConfiguration
property), 40
K
header (aisquared.config.analytic.DeployedAnalytic.DeployedAnalytic (aisquared.config.rendering.FilterRendering.FilterRendering
property), 5 property), 30
header (aisquared.config.analytic.DeployedModel.DeployedModel
property), 6
L
headers (aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient (aisquared.config.rendering.ContainerRendering.ContainerRendering
property), 42 property), 26
height (aisquared.config.rendering.ContainerRendering.ContainerRendering (aisquared.config.rendering.DashboardReplacementRendering.DashboardReplacementRendering
property), 26 property), 27
how (aisquared.config.harvesting.ImageHarvester.ImageHarvester (aisquared.config.rendering.SOSRendering.SOSRendering
property), 11 property), 36
how (aisquared.config.harvesting.TextHarvester.TextHarvester (aisquared.config.rendering.SOSRendering.SOSRendering
property), 13 property), 36
HTMLTagRendering (class in label_map (aisquared.config.feedback.BinaryFeedback.BinaryFeedback
aisquared.config.rendering.HTMLTagRendering), property), 8
31 label_map (aisquared.config.feedback.MulticlassFeedback.MulticlassFeedback
property), 10
label_map (aisquared.config.postprocessing.BinaryClassification.BinaryClassification
property), 14
label_map (aisquared.config.postprocessing.MulticlassClassification.MulticlassClassification
property), 14
label_map (aisquared.config.postprocessing.ObjectDetection.ObjectDetection
property), 15
ImageHarvester (class in length (aisquared.config.preprocessing.text.Steps.PadSequences
aisquared.config.harvesting.ImageHarvester), property), 22
11
ImagePreprocessor (class in limit (aisquared.config.harvesting.TextHarvester.TextHarvester
aisquared.config.preprocessing.image.ImagePreprocessing) property), 13
16
ImageRendering (class in aisquared.config.rendering.LineChartRendering),
aisquared.config.rendering.ImageRendering), 33
32
include_probability list_group_users() (aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient (aisquared.config.rendering.DocumentRendering.DocumentRendering
property), 28 property), 43
method), 43

`list_model_feedback()` (`aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient` method), 43
`list_model_prediction_feedback()` (`aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient` method), 43
`list_model_predictions()` (`aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient` method), 43
`list_model_users()` (`aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient` method), 43
`list_models()` (`aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient` method), 44
`list_prediction_feedback()` (`aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient` method), 44
`list_users()` (`aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient` method), 44
`load_mann_model()` (in module `aisquared.serving.deploy_model`), 48
`LocalAnalytic` (class in `aisquared.config.analytic.LocalAnalytic`), 6
`LocalModel` (class in `aisquared.config.analytic.LocalModel`), 7
`login()` (`aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient` method), 44
`lowercase` (`aisquared.config.preprocessing.text.Steps.ConvertToLowerCase` property), 21
M
`max` (`aisquared.config.postprocessing.Regression.Regression` property), 15
`max_length` (`aisquared.config.harvesting.InputHarvester.InputHarvester` property), 12
`max_vocab` (`aisquared.config.preprocessing.text.Steps.ConvertToVocabulary` property), 22
`maxs` (`aisquared.config.preprocessing.tabular.Steps.MinMax` property), 19
`means` (`aisquared.config.preprocessing.tabular.Steps.ZScore` property), 20
`method` (`aisquared.config.preprocessing.image.Steps.Resize` property), 18
`mimic_model()` (in module `aisquared.utils.utils`), 49
`min` (`aisquared.config.postprocessing.Regression.Regression` property), 15
`MinMax` (class in `aisquared.config.preprocessing.tabular.Steps`), 19
`mins` (`aisquared.config.preprocessing.tabular.Steps.MinMax` property), 19
`mlflow_token` (`aisquared.config.GraphConfiguration.GraphConfiguration` property), 38
`mlflow_token` (`aisquared.config.ModelConfiguration.ModelConfiguration` property), 40
`mlflow_uri` (`aisquared.config.GraphConfiguration.GraphConfiguration` property), 38
`mlflow_uri` (`aisquared.config.ModelConfiguration.ModelConfiguration` property), 40
`mlflow_user` (`aisquared.config.ModelConfiguration.ModelConfiguration` property), 40
`ModelConfiguration` (class in `aisquared.config.ModelConfiguration`), 39
`ModelFeedback` (class in `aisquared.config.feedback.ModelFeedback`), 9
`module`
`aisquared`, 3
`aisquared.base`, 3
`aisquared.base.BaseObject`, 3
`aisquared.base.CustomObject`, 4
`aisquared.base.rendering`, 4
`aisquared.base.stages`, 4
`aisquared.config`, 4
`aisquared.config.analytic`, 5
`aisquared.config.analytic.DeployedAnalytic`, 5
`aisquared.config.analytic.DeployedModel`, 6
`aisquared.config.analytic.LocalAnalytic`, 6
`aisquared.config.analytic.LocalModel`, 7
`aisquared.config.analytic.ReverseMLWorkflow`, 7
`aisquared.config.feedback`, 8
`aisquared.config.feedback.BinaryFeedback`, 8
`aisquared.config.feedback.ModelFeedback`, 9
`aisquared.config.feedback.MulticlassFeedback`, 9
`aisquared.config.feedback.QualitativeFeedback`, 10
`aisquared.config.feedback.RegressionFeedback`, 10
`aisquared.config.feedback.SimpleFeedback`, 11
`aisquared.config.GraphConfiguration`, 38
`aisquared.config.harvesting`, 11
`aisquared.config.harvesting.ImageHarvester`, 11
`aisquared.config.harvesting.InputHarvester`, 12
`aisquared.config.harvesting.QueryParameterHarvester`, 12
`aisquared.config.harvesting.TextHarvester`, 13
`aisquared.config.ModelConfiguration`, 39

[aisquared.config.postprocessing, 14](#)
[aisquared.config.postprocessing.BinaryClassification, 14](#)
[aisquared.config.postprocessing.MulticlassClassification, 14](#)
[aisquared.config.postprocessing.ObjectDetection, 15](#)
[aisquared.config.postprocessing.Regression, 15](#)
[aisquared.config.preprocessing, 16](#)
[aisquared.config.preprocessing.image, 16](#)
[aisquared.config.preprocessing.image.ImagePreprocessing, 16](#)
[aisquared.config.preprocessing.image.Steps, 17](#)
[aisquared.config.preprocessing.tabular, 19](#)
[aisquared.config.preprocessing.tabular.Steps, 19](#)
[aisquared.config.preprocessing.tabular.TabularPreprocessing, 21](#)
[aisquared.config.preprocessing.text, 21](#)
[aisquared.config.preprocessing.text.Steps, 21](#)
[aisquared.config.preprocessing.text.TextPreprocessing, 24](#)
[aisquared.config.rendering, 24](#)
[aisquared.config.rendering.BarChartRendering, 24](#)
[aisquared.config.rendering.ContainerRendering, 26](#)
[aisquared.config.rendering.DashboardReplacementRendering, 27](#)
[aisquared.config.rendering.DocumentRendering, 27](#)
[aisquared.config.rendering.DoughnutChartRendering, 29](#)
[aisquared.config.rendering.FilterRendering, 30](#)
[aisquared.config.rendering.HTMLTagRendering, 31](#)
[aisquared.config.rendering.ImageRendering, 32](#)
[aisquared.config.rendering.LineChartRendering, 33](#)
[aisquared.config.rendering.ObjectRendering, 34](#)
[aisquared.config.rendering.PieChartRendering, 34](#)
[aisquared.config.rendering.SOSRendering, 36](#)
[aisquared.config.rendering.TableRendering, 36](#)
[aisquared.config.rendering.WordRendering, 37](#)
[aisquared.logging, 40](#)
[aisquared.platform, 40](#)
[aisquared.platform.AISquaredPlatformClient, 41](#)
[aisquared.serving, 47](#)
[aisquared.serving.deploy_model, 47](#)
[aisquared.serving.get_remote_prediction, 48](#)
[aisquared.utils, 48](#)
[aisquared.utils.utils, 49](#)
[aisquared.config.postprocessing.MulticlassClassification \(class in aisquared.config.postprocessing.MulticlassClassification\), 14](#)
[aisquared.config.feedback.MulticlassFeedback \(class in aisquared.config.feedback.MulticlassFeedback\), 9](#)
[aisquared.config.preprocessing.image.Steps.MultiplyValue \(class in aisquared.config.preprocessing.image.Steps\), 17](#)

N

[aisquared.config.GraphConfiguration.GraphConfiguration \(property\), 38](#)
[aisquared.config.ModelConfiguration.ModelConfiguration \(property\), 40](#)

O

[aisquared.config.postprocessing.ObjectDetection \(class in aisquared.config.postprocessing.ObjectDetection\), 15](#)
[aisquared.config.rendering.ObjectRendering \(class in aisquared.config.rendering.ObjectRendering\), 34](#)
[aisquared.config.preprocessing.tabular.Steps.OneHot \(class in aisquared.config.preprocessing.tabular.Steps\), 20](#)
[aisquared.config.preprocessing.text.Steps.ConvertToVocabulary \(property\), 22](#)
[aisquared.config.rendering.ContainerRendering.ContainerOrientation \(property\), 26](#)
[aisquared.config.GraphConfiguration.GraphConfiguration \(property\), 38](#)
[aisquared.config.ModelConfiguration.ModelConfiguration \(property\), 40](#)

P

[aisquared.config.preprocessing.text.Steps.PadSequences \(property\), 22](#)
[aisquared.config.preprocessing.text.Steps.PadSequences \(property\), 22](#)
[aisquared.config.preprocessing.text.Steps.PadSequences \(class in aisquared.config.preprocessing.text.Steps\), 22](#)

password (aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient (class in
property), 45
aisquared.config.feedback.RegistrationFeedback),
path (aisquared.config.analytic.LocalAnalytic.LocalAnalytic 10
property), 7
remove_digits (aisquared.config.preprocessing.text.Steps.RemoveCharac
property), 23
path (aisquared.config.analytic.LocalModel.LocalModel
property), 7
remove_punctuation (aisquared.config.preprocessing.text.Steps.RemoveC
property), 23
period (aisquared.config.analytic.ReverseMLWorkflow.ReverseMLWorkflow
property), 8
remove_user_from_group()
PieChartRendering (class in (aisquared.platform.AISquaredPlatformClient.AISquaredPlatform
aisquared.config.rendering.PieChartRendering), method), 45
34
RemoveCharacters (class in
placement (aisquared.config.rendering.ImageRendering.ImageRendering
aisquared.config.preprocessing.text.Steps),
property), 32
23
placement (aisquared.config.rendering.ObjectRendering.ObjectRendering
aisquared.config.ModelConfiguration.ModelConfiguration
property), 34
property), 40
position (aisquared.config.rendering.ContainerRendering.ContainerRendering
aisquared.config.ModelConfiguration.ModelConfigura
property), 26
property), 40
postprocessor_dict (aisquared.config.ModelConfiguration.ModelConfiguration
aisquared.config.preprocessing.image.Steps),
property), 40
18
postprocessing_steps
result_key (aisquared.config.rendering.WordRendering.WordRendering
(aisquared.config.ModelConfiguration.ModelConfiguration property), 37
property), 40
ReverseMLWorkflow (class in
prediction_key (aisquared.config.rendering.DocumentRendering.DocumentRendering
aisquared.config.analytic.ReverseMLWorkflow),
property), 28
7
preprocessor_dict (aisquared.config.ModelConfiguration.ModelConfiguration
aisquared.config.postprocessing.Registration.Registration
property), 40
property), 15
preprocessing_steps
(aisquared.config.ModelConfiguration.ModelConfiguration
property), 40
5
preserve_aspect_ratio
secret (aisquared.config.analytic.DeployedAnalytic.DeployedAnalytic
(aisquared.config.preprocessing.image.Steps.Resize
property), 18
secret (aisquared.config.analytic.DeployedModel.DeployedModel
property), 6
probability_key (aisquared.config.rendering.DocumentRendering.DocumentRendering
aisquared.config.analytic.ReverseMLWorkflow.ReverseMLWorkflow
property), 28
property), 8
Q
share_model_with_group()
(aisquared.platform.AISquaredPlatformClient.AISquaredPlatform
method), 45
qualifier (aisquared.config.rendering.FilterRendering.FilterRendering
property), 30
share_model_with_user()
QualitativeFeedback (class in (aisquared.platform.AISquaredPlatformClient.AISquaredPlatform
aisquared.config.feedback.QualitativeFeedback), method), 45
10
SimpleFeedback (class in
query_keys (aisquared.config.harvesting.QueryParameterHarvester.QueryParameterHarvester
aisquared.config.feedback.SimpleFeedback),
property), 13
11
query_selector (aisquared.config.rendering.ContainerRendering.ContainerRendering
aisquared.config.preprocessing.image.Steps.Resize
property), 26
property), 18
QueryParameterHarvester (class in SOSRendering (class in
aisquared.config.harvesting.QueryParameterHarvester), aisquared.config.rendering.SOSRendering), 36
12
source (aisquared.config.rendering.FilterRendering.FilterRendering
property), 30
R
split_sentences (aisquared.config.preprocessing.text.Steps.Tokenize
property), 23
regex (aisquared.config.harvesting.TextHarvester.TextHarvester
property), 13
split_words (aisquared.config.preprocessing.text.Steps.Tokenize
property), 23
Regression (class in aisquared.config.postprocessing.Registration.Registration
property), 15

stage(aisquared.config.GraphConfiguration.GraphConfiguration property), 39

stage(aisquared.config.ModelConfiguration.ModelConfiguration property), 40

start_character(aisquared.config.preprocessing.text.Steps.CharacterToDict() (aisquared.config.analytic.LocalAnalytic.LocalAnalytic property), 22 method), 7

stds(aisquared.config.preprocessing.tabular.Steps.ZScore to_dict() (aisquared.config.analytic.LocalModel.LocalModel property), 20 method), 7

step_dict(aisquared.config.preprocessing.image.ImagePreprocessing to_dict() (aisquared.config.analytic.ReverseMLWorkflow.ReverseMLWorkflow property), 16 method), 8

step_dict(aisquared.config.preprocessing.text.TextPreprocessing to_dict() (aisquared.config.feedback.BinaryFeedback.BinaryFeedback property), 24 method), 8

SubtractValue (class in to_dict() (aisquared.config.feedback.ModelFeedback.ModelFeedback method), 9

aisquared.config.preprocessing.image.Steps), to_dict() (aisquared.config.feedback.MulticlassFeedback.MulticlassFeedback method), 10

18 to_dict() (aisquared.config.feedback.QualitativeFeedback.QualitativeFeedback method), 10

T to_dict() (aisquared.config.feedback.RegressionFeedback.RegressionFeedback method), 10

TableRendering (class in to_dict() (aisquared.config.feedback.SimpleFeedback.SimpleFeedback method), 11

aisquared.config.rendering.TableRendering), to_dict() (aisquared.config.GraphConfiguration.GraphConfiguration method), 36

TabularPreprocessor (class in to_dict() (aisquared.config.harvesting.ImageHarvester.ImageHarvester method), 11

aisquared.config.preprocessing.tabular.TabularPreprocessing), to_dict() (aisquared.config.harvesting.InputHarvester.InputHarvester method), 13

21 to_dict() (aisquared.config.harvesting.QueryParameterHarvester.QueryParameterHarvester method), 13

test_connection() (aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient to_dict() (aisquared.config.harvesting.TextHarvester.TextHarvester method), 45

TextHarvester (class in to_dict() (aisquared.config.harvesting.TextHarvester.TextHarvester method), 13

aisquared.config.harvesting.TextHarvester), to_dict() (aisquared.config.harvesting.InputHarvester.InputHarvester method), 12

TextPreprocessor (class in to_dict() (aisquared.config.harvesting.QueryParameterHarvester.QueryParameterHarvester method), 13

aisquared.config.preprocessing.text.TextPreprocessing), to_dict() (aisquared.config.harvesting.TextHarvester.TextHarvester method), 13

24 to_dict() (aisquared.config.harvesting.InputHarvester.InputHarvester method), 12

thickness(aisquared.config.rendering.ImageRendering.ImageRendering property), 32

thickness(aisquared.config.rendering.ObjectRendering.ObjectRendering property), 34

threshold(aisquared.config.postprocessing.BinaryClassification.BinaryClassification property), 14

threshold(aisquared.config.postprocessing.ObjectDetection.ObjectDetection property), 15

threshold_key(aisquared.config.rendering.DocumentRendering.DocumentRendering property), 28

threshold_key(aisquared.config.rendering.ImageRendering.ImageRendering property), 32

threshold_key(aisquared.config.rendering.WordRendering.WordRendering property), 37

threshold_value(aisquared.config.rendering.DocumentRendering.DocumentRendering property), 28

threshold_value(aisquared.config.rendering.ImageRendering.ImageRendering property), 32

threshold_value(aisquared.config.rendering.WordRendering.WordRendering property), 37

to_dict() (aisquared.base.BaseObject.BaseObject method), 3

to_dict() (aisquared.base.CustomObject.CustomObject method), 4

to_dict() (aisquared.config.analytic.DeployedAnalytic.DeployedAnalytic method), 5

to_dict() (aisquared.config.analytic.DeployedModel.DeployedModel method), 6

to_dict() (aisquared.config.analytic.LocalAnalytic.LocalAnalytic method), 7

to_dict() (aisquared.config.analytic.LocalModel.LocalModel method), 7

to_dict() (aisquared.config.analytic.ReverseMLWorkflow.ReverseMLWorkflow method), 8

to_dict() (aisquared.config.feedback.BinaryFeedback.BinaryFeedback method), 8

to_dict() (aisquared.config.feedback.ModelFeedback.ModelFeedback method), 9

to_dict() (aisquared.config.feedback.MulticlassFeedback.MulticlassFeedback method), 10

to_dict() (aisquared.config.feedback.QualitativeFeedback.QualitativeFeedback method), 10

to_dict() (aisquared.config.feedback.RegressionFeedback.RegressionFeedback method), 10

to_dict() (aisquared.config.feedback.SimpleFeedback.SimpleFeedback method), 11

to_dict() (aisquared.config.GraphConfiguration.GraphConfiguration method), 36

to_dict() (aisquared.config.harvesting.ImageHarvester.ImageHarvester method), 11

to_dict() (aisquared.config.harvesting.InputHarvester.InputHarvester method), 12

to_dict() (aisquared.config.harvesting.QueryParameterHarvester.QueryParameterHarvester method), 13

to_dict() (aisquared.config.harvesting.TextHarvester.TextHarvester method), 13

to_dict() (aisquared.config.ModelConfiguration.ModelConfiguration method), 40

to_dict() (aisquared.config.postprocessing.BinaryClassification.BinaryClassification method), 14

to_dict() (aisquared.config.postprocessing.MulticlassClassification.MulticlassClassification method), 15

to_dict() (aisquared.config.postprocessing.ObjectDetection.ObjectDetection method), 15

to_dict() (aisquared.config.postprocessing.Regression.Regression method), 15

to_dict() (aisquared.config.preprocessing.image.ImagePreprocessing.ImagePreprocessing method), 16

to_dict() (aisquared.config.preprocessing.image.Steps.AddValue method), 17

to_dict() (aisquared.config.preprocessing.image.Steps.ConvertToColor method), 17

to_dict() (aisquared.config.preprocessing.image.Steps.DivideValue method), 17

to_dict() (aisquared.config.preprocessing.image.Steps.MultiplyValue method), 18

to_dict() (aisquared.config.preprocessing.image.Steps.Resize method), 18

to_dict()	(aisquared.config.preprocessing.image.Steps.SubtractValue	method), 18	aisquared.base.BaseObject.BaseObject	method), 4
to_dict()	(aisquared.config.preprocessing.tabular.Steps.DropColumns	method), 19	aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient	property), 46
to_dict()	(aisquared.config.preprocessing.tabular.Steps.MimicPattern	method), 20	aisquared.config.preprocessing.text.Steps.Tokenize	property), 23
to_dict()	(aisquared.config.preprocessing.tabular.Steps.OneHot	method), 20	Tokenize (class in aisquared.config.preprocessing.text.Steps),	23
to_dict()	(aisquared.config.preprocessing.tabular.Steps.Trim	method), 20	Tokenize (class in aisquared.config.preprocessing.text.Steps),	23
to_dict()	(aisquared.config.preprocessing.tabular.TabularPreprocessing	method), 21	TruncateLocation (aisquared.config.preprocessing.text.Steps.PadSequences	property), 23
to_dict()	(aisquared.config.preprocessing.text.Steps.ConvertToCase	method), 22	underline_color (aisquared.config.rendering.DocumentRendering.DocumentRendering	property), 28
to_dict()	(aisquared.config.preprocessing.text.Steps.ConvertToVocabulary	method), 22	unshare_model_with_user()	(aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient
to_dict()	(aisquared.config.preprocessing.text.Steps.PadSequences	method), 23	upload_model()	(aisquared.config.preprocessing.text.Steps.Tokenize
to_dict()	(aisquared.config.preprocessing.text.Steps.RemoveCharacters	method), 23	upload_model()	(aisquared.config.preprocessing.text.Steps.Tokenize
to_dict()	(aisquared.config.preprocessing.text.Steps.Tokenize	method), 23	url (aisquared.config.analytic.DeployedAnalytic.DeployedAnalytic	property), 5
to_dict()	(aisquared.config.preprocessing.text.Steps.Trim	method), 24	url (aisquared.config.analytic.DeployedModel.DeployedModel	property), 39
to_dict()	(aisquared.config.preprocessing.text.TextPreprocessing	method), 24	url (aisquared.config.GraphConfiguration.GraphConfiguration	property), 39
to_dict()	(aisquared.config.rendering.BarChartRendering.BarChartRendering	method), 25	url (aisquared.config.ModelConfiguration.ModelConfiguration	property), 40
to_dict()	(aisquared.config.rendering.ContainerRendering.ContainerRendering	method), 26	url_locations (aisquared.config.harvesting.QueryParameterHarvester.QueryParameterHarvester	property), 13
to_dict()	(aisquared.config.rendering.DashboardReplacementRendering.DashboardReplacementRendering	method), 27	username (aisquared.platform.AISquaredPlatformClient.AISquaredPlatformClient	property), 47
to_dict()	(aisquared.config.rendering.DocumentRendering.DocumentRendering	method), 28	value (aisquared.config.preprocessing.image.Steps.AddValue	property), 17
to_dict()	(aisquared.config.rendering.DoughnutChartRendering.DoughnutChartRendering	method), 30	value (aisquared.config.preprocessing.image.Steps.DivideValue	property), 17
to_dict()	(aisquared.config.rendering.FilterRendering.FilterRendering	method), 30	value (aisquared.config.preprocessing.image.Steps.MultiplyValue	property), 18
to_dict()	(aisquared.config.rendering.HTMLTagRendering.HTMLTagRendering	method), 31	value (aisquared.config.preprocessing.image.Steps.SubtractValue	property), 18
to_dict()	(aisquared.config.rendering.ImageRendering.ImageRendering	method), 32	value (aisquared.config.rendering.FilterRendering.FilterRendering	property), 30
to_dict()	(aisquared.config.rendering.LineChartRendering.LineChartRendering	method), 33	values (aisquared.config.preprocessing.tabular.Steps.OneHot	property), 20
to_dict()	(aisquared.config.rendering.ObjectRendering.ObjectRendering	method), 34	version (aisquared.config.GraphConfiguration.GraphConfiguration	property), 39
to_dict()	(aisquared.config.rendering.PieChartRendering.PieChartRendering	method), 35	version (aisquared.config.ModelConfiguration.ModelConfiguration	property), 40
to_dict()	(aisquared.config.rendering.SOSRendering.SOSRendering	method), 36	vocabulary (aisquared.config.preprocessing.text.Steps.ConvertToVocabulary	property), 22
to_dict()	(aisquared.config.rendering.TableRendering.TableRendering	method), 36		
to_dict()	(aisquared.config.rendering.WordRendering.WordRendering	method), 37		

W

`where_replace` (*aisquared.config.rendering.DashboardReplacementRendering.DashboardReplacementRendering* property), [27](#)

`width` (*aisquared.config.rendering.ContainerRendering.ContainerRendering* property), [26](#)

`word_list` (*aisquared.config.rendering.WordRendering.WordRendering* property), [37](#)

`WordRendering` (class in *aisquared.config.rendering.WordRendering*), [37](#)

`words` (*aisquared.config.rendering.DocumentRendering.DocumentRendering* property), [28](#)

X

`xoffset` (*aisquared.config.rendering.ContainerRendering.ContainerRendering* property), [26](#)

Y

`yoffset` (*aisquared.config.rendering.ContainerRendering.ContainerRendering* property), [27](#)

Z

`ZScore` (class in *aisquared.config.preprocessing.tabular.Steps*), [20](#)