

```
# Generated by the protocol buffer compiler.  DO NOT EDIT!
# source: hapi/services/tiller.proto
import sys
_b=sys.version_info[0]<3 and (lambda x:x) or (lambda x:x.encode('latin1'))
from google.protobuf import descriptor as _descriptor
from google.protobuf import message as _message
from google.protobuf import reflection as _reflection
from google.protobuf import symbol_database as _symbol_database
from google.protobuf import descriptor_pb2
# @@protoc_insertion_point(imports)
_sym_db = _symbol_database.Default()
from hapi.chart import chart_pb2 as hapi_dot_chart_dot_chart__pb2
from hapi.chart import config_pb2 as hapi_dot_chart_dot_config__pb2
from hapi.release import release_pb2 as hapi_dot_release_dot_release__pb2
from hapi.release import info_pb2 as hapi_dot_release_dot_info__pb2
from hapi.release import test_run_pb2 as hapi_dot_release_dot_test__run__pb2
from hapi.release import status_pb2 as hapi_dot_release_dot_status__pb2
from hapi.version import version_pb2 as hapi_dot_version_dot_version__pb2
DESCRIPTOR = _descriptor.FileDescriptor(
    name='hapi/services/tiller.proto',
    package='hapi.services.tiller',
    syntax='proto3',

    serialized_pb=_b('\n\x1ahapi/services/tiller.proto\x12\x14hapi.services.tiller\x1a\x16
hapi/chart/chart.proto\x1a\x17hapi/chart/config.proto\x1a\x1ahapi/release/release.pro
t\x1a\x17hapi/release/info.proto\x1a\x1bhapi/release/test_run.proto\x1a\x19hapi/releas
e/status.proto\x1a\x1ahapi/version/version.proto"\xfe\x01\n\x13ListReleasesRequest\x1
2\r\n\x05limit\x18\x01
\x01(\x03\x12\x0e\n\x06offset\x18\x02
\x01(\t\x12\x36\n\x07sort_by\x18\x03
\x01(\x0e\x32.hapi.services.tiller.ListSort.SortBy\x12\x0e\n\x06filter\x18\x04
\x01(\t\x12<\n\nsort_order\x18\x05
\x01(\x0e\x32(.hapi.services.tiller.ListSort.SortOrder\x12/\n\x0cstatus_codes\x18\x06
\x03(\x0e\x32\x19.hapi.release.Status.Code\x12\x11\n\tnamespace\x18\x07
\x01(\t"\n\x08ListSort"2\n\x06SortBy\x12\x0b\n\x07UNKNOWN\x10\x00\x12\x08\n\x04NAME
\x10\x01\x12\x11\n\rLAST_RELEASED\x10\x02"\x1e\n\tnSortOrder\x12\x07\n\x03\x41SC\x10\x
00\x12\x08\n\x04\x44\x45SC\x10\x01"kn\x14ListReleasesResponse\x12\r\n\x05\x63ount\x1
8\x01
\x01(\x03\x12\x0c\n\x04next\x18\x02
\x01(\t\x12\r\n\x05total\x18\x03
\x01(\x03\x12\' \n\x08releases\x18\x04
\x03(\x0b\x32\x15.hapi.release.Release"8\n\x17GetReleaseStatusRequest\x12\x0c\n\x04na
me\x18\x01
\x01(\t\x12\x0f\n\x07version\x18\x02
\x01(\x05" ]\n\x18GetReleaseStatusResponse\x12\x0c\n\x04name\x18\x01
\x01(\t\x12
\n\x04info\x18\x02
\x01(\x0b\x32\x12.hapi.release.Info\x12\x11\n\tnamespace\x18\x03
\x01(\t"9\n\x18GetReleaseContentRequest\x12\x0c\n\x04name\x18\x01
\x01(\t\x12\x0f\n\x07version\x18\x02
\x01(\x05"C\n\x19GetReleaseContentResponse\x12&\n\x07release\x18\x01
\x01(\x0b\x32\x15.hapi.release.Release"\xfe\x01\n\x14UpdateReleaseRequest\x12\x0c\n\x
04name\x18\x01
\x01(\t\x12
\n\x05\x63hart\x18\x02
\x01(\x0b\x32\x11.hapi.chart.Chart\x12"\n\x06values\x18\x03
\x01(\x0b\x32\x12.hapi.chart.Config\x12\x0f\n\x07\x64ry_run\x18\x04
\x01(\x08\x12\x15\n\rdisable_hooks\x18\x05
\x01(\x08\x12\x10\n\x08recreate\x18\x06
```

```

\x01(\x08\x12\x0f\n\x07timeout\x18\x07      \x01(\x03\x12\x14\n\x0creset_values\x18\x08
\x01(\x08\x12\x0c\n\x04wait\x18\t            \x01(\x08\x12\x14\n\x0creuse_values\x18\n
\x01(\x08\x12\r\n\x05\x66orce\x18\x0b
\x01(\x08\?"\n\x15UpdateReleaseResponse\x12&\n\x07release\x18\x01
\x01(\x0b\x32\x15.hapi.release.Release\`\x9f\x01\n\x16RollbackReleaseRequest\x12\x0c\n
\x04name\x18\x01                                \x01(\t\x12\x0f\n\x07\x64ry_run\x18\x02
\x01(\x08\x12\x15\n\rdisable_hooks\x18\x03      \x01(\x08\x12\x0f\n\x07version\x18\x04
\x01(\x05\x12\x10\n\x08recreate\x18\x05          \x01(\x08\x12\x0f\n\x07timeout\x18\x06
\x01(\x03\x12\x0c\n\x04wait\x18\x07              \x01(\x08\x12\r\n\x05\x66orce\x18\x08
\x01(\x08\`A\n\x17RollbackReleaseResponse\x12&\n\x07release\x18\x01
\x01(\x0b\x32\x15.hapi.release.Release\`\xf3\x01\n\x15InstallReleaseRequest\x12
\n\x05\x63hart\x18\x01      \x01(\x0b\x32\x11.hapi.chart.Chart\x12`\n\x06values\x18\x02
\x01(\x0b\x32\x12.hapi.chart.Config\x12\x0f\n\x07\x64ry_run\x18\x03
\x01(\x08\x12\x0c\n\x04name\x18\x04              \x01(\t\x12\x15\n\rdisable_hooks\x18\x05
\x01(\x08\x12\x11\n\tnamespace\x18\x06          \x01(\t\x12\x12\n\nreuse_name\x18\x07
\x01(\x08\x12\x0f\n\x07timeout\x18\x08           \x01(\x03\x12\x0c\n\x04wait\x18\t
\x01(\x08\x12\x18\n\x10\x64isable_crd_hook\x18\n
\x01(\x08\`@\n\x16InstallReleaseResponse\x12&\n\x07release\x18\x01
\x01(\x0b\x32\x15.hapi.release.Release\`^\n\x17UninstallReleaseRequest\x12\x0c\n\x04na
me\x18\x01  \x01(\t\x12\x15\n\rdisable_hooks\x18\x02  \x01(\x08\x12\r\n\x05purge\x18\x03
\x01(\x08\x12\x0f\n\x07timeout\x18\x04
\x01(\x03\`P\n\x18UninstallReleaseResponse\x12&\n\x07release\x18\x01
\x01(\x0b\x32\x15.hapi.release.Release\x12\x0c\n\x04info\x18\x02
\x01(\t\`\x13\n\x11GetVersionRequest\`<\n\x12GetVersionResponse\x12&\n\x07Version\x18\
x01
\x01(\x0b\x32\x15.hapi.version.Version\`. \n\x11GetHistoryRequest\x12\x0c\n\x04name\x18
\x01                                \x01(\t\x12\x0b\n\x03max\x18\x02
\x01(\x05\`= \n\x12GetHistoryResponse\x12\` \n\x08releases\x18\x01
\x03(\x0b\x32\x15.hapi.release.Release\`D\n\x12TestReleaseRequest\x12\x0c\n\x04name\x1
8\x01  \x01(\t\x12\x0f\n\x07timeout\x18\x02  \x01(\x03\x12\x0f\n\x07\x63leanup\x18\x03
\x01(\x08\`P\n\x13TestReleaseResponse\x12\x0b\n\x03msg\x18\x01
\x01(\t\x12, \n\x06status\x18\x02
\x01(\x0e\x32\x1c.hapi.release.TestRun.Status2\xdb\x08\n\x0eReleaseService\x12i\n\x0cL
istReleases\x12).hapi.services.tiller.ListReleasesRequest\x1a*.hapi.services.tiller.Li
stReleasesResponse\`\x00\x30\x01\x12s\n\x10GetReleaseStatus\x12-.hapi.services.tiller.
GetReleaseStatusRequest\x1a..hapi.services.tiller.GetReleaseStatusResponse\`\x00\x12v\
\n\x11GetReleaseContent\x12..hapi.services.tiller.GetReleaseContentRequest\x1a/.hapi.se
rvices.tiller.GetReleaseContentResponse\`\x00\x12j\n\rUpdateRelease\x12*.hapi.services.
tiller.UpdateReleaseRequest\x1a+.hapi.services.tiller.UpdateReleaseResponse\`\x00\x12m
\n\x0eInstallRelease\x12+.hapi.services.tiller.InstallReleaseRequest\x1a..hapi.servic
e.s.tiller.InstallReleaseResponse\`\x00\x12s\n\x10UninstallRelease\x12-.hapi.services.ti
ller.UninstallReleaseRequest\x1a..hapi.services.tiller.UninstallReleaseResponse\`\x00\
x12\x61\n\nGetVersion\x12\`.hapi.services.tiller.GetVersionRequest\x1a(.hapi.services.
tiller.GetVersionResponse\`\x00\x12p\n\x0fRollbackRelease\x12..hapi.services.tiller.Ro
llbackReleaseRequest\x1a-.hapi.services.tiller.RollbackReleaseResponse\`\x00\x12\x61\n
\nGetHistory\x12\`.hapi.services.tiller.GetHistoryRequest\x1a(.hapi.services.tiller.Ge
tHistoryResponse\`\x00\x12i\n\x0eRunReleaseTest\x12(.hapi.services.tiller.TestReleaseR
equest\x1a).hapi.services.tiller.TestReleaseResponse\`\x00\x30\x01\x42\nZ\x08servicesb
\x06proto3')

```

```
dependencies=[hapi_dot_chart_dot_chart__pb2.DESRIPTOR,hapi_dot_chart_dot_config__pb2.
DESCRIPTOR,hapi_dot_release_dot_release__pb2.DESRIPTOR,hapi_dot_release_dot_info__pb2.
DESCRIPTOR,hapi_dot_release_dot_test__run__pb2.DESRIPTOR,hapi_dot_release_dot_status__
pb2.DESRIPTOR,hapi_dot_version_dot_version__pb2.DESRIPTOR,])
_sym_db.RegisterFileDescriptor(DESCRIPTOR)
_LISTSORT_SORTBY = _descriptor.EnumDescriptor(
    name='SortBy',
    full_name='hapi.services.tiller.ListSort.SortBy',
    filename=None,
    file=DESCRIPTOR,
    values=[
        _descriptor.EnumValueDescriptor(
            name='UNKNOWN', index=0, number=0,
            options=None,
            type=None),
        _descriptor.EnumValueDescriptor(
            name='NAME', index=1, number=1,
            options=None,
            type=None),
        _descriptor.EnumValueDescriptor(
            name='LAST_RELEASED', index=2, number=2,
            options=None,
            type=None),
    ],#登录
    containing_type=None,
    options=None,
    serialized_start=507,
    serialized_end=557,
)
_sym_db.RegisterEnumDescriptor(_LISTSORT_SORTBY)
_LISTSORT_SORTORDER = _descriptor.EnumDescriptor(
    name='SortOrder',
    full_name='hapi.services.tiller.ListSort.SortOrder',
    filename=None,
    file=DESCRIPTOR,
    values=[
        _descriptor.EnumValueDescriptor(
            name='ASC', index=0, number=0,
            options=None,
            type=None),
        _descriptor.EnumValueDescriptor(
            name='DESC', index=1, number=1,
            options=None,
            type=None),
    ],
    containing_type=None,
    options=None,
    serialized_start=559,
    serialized_end=589,
```

```

)
_sym_db.RegisterEnumDescriptor(_LISTSORT_SORTORDER)
_LISTRELEASESREQUEST = _descriptor.Descriptor(
    name='ListReleasesRequest',
    full_name='hapi.services.tiller.ListReleasesRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='limit',          full_name='hapi.services.tiller.ListReleasesRequest.limit',
index=0,
            number=1, type=3, cpp_type=2, label=1,
            has_default_value=False, default_value=0,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='offset',          full_name='hapi.services.tiller.ListReleasesRequest.offset',
index=1,
            number=2, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='sort_by',          full_name='hapi.services.tiller.ListReleasesRequest.sort_by',
index=2,
            number=3, type=14, cpp_type=8, label=1,
            has_default_value=False, default_value=0,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='filter',          full_name='hapi.services.tiller.ListReleasesRequest.filter',
index=3,
            number=4, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='sort_order',
full_name='hapi.services.tiller.ListReleasesRequest.sort_order', index=4,
            number=5, type=14, cpp_type=8, label=1,
            has_default_value=False, default_value=0,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(

```

```

        name='status_codes',
full_name='hapi.services.tiller.ListReleasesRequest.status_codes', index=5,
        number=6, type=14, cpp_type=8, label=3,
        has_default_value=False, default_value=[],
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='namespace', full_name='hapi.services.tiller.ListReleasesRequest.namespace',
index=6,
        number=7, type=9, cpp_type=9, label=1,
        has_default_value=False, default_value=_b("").decode('utf-8'),
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
],
extensions=[
],
nested_types=[],
enum_types=[
],
options=None,
is_extendable=False,
syntax='proto3',
extension_ranges=[],
oneofs=[
],
serialized_start=239,
serialized_end=493,
)
_LISTSORT = _descriptor.Descriptor(
    name='ListSort',
    full_name='hapi.services.tiller.ListSort',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
        _LISTSORT_SORTBY,
        _LISTSORT_SORTORDER,
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[

```

```

    ],
    serialized_start=495,
    serialized_end=589,
)#系统主页
_LISTRELEASESRESPONSE = _descriptor.Descriptor(
    name='ListReleasesResponse',
    full_name='hapi.services.tiller.ListReleasesResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='count',          full_name='hapi.services.tiller.ListReleasesResponse.count',
index=0,
            number=1, type=3, cpp_type=2, label=1,
            has_default_value=False, default_value=0,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='next', full_name='hapi.services.tiller.ListReleasesResponse.next', index=1,
            number=2, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='total',          full_name='hapi.services.tiller.ListReleasesResponse.total',
index=2,
            number=3, type=3, cpp_type=2, label=1,
            has_default_value=False, default_value=0,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='releases', full_name='hapi.services.tiller.ListReleasesResponse.releases',
index=3,
            number=4, type=11, cpp_type=10, label=3,
            has_default_value=False, default_value=[],
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,

```

```

    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=591,
    serialized_end=698,
)
_GETRELEASESTATUSREQUEST = _descriptor.Descriptor(
    name='GetReleaseStatusRequest',
    full_name='hapi.services.tiller.GetReleaseStatusRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='name',          full_name='hapi.services.tiller.GetReleaseStatusRequest.name',
index=0,
            number=1, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='version', full_name='hapi.services.tiller.GetReleaseStatusRequest.version',
index=1,
            number=2, type=5, cpp_type=1, label=1,
            has_default_value=False, default_value=0,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=700,
    serialized_end=756,
)
_GETRELEASESTATUSRESPONSE = _descriptor.Descriptor(
    name='GetReleaseStatusResponse',
    full_name='hapi.services.tiller.GetReleaseStatusResponse',
    filename=None,
    file=DESCRIPTOR,

```

```

containing_type=None,
fields=[
    _descriptor.FieldDescriptor(
        name='name',      full_name='hapi.services.tiller.GetReleaseStatusResponse.name',
index=0,
        number=1, type=9, cpp_type=9, label=1,
        has_default_value=False, default_value=_b("").decode('utf-8'),
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='info',      full_name='hapi.services.tiller.GetReleaseStatusResponse.info',
index=1,
        number=2, type=11, cpp_type=10, label=1,
        has_default_value=False, default_value=None,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='namespace',
full_name='hapi.services.tiller.GetReleaseStatusResponse.namespace', index=2,
        number=3, type=9, cpp_type=9, label=1,
        has_default_value=False, default_value=_b("").decode('utf-8'),
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
],
extensions=[
],
nested_types=[],
enum_types=[
],
options=None,
is_extendable=False,
syntax='proto3',
extension_ranges=[],
oneofs=[
],
serialized_start=758,
serialized_end=851,
)
_GETRELEASECONTENTREQUEST = _descriptor.Descriptor(
    name='GetReleaseContentRequest',
    full_name='hapi.services.tiller.GetReleaseContentRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='name',      full_name='hapi.services.tiller.GetReleaseContentRequest.name',

```



```

index=0,
    number=1, type=9, cpp_type=9, label=1,
    has_default_value=False, default_value=_b("").decode('utf-8'),
    message_type=None, enum_type=None, containing_type=None,
    is_extension=False, extension_scope=None,
    options=None),
    _descriptor.FieldDescriptor(
        name='version',
full_name='hapi.services.tiller.GetReleaseContentRequest.version', index=1,
        number=2, type=5, cpp_type=1, label=1,
        has_default_value=False, default_value=0,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
],
extensions=[
],
nested_types=[],
enum_types=[
],
options=None,
is_extendable=False,
syntax='proto3',
extension_ranges=[],
oneofs=[
],
serialized_start=853,
serialized_end=910,
)
_GETRELEASECONTENTRESPONSE = _descriptor.Descriptor(
    name='GetReleaseContentResponse',
    full_name='hapi.services.tiller.GetReleaseContentResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release',
full_name='hapi.services.tiller.GetReleaseContentResponse.release', index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
],
extensions=[
],
nested_types=[],
enum_types=[
],

```

```

options=None,
is_extendable=False,
syntax='proto3',
extension_ranges=[],
oneofs=[
],
serialized_start=912,
serialized_end=979,
)#导航栏
_UPDATERELEASEREQUEST = _descriptor.Descriptor(
    name='UpdateReleaseRequest',
    full_name='hapi.services.tiller.UpdateReleaseRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='name', full_name='hapi.services.tiller.UpdateReleaseRequest.name', index=0,
            number=1, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='chart', full_name='hapi.services.tiller.UpdateReleaseRequest.chart',
index=1,
            number=2, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='values', full_name='hapi.services.tiller.UpdateReleaseRequest.values',
index=2,
            number=3, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='dry_run', full_name='hapi.services.tiller.UpdateReleaseRequest.dry_run',
index=3,
            number=4, type=8, cpp_type=7, label=1,
            has_default_value=False, default_value=False,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='disable_hooks',
full_name='hapi.services.tiller.UpdateReleaseRequest.disable_hooks', index=4,

```

```

        number=5, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='recreate', full_name='hapi.services.tiller.UpdateReleaseRequest.recreate',
index=5,
        number=6, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='timeout', full_name='hapi.services.tiller.UpdateReleaseRequest.timeout',
index=6,
        number=7, type=3, cpp_type=2, label=1,
        has_default_value=False, default_value=0,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='reset_values',
full_name='hapi.services.tiller.UpdateReleaseRequest.reset_values', index=7,
        number=8, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='wait', full_name='hapi.services.tiller.UpdateReleaseRequest.wait', index=8,
        number=9, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='reuse_values',
full_name='hapi.services.tiller.UpdateReleaseRequest.reuse_values', index=9,
        number=10, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='force', full_name='hapi.services.tiller.UpdateReleaseRequest.force',
index=10,
        number=11, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,

```

```

        is_extension=False, extension_scope=None,
        options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=982,
    serialized_end=1236,
)
_UPDATERELEASERESPONSE = _descriptor.Descriptor(
    name='UpdateReleaseResponse',
    full_name='hapi.services.tiller.UpdateReleaseResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.tiller.UpdateReleaseResponse.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=1238,
    serialized_end=1301,
)
_ROLLBACKRELEASEREQUEST = _descriptor.Descriptor(
    name='RollbackReleaseRequest',
    full_name='hapi.services.tiller.RollbackReleaseRequest',

```

```

filename=None,
file=DESCRIPTOR,
containing_type=None,
fields=[
    _descriptor.FieldDescriptor(
        name='name',          full_name='hapi.services.tiller.RollbackReleaseRequest.name',
index=0,
        number=1, type=9, cpp_type=9, label=1,
        has_default_value=False, default_value=_b("").decode('utf-8'),
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='dry_run', full_name='hapi.services.tiller.RollbackReleaseRequest.dry_run',
index=1,
        number=2, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='disable_hooks',
full_name='hapi.services.tiller.RollbackReleaseRequest.disable_hooks', index=2,
        number=3, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='version', full_name='hapi.services.tiller.RollbackReleaseRequest.version',
index=3,
        number=4, type=5, cpp_type=1, label=1,
        has_default_value=False, default_value=0,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='recreate',
full_name='hapi.services.tiller.RollbackReleaseRequest.recreate', index=4,
        number=5, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='timeout', full_name='hapi.services.tiller.RollbackReleaseRequest.timeout',
index=5,
        number=6, type=3, cpp_type=2, label=1,
        has_default_value=False, default_value=0,
        message_type=None, enum_type=None, containing_type=None,

```

```

        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='wait',          full_name='hapi.services.tiller.RollbackReleaseRequest.wait',
index=6,
        number=7, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='force',          full_name='hapi.services.tiller.RollbackReleaseRequest.force',
index=7,
        number=8, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
],#设备连接
extensions=[
],
nested_types=[],
enum_types=[
],
options=None,
is_extendable=False,
syntax='proto3',
extension_ranges=[],
oneofs=[
],
serialized_start=1304,
serialized_end=1463,
)
_ROLLBACKRELEASERESPONSE = _descriptor.Descriptor(
    name='RollbackReleaseResponse',
    full_name='hapi.services.tiller.RollbackReleaseResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.tiller.RollbackReleaseResponse.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[

```

```

    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=1465,
    serialized_end=1530,
)
_INSTALLRELEASEREQUEST = _descriptor.Descriptor(
    name='InstallReleaseRequest',
    full_name='hapi.services.tiller.InstallReleaseRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='chart',          full_name='hapi.services.tiller.InstallReleaseRequest.chart',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='values',         full_name='hapi.services.tiller.InstallReleaseRequest.values',
index=1,
            number=2, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='dry_run',       full_name='hapi.services.tiller.InstallReleaseRequest.dry_run',
index=2,
            number=3, type=8, cpp_type=7, label=1,
            has_default_value=False, default_value=False,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='name',          full_name='hapi.services.tiller.InstallReleaseRequest.name',
index=3,
            number=4, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),
            message_type=None, enum_type=None, containing_type=None,

```

```

        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='disable_hooks',
full_name='hapi.services.tiller.InstallReleaseRequest.disable_hooks', index=4,
        number=5, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='namespace',
full_name='hapi.services.tiller.InstallReleaseRequest.namespace', index=5,
        number=6, type=9, cpp_type=9, label=1,
        has_default_value=False, default_value=_b("").decode('utf-8'),
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='reuse_name',
full_name='hapi.services.tiller.InstallReleaseRequest.reuse_name', index=6,
        number=7, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='timeout', full_name='hapi.services.tiller.InstallReleaseRequest.timeout',
index=7,
        number=8, type=3, cpp_type=2, label=1,
        has_default_value=False, default_value=0,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='wait', full_name='hapi.services.tiller.InstallReleaseRequest.wait',
index=8,
        number=9, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='disable_crd_hook',
full_name='hapi.services.tiller.InstallReleaseRequest.disable_crd_hook', index=9,
        number=10, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),

```



```

    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=1533,
    serialized_end=1776,
)
_INSTALLRELEASERESPONSE = _descriptor.Descriptor(
    name='InstallReleaseResponse',
    full_name='hapi.services.tiller.InstallReleaseResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.tiller.InstallReleaseResponse.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=1778,
    serialized_end=1842,
)
_UNINSTALLRELEASEREQUEST = _descriptor.Descriptor(
    name='UninstallReleaseRequest',
    full_name='hapi.services.tiller.UninstallReleaseRequest',
    filename=None,
    file=DESCRIPTOR,

```

```

    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='name',          full_name='hapi.services.tiller.UninstallReleaseRequest.name',
index=0,
            number=1, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='disable_hooks',
full_name='hapi.services.tiller.UninstallReleaseRequest.disable_hooks', index=1,
            number=2, type=8, cpp_type=7, label=1,
            has_default_value=False, default_value=False,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='purge',          full_name='hapi.services.tiller.UninstallReleaseRequest.purge',
index=2,
            number=3, type=8, cpp_type=7, label=1,
            has_default_value=False, default_value=False,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='timeout', full_name='hapi.services.tiller.UninstallReleaseRequest.timeout',
index=3,
            number=4, type=3, cpp_type=2, label=1,
            has_default_value=False, default_value=0,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=1844,
    serialized_end=1938,
) #添加 IP
_UNINSTALLRELEASERESPONSE = _descriptor.Descriptor(

```

```

    name='UninstallReleaseResponse',
    full_name='hapi.services.tiller.UninstallReleaseResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release',
full_name='hapi.services.tiller.UninstallReleaseResponse.release', index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='info', full_name='hapi.services.tiller.UninstallReleaseResponse.info',
index=1,
            number=2, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=1940,
    serialized_end=2020,
)
_GETVERSIONREQUEST = _descriptor.Descriptor(
    name='GetVersionRequest',
    full_name='hapi.services.tiller.GetVersionRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],

```

```

options=None,
is_extendable=False,
syntax='proto3',
extension_ranges=[],
oneofs=[
],
serialized_start=2022,
serialized_end=2041,
)
_GETVERSIONRESPONSE = _descriptor.Descriptor(
    name='GetVersionResponse',
    full_name='hapi.services.tiller.GetVersionResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='Version',          full_name='hapi.services.tiller.GetVersionResponse.Version',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=2043,
    serialized_end=2103,
)
_GETHISTORYREQUEST = _descriptor.Descriptor(
    name='GetHistoryRequest',
    full_name='hapi.services.tiller.GetHistoryRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='name', full_name='hapi.services.tiller.GetHistoryRequest.name', index=0,
            number=1, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),

```

```

        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='max', full_name='hapi.services.tiller.GetHistoryRequest.max', index=1,
        number=2, type=5, cpp_type=1, label=1,
        has_default_value=False, default_value=0,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
],
extensions=[
],
nested_types=[],
enum_types=[
],
options=None,
is_extendable=False,
syntax='proto3',
extension_ranges=[],
oneofs=[
],
serialized_start=2105,
serialized_end=2151,
)
_GETHISTORYRESPONSE = _descriptor.Descriptor(
    name='GetHistoryResponse',
    full_name='hapi.services.tiller.GetHistoryResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='releases', full_name='hapi.services.tiller.GetHistoryResponse.releases',
            index=0,
            number=1, type=11, cpp_type=10, label=3,
            has_default_value=False, default_value=[],
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],

```

```

    oneofs=[
    ],
    serialized_start=2153,
    serialized_end=2214,
)
_TESTRELEASEREQUEST = _descriptor.Descriptor(
    name='TestReleaseRequest',
    full_name='hapi.services.tiller.TestReleaseRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='name', full_name='hapi.services.tiller.TestReleaseRequest.name', index=0,
            number=1, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='timeout', full_name='hapi.services.tiller.TestReleaseRequest.timeout',
index=1,
            number=2, type=3, cpp_type=2, label=1,
            has_default_value=False, default_value=0,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='cleanup', full_name='hapi.services.tiller.TestReleaseRequest.cleanup',
index=2,
            number=3, type=8, cpp_type=7, label=1,
            has_default_value=False, default_value=False,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=2216,
    serialized_end=2284,
)

```

```

_TESTRELEASESERESPONSE = _descriptor.Descriptor(
    name='TestReleaseResponse',
    full_name='hapi.services.tiller.TestReleaseResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='msg', full_name='hapi.services.tiller.TestReleaseResponse.msg', index=0,
            number=1, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='status', full_name='hapi.services.tiller.TestReleaseResponse.status',
index=1,
            number=2, type=14, cpp_type=8, label=1,
            has_default_value=False, default_value=0,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],#流量管理
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=2286,
    serialized_end=2366,
)

_LISTRELEASESREQUEST.fields_by_name['sort_by'].enum_type = _LISTSORT_SORTBY
_LISTRELEASESREQUEST.fields_by_name['sort_order'].enum_type = _LISTSORT_SORTORDER
_LISTRELEASESREQUEST.fields_by_name['status_codes'].enum_type =
hapi_dot_release_dot_status_pb2._STATUS_CODE
_LISTSORT_SORTBY.containing_type = _LISTSORT
_LISTSORT_SORTORDER.containing_type = _LISTSORT
_LISTRELEASESRESPONSE.fields_by_name['releases'].message_type =
hapi_dot_release_dot_release_pb2._RELEASE
_GETRELEASESTATUSRESPONSE.fields_by_name['info'].message_type =
hapi_dot_release_dot_info_pb2._INFO
_GETRELEASECONTENTRESPONSE.fields_by_name['release'].message_type =
hapi_dot_release_dot_release_pb2._RELEASE
_UPDATERELEASEREQUEST.fields_by_name['chart'].message_type =

```

```

hapi_dot_chart_dot_chart__pb2._CHART
_UPDATERELEASEREQUEST.fields_by_name['values'].message_type =
hapi_dot_chart_dot_config__pb2._CONFIG
_UPDATERELEASERESPONSE.fields_by_name['release'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_ROLLBACKRELEASERESPONSE.fields_by_name['release'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_INSTALLRELEASEREQUEST.fields_by_name['chart'].message_type =
hapi_dot_chart_dot_chart__pb2._CHART
_INSTALLRELEASEREQUEST.fields_by_name['values'].message_type =
hapi_dot_chart_dot_config__pb2._CONFIG
_INSTALLRELEASERESPONSE.fields_by_name['release'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_UNINSTALLRELEASERESPONSE.fields_by_name['release'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_GETVERSIONRESPONSE.fields_by_name['Version'].message_type =
hapi_dot_version_dot_version__pb2._VERSION
_GETHISTORYRESPONSE.fields_by_name['releases'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_TESTRELEASERESPONSE.fields_by_name['status'].enum_type =
hapi_dot_release_dot_test__run__pb2._TESTRUN_STATUS
DESCRIPTOR.message_types_by_name['ListReleasesRequest'] = _LISTRELEASESREQUEST
DESCRIPTOR.message_types_by_name['ListSort'] = _LISTSORT
DESCRIPTOR.message_types_by_name['ListReleasesResponse'] = _LISTRELEASESRESPONSE
DESCRIPTOR.message_types_by_name['GetReleaseStatusRequest'] = _GETRELEASESTATUSREQUEST
DESCRIPTOR.message_types_by_name['GetReleaseStatusResponse'] =
_GETRELEASESTATUSRESPONSE
DESCRIPTOR.message_types_by_name['GetReleaseContentRequest'] =
_GETRELEASECONTENTREQUEST
DESCRIPTOR.message_types_by_name['GetReleaseContentResponse'] =
_GETRELEASECONTENTRESPONSE
DESCRIPTOR.message_types_by_name['UpdateReleaseRequest'] = _UPDATERELEASEREQUEST
DESCRIPTOR.message_types_by_name['UpdateReleaseResponse'] = _UPDATERELEASERESPONSE
DESCRIPTOR.message_types_by_name['RollbackReleaseRequest'] = _ROLLBACKRELEASEREQUEST
DESCRIPTOR.message_types_by_name['RollbackReleaseResponse'] = _ROLLBACKRELEASERESPONSE
DESCRIPTOR.message_types_by_name['InstallReleaseRequest'] = _INSTALLRELEASEREQUEST
DESCRIPTOR.message_types_by_name['InstallReleaseResponse'] = _INSTALLRELEASERESPONSE
DESCRIPTOR.message_types_by_name['UninstallReleaseRequest'] = _UNINSTALLRELEASEREQUEST
DESCRIPTOR.message_types_by_name['UninstallReleaseResponse'] =
_UNINSTALLRELEASERESPONSE
DESCRIPTOR.message_types_by_name['GetVersionRequest'] = _GETVERSIONREQUEST
DESCRIPTOR.message_types_by_name['GetVersionResponse'] = _GETVERSIONRESPONSE
DESCRIPTOR.message_types_by_name['GetHistoryRequest'] = _GETHISTORYREQUEST
DESCRIPTOR.message_types_by_name['GetHistoryResponse'] = _GETHISTORYRESPONSE
DESCRIPTOR.message_types_by_name['TestReleaseRequest'] = _TESTRELEASEREQUEST
DESCRIPTOR.message_types_by_name['TestReleaseResponse'] = _TESTRELEASERESPONSE
ListReleasesRequest = _reflection.GeneratedProtocolMessageType('ListReleasesRequest',
(_message.Message,), dict(
    DESCRIPTOR = _LISTRELEASESREQUEST,
    __module__ = 'hapi.services.tiller_pb2'

```



```

    # @@protoc_insertion_point(class_scope:hapi.services.tiller.ListReleasesRequest)
    ))
_sym_db.RegisterMessage(ListReleasesRequest)
ListSort = _reflection.GeneratedProtocolMessageType('ListSort', (_message.Message,),
dict(
    DESCRIPTOR = _LISTSORT,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.ListSort)
    ))

_sym_db.RegisterMessage(ListSort)
ListReleasesResponse = _reflection.GeneratedProtocolMessageType('ListReleasesResponse',
(_message.Message,), dict(
    DESCRIPTOR = _LISTRELEASESRESPONSE,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.ListReleasesResponse)
    ))
_sym_db.RegisterMessage(ListReleasesResponse)
GetReleaseStatusRequest =
_reflection.GeneratedProtocolMessageType('GetReleaseStatusRequest',
(_message.Message,), dict(
    DESCRIPTOR = _GETRELEASESTATUSREQUEST,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.GetReleaseStatusRequest)
    ))
_sym_db.RegisterMessage(GetReleaseStatusRequest)
GetReleaseStatusResponse =
_reflection.GeneratedProtocolMessageType('GetReleaseStatusResponse',
(_message.Message,), dict(
    DESCRIPTOR = _GETRELEASESTATUSRESPONSE,
    __module__ = 'hapi.services.tiller_pb2'
    #
    @@protoc_insertion_point(class_scope:hapi.services.tiller.GetReleaseStatusResponse)
    ))
_sym_db.RegisterMessage(GetReleaseStatusResponse)
GetReleaseContentRequest =
_reflection.GeneratedProtocolMessageType('GetReleaseContentRequest',
(_message.Message,), dict(
    DESCRIPTOR = _GETRELEASECONTENTREQUEST,
    __module__ = 'hapi.services.tiller_pb2'
    #
    @@protoc_insertion_point(class_scope:hapi.services.tiller.GetReleaseContentRequest)
    ))
_sym_db.RegisterMessage(GetReleaseContentRequest)
GetReleaseContentResponse =
_reflection.GeneratedProtocolMessageType('GetReleaseContentResponse',
(_message.Message,), dict(
    DESCRIPTOR = _GETRELEASECONTENTRESPONSE,
    __module__ = 'hapi.services.tiller_pb2'
    #

```

```

@@protoc_insertion_point(class_scope:hapi.services.tiller.GetReleaseContentResponse)
    ))
_sym_db.RegisterMessage(GetReleaseContentResponse)
UpdateReleaseRequest = _reflection.GeneratedProtocolMessageType('UpdateReleaseRequest',
(_message.Message,), dict(
    DESCRIPTOR = _UPDATERELEASEREQUEST,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.UpdateReleaseRequest)
    ))
_sym_db.RegisterMessage(UpdateReleaseRequest)
UpdateReleaseResponse =
_reflection.GeneratedProtocolMessageType('UpdateReleaseResponse', (_message.Message,),
dict(
    DESCRIPTOR = _UPDATERELEASERESPONSE,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.UpdateReleaseResponse)
    ))
_sym_db.RegisterMessage(UpdateReleaseResponse)
RollbackReleaseRequest =
_reflection.GeneratedProtocolMessageType('RollbackReleaseRequest', (_message.Message,),
dict(
    DESCRIPTOR = _ROLLBACKRELEASEREQUEST,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.RollbackReleaseRequest)
    ))
_sym_db.RegisterMessage(RollbackReleaseRequest)
RollbackReleaseResponse =
_reflection.GeneratedProtocolMessageType('RollbackReleaseResponse',
(_message.Message,), dict(
    DESCRIPTOR = _ROLLBACKRELEASERESPONSE,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.RollbackReleaseResponse)
    ))
_sym_db.RegisterMessage(RollbackReleaseResponse)
InstallReleaseRequest =
_reflection.GeneratedProtocolMessageType('InstallReleaseRequest', (_message.Message,),
dict(
    DESCRIPTOR = _INSTALLRELEASEREQUEST,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.InstallReleaseRequest)
    ))
_sym_db.RegisterMessage(InstallReleaseRequest)
InstallReleaseResponse =
_reflection.GeneratedProtocolMessageType('InstallReleaseResponse', (_message.Message,),
dict(
    DESCRIPTOR = _INSTALLRELEASERESPONSE,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.InstallReleaseResponse)
    ))
_sym_db.RegisterMessage(InstallReleaseResponse)

```

```

UninstallReleaseRequest                                     =
_reflection.GeneratedProtocolMessageType(' UninstallReleaseRequest',
(_message.Message,), dict(
    DESCRIPTOR = _UNINSTALLRELEASEREQUEST,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.UninstallReleaseRequest)
))
_sym_db.RegisterMessage(UninstallReleaseRequest)
UninstallReleaseResponse                                   =
_reflection.GeneratedProtocolMessageType(' UninstallReleaseResponse',
(_message.Message,), dict(
    DESCRIPTOR = _UNINSTALLRELEASERESPONSE,
    __module__ = 'hapi.services.tiller_pb2'
    #
    @@protoc_insertion_point(class_scope:hapi.services.tiller.UninstallReleaseResponse)
))
_sym_db.RegisterMessage(UninstallReleaseResponse)
GetVersionRequest    =    _reflection.GeneratedProtocolMessageType(' GetVersionRequest',
(_message.Message,), dict(
    DESCRIPTOR = _GETVERSIONREQUEST,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.GetVersionRequest)
))
_sym_db.RegisterMessage(GetVersionRequest)
GetVersionResponse    =    _reflection.GeneratedProtocolMessageType(' GetVersionResponse',
(_message.Message,), dict(
    DESCRIPTOR = _GETVERSIONRESPONSE,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.GetVersionResponse)
))
_sym_db.RegisterMessage(GetVersionResponse)
GetHistoryRequest    =    _reflection.GeneratedProtocolMessageType(' GetHistoryRequest',
(_message.Message,), dict(
    DESCRIPTOR = _GETHISTORYREQUEST,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.GetHistoryRequest)
))
_sym_db.RegisterMessage(GetHistoryRequest)
GetHistoryResponse    =    _reflection.GeneratedProtocolMessageType(' GetHistoryResponse',
(_message.Message,), dict(
    DESCRIPTOR = _GETHISTORYRESPONSE,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.GetHistoryResponse)
))
_sym_db.RegisterMessage(GetHistoryResponse)
TestReleaseRequest    =    _reflection.GeneratedProtocolMessageType(' TestReleaseRequest',
(_message.Message,), dict(
    DESCRIPTOR = _TESTRELEASEREQUEST,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.TestReleaseRequest)

```

```

))

_sym_db.RegisterMessage(TestReleaseRequest)
TestReleaseResponse = _reflection.GeneratedProtocolMessageType('TestReleaseResponse',
(_message.Message,), dict(
    DESCRIPTOR = _TESTRELEASESERESPONSE,
    __module__ = 'hapi.services.tiller_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.tiller.TestReleaseResponse)
))#远程文件传输
_sym_db.RegisterMessage(TestReleaseResponse)
DESCRIPTOR.has_options = True
DESCRIPTOR._options = _descriptor._ParseOptions(descriptor_pb2.FileOptions(),
_b('Z\010services'))
try:
    # THESE ELEMENTS WILL BE DEPRECATED.
    # Please use the generated *_pb2_grpc.py files instead.
    import grpc
    from grpc.framework.common import cardinality
    from grpc.framework.interfaces.face import utilities as face_utilities
    from grpc.beta import implementations as beta_implementations
    from grpc.beta import interfaces as beta_interfaces
    class ReleaseServiceStub(object):
        """ReleaseService is the service that a helm application uses to mutate,
        query, and manage releases.

            Release: A named installation composed of a chart and
                    config. At any given time a release has one
                    chart and one config.

            Config: A config is a YAML file that supplies values
                    to the parametrizable templates of a chart.

            Chart: A chart is a helm package that contains
                   metadata, a default config, zero or more
                   optionally parameterizable templates, and
                   zero or more charts (dependencies).

        """
        def __init__(self, channel):
            """Constructor.

            Args:
                channel: A grpc.Channel.

            """
            self.ListReleases = channel.unary_stream(
                '/hapi.services.tiller.ReleaseService/ListReleases',
                request_serializer=ListReleasesRequest.SerializeToString,
                response_deserializer=ListReleasesResponse.FromString,
            )
            self.GetReleaseStatus = channel.unary_unary(
                '/hapi.services.tiller.ReleaseService/GetReleaseStatus',
                request_serializer=GetReleaseStatusRequest.SerializeToString,
                response_deserializer=GetReleaseStatusResponse.FromString,
            )
            self.GetReleaseContent = channel.unary_unary(

```

```

        '/hapi.services.tiller.ReleaseService/GetReleaseContent',
        request_serializer=GetReleaseContentRequest.SerializeToString,
        response_deserializer=GetReleaseContentResponse.FromString,
    )
    self.UpdateRelease = channel.unary_unary(
        '/hapi.services.tiller.ReleaseService/UpdateRelease',
        request_serializer=UpdateReleaseRequest.SerializeToString,
        response_deserializer=UpdateReleaseResponse.FromString,
    )
    self.InstallRelease = channel.unary_unary(
        '/hapi.services.tiller.ReleaseService/InstallRelease',
        request_serializer=InstallReleaseRequest.SerializeToString,
        response_deserializer=InstallReleaseResponse.FromString,
    )
    self.UninstallRelease = channel.unary_unary(
        '/hapi.services.tiller.ReleaseService/UninstallRelease',
        request_serializer=UninstallReleaseRequest.SerializeToString,
        response_deserializer=UninstallReleaseResponse.FromString,
    )
    self.GetVersion = channel.unary_unary(
        '/hapi.services.tiller.ReleaseService/GetVersion',
        request_serializer=GetVersionRequest.SerializeToString,
        response_deserializer=GetVersionResponse.FromString,
    )
    self.RollbackRelease = channel.unary_unary(
        '/hapi.services.tiller.ReleaseService/RollbackRelease',
        request_serializer=RollbackReleaseRequest.SerializeToString,
        response_deserializer=RollbackReleaseResponse.FromString,
    )
    self.GetHistory = channel.unary_unary(
        '/hapi.services.tiller.ReleaseService/GetHistory',
        request_serializer=GetHistoryRequest.SerializeToString,
        response_deserializer=GetHistoryResponse.FromString,
    )
    self.RunReleaseTest = channel.unary_stream(
        '/hapi.services.tiller.ReleaseService/RunReleaseTest',
        request_serializer=TestReleaseRequest.SerializeToString,
        response_deserializer=TestReleaseResponse.FromString,
    )
class ReleaseServiceServicer(object):
    """ReleaseService is the service that a helm application uses to mutate,
    query, and manage releases.

    Release: A named installation composed of a chart and
             config. At any given time a release has one
             chart and one config.

    Config: A config is a YAML file that supplies values
            to the parametrizable templates of a chart.

    Chart: A chart is a helm package that contains
            metadata, a default config, zero or more
            optionally parameterizable templates, and

```

```

        zero or more charts (dependencies).
    """

def ListReleases(self, request, context):
    """ListReleases retrieves release history.
    TODO: Allow filtering the set of releases by
    release status. By default, ListAllReleases returns the releases who
    current status is "Active".
    """

    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def GetReleaseStatus(self, request, context):
    """GetReleaseStatus retrieves status information for the specified release.
    """

    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def GetReleaseContent(self, request, context):
    """GetReleaseContent retrieves the release content (chart + value) for the specified
release.
    """

    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def UpdateRelease(self, request, context):
    """UpdateRelease updates release content.
    """

    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def InstallRelease(self, request, context):
    """InstallRelease requests installation of a chart as a new release.
    """

    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def UninstallRelease(self, request, context):
    """UninstallRelease requests deletion of a named release.
    """

    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def GetVersion(self, request, context):
    """GetVersion returns the current version of the server.
    """

    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def RollbackRelease(self, request, context):
    """RollbackRelease rolls back a release to a previous version.

```

```

"""
    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def GetHistory(self, request, context):
    """ReleaseHistory retrieves a release's history.
    """
    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def RunReleaseTest(self, request, context):
    """RunReleaseTest executes the tests defined of a named release
    """
    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def add_ReleaseServiceServicer_to_server(servicer, server):
    rpc_method_handlers = {
        'ListReleases': grpc.unary_stream_rpc_method_handler(
            servicer.ListReleases,
            request_deserializer=ListReleasesRequest.FromString,
            response_serializer=ListReleasesResponse.SerializeToString,
        ),
        'GetReleaseStatus': grpc.unary_unary_rpc_method_handler(
            servicer.GetReleaseStatus,
            request_deserializer=GetReleaseStatusRequest.FromString,
            response_serializer=GetReleaseStatusResponse.SerializeToString,
        ),
        'GetReleaseContent': grpc.unary_unary_rpc_method_handler(
            servicer.GetReleaseContent,
            request_deserializer=GetReleaseContentRequest.FromString,
            response_serializer=GetReleaseContentResponse.SerializeToString,
        ),
        'UpdateRelease': grpc.unary_unary_rpc_method_handler(
            servicer.UpdateRelease,
            request_deserializer=UpdateReleaseRequest.FromString,
            response_serializer=UpdateReleaseResponse.SerializeToString,
        ),
        'InstallRelease': grpc.unary_unary_rpc_method_handler(
            servicer.InstallRelease,
            request_deserializer=InstallReleaseRequest.FromString,
            response_serializer=InstallReleaseResponse.SerializeToString,
        ),
        'UninstallRelease': grpc.unary_unary_rpc_method_handler(
            servicer.UninstallRelease,
            request_deserializer=UninstallReleaseRequest.FromString,
            response_serializer=UninstallReleaseResponse.SerializeToString,
        ),
        'GetVersion': grpc.unary_unary_rpc_method_handler(

```

```

        servicer.GetVersion,
        request_deserializer=GetVersionRequest.FromString,
        response_serializer=GetVersionResponse.SerializeToString,
    ),
    'RollbackRelease': grpc.unary_unary_rpc_method_handler(
        servicer.RollbackRelease,
        request_deserializer=RollbackReleaseRequest.FromString,
        response_serializer=RollbackReleaseResponse.SerializeToString,
    ), #上网记录查询
    'GetHistory': grpc.unary_unary_rpc_method_handler(
        servicer.GetHistory,
        request_deserializer=GetHistoryRequest.FromString,
        response_serializer=GetHistoryResponse.SerializeToString,
    ),
    'RunReleaseTest': grpc.unary_stream_rpc_method_handler(
        servicer.RunReleaseTest,
        request_deserializer=TestReleaseRequest.FromString,
        response_serializer=TestReleaseResponse.SerializeToString,
    ),
}

_sym_db.RegisterEnumDescriptor(_RESULT_STATUS)
_RESULT = _descriptor.Descriptor(
    name='Result',
    full_name='hapi.services.rudder.Result',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='info', full_name='hapi.services.rudder.Result.info', index=0,
            number=1, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='log', full_name='hapi.services.rudder.Result.log', index=1,
            number=2, type=9, cpp_type=9, label=3,
            has_default_value=False, default_value=[],
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],

    extensions=[
    ],
    nested_types=[],
    enum_types=[
        _RESULT_STATUS,
    ],

```



```

options=None,
is_extendable=False,
syntax='proto3',
extension_ranges=[],
oneofs=[
],
serialized_start=103,
serialized_end=200,
)
_VERSIONRELEASEREQUEST = _descriptor.Descriptor(
    name='VersionReleaseRequest',
    full_name='hapi.services.rudder.VersionReleaseRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=202,
    serialized_end=225,
)
_VERSIONRELEASERESPONSE = _descriptor.Descriptor(
    name='VersionReleaseResponse',
    full_name='hapi.services.rudder.VersionReleaseResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='name',          full_name='hapi.services.rudder.VersionReleaseResponse.name',
index=0,
            number=1, type=9, cpp_type=9, label=1,
            has_default_value=False, default_value=_b("").decode('utf-8'),
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='version', full_name='hapi.services.rudder.VersionReleaseResponse.version',
index=1,
            number=2, type=9, cpp_type=9, label=1,

```

```

        has_default_value=False, default_value=_b("").decode('utf-8'),
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=227,
    serialized_end=282,
)
_INSTALLRELEASEREQUEST = _descriptor.Descriptor(
    name='InstallReleaseRequest',
    full_name='hapi.services.rudder.InstallReleaseRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.rudder.InstallReleaseRequest.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ], #流量监控
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=284,
    serialized_end=347,
)
_INSTALLRELEASERESPONSE = _descriptor.Descriptor(

```

```

    name='InstallReleaseResponse',
    full_name='hapi.services.rudder.InstallReleaseResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.rudder.InstallReleaseResponse.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='result', full_name='hapi.services.rudder.InstallReleaseResponse.result',
index=1,
            number=2, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=349,
    serialized_end=459,
)
_DELETEERELEASEREQUEST = _descriptor.Descriptor(
    name='DeleteReleaseRequest',
    full_name='hapi.services.rudder.DeleteReleaseRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.rudder.DeleteReleaseRequest.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,

```

```

        is_extension=False, extension_scope=None,
        options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=461,
    serialized_end=523,
)
_DELETEERELEASERESPONSE = _descriptor.Descriptor(
    name='DeleteReleaseResponse',
    full_name='hapi.services.rudder.DeleteReleaseResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.rudder.DeleteReleaseResponse.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='result', full_name='hapi.services.rudder.DeleteReleaseResponse.result',
index=1,
            number=2, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],

```

```

    oneofs=[
    ],
    serialized_start=525,
    serialized_end=634,
)
_UPGRADERELEASEREQUEST = _descriptor.Descriptor(
    name='UpgradeReleaseRequest',
    full_name='hapi.services.rudder.UpgradeReleaseRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='current', full_name='hapi.services.rudder.UpgradeReleaseRequest.current',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='target', full_name='hapi.services.rudder.UpgradeReleaseRequest.target',
index=1,
            number=2, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='Timeout', full_name='hapi.services.rudder.UpgradeReleaseRequest.Timeout',
index=2,
            number=3, type=3, cpp_type=2, label=1,
            has_default_value=False, default_value=0,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='Wait', full_name='hapi.services.rudder.UpgradeReleaseRequest.Wait',
index=3,
            number=4, type=8, cpp_type=7, label=1,
            has_default_value=False, default_value=False,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='Recreate', full_name='hapi.services.rudder.UpgradeReleaseRequest.Recreate',
index=4,
            number=5, type=8, cpp_type=7, label=1,
            has_default_value=False, default_value=False,
            message_type=None, enum_type=None, containing_type=None,

```

```

        is_extension=False, extension_scope=None,
        options=None),
    _descriptor.FieldDescriptor(
        name='Force',      full_name='hapi.services.rudder.UpgradeReleaseRequest.Force',
index=5,
        number=6, type=8, cpp_type=7, label=1,
        has_default_value=False, default_value=False,
        message_type=None, enum_type=None, containing_type=None,
        is_extension=False, extension_scope=None,
        options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=637,
    serialized_end=803,
)
_UPGRADERELEASERESPONSE = _descriptor.Descriptor(
    name='UpgradeReleaseResponse',
    full_name='hapi.services.rudder.UpgradeReleaseResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.rudder.UpgradeReleaseResponse.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='result', full_name='hapi.services.rudder.UpgradeReleaseResponse.result',
index=1,
            number=2, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[

```

```

],
nested_types=[],
enum_types=[
],
options=None,
is_extendable=False,
syntax='proto3',
extension_ranges=[],
oneofs=[
],
serialized_start=805,
serialized_end=915,
)
_ROLLBACKRELEASEREQUEST = _descriptor.Descriptor(
    name='RollbackReleaseRequest',
    full_name='hapi.services.rudder.RollbackReleaseRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='current', full_name='hapi.services.rudder.RollbackReleaseRequest.current',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='target', full_name='hapi.services.rudder.RollbackReleaseRequest.target',
index=1,
            number=2, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='Timeout', full_name='hapi.services.rudder.RollbackReleaseRequest.Timeout',
index=2,
            number=3, type=3, cpp_type=2, label=1,
            has_default_value=False, default_value=0,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='Wait', full_name='hapi.services.rudder.RollbackReleaseRequest.Wait',
index=3,
            number=4, type=8, cpp_type=7, label=1,
            has_default_value=False, default_value=False,
            message_type=None, enum_type=None, containing_type=None,

```

```

        is_extension=False, extension_scope=None,
        options=None),
        _descriptor.FieldDescriptor(
            name='Recreate',
full_name='hapi.services.rudder.RollbackReleaseRequest.Recreate', index=4,
            number=5, type=8, cpp_type=7, label=1,
            has_default_value=False, default_value=False,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='Force',      full_name='hapi.services.rudder.RollbackReleaseRequest.Force',
index=5,
            number=6, type=8, cpp_type=7, label=1,
            has_default_value=False, default_value=False,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],#数据管理
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=918,
    serialized_end=1085,
)

_ROLLBACKRELEASERESPONSE = _descriptor.Descriptor(
    name='RollbackReleaseResponse',
    full_name='hapi.services.rudder.RollbackReleaseResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.rudder.RollbackReleaseResponse.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='result',   full_name='hapi.services.rudder.RollbackReleaseResponse.result',

```



```

index=1,
    number=2, type=11, cpp_type=10, label=1,
    has_default_value=False, default_value=None,
    message_type=None, enum_type=None, containing_type=None,
    is_extension=False, extension_scope=None,
    options=None),
],
extensions=[
],
nested_types=[],
enum_types=[
],
options=None,
is_extendable=False,
syntax='proto3',
extension_ranges=[],
oneofs=[
],
serialized_start=1087,
serialized_end=1198,
)
_RELEASESTATUSREQUEST = _descriptor.Descriptor(
    name='ReleaseStatusRequest',
    full_name='hapi.services.rudder.ReleaseStatusRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.rudder.ReleaseStatusRequest.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
],
extensions=[
],
nested_types=[],
enum_types=[
],
options=None,
is_extendable=False,
syntax='proto3',
extension_ranges=[],
oneofs=[
],
serialized_start=1200,
serialized_end=1262,

```

```

)
_RELEASESTATUSRESPONSE = _descriptor.Descriptor(
    name='ReleaseStatusResponse',
    full_name='hapi.services.rudder.ReleaseStatusResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.rudder.ReleaseStatusResponse.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
        _descriptor.FieldDescriptor(
            name='info', full_name='hapi.services.rudder.ReleaseStatusResponse.info',
index=1,
            number=2, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=1264,
    serialized_end=1361,
)
_RESULT_STATUS.containing_type = _RESULT
_INSTALLRELEASEREQUEST.fields_by_name['release'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_INSTALLRELEASERESPONSE.fields_by_name['release'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_INSTALLRELEASERESPONSE.fields_by_name['result'].message_type = _RESULT
_DELETERELEASEREQUEST.fields_by_name['release'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_DELETERELEASERESPONSE.fields_by_name['release'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_DELETERELEASERESPONSE.fields_by_name['result'].message_type = _RESULT

```

```

_UPGRADERELEASEREQUEST.fields_by_name['current'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_UPGRADERELEASEREQUEST.fields_by_name['target'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_UPGRADERELEASERESPONSE.fields_by_name['release'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_UPGRADERELEASERESPONSE.fields_by_name['result'].message_type = _RESULT
_ROLLBACKRELEASEREQUEST.fields_by_name['current'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_ROLLBACKRELEASEREQUEST.fields_by_name['target'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_ROLLBACKRELEASERESPONSE.fields_by_name['release'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_ROLLBACKRELEASERESPONSE.fields_by_name['result'].message_type = _RESULT
_RELEASESTATUSREQUEST.fields_by_name['release'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_RELEASESTATUSRESPONSE.fields_by_name['release'].message_type =
hapi_dot_release_dot_release__pb2._RELEASE
_RELEASESTATUSRESPONSE.fields_by_name['info'].message_type =
hapi_dot_release_dot_info__pb2._INFO
DESCRIPTOR.message_types_by_name['Result'] = _RESULT
DESCRIPTOR.message_types_by_name['VersionReleaseRequest'] = _VERSIONRELEASEREQUEST
DESCRIPTOR.message_types_by_name['VersionReleaseResponse'] = _VERSIONRELEASERESPONSE
DESCRIPTOR.message_types_by_name['InstallReleaseRequest'] = _INSTALLRELEASEREQUEST
DESCRIPTOR.message_types_by_name['InstallReleaseResponse'] = _INSTALLRELEASERESPONSE
DESCRIPTOR.message_types_by_name['DeleteReleaseRequest'] = _DELETERELEASEREQUEST
DESCRIPTOR.message_types_by_name['DeleteReleaseResponse'] = _DELETERELEASERESPONSE
DESCRIPTOR.message_types_by_name['UpgradeReleaseRequest'] = _UPGRADERELEASEREQUEST
DESCRIPTOR.message_types_by_name['UpgradeReleaseResponse'] = _UPGRADERELEASERESPONSE
DESCRIPTOR.message_types_by_name['RollbackReleaseRequest'] = _ROLLBACKRELEASEREQUEST
DESCRIPTOR.message_types_by_name['RollbackReleaseResponse'] = _ROLLBACKRELEASERESPONSE
DESCRIPTOR.message_types_by_name['ReleaseStatusRequest'] = _RELEASESTATUSREQUEST
DESCRIPTOR.message_types_by_name['ReleaseStatusResponse'] = _RELEASESTATUSRESPONSE
Result = _reflection.GeneratedProtocolMessageType('Result', (_message.Message,), dict(
    DESCRIPTOR = _RESULT,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.Result)
))
_sym_db.RegisterMessage(Result)
VersionReleaseRequest =
_reflection.GeneratedProtocolMessageType('VersionReleaseRequest', (_message.Message,),
dict(
    DESCRIPTOR = _VERSIONRELEASEREQUEST,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.VersionReleaseRequest)
))
_sym_db.RegisterMessage(VersionReleaseRequest)
VersionReleaseResponse =
_reflection.GeneratedProtocolMessageType('VersionReleaseResponse', (_message.Message,),
dict(

```

```

    DESCRIPTOR = _VERSIONRELEASERESPONSE,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.VersionReleaseResponse)
))
_sym_db.RegisterMessage(VersionReleaseResponse)
InstallReleaseRequest =
_reflection.GeneratedProtocolMessageType('InstallReleaseRequest', (_message.Message,),
dict(
    DESCRIPTOR = _INSTALLRELEASEREQUEST,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.InstallReleaseRequest)
))
_sym_db.RegisterMessage(InstallReleaseRequest)
InstallReleaseResponse =
_reflection.GeneratedProtocolMessageType('InstallReleaseResponse', (_message.Message,),
dict(
    DESCRIPTOR = _INSTALLRELEASERESPONSE,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.InstallReleaseResponse)
))
_sym_db.RegisterMessage(InstallReleaseResponse)
DeleteReleaseRequest = _reflection.GeneratedProtocolMessageType('DeleteReleaseRequest',
(_message.Message,), dict(
    DESCRIPTOR = _DELETERELEASEREQUEST,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.DeleteReleaseRequest)
))
_sym_db.RegisterMessage(DeleteReleaseRequest)
DeleteReleaseResponse =
_reflection.GeneratedProtocolMessageType('DeleteReleaseResponse', (_message.Message,),
dict(
    DESCRIPTOR = _DELETERELEASERESPONSE,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.DeleteReleaseResponse)
))
_sym_db.RegisterMessage(DeleteReleaseResponse)
UpgradeReleaseRequest =
_reflection.GeneratedProtocolMessageType('UpgradeReleaseRequest', (_message.Message,),
dict(
    DESCRIPTOR = _UPGRADERELEASEREQUEST,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.UpgradeReleaseRequest)
))#聊天流量统计
_sym_db.RegisterMessage(UpgradeReleaseRequest)
UpgradeReleaseResponse =
_reflection.GeneratedProtocolMessageType('UpgradeReleaseResponse', (_message.Message,),
dict(
    DESCRIPTOR = _UPGRADERELEASERESPONSE,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.UpgradeReleaseResponse)

```

```

    ))
    _sym_db.RegisterMessage(UpgradeReleaseResponse)
RollbackReleaseRequest =
    _reflection.GeneratedProtocolMessageType('RollbackReleaseRequest', (_message.Message,),
dict(
    DESCRIPTOR = _ROLLBACKRELEASEREQUEST,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.RollbackReleaseRequest)
))
    _sym_db.RegisterMessage(RollbackReleaseRequest)
RollbackReleaseResponse =
    _reflection.GeneratedProtocolMessageType('RollbackReleaseResponse',
(_message.Message,), dict(
    DESCRIPTOR = _ROLLBACKRELEASERESPONSE,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.RollbackReleaseResponse)
))
    _sym_db.RegisterMessage(RollbackReleaseResponse)
ReleaseStatusRequest = _reflection.GeneratedProtocolMessageType('ReleaseStatusRequest',
(_message.Message,), dict(
    DESCRIPTOR = _RELEASESTATUSREQUEST,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.ReleaseStatusRequest)
))
    _sym_db.RegisterMessage(ReleaseStatusRequest)
ReleaseStatusResponse =
    _reflection.GeneratedProtocolMessageType('ReleaseStatusResponse', (_message.Message,),
dict(
    DESCRIPTOR = _RELEASESTATUSRESPONSE,
    __module__ = 'hapi.rudder.rudder_pb2'
    # @@protoc_insertion_point(class_scope:hapi.services.rudder.ReleaseStatusResponse)
))
    _sym_db.RegisterMessage(ReleaseStatusResponse)
DESCRIPTOR.has_options = True
DESCRIPTOR._options = _descriptor._ParseOptions(descriptor_pb2.FileOptions(),
_b('Z\006rudder'))
try:
    # THESE ELEMENTS WILL BE DEPRECATED.
    # Please use the generated *_pb2_grpc.py files instead.
    import grpc
    from grpc.framework.common import cardinality
    from grpc.framework.interfaces.face import utilities as face_utilities
    from grpc.beta import implementations as beta_implementations
    from grpc.beta import interfaces as beta_interfaces
    class ReleaseModuleServiceStub(object):
        def __init__(self, channel):
            """Constructor.

            Args:
                channel: A grpc.Channel.
            """

```

```

        self.Version = channel.unary_unary(
            '/hapi.services.rudder.ReleaseModuleService/Version',
            request_serializer=VersionReleaseRequest.SerializeToString,
            response_deserializer=VersionReleaseResponse.FromString,
        )
_INSTALLRELEASEREQUEST = _descriptor.Descriptor(
    name='InstallReleaseRequest',
    full_name='hapi.services.rudder.InstallReleaseRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.rudder.InstallReleaseRequest.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=284,
    serialized_end=347,
)
_INSTALLRELEASERESPONSE = _descriptor.Descriptor(
    name='InstallReleaseResponse',
    full_name='hapi.services.rudder.InstallReleaseResponse',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release', full_name='hapi.services.rudder.InstallReleaseResponse.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=354,
    serialized_end=417,
)

```

```

        _descriptor.FieldDescriptor(
            name='result',    full_name='hapi.services.rudder.InstallReleaseResponse.result',
index=1,
            number=2, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],
    serialized_start=349,
    serialized_end=459,
)
_DELETEERELEASEREQUEST = _descriptor.Descriptor(
    name='DeleteReleaseRequest',
    full_name='hapi.services.rudder.DeleteReleaseRequest',
    filename=None,
    file=DESCRIPTOR,
    containing_type=None,
    fields=[
        _descriptor.FieldDescriptor(
            name='release',    full_name='hapi.services.rudder.DeleteReleaseRequest.release',
index=0,
            number=1, type=11, cpp_type=10, label=1,
            has_default_value=False, default_value=None,
            message_type=None, enum_type=None, containing_type=None,
            is_extension=False, extension_scope=None,
            options=None),
    ],
    extensions=[
    ],
    nested_types=[],
    enum_types=[
    ],
    options=None,
    is_extendable=False,
    syntax='proto3',
    extension_ranges=[],
    oneofs=[
    ],

```

```

        serialized_start=461,
        serialized_end=523,
    )
    _DELETERELEASERESPONSE = _descriptor.Descriptor(
        name='DeleteReleaseResponse',
        full_name='hapi.services.rudder.DeleteReleaseResponse',
        filename=None,
        file=DESCRIPTOR,
        containing_type=None,
        fields=[
            _descriptor.FieldDescriptor(
                name='release', full_name='hapi.services.rudder.DeleteReleaseResponse.release',
index=0,
                number=1, type=11, cpp_type=10, label=1,
                has_default_value=False, default_value=None,
                message_type=None, enum_type=None, containing_type=None,
                is_extension=False, extension_scope=None,
                options=None),
            _descriptor.FieldDescriptor(
                name='result', full_name='hapi.services.rudder.DeleteReleaseResponse.result',
index=1,
                number=2, type=11, cpp_type=10, label=1,
                has_default_value=False, default_value=None,
                message_type=None, enum_type=None, containing_type=None,
                is_extension=False, extension_scope=None,
                options=None),
        ],
        extensions=[
        ],
        nested_types=[],
        enum_types=[
        ], #上网流量统计
        options=None,
        is_extendable=False,
        syntax='proto3',
        extension_ranges=[],
        oneofs=[
        ],
        serialized_start=525,
        serialized_end=634,
    )
    _UPGRADERELEASEREQUEST = _descriptor.Descriptor(
        name='UpgradeReleaseRequest',
        full_name='hapi.services.rudder.UpgradeReleaseRequest',
        filename=None,
        file=DESCRIPTOR,
        containing_type=None,
        fields=[
            _descriptor.FieldDescriptor(
                name='current', full_name='hapi.services.rudder.UpgradeReleaseRequest.current',

```



```

index=0,
    number=1, type=11, cpp_type=10, label=1,
    has_default_value=False, default_value=None,
    message_type=None, enum_type=None, containing_type=None,
    is_extension=False, extension_scope=None,
    options=None),
    _descriptor.FieldDescriptor(
        name='target',      full_name='hapi.services.rudder.UpgradeReleaseRequest.target',
index=1,
    number=2, type=11, cpp_type=10, label=1,
    has_default_value=False, default_value=None,
    message_type=None, enum_type=None, containing_type=None,
    is_extension=False, extension_scope=None,
    options=None),
    _descriptor.FieldDescriptor(
        name='Timeout',    full_name='hapi.services.rudder.UpgradeReleaseRequest.Timeout',
index=2,
    number=3, type=3, cpp_type=2, label=1,
    has_default_value=False, default_value=0,
    message_type=None, enum_type=None, containing_type=None,
    is_extension=False, extension_scope=None,
    options=None),
    _descriptor.FieldDescriptor(
        name='Wait',       full_name='hapi.services.rudder.UpgradeReleaseRequest.Wait',
index=3,
    number=4, type=8, cpp_type=7, label=1,
    has_default_value=False, default_value=False,
    message_type=None, enum_type=None, containing_type=None,
    is_extension=False, extension_scope=None,
    options=None),
    _descriptor.FieldDescriptor(
        name='Recreate',   full_name='hapi.services.rudder.UpgradeReleaseRequest.Recreate',
index=4,
    number=5, type=8, cpp_type=7, label=1,
    has_default_value=False, default_value=False,
    message_type=None, enum_type=None, containing_type=None,
    is_extension=False, extension_scope=None,
    options=None),
    _descriptor.FieldDescriptor(
        name='Force',      full_name='hapi.services.rudder.UpgradeReleaseRequest.Force',
index=5,
    number=6, type=8, cpp_type=7, label=1,
    has_default_value=False, default_value=False,
    message_type=None, enum_type=None, containing_type=None,
    is_extension=False, extension_scope=None,
    options=None),
],
extensions=[
],
nested_types=[],

```

```

enum_types=[
],
options=None,
is_extendable=False,
syntax='proto3',
extension_ranges=[],
oneofs=[
],
serialized_start=637,
serialized_end=803,
)

self.InstallRelease = channel.unary_unary(
    '/hapi.services.rudder.ReleaseModuleService/InstallRelease',
    request_serializer=InstallReleaseRequest.SerializeToString,
    response_deserializer=InstallReleaseResponse.FromString,
)

self.DeleteRelease = channel.unary_unary(
    '/hapi.services.rudder.ReleaseModuleService/DeleteRelease',
    request_serializer=DeleteReleaseRequest.SerializeToString,
    response_deserializer=DeleteReleaseResponse.FromString,
)

self.RollbackRelease = channel.unary_unary(
    '/hapi.services.rudder.ReleaseModuleService/RollbackRelease',
    request_serializer=RollbackReleaseRequest.SerializeToString,
    response_deserializer=RollbackReleaseResponse.FromString,
)

self.UpgradeRelease = channel.unary_unary(
    '/hapi.services.rudder.ReleaseModuleService/UpgradeRelease',
    request_serializer=UpgradeReleaseRequest.SerializeToString,
    response_deserializer=UpgradeReleaseResponse.FromString,
)

self.ReleaseStatus = channel.unary_unary(
    '/hapi.services.rudder.ReleaseModuleService/ReleaseStatus',
    request_serializer=ReleaseStatusRequest.SerializeToString,
    response_deserializer=ReleaseStatusResponse.FromString,
) #下载流量记录

class ReleaseModuleServiceServicer(object):
    def Version(self, request, context):
        context.set_code(grpc.StatusCode.UNIMPLEMENTED)
        context.set_details('Method not implemented!')
        raise NotImplementedError('Method not implemented!')
    def InstallRelease(self, request, context):
        """InstallRelease requests installation of a chart as a new release.
        """
        context.set_code(grpc.StatusCode.UNIMPLEMENTED)
        context.set_details('Method not implemented!')
        raise NotImplementedError('Method not implemented!')
    def DeleteRelease(self, request, context):
        """DeleteRelease requests deletion of a named release.
        """

```

```

        context.set_code(grpc.StatusCode.UNIMPLEMENTED)
        context.set_details('Method not implemented!')
        raise NotImplementedError('Method not implemented!')
def RollbackRelease(self, request, context):
    """RollbackRelease rolls back a release to a previous version.
    """
    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def UpgradeRelease(self, request, context):
    """UpgradeRelease updates release content.
    """
    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def ReleaseStatus(self, request, context):
    """ReleaseStatus retrieves release status.
    """
    context.set_code(grpc.StatusCode.UNIMPLEMENTED)
    context.set_details('Method not implemented!')
    raise NotImplementedError('Method not implemented!')
def add_ReleaseModuleServiceServicer_to_server(servicer, server):
    rpc_method_handlers = {
        'Version': grpc.unary_unary_rpc_method_handler(
            servicer.Version,
            request_deserializer=VersionReleaseRequest.FromString,
            response_serializer=VersionReleaseResponse.SerializeToString,
        ),
        'InstallRelease': grpc.unary_unary_rpc_method_handler(
            servicer.InstallRelease,
            request_deserializer=InstallReleaseRequest.FromString,
            response_serializer=InstallReleaseResponse.SerializeToString,
        ),
        'DeleteRelease': grpc.unary_unary_rpc_method_handler(
            servicer.DeleteRelease,
            request_deserializer=DeleteReleaseRequest.FromString,
            response_serializer=DeleteReleaseResponse.SerializeToString,
        ),
        'RollbackRelease': grpc.unary_unary_rpc_method_handler(
            servicer.RollbackRelease,
            request_deserializer=RollbackReleaseRequest.FromString,
            response_serializer=RollbackReleaseResponse.SerializeToString,
        ),
        'UpgradeRelease': grpc.unary_unary_rpc_method_handler(
            servicer.UpgradeRelease,
            request_deserializer=UpgradeReleaseRequest.FromString,
            response_serializer=UpgradeReleaseResponse.SerializeToString,
        ),
        'ReleaseStatus': grpc.unary_unary_rpc_method_handler(
            servicer.ReleaseStatus,

```

```

        request_deserializer=ReleaseStatusRequest.FromString,
        response_serializer=ReleaseStatusResponse.SerializeToString,
    ),
}

generic_handler = grpc.method_handlers_generic_handler(
    'hapi.services.rudder.ReleaseModuleService', rpc_method_handlers)
server.add_generic_rpc_handlers((generic_handler,))

class BetaReleaseModuleServiceServicer(object):
    """The Beta API is deprecated for 0.15.0 and later.
    It is recommended to use the GA API (classes and functions in this
    file not marked beta) for all further purposes. This class was generated
    only to ease transition from grpcio<0.15.0 to grpcio>=0.15.0."""
    def Version(self, request, context):
        context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
    def InstallRelease(self, request, context):
        """InstallRelease requests installation of a chart as a new release.
        """
        context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
    def DeleteRelease(self, request, context):
        """DeleteRelease requests deletion of a named release.
        """
        context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
    def RollbackRelease(self, request, context):
        """RollbackRelease rolls back a release to a previous version.
        """
        context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
    def UpgradeRelease(self, request, context):
        """UpgradeRelease updates release content.
        """
        context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
    def ReleaseStatus(self, request, context):
        """ReleaseStatus retrieves release status.
        """
        context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)

class BetaReleaseModuleServiceStub(object):
    """The Beta API is deprecated for 0.15.0 and later.
    It is recommended to use the GA API (classes and functions in this
    file not marked beta) for all further purposes. This class was generated
    only to ease transition from grpcio<0.15.0 to grpcio>=0.15.0."""
    def Version(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
        raise NotImplementedError()
    Version.future = None
    def InstallRelease(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
        """InstallRelease requests installation of a chart as a new release.
        """
        raise NotImplementedError()
    InstallRelease.future = None
    def DeleteRelease(self, request, timeout, metadata=None, with_call=False,

```

```

protocol_options=None):
    """DeleteRelease requests deletion of a named release.
    """
    raise NotImplementedError()
DeleteRelease.future = None
def RollbackRelease(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
    """RollbackRelease rolls back a release to a previous version.
    """
    raise NotImplementedError()
RollbackRelease.future = None
def UpgradeRelease(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
    """UpgradeRelease updates release content.
    """
    raise NotImplementedError()
UpgradeRelease.future = None
def ReleaseStatus(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
    """ReleaseStatus retrieves release status.
    """
    raise NotImplementedError()
ReleaseStatus.future = None
def beta_create_ReleaseModuleService_server(servicer, pool=None, pool_size=None,
default_timeout=None, maximum_timeout=None):
    """The Beta API is deprecated for 0.15.0 and later.
    It is recommended to use the GA API (classes and functions in this
    file not marked beta) for all further purposes. This function was
    generated only to ease transition from grpcio<0.15.0 to grpcio>=0.15.0"""
    request_deserializers = {
        ('hapi.services.rudder.ReleaseModuleService',          'DeleteRelease'):
DeleteReleaseRequest.FromString,
        ('hapi.services.rudder.ReleaseModuleService',          'InstallRelease'):
InstallReleaseRequest.FromString,
        ('hapi.services.rudder.ReleaseModuleService',          'ReleaseStatus'):
ReleaseStatusRequest.FromString,
        ('hapi.services.rudder.ReleaseModuleService',          'RollbackRelease'):
RollbackReleaseRequest.FromString,
        ('hapi.services.rudder.ReleaseModuleService',          'UpgradeRelease'):
UpgradeReleaseRequest.FromString,
        ('hapi.services.rudder.ReleaseModuleService',          'Version'):
VersionReleaseRequest.FromString,
    }
    response_serializers = {
        ('hapi.services.rudder.ReleaseModuleService',          'DeleteRelease'):
DeleteReleaseResponse.SerializeToString,
        ('hapi.services.rudder.ReleaseModuleService',          'InstallRelease'):
InstallReleaseResponse.SerializeToString,
        ('hapi.services.rudder.ReleaseModuleService',          'ReleaseStatus'):
ReleaseStatusResponse.SerializeToString,

```

```

        ('hapi.services.rudder.ReleaseModuleService',
RollbackReleaseResponse.SerializeToString,
        ('hapi.services.rudder.ReleaseModuleService',
UpgradeReleaseResponse.SerializeToString,
        ('hapi.services.rudder.ReleaseModuleService',
VersionReleaseResponse.SerializeToString,
        })
    method_implementations = {
        ('hapi.services.rudder.ReleaseModuleService',
face_utilities.unary_unary_inline(servicer.DeleteRelease),
        ('hapi.services.rudder.ReleaseModuleService',
face_utilities.unary_unary_inline(servicer.InstallRelease),
        ('hapi.services.rudder.ReleaseModuleService',
face_utilities.unary_unary_inline(servicer.ReleaseStatus),
        ('hapi.services.rudder.ReleaseModuleService',
face_utilities.unary_unary_inline(servicer.RollbackRelease),
        ('hapi.services.rudder.ReleaseModuleService',
face_utilities.unary_unary_inline(servicer.UpgradeRelease),
        ('hapi.services.rudder.ReleaseModuleService',
face_utilities.unary_unary_inline(servicer.Version),
    }#系统设置管理
    server_options
    beta_implementations.server_options(request_deserializers=request_deserializers,
response_serializers=response_serializers, thread_pool=pool, thread_pool_size=pool_size,
default_timeout=default_timeout, maximum_timeout=maximum_timeout)
    return beta_implementations.server(method_implementations, options=server_options)
    def beta_create_ReleaseService_stub(channel, host=None, metadata_transformer=None,
pool=None, pool_size=None):
        """The Beta API is deprecated for 0.15.0 and later.
        It is recommended to use the GA API (classes and functions in this
        file not marked beta) for all further purposes. This function was
        generated only to ease transition from grpcio<0.15.0 to grpcio>=0.15.0"""
        request_serializers = {
            ('hapi.services.tiller.ReleaseService',
GetHistoryRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',
GetReleaseContentRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',
GetReleaseStatusRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',
GetVersionRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',
InstallReleaseRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',
ListReleasesRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',
RollbackReleaseRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',
TestReleaseRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',

```

```

UninstallReleaseRequest.SerializeToString,
    ('hapi.services.tiller.ReleaseService',
UpdateReleaseRequest.SerializeToString,
    }
    generic_handler = grpc.method_handlers_generic_handler(
        'hapi.services.tiller.ReleaseService', rpc_method_handlers)
    server.add_generic_rpc_handlers((generic_handler,))
class BetaReleaseServiceServicer(object):
    """The Beta API is deprecated for 0.15.0 and later.
    It is recommended to use the GA API (classes and functions in this
    file not marked beta) for all further purposes. This class was generated
    only to ease transition from grpcio<0.15.0 to grpcio>=0.15.0."""
    """ReleaseService is the service that a helm application uses to mutate,
    query, and manage releases.
        Release: A named installation composed of a chart and
            config. At any given time a release has one
            chart and one config.
        Config: A config is a YAML file that supplies values
            to the parametrizable templates of a chart.
        Chart: A chart is a helm package that contains
            metadata, a default config, zero or more
            optionally parameterizable templates, and
            zero or more charts (dependencies).
    """
    def ListReleases(self, request, context):
        """ListReleases retrieves release history.
        TODO: Allow filtering the set of releases by
        release status. By default, ListAllReleases returns the releases who
        current status is "Active".
        """
        context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
    def GetReleaseStatus(self, request, context):
        """GetReleaseStatus retrieves status information for the specified release.
        """
        context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
    def GetReleaseContent(self, request, context):
        """GetReleaseContent retrieves the release content (chart + value) for the specified
release.
        """
        context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
    def UpdateRelease(self, request, context):
        """UpdateRelease updates release content.
        """
        context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
    def InstallRelease(self, request, context):
        """InstallRelease requests installation of a chart as a new release.
        """
        context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
    def UninstallRelease(self, request, context):
        """UninstallRelease requests deletion of a named release.

```

```

"""
    context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
def GetVersion(self, request, context):
    """GetVersion returns the current version of the server.
    """
    context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
def RollbackRelease(self, request, context):
    """RollbackRelease rolls back a release to a previous version.
    """
    context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
def GetHistory(self, request, context):
    """ReleaseHistory retrieves a release's history.
    """
    context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
def RunReleaseTest(self, request, context):
    """RunReleaseTest executes the tests defined of a named release
    """
    context.code(beta_interfaces.StatusCode.UNIMPLEMENTED)
class BetaReleaseServiceStub(object):
    """The Beta API is deprecated for 0.15.0 and later.
    It is recommended to use the GA API (classes and functions in this
    file not marked beta) for all further purposes. This class was generated
    only to ease transition from grpcio<0.15.0 to grpcio>=0.15.0."""
    """ReleaseService is the service that a helm application uses to mutate,
    query, and manage releases.
        Release: A named installation composed of a chart and
            config. At any given time a release has one
            chart and one config.
        Config: A config is a YAML file that supplies values
            to the parametrizable templates of a chart.
        Chart: A chart is a helm package that contains
            metadata, a default config, zero or more
            optionally parameterizable templates, and
            zero or more charts (dependencies).
    """
    def ListReleases(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
        """ListReleases retrieves release history.
        TODO: Allow filtering the set of releases by
        release status. By default, ListAllReleases returns the releases who
        current status is "Active".
        """
        raise NotImplementedError()
    def GetReleaseStatus(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
        """GetReleaseStatus retrieves status information for the specified release.
        """
        raise NotImplementedError()
    GetReleaseStatus.future = None
    def GetReleaseContent(self, request, timeout, metadata=None, with_call=False,

```



```

protocol_options=None):
    """GetReleaseContent retrieves the release content (chart + value) for the specified
    release.
    """
    raise NotImplementedError()
    GetReleaseContent.future = None
    def UpdateRelease(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
        """UpdateRelease updates release content.
        """
        raise NotImplementedError()
        UpdateRelease.future = None
        def InstallRelease(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
            """InstallRelease requests installation of a chart as a new release.
            """
            raise NotImplementedError()
            InstallRelease.future = None
            def UninstallRelease(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
                """UninstallRelease requests deletion of a named release.
                """
                raise NotImplementedError()
                UninstallRelease.future = None
                def GetVersion(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
                    """GetVersion returns the current version of the server.
                    """
                    raise NotImplementedError()
                    GetVersion.future = None
                    def RollbackRelease(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
                        """RollbackRelease rolls back a release to a previous version.
                        """
                        raise NotImplementedError()
                        RollbackRelease.future = None
                        def GetHistory(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
                            """ReleaseHistory retrieves a release's history.
                            """
                            raise NotImplementedError()
                            GetHistory.future = None
                            def RunReleaseTest(self, request, timeout, metadata=None, with_call=False,
protocol_options=None):
                                """RunReleaseTest executes the tests defined of a named release
                                """
                                raise NotImplementedError()
                                def beta_create_ReleaseService_server(servicer, pool=None, pool_size=None,
default_timeout=None, maximum_timeout=None):
                                    """The Beta API is deprecated for 0.15.0 and later.

```

It is recommended to use the GA API (classes and functions in this file not marked beta) for all further purposes. This function was generated only to ease transition from grpcio<0.15.0 to grpcio>=0.15.0"""

```
request_deserializers = {
    ('hapi.services.tiller.ReleaseService',
GetHistoryRequest.FromString,
    ('hapi.services.tiller.ReleaseService',
GetReleaseContentRequest.FromString,
    ('hapi.services.tiller.ReleaseService',
GetReleaseStatusRequest.FromString,
    ('hapi.services.tiller.ReleaseService',
GetVersionRequest.FromString,
    ('hapi.services.tiller.ReleaseService',
InstallReleaseRequest.FromString,
    ('hapi.services.tiller.ReleaseService',
ListReleasesRequest.FromString,
    ('hapi.services.tiller.ReleaseService',
RollbackReleaseRequest.FromString,
    ('hapi.services.tiller.ReleaseService',
TestReleaseRequest.FromString,
    ('hapi.services.tiller.ReleaseService',
UninstallReleaseRequest.FromString,
    ('hapi.services.tiller.ReleaseService',
UpdateReleaseRequest.FromString,
    }
    response_serializers = {
    ('hapi.services.tiller.ReleaseService',
GetHistoryResponse.SerializeToString,
    ('hapi.services.tiller.ReleaseService',
GetReleaseContentResponse.SerializeToString,
    ('hapi.services.tiller.ReleaseService',
GetReleaseStatusResponse.SerializeToString,
    ('hapi.services.tiller.ReleaseService',
GetVersionResponse.SerializeToString,
    ('hapi.services.tiller.ReleaseService',
InstallReleaseResponse.SerializeToString,
    ('hapi.services.tiller.ReleaseService',
ListReleasesResponse.SerializeToString,
    ('hapi.services.tiller.ReleaseService',
RollbackReleaseResponse.SerializeToString,
    ('hapi.services.tiller.ReleaseService',
TestReleaseResponse.SerializeToString,
    ('hapi.services.tiller.ReleaseService',
UninstallReleaseResponse.SerializeToString,
    ('hapi.services.tiller.ReleaseService',
UpdateReleaseResponse.SerializeToString,
    }#退出
    self.InstallRelease = channel.unary_unary(
        '/hapi.services.tiller.ReleaseService/InstallRelease',
        request_serializer=InstallReleaseRequest.SerializeToString,
```

```

        response_deserializer=InstallReleaseResponse.FromString,
    )
    method_implementations = {
        ('hapi.services.tiller.ReleaseService',                'GetHistory'):
face_utilities.unary_unary_inline(servicer.GetHistory),
        ('hapi.services.tiller.ReleaseService',                'GetReleaseContent'):
face_utilities.unary_unary_inline(servicer.GetReleaseContent),
        ('hapi.services.tiller.ReleaseService',                'GetReleaseStatus'):
face_utilities.unary_unary_inline(servicer.GetReleaseStatus),
        ('hapi.services.tiller.ReleaseService',                'GetVersion'):
face_utilities.unary_unary_inline(servicer.GetVersion),
        ('hapi.services.tiller.ReleaseService',                'InstallRelease'):
face_utilities.unary_unary_inline(servicer.InstallRelease),
        ('hapi.services.tiller.ReleaseService',                'ListReleases'):
face_utilities.unary_stream_inline(servicer.ListReleases),
        ('hapi.services.tiller.ReleaseService',                'RollbackRelease'):
face_utilities.unary_unary_inline(servicer.RollbackRelease),
        ('hapi.services.tiller.ReleaseService',                'RunReleaseTest'):
face_utilities.unary_stream_inline(servicer.RunReleaseTest),
        ('hapi.services.tiller.ReleaseService',                'UninstallRelease'):
face_utilities.unary_unary_inline(servicer.UninstallRelease),
        ('hapi.services.tiller.ReleaseService',                'UpdateRelease'):
face_utilities.unary_unary_inline(servicer.UpdateRelease),
    }
    server_options =
beta_implementations.server_options(request_deserializers=request_deserializers,
response_serializers=response_serializers, thread_pool=pool, thread_pool_size=pool_size,
default_timeout=default_timeout, maximum_timeout=maximum_timeout)
    return beta_implementations.server(method_implementations, options=server_options)
    def beta_create_ReleaseService_stub(channel, host=None, metadata_transformer=None,
pool=None, pool_size=None):
        """The Beta API is deprecated for 0.15.0 and later.
        It is recommended to use the GA API (classes and functions in this
        file not marked beta) for all further purposes. This function was
        generated only to ease transition from grpcio<0.15.0 to grpcio>=0.15.0"""
        request_serializers = {
            ('hapi.services.tiller.ReleaseService',                'GetHistory'):
GetHistoryRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',                'GetReleaseContent'):
GetReleaseContentRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',                'GetReleaseStatus'):
GetReleaseStatusRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',                'GetVersion'):
GetVersionRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',                'InstallRelease'):
InstallReleaseRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',                'ListReleases'):
ListReleasesRequest.SerializeToString,
            ('hapi.services.tiller.ReleaseService',                'RollbackRelease'):
RollbackReleaseRequest.SerializeToString,

```

```

        ('hapi.services.tiller.ReleaseService',
TestReleaseRequest.SerializeToString,
        ('hapi.services.tiller.ReleaseService',
UninstallReleaseRequest.SerializeToString,
        ('hapi.services.tiller.ReleaseService',
UpdateReleaseRequest.SerializeToString,
    }
    response_deserializers = {
        ('hapi.services.tiller.ReleaseService',
GetHistoryResponse.FromString,
        ('hapi.services.tiller.ReleaseService',
GetReleaseContentResponse.FromString,
        ('hapi.services.tiller.ReleaseService',
GetReleaseStatusResponse.FromString,
        ('hapi.services.tiller.ReleaseService',
GetVersionResponse.FromString,
        ('hapi.services.tiller.ReleaseService',
InstallReleaseResponse.FromString,
        ('hapi.services.tiller.ReleaseService',
ListReleasesResponse.FromString,
        ('hapi.services.tiller.ReleaseService',
RollbackReleaseResponse.FromString,
        ('hapi.services.tiller.ReleaseService',
TestReleaseResponse.FromString,
        ('hapi.services.tiller.ReleaseService',
UninstallReleaseResponse.FromString,
        ('hapi.services.tiller.ReleaseService',
UpdateReleaseResponse.FromString,
    }
    cardinalities = {
        'GetHistory': cardinality.Cardinality.UNARY_UNARY,
        'GetReleaseContent': cardinality.Cardinality.UNARY_UNARY,
        'GetReleaseStatus': cardinality.Cardinality.UNARY_UNARY,
        'GetVersion': cardinality.Cardinality.UNARY_UNARY,
        'InstallRelease': cardinality.Cardinality.UNARY_UNARY,
        'ListReleases': cardinality.Cardinality.UNARY_STREAM,
        'RollbackRelease': cardinality.Cardinality.UNARY_UNARY,
        'RunReleaseTest': cardinality.Cardinality.UNARY_STREAM,
        'UninstallRelease': cardinality.Cardinality.UNARY_UNARY,
        'UpdateRelease': cardinality.Cardinality.UNARY_UNARY,
    }
    stub_options = beta_implementations.stub_options(host=host,
metadata_transformer=metadata_transformer, request_serializers=request_serializers,
response_deserializers=response_deserializers, thread_pool=pool,
thread_pool_size=pool_size)
    return beta_implementations.dynamic_stub(channel,
'hapi.services.tiller.ReleaseService', cardinalities, options=stub_options)
except ImportError:
    pass
# @@protoc_insertion_point(module_scope)

```