

Quorum Sensing Work-Precision Diagrams

David Widmann, Chris Rackauckas


April 28, 2019

1 Quorum Sensing

Here we test a model of quorum sensing of *Pseudomonas putida* IsoF in continuous cultures with constant delay which was published by K. Buddrus-Schiemann et al. in "Analysis of N-Acylhomoserine Lactone Dynamics in Continuous Cultures of *Pseudomonas Putida* IsoF By Use of ELISA and UHPLC/qTOF-MS-derived Measurements and Mathematical Models", Analytical and Bioanalytical Chemistry, 2014.


```
using DelayDiffEq, DiffEqDevTools, DiffEqProblemLibrary, Plots
using DiffEqProblemLibrary.DDEProblemLibrary: importddeproblems; importddeproblems()
import DiffEqProblemLibrary.DDEProblemLibrary: prob_dde_qs
gr()

sol = solve(prob_dde_qs, MethodOfSteps(Vern9()), max_fixedpoint_iters=1000;
    reltol=1e-14, abstol=1e-14)
plot(sol)
```



Particularly, we are interested in the third, low-level component of the system:

```
sol = solve(prob_dde_qs, MethodOfSteps(Vern9(), max_fixedpoint_iters=1000);  
    reltol=1e-14, abstol=1e-14, save_idxs=3)  
test_sol = TestSolution(sol)  
plot(sol)
```




1.1 Qualitative comparisons


First we compare the quality of the solution's third component for different algorithms, using the default tolerances.

1.1.1 RK methods

```
sol = solve(prob_dde_qs, MethodOfSteps(BS3())); reltol=1e-3, abstol=1e-6, save_idxs=3)  
p = plot(sol);  
scatter!(p, sol.t, sol.u)  
p
```



```
sol = solve(prob_dde_qs, MethodOfSteps(Tsit5()); reltol=1e-3, abstol=1e-6, save_idxs=3)
p = plot(sol);
scatter!(p, sol.t, sol.u)
p
```




```
sol = solve(prob_dde_qs, MethodOfSteps(RK4()); reltol=1e-3, abstol=1e-6, save_idxs=3)
```

```

p = plot(sol);
scatter!(p,sol.t, sol.u)
p


```




```

sol = solve(prob_dde_qs, MethodOfSteps(DP5())); reltol=1e-3, abstol=1e-6, save_idxs=3)
p = plot(sol);
scatter!(p,sol.t, sol.u)
p

```




```
sol = solve(prob_dde_qs, MethodOfSteps(DP8())); reltol=1e-3, abstol=1e-6, save_idxs=3)
p = plot(sol);
scatter!(p,sol.t, sol.u)
p
```



```

sol = solve(prob_dde_qs, MethodOfSteps(OwrenZen3())); reltol=1e-3, abstol=1e-6,
    save_idxs=3)
p = plot(sol);
scatter!(p,sol.t, sol.u)
p


```




```

sol = solve(prob_dde_qs, MethodOfSteps(OwrenZen4())); reltol=1e-3, abstol=1e-6,
    save_idxs=3)
p = plot(sol);
scatter!(p,sol.t, sol.u)
p

```




```
sol = solve(prob_dde_qs, MethodOfSteps(OwrenZen5())); reltol=1e-3, abstol=1e-6,
    save_idxs=3)
p = plot(sol);
scatter!(p,sol.t, sol.u)
p
```




1.1.2 Rosenbrock methods

```
sol = solve(prob_dde_qs, MethodOfSteps(Rosenbrock23()); reltol=1e-3, abstol=1e-6,
    save_idxs=3)
p = plot(sol);
scatter!(p, sol.t, sol.u)
p
```


```
sol = solve(prob_dde_qs, MethodOfSteps(Rosenbrock32()); reltol=1e-3, abstol=1e-6,
    save_idxs=3)
p = plot(sol);
scatter!(p, sol.t, sol.u)
p
```



```

sol = solve(prob_dde_qs, MethodOfSteps(Rodas4())); reltol=1e-3, abstol=1e-6, save_idxs=3)
p = plot(sol);
scatter!(p,sol.t, sol.u)
p


```



```


sol = solve(prob_dde_qs, MethodOfSteps(Rodas5())); reltol=1e-4, abstol=1e-6, save_idxs=3)
p = plot(sol);
scatter!(p,sol.t, sol.u)
p

```




1.1.3 Lazy interpolants

```
sol = solve(prob_dde_qs, MethodOfSteps(Vern7()); reltol=1e-3, abstol=1e-6, save_idxs=3)
p = plot(sol);
scatter!(p, sol.t, sol.u)
p
```



```
sol = solve(prob_dde_qs, MethodOfSteps(Vern9())); reltol=1e-3, abstol=1e-6, save_idxs=3)
p = plot(sol);
scatter!(p,sol.t, sol.u)
p
```



1.2 Qualitative comparisons

Now we compare these methods quantitatively.


1.2.1 High tolerances

RK methods We start with RK methods at high tolerances.

```
abstols = 1.0 ./ 10.0 .^ (4:7)
reltols = 1.0 ./ 10.0 .^ (1:4)

setups = [Dict(:alg=>MethodOfSteps(BS3())),
          Dict(:alg=>MethodOfSteps(Tsit5())),
          Dict(:alg=>MethodOfSteps(RK4())),
          Dict(:alg=>MethodOfSteps(DP5())),
          Dict(:alg=>MethodOfSteps(OwrenZen3())),
          Dict(:alg=>MethodOfSteps(OwrenZen4())),
          Dict(:alg=>MethodOfSteps(OwrenZen5()))]
names = ["BS3", "Tsit5", "RK4", "DP5", "OwrenZen3", "OwrenZen4", "OwrenZen5"]
wp = WorkPrecisionSet(prob_dde_qs,abstols,reltols,setups;names=names,

    save_idx=3,appxsol=test_sol,maxiters=Int(1e5),error_estimate=:final)
plot(wp)
```



We also compare interpolation errors:


```
abstols = 1.0 ./ 10.0 .^ (4:7)
```

```
reltols = 1.0 ./ 10.0 .^ (1:4)
```

```

setups = [Dict(:alg=>MethodOfSteps(BS3())),
          Dict(:alg=>MethodOfSteps(Tsit5())),
          Dict(:alg=>MethodOfSteps(RK4())),
          Dict(:alg=>MethodOfSteps(DP5())),
          Dict(:alg=>MethodOfSteps(OwrenZen3())),
          Dict(:alg=>MethodOfSteps(OwrenZen4())),
          Dict(:alg=>MethodOfSteps(OwrenZen5()))]
names = ["BS3", "Tsit5", "RK4", "DP5", "OwrenZen3", "OwrenZen4", "OwrenZen5"]
wp = WorkPrecisionSet(prob_dde_qs,abstols,reltols,setups;names=names,
                     save_idx=3,appxsol=test_sol,maxiters=Int(1e5),error_estimate=:L2)
plot(wp)

```



And the maximal interpolation error:

```
abstols = 1.0 ./ 10.0 .^ (4:7)
```


```
reltols = 1.0 ./ 10.0 .^ (1:4)
```

```
setups = [Dict(:alg=>MethodOfSteps(BS3())),
           Dict(:alg=>MethodOfSteps(Tsit5())),
           Dict(:alg=>MethodOfSteps(RK4())),
           Dict(:alg=>MethodOfSteps(DP5())),
           Dict(:alg=>MethodOfSteps(OwrenZen3())),
           Dict(:alg=>MethodOfSteps(OwrenZen4())),
           Dict(:alg=>MethodOfSteps(OwrenZen5()))]
```

```
names = ["BS3", "Tsit5", "RK4", "DP5", "OwrenZen3", "OwrenZen4", "OwrenZen5"]
```

```
wp = WorkPrecisionSet(prob_dde_qs,abstols,reltols,setups;names=names,
                      save_idxs=3,appxsol=test_sol,maxiters=Int(1e5),error_estimate=:L∞)
```

```
plot(wp)
```




Since the correct solution is in the range of $1e-7$, we see that most solutions, even at the lower end of tested tolerances, always lead to relative maximal interpolation errors of at least $1e-1$ (and usually worse). RK4 performs slightly better with relative maximal errors of at least $1e-2$. This matches our qualitative analysis above.

Rosenbrock methods We repeat these tests with Rosenbrock methods, and include RK4 as reference.

```
abstols = 1.0 ./ 10.0 .^ (4:7)
reltols = 1.0 ./ 10.0 .^ (1:4)

setups = [Dict(:alg=>MethodOfSteps(Rosenbrock23())),
          Dict(:alg=>MethodOfSteps(Rosenbrock32())),
          Dict(:alg=>MethodOfSteps(Rodas4())),
          Dict(:alg=>MethodOfSteps(RK4()))]
names = ["Rosenbrock23", "Rosenbrock32", "Rodas4", "RK4"]
wp = WorkPrecisionSet(prob_dde_qs,abstols,reltols,setups;names=names,

    save_idx=3,appxsol=test_sol,maxiters=Int(1e5),error_estimate=:final)
plot(wp)
```





```

abstols = 1.0 ./ 10.0 .^ (4:7)
reltols = 1.0 ./ 10.0 .^ (1:4)

setups = [Dict(:alg=>MethodOfSteps(Rosenbrock23())),
           Dict(:alg=>MethodOfSteps(Rosenbrock32())),
           Dict(:alg=>MethodOfSteps(Rodas4())),
           Dict(:alg=>MethodOfSteps(RK4()))]
names = ["Rosenbrock23", "Rosenbrock32", "Rodas4", "RK4"]
wp = WorkPrecisionSet(prob_dde_qs,abstols,reltols,setups;names=names,
                      save_idx=3,appxsol=test_sol,maxiters=Int(1e5),error_estimate=:L2)
plot(wp)

```




```

abstols = 1.0 ./ 10.0 .^ (4:7)
reltols = 1.0 ./ 10.0 .^ (1:4)

setups = [Dict(:alg=>MethodOfSteps(Rosenbrock23())),
           Dict(:alg=>MethodOfSteps(Rosenbrock32())),
           Dict(:alg=>MethodOfSteps(Rodas4())),
           Dict(:alg=>MethodOfSteps(RK4()))]
names = ["Rosenbrock23", "Rosenbrock32", "Rodas4", "RK4"]
wp = WorkPrecisionSet(prob_dde_qs,abstols,reltols,setups;names=names,
                      save_idx=3,appxsol=test_sol,maxiters=Int(1e5),error_estimate=:L∞)
plot(wp)

```




Out of the tested Rosenbrock methods Rodas4 and Rosenbrock23 perform best at high tolerances.

Lazy interpolants Finally we test the Verner methods with lazy interpolants, and include Rosenbrock23 as reference.

```
abstols = 1.0 ./ 10.0 .^ (4:7)
reltols = 1.0 ./ 10.0 .^ (1:4)

setups = [Dict(:alg=>MethodOfSteps(Vern6())),
          Dict(:alg=>MethodOfSteps(Vern7())),
          Dict(:alg=>MethodOfSteps(Vern8())),
          Dict(:alg=>MethodOfSteps(Vern9())),
          Dict(:alg=>MethodOfSteps(Rosenbrock23()))]
names = ["Vern6", "Vern7", "Vern8", "Vern9", "Rosenbrock23"]
wp = WorkPrecisionSet(prob_dde_qs,abstols,reltols,setups;names=names,

    save_idx=3,appxsol=test_sol,maxiters=Int(1e5),error_estimate=:final)
plot(wp)
```




```

abstols = 1.0 ./ 10.0 .^ (4:7)
reltols = 1.0 ./ 10.0 .^ (1:4)

setups = [Dict(:alg=>MethodOfSteps(Vern6()),
           Dict(:alg=>MethodOfSteps(Vern7()),
           Dict(:alg=>MethodOfSteps(Vern8()),
           Dict(:alg=>MethodOfSteps(Vern9()),
           Dict(:alg=>MethodOfSteps(Rosenbrock23())))]
names = ["Vern6", "Vern7", "Vern8", "Vern9", "Rosenbrock23"]
wp = WorkPrecisionSet(prob_dde_qs,abstols,reltols,setups;names=names,
                      save_idx=3,appxsol=test_sol,maxiters=Int(1e5),error_estimate=:L2)
plot(wp)

```




```

abstols = 1.0 ./ 10.0 .^ (4:7)
reltols = 1.0 ./ 10.0 .^ (1:4)

setups = [Dict(:alg=>MethodOfSteps(Vern6()),
          Dict(:alg=>MethodOfSteps(Vern7()),
          Dict(:alg=>MethodOfSteps(Vern8()),
          Dict(:alg=>MethodOfSteps(Vern9()),
          Dict(:alg=>MethodOfSteps(Rosenbrock23())))]
names = ["Vern6", "Vern7", "Vern8", "Vern9", "Rosenbrock23"]
wp = WorkPrecisionSet(prob_dde_qs,abstols,reltols,setups;names=names,
                      save_idx=3,appxsol=test_sol,maxiters=Int(1e5),error_estimate=:L∞)
plot(wp)

```



All in all, at high tolerances Rodas5 and Rosenbrock23 are the best methods for solving this stiff DDE.


1.2.2 Low tolerances

Rosenbrock methods We repeat our tests of Rosenbrock methods Rosenbrock23 and Rodas5 at low tolerances:

```
abstols = 1.0 ./ 10.0 .^ (8:11)
reltols = 1.0 ./ 10.0 .^ (5:8)

setups = [Dict(:alg=>MethodOfSteps(Rosenbrock23()),
          Dict(:alg=>MethodOfSteps(Rodas4()),
          Dict(:alg=>MethodOfSteps(Rodas5()))]
names = ["Rosenbrock23", "Rodas4", "Rodas5"]
wp = WorkPrecisionSet(prob_dde_qs,abstols,reltols,setups;names=names,

    save_idx=3,appxsol=test_sol,maxiters=Int(1e5),error_estimate=:final)
plot(wp)
```




```

abstols = 1.0 ./ 10.0 .^ (8:11)
reltols = 1.0 ./ 10.0 .^ (5:8)

setups = [Dict(:alg=>MethodOfSteps(Rosenbrock23())),
          Dict(:alg=>MethodOfSteps(Rodas4())),
          Dict(:alg=>MethodOfSteps(Rodas5()))]
names = ["Rosenbrock23", "Rodas4", "Rodas5"]
wp = WorkPrecisionSet(prob_dde_qs,abstols,reltols,setups;names=names,
                      save_idx=3,appxsol=test_sol,maxiters=Int(1e5),error_estimate=:L2)
plot(wp)

```




```

abstols = 1.0 ./ 10.0 .^ (8:11)
reltols = 1.0 ./ 10.0 .^ (5:8)

setups = [Dict(:alg=>MethodOfSteps(Rosenbrock23())),
          Dict(:alg=>MethodOfSteps(Rodas4())),
          Dict(:alg=>MethodOfSteps(Rodas5()))]
names = ["Rosenbrock23", "Rodas4", "Rodas5"]
wp = WorkPrecisionSet(prob_dde_qs,abstols,reltols,setups;names=names,
                      save_idx=3,appxsol=test_sol,maxiters=Int(1e5),error_estimate=:L∞)
plot(wp)

```

Thus at low tolerances Rodas5 outperforms Rosenbrock23.

```
using DiffEqBenchmarks
DiffEqBenchmarks.bench_footer(WEAVE_ARGS[:folder], WEAVE_ARGS[:file])
```

1.3 Appendix

These benchmarks are a part of the DiffEqBenchmarks.jl repository, found at: <https://github.com/JuliaDiffEq/DiffEqBenchmarks.jl>

To locally run this tutorial, do the following commands:

```
using DiffEqBenchmarks
DiffEqBenchmarks.weave_file("StiffDDE", "QuorumSensing.jmd")
```

Computer Information:

```
Julia Version 1.1.0
Commit 80516ca202 (2019-01-21 21:24 UTC)
Platform Info:
  OS: Linux (x86_64-pc-linux-gnu)
  CPU: Intel(R) Xeon(R) CPU E5-2680 v4 @ 2.40GHz
  WORD_SIZE: 64
  LIBM: libopenlibm
  LLVM: libLLVM-6.0.1 (ORCJIT, haswell)
```

Package Information:

```
Status: `~/home/crackauckas/.julia/environments/v1.1/Project.toml`
[c52e3926-4ff0-5f6e-af25-54175e0327b1] Atom 0.8.5
[bcd4f6db-9728-5f36-b5f7-82caef46ccdb] DelayDiffEq 5.2.0
[bb2cbb15-79fc-5d1e-9bf1-8ae49c7c1650] DiffEqBenchmarks 0.1.0
[459566f4-90b8-5000-8ac3-15dfb0a30def] DiffEqCallbacks 2.5.2
[f3b72e0c-5b89-59e1-b016-84e28bfd966d] DiffEqDevTools 2.7.2+
[055956cb-9e8b-5191-98cc-73ae4a59e68a] DiffEqPhysics 3.1.0
[a077e3f3-b75c-5d7f-a0c6-6bc4c8ec64a9] DiffEqProblemLibrary 4.1.0
[0c46a032-eb83-5123-abaf-570d42b7fbba] DifferentialEquations 6.3.0
[b305315f-e792-5b7a-8f41-49f472929428] Elliptic 0.5.0
[e5e0dc1b-0480-54bc-9374-aad01c23163d] Juno 0.7.0
[7f56f5a3-f504-529b-bc02-0b1fe5e64312] LSODA 0.4.0
[c030b06c-0b6d-57c2-b091-7029874bd033] ODE 2.4.0
[54ca160b-1b9f-5127-a996-1867f4bc2a2c] ODEInterface 0.4.5
[09606e27-ecf5-54fc-bb29-004bd9f985bf] ODEInterfaceDiffEq 3.1.0
[1dea7af3-3e70-54e6-95c3-0bf5283fa5ed] OrdinaryDiffEq 5.5.0
[65888b18-ceab-5e60-b2b9-181511a3b968] ParameterizedFunctions 4.1.1
[91a5bcdd-55d7-5caf-9e0b-520d859cae80] Plots 0.24.0
[d330b81b-6aea-500a-939a-2ce795aea3ee] PyPlot 2.8.1
[90137ffa-7385-5640-81b9-e52037218182] StaticArrays 0.10.3
[789caeaf-c7a9-5a7d-9973-96adeb23e2a0] StochasticDiffEq 6.1.1
[c3572dad-4567-51f8-b174-8c6c989267f4] Sundials 3.3.0+
[92b13dbe-c966-51a2-8445-caca9f8a7d42] TaylorIntegration 0.4.1
[44d3d7a6-8a23-5bf8-98c5-b353f8df5ec9] Weave 0.9.0
```