


OREGO Work-Precision Diagrams

Chris Rackauckas

June 12, 2019

```
using OrdinaryDiffEq, DiffEqDevTools, ParameterizedFunctions, Plots, ODE,  
    ODEInterfaceDiffEq, LSODA, Sundials  
gr() #gr(fmt=:png)  
  
f = @ode_def Orego begin  
    dy1 = p1*(y2+y1*(1-p2*y1-y2))  
    dy2 = (y3-(1+y1)*y2)/p1  
    dy3 = p3*(y1-y3)  
end p1 p2 p3  
  
p = [77.27,8.375e-6,0.161]  
prob = ODEProblem(f,[1.0,2.0,3.0],(0.0,30.0),p)  
sol = solve(prob,Rodas5(), abstol=1/10^14, reltol=1/10^14)  
test_sol = TestSolution(sol)  
abstols = 1.0 ./ 10.0 .^ (4:11)  
reltols = 1.0 ./ 10.0 .^ (1:8);  
  
plot_prob = ODEProblem(f,[1.0,2.0,3.0],(0.0,400.0),p)  
sol = solve(plot_prob,CVODE_BDF())  
plot(sol,yscale=:log10)
```



0.1 Omissions and Tweaking

The following were omitted from the tests due to convergence failures. ODE.jl's adaptivity is not able to stabilize its algorithms, while GeometricIntegratorsDiffEq has not upgraded to Julia 1.0. GeometricIntegrators.jl's methods used to be either fail to converge at comparable dts (or on some computers errors due to type conversions).

```
#sol = solve(prob,ode23s()); println("Total ODE.jl steps: $(length(sol))")
#using GeometricIntegratorsDiffEq
#try
# sol = solve(prob,GIRadIIA3(),dt=1/10)
#catch e
# println(e)
#end
```

```
sol = solve(prob,ARKODE(), abstol=1e-5, reltol=1e-1);
```

```
sol = solve(prob,ARKODE(nonlinear_convergence_coefficient =
    1e-3), abstol=1e-5, reltol=1e-1);
```

```
sol = solve(prob,ARKODE(order=3), abstol=1e-5, reltol=1e-1);
```

```
sol = solve(prob,ARKODE(order=3, nonlinear_convergence_coefficient =
    1e-5), abstol=1e-5, reltol=1e-1);
```

```
sol = solve(prob,ARKODE(order=5), abstol=1e-5, reltol=1e-1);
```


0.2 High Tolerances

This is the speed when you just want the answer.

```

solve(prob, ddebdfe())
solve(prob, rodas())
solve(prob, radau())
abstols = 1.0 ./ 10.0 .^ (5:8)
reltols = 1.0 ./ 10.0 .^ (1:4);
setups = [Dict(:alg=>Rosenbrock23()),
          Dict(:alg=>Rodas3()),
          Dict(:alg=>TRBDF2()),
          Dict(:alg=>CVODE_BDF()),
          Dict(:alg=>rodas()),
          Dict(:alg=>radau()),
          Dict(:alg=>lsoda()),
          Dict(:alg=>ROCK2()),
          Dict(:alg=>ROCK4())
        ]
wp = WorkPrecisionSet(prob,abstols,reltols,setups;
                      save_everystep=false,appxsol=test_sol,maxiters=Int(1e5),numruns=10)
plot(wp)


```




```

wp = WorkPrecisionSet(prob,abstols,reltols,setups;dense = false,verbose=false,
                      appxsol=test_sol,maxiters=Int(1e5),error_estimate=:l2,numruns=10)
plot(wp)

```



```
wp = WorkPrecisionSet(prob, abstols, reltols, setups;
    appxsol=test_sol, maxiters=Int(1e5), error_estimate=:L2, numruns=10)
plot(wp)
```




```
setups = [Dict(:alg=>Rosenbrock23()),
    Dict(:alg=>Kvaerno3()),
```

```

Dict(:alg=>CVODE_BDF()),
Dict(:alg=>KenCarp4()),
Dict(:alg=>TRBDF2()),
Dict(:alg=>KenCarp3()),
# Dict(:alg=>SDIRK2()), # Removed because it's bad
Dict(:alg=>radau())]
wp = WorkPrecisionSet(prob, abstols, reltols, setups;
                      save_everystep=false, appxsol=test_sol, maxiters=Int(1e5), numruns=10)
plot(wp)


```




```

wp = WorkPrecisionSet(prob, abstols, reltols, setups; dense = false, verbose = false,
                      appxsol=test_sol, maxiters=Int(1e5), error_estimate=:l2, numruns=10)
plot(wp)

```



```
wp = WorkPrecisionSet(prob, abstols, reltols, setups;
    appxsol=test_sol, maxiters=Int(1e5), error_estimate=:L2, numruns=10)
plot(wp)
```




```
setups = [Dict(:alg=>Rosenbrock23()),
    Dict(:alg=>KenCarp5()),
```

```

Dict(:alg=>KenCarp4()),
Dict(:alg=>KenCarp3()),
Dict(:alg=>ARKODE(order=5)),
Dict(:alg=>ARKODE(nonlinear_convergence_coefficient = 1e-6)),
Dict(:alg=>ARKODE(nonlinear_convergence_coefficient = 1e-5,order=3))
]
names = ["Rosenbrock23" "KenCarp5" "KenCarp4" "KenCarp3" "ARKODE5" "ARKODE4" "ARKODE3"]
wp = WorkPrecisionSet(prob, abstols, reltols, setups;
    names=names,
    save_everystep=false, appxsol=test_sol, maxiters=Int(1e5), numruns=10)
plot(wp)

```



0.2.1 Low Tolerances

This is the speed at lower tolerances, measuring what's good when accuracy is needed.

```

abstols = 1.0 ./ 10.0 .^ (7:13)
reltols = 1.0 ./ 10.0 .^ (4:10)

setups = [Dict(:alg=>GRK4A()),
    Dict(:alg=>Rodas4P()),
    Dict(:alg=>CVODE_BDF()),
    Dict(:alg=>ddebdf()),
    Dict(:alg=>Rodas4()),
    Dict(:alg=>rodas()),
    Dict(:alg=>radau()),
    Dict(:alg=>lsoda()),
    #Dict(:alg=>ROCK2()), #Needs more iterations
    Dict(:alg=>ROCK4())
]
wp = WorkPrecisionSet(prob, abstols, reltols, setups;


```

```

save_everystep=false, appxsol=test_sol,maxiters=Int(1e5),numruns=10)

plot(wp)

```




```

wp = WorkPrecisionSet(prob, abstols, reltols, setups; verbose=false,


    dense=false, appxsol=test_sol,maxiters=Int(1e5), error_estimate=:l2,numruns=10)

plot(wp)

```

```
wp = WorkPrecisionSet(prob, abstols, reltols, setups;
    appxsol=test_sol, maxiters=Int(1e5), error_estimate=:L2, numruns=10)
plot(wp)
```




```
setups = [
    Dict(:alg=>Rodas5()),
```

```

Dict(:alg=>Kvaerno5()),
Dict(:alg=>CVODE_BDF()),
Dict(:alg=>KenCarp4()),
Dict(:alg=>KenCarp5()),
Dict(:alg=>Rodas4()),
Dict(:alg=>radau())]
wp = WorkPrecisionSet(prob, abstols, reltols, setups;
    save_everystep=false, appxsol=test_sol, maxiters=Int(1e5), numruns=10)
plot(wp)


```




```

wp = WorkPrecisionSet(prob, abstols, reltols, setups; verbose=false,
    dense=false, appxsol=test_sol, maxiters=Int(1e5), error_estimate=:l2, numruns=10)
plot(wp)

```



```
wp = WorkPrecisionSet(prob, abstols, reltols, setups;
    appxsol=test_sol, maxiters=Int(1e5), error_estimate=:L2, numruns=10)
plot(wp)
```



The following algorithms were removed since they failed.

```

#setups = [Dict(:alg=>Hairer4()),
            #Dict(:alg=>Hairer42()),
            #Dict(:alg=>Rodas3()),
            #Dict(:alg=>Kvaerno4()),
            #Dict(:alg=>Cash4())
#]
#wp = WorkPrecisionSet(prob, abstols, reltols, setups;
# save_everystep=false, appxsol=test_sol, maxiters=Int(1e5), numruns=10)
#plot(wp)

```

0.2.2 Conclusion

At high tolerances, `Rosenbrock23` hits the the error estimates and is fast. At lower tolerances and normal user tolerances, `Rodas4` and `Rodas5` are extremely fast. When you get down to `reltol=1e-9` `radau` begins to become as efficient as `Rodas4`, and it continues to do well below that.

```

using DiffEqBenchmarks
DiffEqBenchmarks.bench_footer(WEAVE_ARGS[:folder], WEAVE_ARGS[:file])

```

0.3 Appendix

These benchmarks are a part of the `DiffEqBenchmarks.jl` repository, found at: <https://github.com/JuliaDiffEq/DiffEqBenchmarks.jl>

To locally run this tutorial, do the following commands:

```

using DiffEqBenchmarks
DiffEqBenchmarks.weave_file("StiffODE", "Orego.jmd")

```

Computer Information:

```

Julia Version 1.1.0
Commit 80516ca202 (2019-01-21 21:24 UTC)
Platform Info:
  OS: Linux (x86_64-pc-linux-gnu)
  CPU: Intel(R) Xeon(R) CPU E5-2680 v4 @ 2.40GHz
  WORD_SIZE: 64
  LIBM: libopenlibm
  LLVM: libLLVM-6.0.1 (ORCJIT, haswell)

```

Package Information:

```

Status: `~/home/crackauckas/.julia/environments/v1.1/Project.toml`
[c52e3926-4ff0-5f6e-af25-54175e0327b1] Atom 0.8.7
[bcd4f6db-9728-5f36-b5f7-82caef46ccdb] DelayDiffEq 5.3.0
[bb2cbb15-79fc-5d1e-9bf1-8ae49c7c1650] DiffEqBenchmarks 0.1.0
[459566f4-90b8-5000-8ac3-15dfb0a30def] DiffEqCallbacks 2.5.2
[f3b72e0c-5b89-59e1-b016-84e28bfd966d] DiffEqDevTools 2.8.0

```

[aae7a2af-3d4f-5e19-a356-7da93b79d9d0] DiffEqFlux 0.5.0
 [78ddff82-25fc-5f2b-89aa-309469cbf16f] DiffEqMonteCarlo 0.14.0
 [77a26b50-5914-5dd7-bc55-306e6241c503] DiffEqNoiseProcess 3.3.1
 [9fdde737-9c7f-55bf-ade8-46b3f136cc48] DiffEqOperators 3.5.0
 [055956cb-9e8b-5191-98cc-73ae4a59e68a] DiffEqPhysics 3.1.0
 [a077e3f3-b75c-5d7f-a0c6-6bc4c8ec64a9] DiffEqProblemLibrary 4.1.0
 [41bf760c-e81c-5289-8e54-58b1f1f8abe2] DiffEqSensitivity 3.2.2
 [0c46a032-eb83-5123-abaf-570d42b7fbaa] DifferentialEquations 6.4.0
 [b305315f-e792-5b7a-8f41-49f472929428] Elliptic 0.5.0
 [587475ba-b771-5e3f-ad9e-33799f191a9c] Flux 0.8.3
 [e5e0dc1b-0480-54bc-9374-aad01c23163d] Juno 0.7.0
 [7f56f5a3-f504-529b-bc02-0b1fe5e64312] LSODA 0.4.0
 [c030b06c-0b6d-57c2-b091-7029874bd033] ODE 2.4.0
 [54ca160b-1b9f-5127-a996-1867f4bc2a2c] ODEInterface 0.4.5
 [09606e27-ecf5-54fc-bb29-004bd9f985bf] ODEInterfaceDiffEq 3.3.0
 [1dea7af3-3e70-54e6-95c3-0bf5283fa5ed] OrdinaryDiffEq 5.8.1
 [2dcacdae-9679-587a-88bb-8b444fb7085b] ParallelDataTransfer 0.5.0
 [65888b18-ceab-5e60-b2b9-181511a3b968] ParameterizedFunctions 4.1.1
 [91a5bcdd-55d7-5caf-9e0b-520d859cae80] Plots 0.25.1
 [d330b81b-6aea-500a-939a-2ce795aea3ee] PyPlot 2.8.1
 [731186ca-8d62-57ce-b412-fbd966d074cd] RecursiveArrayTools 0.20.0
 [295af30f-e4ad-537b-8983-00126c2a3abe] Revise 2.1.6
 [90137ffa-7385-5640-81b9-e52037218182] StaticArrays 0.11.0
 [789caeaf-c7a9-5a7d-9973-96adeb23e2a0] StochasticDiffEq 6.2.0
 [c3572dad-4567-51f8-b174-8c6c989267f4] Sundials 3.6.0
 [92b13dbe-c966-51a2-8445-caca9f8a7d42] TaylorIntegration 0.5.0
 [44d3d7a6-8a23-5bf8-98c5-b353f8df5ec9] Weave 0.9.0
 [e88e6eb3-aa80-5325-afca-941959d7151f] Zygote 0.3.1