

CSS Selectors - Beginner Chapter (Sample)

A CSS selector tells the browser which HTML elements should receive a style. Every CSS rule has a selector, one or more properties, and values.

CSS Rule Syntax

```
selector {  
  property: value;  
}
```

Example: h1 is the selector, color is the property, and red is the value.

```
h1 {  
  color: red;  
}
```

1. Universal Selector (*)

The universal selector matches every element. It is commonly used to remove default browser spacing.

```
* {  
  margin:0;  
  padding:0;  
  box-sizing:border-box;  
}
```

2. Element Selector

Selects all elements with a particular HTML tag.

```
p {  
  color:blue;  
  font-size:18px;  
}
```

Class and ID Selectors

3. Class Selector

A class can be reused on many elements. Prefix with a dot.

```
.card {  
  border:1px solid #333;  
  padding:20px;  
}
```

4. ID Selector

An ID should identify one unique element on the page. Prefix with #.

```
#header {  
  background:black;  
  color:white;  
}
```

Example HTML

```
<div id="header">Header</div>  
<div class="card">Card 1</div>  
<div class="card">Card 2</div>
```

Relationship Selectors

Relationship selectors depend on how elements are nested.

Descendant

```
div p { color:green; }
```

Child

```
div > p { font-weight:bold; }
```

Adjacent sibling

```
h1 + p { color:red; }
```

General sibling

```
h1 ~ p { color:orange; }
```

Attribute & Pseudo Selectors

Attribute

```
input[type="text"] {  
  border:2px solid blue;  
}
```

Pseudo-class

```
button:hover {  
  background:black;  
  color:white;  
}
```

Pseudo-element

```
p::first-letter {  
  font-size:36px;  
  color:red;  
}
```

Complete Example

```
<!DOCTYPE html>
<html>
<style>
*{margin:0;padding:0}
#title{text-align:center}
.note{background:yellow}
div p{color:green}
button:hover{background:black;color:white}
</style>
<body>
<h1 id="title">CSS Selectors</h1>
<p class="note">welcome</p>
<div><p>Inside div</p></div>
<button>Hover</button>
</body></html>
```

Practice

1. Create three paragraphs and style them using an element selector. 2. Create two cards with the same class. 3. Style an input using an attribute selector. 4. Add a hover effect to a button.