


Task 2: Question Answers

1. Include the screenshot of your operations, such as commands and output.



```

File Actions Edit View Help
(kali@kali)-[~/cybersecurity-experiments/Module3]
$ openssl genrsa -des3 -out server.key 4096
Enter PEM pass phrase:
Verifying - Enter PEM pass phrase:


File Actions Edit View Help
(kali@kali)-[~/cybersecurity-experiments/Module3]
$ openssl req -new -key server.key -out server.csr -config openssl.cnf
Enter pass phrase for server.key:
You are about to be asked to enter information that will be incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
.
Country Name (2 letter code) [AU]:US
State or Province Name (full name) [Some-State]:Pennsylvania
Locality Name (eg, city) []:
Organization Name (eg, company) [Internet Widgits Pty Ltd]:
Organizational Unit Name (eg, section) []:
Common Name (e.g. server FQDN or YOUR name) []:PKILabServer
Email Address []:

Please enter the following 'extra' attributes
to be sent with your certificate request
A challenge password []:
An optional company name []:

(kali@kali)-[~/cybersecurity-experiments/Module3]
$ openssl ca -in server.csr -out server.crt -cert ca.crt -keyfile ca.key -config openssl.cnf
Using configuration from openssl.cnf
Enter pass phrase for ca.key:
Check that the request matches the signature
Signature ok
Certificate Details:
  Serial Number: 4097 (0x1001)
  Validity
    Not Before: Feb  7 20:14:16 2023 GMT
    Not After : Feb  7 20:14:16 2024 GMT
  Subject:
    countryName           = US
    stateOrProvinceName   = Pennsylvania
    organizationName      = Internet Widgits Pty Ltd
    commonName            = PKILabServer
  X509v3 extensions:
    X509v3 Basic Constraints: CA:FALSE
    X509v3 Subject Key Identifier:
      33:25:82:58:5D:3F:F1:5F:5C:49:EE:DD:E2:E8:DC:60:21:B7:43:08
    X509v3 Authority Key Identifier:
      ED:53:22:5B:F3:E0:A9:2C:EE:A5:D4:46:64:62:03:97:86:0E:F9:9A
Certificate is to be certified until Feb  7 20:14:16 2024 GMT (365 days)
Sign the certificate? [y/n]:y

1 out of 1 certificate requests certified, commit? [y/n]y
Write out database with 1 new entries

```



```
(kali@kali)-[~/cybersecurity-experiments/Module3/Task1-3]
$ openssl x509 -req -days 365 -CA ca.crt -CAkey ca.key -CAcreateserial \
  -extensions SAN \
  -extfile <(cat ./openssl.cnf \
    <(printf "[SAN]\nsubjectAltName=DNS:pkilabserver.com,DNS:www.pkilabserver.com")) \
  -in server.csr -out server.crt
Certificate request self-signature ok
subject=C = US, ST = Pennsylvania, O = Internet Widgits Pty Ltd, CN = PKILabServer
Enter pass phrase for ca.key:

(kali@kali)-[~/cybersecurity-experiments/Module3/Task1-3]
$ cp server.key server.pem

(kali@kali)-[~/cybersecurity-experiments/Module3/Task1-3]
$ cat server.crt >> server.pem

(kali@kali)-[~/cybersecurity-experiments/Module3/Task1-3]
$ openssl s_server -cert server.pem -www
Enter pass phrase for server.pem:
Could not read server certificate private key from server.pem
4067B2943E7F0000:error:1608010C:STORE routines:ossl_store_handle_load_result:unsupported:../crypto/store/store_result.c:151:
4067B2943E7F0000:error:1C800064:Provider routines:ossl_cipher_unpadblock:bad decrypt:../providers/impl
  ementations/ciphers/ciphercommon_block.c:124:
4067B2943E7F0000:error:11800074:PKCS12 routines:PKCS12_pbe_crypt_ex:pkcs12 cipherfinal error:../crypto
  /pkcs12/p12_decr.c:86:maybe wrong password

(kali@kali)-[~/cybersecurity-experiments/Module3/Task1-3]
$ openssl s_server -cert server.pem -www
Enter pass phrase for server.pem:
Enter pass phrase for server.pem:
Using default temp DH parameters
ACCEPT
```


Task 3

Task 3: Summary

In Task 3, we load the root certificate generated in task 1 into our web browser. We then try to connect to a web server that has a certificate signed by the root certificate we loaded so we can verify their identity. (We are also hosting the web browser.)

Task 3: Question Answers

The screenshot of your operations can be included for better demo.



1. (a) Please describe and explain your observations

The web browser did not trust the certificate provided by pkilabserver.com until we loaded the Certificate Authorities certificate.

To my understanding, since the server's certificate is signed by the CA's private key, the CA certificate we loaded into the web browser was the public key necessary to decrypt the CA signature on the server's signature. However, I don't understand why the server's private key was necessary to generate the server's certificate in Task 2. The client never gets the server's public key so they wouldn't be able to verify the server's signature anyway.

2. (b) What do you observe?

The webserver says it "cannot read the certificate private key". Which confuses me on what the purpose of the server private key is for. Throughout the lab when referring to the server key, it is never

2. (b) Please describe whether your observations are similar to those from the outputs of the `speed` command.

```
File Actions Edit View Help
(kali@kali)-[~/cybersecurity-experiments/Module3/Task1-3]
$ openssl speed rsa
Doing 512 bits private rsa's for 10s: 297070 512 bits private RSA's in 9.97s
Doing 512 bits public rsa's for 10s: 4071780 512 bits public RSA's in 9.98s
Doing 1024 bits private rsa's for 10s: 103764 1024 bits private RSA's in 9.97s
Doing 1024 bits public rsa's for 10s: 1553033 1024 bits public RSA's in 9.98s
Doing 2048 bits private rsa's for 10s: 13680 2048 bits private RSA's in 9.98s
Doing 2048 bits public rsa's for 10s: 464294 2048 bits public RSA's in 9.98s
Doing 3072 bits private rsa's for 10s: 4380 3072 bits private RSA's in 9.97s
Doing 3072 bits public rsa's for 10s: 217451 3072 bits public RSA's in 9.98s
Doing 4096 bits private rsa's for 10s: 1910 4096 bits private RSA's in 9.98s
Doing 4096 bits public rsa's for 10s: 125361 4096 bits public RSA's in 9.97s
Doing 7680 bits private rsa's for 10s: 218 7680 bits private RSA's in 10.01s
Doing 7680 bits public rsa's for 10s: 36189 7680 bits public RSA's in 9.97s
Doing 15360 bits private rsa's for 10s: 40 15360 bits private RSA's in 10.16s
Doing 15360 bits public rsa's for 10s: 9212 15360 bits public RSA's in 9.98s
version: 3.0.7
built on: Tue Nov 1 20:39:01 2022 UTC
options: bn(64,64)
compiler: gcc -fPIC -pthread -m64 -Wa,--noexecstack -Wall -fzero-call-used-regs=used-gpr -DOPE
NSSL_TLS_SECURITY_LEVEL=2 -Wa,--noexecstack -g -O2 -ffile-prefix-map=/build/openssl-vMvW8q/ope
nssl-3.0.7=. -fstack-protector-strong -Wformat -Werror=format-security -DOPENSSL_USE_NODELETE
-DL_ENDIAN -DOPENSSL_PIC -DOPENSSL_BUILDING_OPENSSL -DNDEBUG -Wdate-time -D_FORTIFY_SOURCE=2
CPUINFO: OPENSSL_ia32cap=0x9ed83203078bffff:0x0
sign verify sign/s verify/s
rsa 512 bits 0.000034s 0.000002s 29796.4 407994.0
rsa 1024 bits 0.000096s 0.000006s 10407.6 155614.5
rsa 2048 bits 0.000730s 0.000021s 1370.7 46522.4
rsa 3072 bits 0.002276s 0.000046s 439.3 21788.7
rsa 4096 bits 0.005225s 0.000080s 191.4 12573.8
rsa 7680 bits 0.045917s 0.000275s 21.8 3629.8
rsa 15360 bits 0.254000s 0.001083s 3.9 923.0
```

```
File Actions Edit View Help
(kali@kali)-[~/cybersecurity-experiments/Module3/Task1-3]
$ openssl speed aes
Doing aes-128-cbc for 3s on 16 size blocks: 160364247 aes-128-cbc's in 3.00s
Doing aes-128-cbc for 3s on 64 size blocks: 66655248 aes-128-cbc's in 3.00s
Doing aes-128-cbc for 3s on 256 size blocks: 17299133 aes-128-cbc's in 3.00s
Doing aes-128-cbc for 3s on 1024 size blocks: 4327831 aes-128-cbc's in 3.00s
Doing aes-128-cbc for 3s on 8192 size blocks: 528826 aes-128-cbc's in 3.00s
Doing aes-128-cbc for 3s on 16384 size blocks: 263381 aes-128-cbc's in 3.00s
Doing aes-192-cbc for 3s on 16 size blocks: 155045727 aes-192-cbc's in 2.99s
Doing aes-192-cbc for 3s on 64 size blocks: 54418354 aes-192-cbc's in 3.00s
Doing aes-192-cbc for 3s on 256 size blocks: 14004082 aes-192-cbc's in 2.99s
Doing aes-192-cbc for 3s on 1024 size blocks: 3543638 aes-192-cbc's in 3.00s
Doing aes-192-cbc for 3s on 8192 size blocks: 443227 aes-192-cbc's in 3.00s
Doing aes-192-cbc for 3s on 16384 size blocks: 220598 aes-192-cbc's in 3.00s
Doing aes-256-cbc for 3s on 16 size blocks: 150730994 aes-256-cbc's in 3.00s
Doing aes-256-cbc for 3s on 64 size blocks: 47616064 aes-256-cbc's in 2.99s
Doing aes-256-cbc for 3s on 256 size blocks: 12146301 aes-256-cbc's in 2.99s
Doing aes-256-cbc for 3s on 1024 size blocks: 3061329 aes-256-cbc's in 3.00s
Doing aes-256-cbc for 3s on 8192 size blocks: 384818 aes-256-cbc's in 3.00s
Doing aes-256-cbc for 3s on 16384 size blocks: 197479 aes-256-cbc's in 3.00s
version: 3.0.7
built on: Tue Nov 1 20:39:01 2022 UTC
options: bn(64,64)
compiler: gcc -fPIC -pthread -m64 -Wa,--noexecstack -Wall -fzero-call-used-regs=used-gpr -DOPE
NSSL_TLS_SECURITY_LEVEL=2 -Wa,--noexecstack -g -O2 -ffile-prefix-map=/build/openssl-vMvW8q/ope
nssl-3.0.7=. -fstack-protector-strong -Wformat -Werror=format-security -DOPENSSL_USE_NODELETE
-DL_ENDIAN -DOPENSSL_PIC -DOPENSSL_BUILDING_OPENSSL -DNDEBUG -Wdate-time -D_FORTIFY_SOURCE=2
CPUINFO: OPENSSL_ia32cap=0x9ed83203078bffff:0x0
The 'numbers' are in 1000s of bytes per second processed.
type      16 bytes      64 bytes      256 bytes      1024 bytes      8192 bytes      16384 bytes
aes-128-cbc 855275.98k 1421978.62k 1476192.68k 1477232.98k 1444047.53k 1438411.43k
aes-192-cbc 829676.13k 1160924.89k 1199011.70k 1209561.77k 1210305.19k 1204759.21k
aes-256-cbc 803898.63k 1019206.72k 1039950.85k 1044933.63k 1050809.69k 1078498.65k
```

For RSA-4096, the "speed" tool recorded 29796 encryptions per second and 407994 decryptions per second per 32 bytes. To compare it to AES later, we need to find the time per 16 bytes. Taking the inverse and dividing by 2, we find that it took 0.0168 ms to encrypt and 0.00245 ms to decrypt 16 bytes.

For AES-128-ECB, 160364247 16 byte sized blocks can be encrypted in 3 seconds. That's a speed of 0.0000187 ms per 16 byte block.

The speed tool reports much faster times than the bash script. This is due to the latencies in calling a command line tool over and over.

Task 5

Task 5: Summary

In Task 5, we sign a file to create digital signature with a private key. Then we verify the file and signature using the corresponding public key.

Task 5: Question Answers

The screenshot of your operations can be included for better demo.

```

File Actions Edit View Help

(kali@kali)-[~/cybersecurity-experiments/Module3/Task5] a public key from
$ openssl genrsa -out signing.key 4096

(kali@kali)-[~/cybersecurity-experiments/Module3/Task5]
$ openssl rsa -in signing.key -pubout > verify.key
writing RSA key

(kali@kali)-[~/cybersecurity-experiments/Module3/Task5]
$ openssl dgst -sha256 -sign signing.key -out example.sha256 example.txt

(kali@kali)-[~/cybersecurity-experiments/Module3/Task5]
$ openssl dgst -sha256 -verify verify.key -signature ./example.sha256 example.txt
Verified OK

(kali@kali)-[~/cybersecurity-experiments/Module3/Task5]
$ sudo nano example.T

(kali@kali)-[~/cybersecurity-experiments/Module3/Task5]
$ sudo nano example.txt

(kali@kali)-[~/cybersecurity-experiments/Module3/Task5]
$ openssl dgst -sha256 -verify verify.key -signature ./example.sha256 example.txt
Verification failure
40E7CF0E4B7F0000:error:02000068:rsa routines:ossl_rsa_verify:bad signature:../crypto/rsa/rsa_sign.c:430:
40E7CF0E4B7F0000:error:1C880004:Provider routines:rsa_verify:RSA lib:../providers/implementations/signature/r
sa_sig.c:774:

```

1. (a) Please describe how you did the above operations (e.g., what commands do you use, etc.)

I used the "genrsa" and "rsa" tools to create the private and public keys. Then I used the "dgst" or digest tool to create the hash and signature in one command. Only the signature was generated. I then verified the file and signature with the "dgst" again.

2. (b) Explain your observations.

After changing the original file, verifying using the old signature did not work.

3. (c) Please also explain why digital signatures are useful.

Digital signatures are useful because they allow us to verify the integrity of a file. If a file was tampered with, the signature would not match when there is an attempt to verify the file.

