

The University of York

Department of Computer Science

**Submitted in part fulfilment for the degree of MEng in  
Computer Science with Embedded Systems Engineering.**

# **Self-Healing in Wireless Sensor Networks**

Andrew Durant

<b>DRAFT PROCESSED 2nd February 2016</b>
--

Supervisor: James Harbin

Number of words = 0, as counted by `texcount -sum -1  
project-report.tex`.

This includes the body of the report only.

## Abstract

# Contents

<b>1</b>	<b>Introduction</b>	<b>7</b>
1.1	Project Aims . . . . .	7
1.2	Report Structure . . . . .	7
1.3	Statement of Ethics . . . . .	7
<b>2</b>	<b>Literature Review</b>	<b>8</b>
2.1	WSN applications . . . . .	8
2.2	Approaches to self-healing in WSNs . . . . .	9
2.2.1	Centralised . . . . .	9
2.2.2	Distributed . . . . .	11
2.3	Metrics for evaluating self-healing WSNs . . . . .	13
2.4	Review of evaluation techniques for WSNs . . . . .	13
2.5	Conclusions . . . . .	14

## List of Figures

## List of Tables

## List of Listings

# **1 Introduction**

## **1.1 Project Aims**

## **1.2 Report Structure**

## **1.3 Statement of Ethics**

## 2 Literature Review

In order to consider self-healing in real-world applications of wireless sensor networks an understanding of the possible applications is required. A survey of approaches to self-healing is then presented along with metrics that can be used to evaluate and compare them. This is followed with a review of evaluation techniques and real-world factors for wireless sensor networks.

### 2.1 WSN applications

The possible applications for wireless sensor networks are diverse and far reaching. The small self-powered devices that can gather data from a wide area, to detect events and communicate information back to a base station either processed or for processing lend themselves to a large number of applications. Each of these applications utilise the WSN in different ways and thereby bring new challenges to the developer of the systems. Due to this the design of the network is highly dependent on the application domain. Just some of the fields WSNs have been used in are environmental monitoring, warfare, agriculture, surveillance, medical care, education and micro-surgery.

Habitat monitoring using WSNs has been taking place on an island of ducks where ordinary monitoring techniques cause disturbance to the animals with problems such as increasing mortality and eventual abandonment of the habitat. The use of WSNs that can be deployed prior to seasonal habitation enables constant monitoring over the time without the need to disturb the inhabitants. Mainwaring et al. [1] detail the requirements of the network and how it has been developed. Longevity of the devices, remote management, and inconspicuous operation are required to ensure the WSN is reliable and the data is able to be collected. The locations used for WSNs are often extreme, particularly for habitat monitoring. Similar requirements to the above are generated by Biagioni and Bridges [2] for monitoring endangered plants. Most importantly however for collecting scientific data is ensuring the system is reliable



and the user can have confidence in the data.

A very different approach was taken by Juang et al. [3] in developing ZebraNet. Rather than statically positioned nodes, the devices are attached to the herd of zebra being monitored with collars. The nature of this system is entirely mobile, without even a fixed base station to report to. Because of this the nodes pass data between them when within range forming a distributed collection and storage network. The mobile base station can then be deployed occasionally to collect the dataset only needing to meet a few devices to obtain all of the data gathered by the network. This network is inherently ad-hoc where nodes may or may not come into contact with one another frequently, and there is no fixed or permanent base station to report to. Again longevity is an important requirement as deploying or re-deploying the sensors requires capture of the animals, so the systems must run for at least a year with no intervention.

Environmental monitoring on volcanoes has been investigated by Werner-Allen et al. [4] where the use of WSNs enables data collection over a wider area for a longer amount of time compared to using traditional equipment. WSN nodes can be deployed easily and left unattended to monitor the volcano area over a period of several weeks or months. Whereas traditional equipment is bulky and heavy, and therefore difficult to deploy limiting the area of research. The WSN transmitting the collected data back to the base station also removes the need to frequently return to the sensor devices to retrieve data. This is a clear example of using the advantages of wireless sensor networks. However a number of potential issues are raised. The nodes are deployed at the limits of their range to the nearest neighbour, this allows as large an area as possible to be covered, however if a single node fails all other nodes that were dependent upon it will be unreachable. In the scale of this network, where the maximum hop length from the base station is 6 this may seem insignificant, however that is 37.5% of the network nodes.

## 2.2 Approaches to self-healing in WSNs

### 2.2.1 Centralised

The main way centralised approaches are used in WSNs is in the configuration of the network structure to minimise energy use and ensure good coverage of the area of interest [5–8]. Centralised evaluation of the

network and area of interest prior to deployment ensures the connectivity and coverage requirements of the application are met.

Coverage requires that every location in the sensing field is monitored by at least one sensor. Connectivity requires that the network is not partitioned in terms of nodes' communication capability. Note that coverage is affected by sensors' sensitivity, while connectivity is influenced by sensors' communication ranges. [7]

These vary by application for instance, detection and localisation of events require multiple nodes covering smaller areas (a dense coverage) whereas other applications may only need one node within its transmission range (a sparse coverage). By pre-planning to match the deployment to the application needs the network will be much more efficient in power use and accurate in data collection.

Networks with a high degree of connectivity are more resilient to node failures. Wang et al. [5] investigate the relationship between coverage and connectivity to produce an integrated solution that is able to maintain both requirements whilst reducing energy consumption. The degree of connectivity is described as  $K$ -connected, where any  $K - 1$  nodes may fail without losing network connectivity. So the higher the connectivity ( $> K$ ) the more nodes are able to fail without disrupting the rest of the functioning network.

Due to the differences in applications a number of application specific methods have been proposed in addition to those previously mentioned [9–11]. All of these provide for different application requirements in different ways. However a single parametrised method that can be applied to many differing applications has been developed by Derr and Manic [8]. This allows the specification of the number of nodes and the distance between the nodes which defines the desired coverage and connectivity respectively. The algorithm can then take a mesh of the area and simplify it to provide the desired parameters.

Most centralised approaches use a priori information to specify exact deployment in the area of interest. However Qu and Georgakopoulos [12] have developed a post deployment particle swarm optimization (PSO) algorithm that is computed centrally to provide optimal coverage and reduce energy consumption. A centralised algorithm is able to understand the entire network, available devices, and area, and therefore produce the optimal distribution of nodes. The nodes are on a mobile platform that is able to move within the area. Reduction of energy

consumption is done by dynamically reducing the range of sensing and communication on each device to the minimum needed once the locations have been determined. Qu and Georgakopoulos do not address node failures, as they assume all nodes are working throughout the time of use.

### 2.2.2 Distributed

In Abbasi et al. [13]'s seminal paper DARA (a Distributed Actor Recovery Algorithm) is introduced. Developing a localised scheme to restore a network of mobile nodes when it has been partitioned by a node failure. The distributed nature of the algorithm avoids involving every single node, only requiring the local nodes to respond. The algorithm selects a node to replace a failed node and coordinates the local nodes to relocate to rebuild the network. As nodes relocate they may cause other partitioning, but this is dealt with in the same way forming a chain reaction until the entire network is reconnected. The self-healing process requires no supervision or centralised control.

There have been many algorithms developed for distributed control and self-healing for WSNs as a large amount of academic research has gone into systems such as environmental monitoring. A basis for many of these are DARA [13] and PADRA [14] which both aim to restore connectivity to a local area after a node has failed, whilst minimising the total distance travelled, and without external supervision or involvement.

RIM [15] improves upon DARA and PADRA which each need 2-hop knowledge of the network to only requiring 1-hop knowledge on each node. This significantly reduces the network overhead for maintaining the required knowledge of the network topology, however the simplicity means that the distance travelled by the nodes is greater in larger networks for RIM than for DARA or PADRA. Calculating and transmitting a lot of detailed information is often considered too much overhead for low-power, low-complexity systems, particularly if the network can change often or easily. Depending on the application for the WSN the communication overhead to maintain the topology data could be justified over the generally more efficient algorithm.

Another flaw in RIM is that it assumes and requires only one node failure at a time. Whilst this may be the case, failures in WSNs are most commonly battery depletion, which is likely to occur at similar times across the network, or random failure due to environmental conditions, which could happen at any time to one or multiple nodes.

SFRA [16] is designed specifically to deal with multiple simultaneous

failures to combat the multiple failure problem in RIM. Network trees are built from the root node, with local cluster-head nodes, this introduces a fair amount of network overhead compared with RIM. The number of updates needed to send is reduced by waiting for all child node messages before propagating back up the tree.

Distributed approaches become much more efficient as the network scales because they are only concerned with the local nodes that are directly reachable. This allows networks built upon distributed algorithms to become much larger, and cover much wider areas as the overhead increase from additional nodes is minimal compared with the exponential increase in complexity from the centralised approaches.

A number of biologically-inspired approaches exist utilising animal and insect coordination and inspired methods of load balancing. Caliskanelli [17] suggests the application of bee pheromone based load balancing to node distribution. The main thesis applies this algorithm to node redundancy enabling and disabling nodes within a dense area to preserve their life when they are unneeded. By deciding upon a cluster head for an area all other nodes move to a dormant state but coverage is maintained. If an active cluster head fails then a new cluster head will be assigned. Each cluster head emits a pheromone signal that prevents other nodes from becoming the head. To apply this to distribution, each node could emit a pheromone signal and move away from other signals within a maximum distance.

Another approach based upon the behaviour of ants in a colony has been introduced by Wang [18]. The system separates mobile nodes from the normal sensor nodes that are static. The network functions as normal on the static nodes. However if there is a need for relocation of a node, due to failure or any other cause, the mobile nodes can pick up the static nodes and travel with them to another location redeploying them there. This reduces the power and cost overheads of adding mobility to all of the nodes. The mobile nodes can carry a larger battery or travel to a charging station when not actively moving nodes.

A similar approach has been taken by Xu et al. [19] for mobile nodes with high power capacity to travel between static sensor nodes, however the mobile nodes here are for recharging the static nodes. In most cases the reason for node failure is depletion of the battery, if this is the case, being able to recharge the sensor nodes in place increases the theoretical length of network use indefinitely.

## 2.3 Metrics for evaluating self-healing WSNs

The most common metric used for evaluating recovery approaches is the distance travelled [20]. The total distance travelled is ideally minimised as excessive movement for recovery will have high power consumption. Another use of distance is average movement distance per node failure which allows comparison between multi-node and single-node recovery algorithms. Measurement of distance is trivial for simulated environments and therefore gives a good approximation of the power usage.

Another common measurement is the number of messages transmitted with regard to recovery. This shows the overhead produced by the recovery algorithm [13]. As movement and radio use have the highest power usage, measuring and minimising them will produce the system with the lowest power consumption which is the ultimate objective for most WSN implementers.

Measuring the number of nodes that have to be relocated shows the spread of power consumption across the network [15]. A larger spread means that the time until the first node fails will be increased as the load has been balanced across the nodes. This is obviously countered if nodes are moving unnecessarily.

As discussed previously, connectivity and coverage are both important to WSNs. The average node degree is a good metric for connectivity as it shows the average number of direct neighbours for each node. Coverage can be measured by the sum area of the sensing radii. Higher degrees of connectivity allow for re-routing and improve network reliability without the addition of movement, however it may be desired to reduce the degree of connectivity and thereby the density of the network so that the fewer nodes are needed and costs are lowered.

Most distribution / relocation algorithms require knowledge of the node location. Investigation into this is outside the scope of this paper, however there are many methods of obtaining location from GPS receivers to self-localisation algorithms that are well summarised by Hu and Evans [21] and Mao, Fidan, and Anderson [22].

## 2.4 Review of evaluation techniques for WSNs

When testing self-healing networks node failures must be induced, to do this a reliability function to control the failure rate of devices is needed.

## *2 Literature Review*

Lee et al. [23] analyse the failures of nodes, which are predominantly due to energy depletion.

Zhou et al. [24] investigate radio performance and integrity.

Instantaneous simulation - detecting channel collisions.

simulating Power usage

## **2.5 Conclusions**

### 3

Wireless sensor networks are used in a wide range of applications, and in recent times this is only expanding. Due to their nature of being small, low-power devices, and the common network connectivity being multi-hop routing, network drop-outs and partitioning of devices is a common problem that has been tackled in a variety of ways. There are two main approaches to network and device management for combating and fixing these issues, the distributed approach and the centralised approach.

According to Tong et al. [25] self-healing by means of mobile nodes still remains a greatly unstudied area.

The effectiveness of these two approaches is debated, however the application for a particular WSN determines the effectiveness of a particular algorithm or management paradigm. Certain use cases, for example in industrial equipment monitoring, power usage is less likely to be an important contributing factor but speed of detection and recovery might be more pressing. In an environmental monitoring situation network nodes are more likely to be physically difficult to get to once deployed, and longevity of battery power is highly important.

With these considerations, performance metrics for particular algorithms may not give a fair comparison, as algorithms optimised for low power consumption have a very different purpose to those optimised for rapid recovery. However the approaches and algorithms for communication in WSNs are still very different from traditional networking models because it is common for the network topology and availability to change often and quickly, the storage and network capacity is much lower, and wireless channels are prone to interference and drop-outs.

## Bibliography

- [1] A. Mainwaring, D. Culler, J. Polastre, R. Szewczyk, and J. Anderson, "Wireless Sensor Networks for Habitat Monitoring," *Proceedings of the 1st {ACM} International Workshop on Wireless Sensor Networks and Applications*, pp. 88—97, 2002. [Online]. Available: <http://doi.acm.org/10.1145/570738.570751>
- [2] E. S. Biagioni and K. Bridges, "The Application of Remote Sensor Technology To Assist the Recovery of Rare and Endangered Species," *International Journal of High Performance Computing Applications*, vol. 16, no. 3, pp. 315—324, 2002.
- [3] P. Juang, H. Oki, Y. Wang, M. Martonosi, L. S. Peh, and D. Rubenstein, "Energy-efficient computing for wildlife tracking," in *Proceedings of the 10th international conference on architectural support for programming languages and operating systems (ASPLOS-X) - ASPLOS '02*. New York, New York, USA: ACM Press, 2002, pp. 96—107. [Online]. Available: <http://portal.acm.org/citation.cfm?doid=605397.605408>
- [4] G. Werner-Allen, K. Lorincz, M. Welsh, O. Marcillo, J. Johnson, M. Ruiz, and J. Lees, "Deploying a wireless sensor network on an active volcano," *IEEE Internet Computing*, vol. 10, no. April, pp. 18—25, 2006.
- [5] X. Wang, G. Xing, Y. Zhang, C. Lu, R. Pless, and C. Gill, "Integrated coverage and connectivity configuration in wireless sensor networks," in *Proceedings of the first international conference on Embedded networked sensor systems - SenSys '03*. New York, New York, USA: ACM Press, 2003, pp. 28—39. [Online]. Available: <http://portal.acm.org/citation.cfm?doid=958491.958496>
- [6] N. Ding and P. X. Liu, "A Centralized Approach to Energy-Efficient Protocols for Wireless Sensor Networks," *Computer Engineering*, no. July, pp. 1636—1641, 2005.



- [7] Y.-c. Wang, C.-c. Hu, and Y.-c. Tseng, "Efficient Deployment Algorithms for Ensuring Coverage and Connectivity of Wireless Sensor Networks," *First International Conference on Wireless Internet (WICON'05)*, pp. 114—121, 2005. [Online]. Available: <http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=1509645>
- [8] K. Derr and M. Manic, "Wireless Sensor Network Configuration — Part I: Mesh Simplification for Centralized Algorithms," *IEEE Transactions on Industrial Informatics*, vol. 9, no. 3, pp. 1717—1727, aug 2013. [Online]. Available: [http://ieeexplore.ieee.org/xpls/abs\[\\_\]all.jsp?arnumber=6459011](http://ieeexplore.ieee.org/xpls/abs[_]all.jsp?arnumber=6459011)
- [9] S. Meguerdichian, F. Koushanfar, M. Potkonjak, and M. B. Srivastava, "Coverage problems in wireless ad-hoc sensor networks," *Proceedings IEEE INFOCOM 2001. Conference on Computer Communications. Twentieth Annual Joint Conference of the IEEE Computer and Communications Society (Cat. No.01CH37213)*, vol. 3, no. 4, pp. 1380—1387, 2001. [Online]. Available: <http://www.sciencedirect.com/science/article/pii/S014036640500037X>
- [10] S. Meguerdichian, F. Koushanfar, G. Qu, and M. Potkonjak, "Exposure in wireless Ad-Hoc sensor networks," *Proceedings of the 7th annual international conference on Mobile computing and networking - MobiCom '01*, pp. 139—150, 2001. [Online]. Available: <http://portal.acm.org/citation.cfm?doid=381677.381691>
- [11] S. Meguerdichian and M. Potkonjak, "Low Power o / 1 Coverage and Scheduling Techniques in Sensor Networks," Tech. Rep., 2003.
- [12] Y. Qu and S. V. Georgakopoulos, "A centralized algorithm for prolonging the lifetime of wireless sensor networks using Particle Swarm Optimization," in *WAMICON 2012 IEEE Wireless & Microwave Technology Conference*. IEEE, apr 2012, pp. 1–6. [Online]. Available: <http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=6208432>
- [13] A. A. Abbasi, K. Akkaya, and M. F. Younis, "A Distributed Connectivity Restoration Algorithm in Wireless Sensor and Actor Networks," *32nd IEEE Conference on Local Computer Networks (LCN 2007)*, pp. 496—503, 2007. [Online]. Available: <http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=4367880>

## Bibliography

- [14] K. Akkaya, A. Thimmapuram, F. Senel, and S. Uludag, "Distributed Recovery of Actor Failures in Wireless Sensor and Actor Networks," *2008 IEEE Wireless Communications and Networking Conference*, pp. 2480—2485, 2008. [Online]. Available: <http://ieeexplore.ieee.org/lpdocs/epico3/wrapper.htm?arnumber=4489467>
- [15] M. F. Younis and S. Lee, "A localized algorithm for restoring internode connectivity in networks of moveable sensors," *Computers, IEEE Transactions*, vol. 59, no. 12, pp. 1669—1682, 2010. [Online]. Available: <http://ieeexplore.ieee.org/xpls/abs{ }all.jsp?arnumber=5551121>
- [16] A. Alfadhly, U. Baroudi, and M. F. Younis, "An effective approach for tolerating simultaneous failures in wireless sensor and actor networks," *Proceedings of the first ACM international workshop on Mission-oriented wireless sensor networking*, pp. 21—26, 2012.
- [17] I. Caliskanelli, "A Bio-inspired Load Balancing Technique for Wireless Sensor Networks," Ph.D. dissertation, University of York, 2014.
- [18] Y. Wang, "Localized Ant Colony of Robots for Redeployment in Wireless Sensor Networks," Ph.D. dissertation, 2014.
- [19] W. Xu, W. Liang, X. Lin, and G. Mao, "Efficient Scheduling of Multiple Mobile Chargers for Wireless Sensor Networks," *IEEE Transactions on Vehicular Technology*, pp. 1—1, 2015. [Online]. Available: <http://ieeexplore.ieee.org/lpdocs/epico3/wrapper.htm?arnumber=7362022>
- [20] M. F. Younis, I. F. Senturk, K. Akkaya, S. Lee, and F. Senel, "Topology management techniques for tolerating node failures in wireless sensor networks: A survey," *Computer Networks*, vol. 58, pp. 254—283, 2014. [Online]. Available: <http://linkinghub.elsevier.com/retrieve/pii/S1389128613002879>
- [21] L. Hu and D. Evans, "Localization for mobile sensor networks," in *Proceedings of the 10th annual international conference on Mobile computing and networking - MobiCom '04*, no. October. New York, New York, USA: ACM Press, 2004, p. 45. [Online]. Available: <http://portal.acm.org/citation.cfm?doid=1023720.1023726>
- [22] G. Mao, B. Fidan, and B. D. Anderson, "Wireless sensor network localization techniques," *Computer Networks*, vol. 51,

- no. 10, pp. 2529–2553, jul 2007. [Online]. Available: <http://linkinghub.elsevier.com/retrieve/pii/S1389128606003227>
- [23] J.-J. Lee, B. Krishnamachari, and C.-C. J. Kuo, “Impact of energy depletion and reliability on wireless sensor network connectivity,” in *In Proceedings of the SPIE Defense and Security*, R. M. Rao, S. A. Dianat, and M. D. Zoltowski, Eds., aug 2004, pp. 169–180. [Online]. Available: <http://proceedings.spiedigitallibrary.org/proceeding.aspx?articleid=844812>
- [24] G. Zhou, T. He, S. Krishnamurthy, and J. a. Stankovic, “Impact of radio irregularity on wireless sensor networks,” *Proceedings of the 2nd international conference on Mobile systems, applications, and services*, p. 125, 2004. [Online]. Available: <http://dl.acm.org/citation.cfm?id=990064.990081>
- [25] B. Tong, Z. Li, G. Wang, and W. Zhang, “On-Demand Node Reclamation and Replacement for Guaranteed Area Coverage in Long-Lived Sensor Networks,” *Quality of Service in Heterogeneous Networks*, vol. 22, pp. 148—166, 2009.