

# RSM - Call for papers on data visualization

## Contents

<b>1</b>	<b>Front Matter</b>	<b>1</b>
<b>2</b>	<b>Abstract</b>	<b>2</b>
<b>3</b>	<b>Introduction</b>	<b>2</b>
<b>4</b>	<b>Development</b>	<b>3</b>
<b>5</b>	<b>Functionality</b>	<b>3</b>
5.1	R package . . . . .	3
5.2	Shiny web app . . . . .	5
<b>6</b>	<b>Discussion</b>	<b>5</b>
<b>7</b>	<b>Back Matter</b>	<b>6</b>
7.1	Acknowledgments . . . . .	6
7.2	Code/Data availability statement . . . . .	6
<b>8</b>	<b>Highlights</b>	<b>6</b>
<b>9</b>	<b>Tables/Figures</b>	<b>7</b>
	<b>Bibliography</b>	<b>7</b>

## 1 Front Matter

### Title:

robvis: an R package and Shiny web app for visualizing risk-of-bias assessments

### Authors and Affiliations

Luke A McGuinness<sup>1,2</sup> (ORCID: 0000-0001-8730-9761), Julian PT Higgins<sup>1,2</sup> (ORCID: 0000-0002-8323-2514)

(1) MRC University of Bristol Integrative Epidemiology Unit, Bristol, UK

(2) Bristol Medical School: Population Health Sciences, University of Bristol, Bristol, UK

### Corresponding author:

Luke McGuinness; Bristol Medical School, University of Bristol, Canynge Hall, 39 Whatley Road, Bristol, BS8 2PS, United Kingdom.; luke.mcguinness@bristol.ac.uk

### Article type

## **Funding**

LAM is supported by an NIHR Doctoral Research Fellowship (DRF-2018-11-ST2-048). Attendance at the Evidence Synthesis Hackathon in April 2019 was supported by a grant from the Evidence Synthesis Hackathon itself and the University of Bristol Alumni Foundation.

## **Keywords**

Risk of bias; Evidence synthesis; Data visualisation; R

### **1.0.0.0.1**

## **2 Abstract**

Despite a major increase in the range and number of software offerings now available to help researchers produce evidence syntheses, there is currently no generic tool for producing figures to display and explore the risk-of-bias assessments that routinely take place as part of systematic review. Fortunately, tools such as the R programming environment and **Shiny** (an R package for building interactive web apps) have made it easier than ever to produce new tools to help in producing evidence syntheses.

We present a new tool, **robvis** (Risk-Of-Bias VISualization; available as an R package and web app) which facilitates rapid production of publication-quality risk-of-bias assessment figures. We present a timeline of the tool’s development and its key functionality.

### **2.0.0.0.1**

## **3 Introduction**

Evidence synthesis, the act of drawing together all relevant studies on a defined topic, is becoming more important than ever in informing policy across an increasingly wide range of fields.<sup>1</sup> Risk of bias assessment - evaluation of the internal validity of studies included in a systematic review - often forms a key part of the evidence synthesis process, particularly in the health sciences.<sup>2</sup> A well-developed family of tools is widely used, which have in common the characteristic that they evaluate specific domains of bias rather being constructed as a checklist of a quantitative score.<sup>2</sup> These tools include the RoB 2 tool for randomized trials,<sup>3</sup> the ROBINS-I tool for non-randomized studies of interventions,<sup>4</sup> the QUADAS 2 tool for test accuracy and the ROBIS tool for systematic reviews.<sup>5</sup> Within each bias domains a judgement is reached about the strength of the study in that regard: for example, the first domain in the Cochrane RoB 2 tool deals with bias arising from the randomization process.<sup>3</sup> Accessible graphics summarizing the results of these domain-based risk-of-bias assessments are included in reports of systematic reviews. A convenient plot in many reviews is a “traffic light” plot, which tabulates the judgement for each study in each domain. For larger numbers of studies, when such a table become unmanageable, a popular alternative is a weighted bar plot, which show the proportion of information with each judgement for each domain.<sup>6</sup>

Researchers can face a number of barriers in creating these plots. While some evidence synthesis platforms, such as Cochrane’s Review Manager,<sup>7</sup> are able to produce these visualizations, not all researchers use these systems to conduct their systematic reviews, and copying the risk-of-bias data into these systems simply to produce the plots is inefficient and error prone. Likewise, creating the figures by hand, through software such

as MS PowerPoint or Adobe Illustrator, may lead to unintentional errors and require the plots to be redrawn during an (increasingly common) update to the review. Additionally, while the field of evidence synthesis software has grown rapidly in recent years,<sup>8</sup> this growth has not been equally distributed across the different aspects of the systematic review process. For example, a recent review found several software offerings aimed specifically at the abstract screening stage of the review process,<sup>9</sup> but no similar time- and error-reducing tool has been proposed for visualizing the results of risk-of-bias assessments.

Fortunately, tools such as R, RStudio and **Shiny** (an R package for building interactive web apps) have made it easier than ever to produce such a tool.<sup>10–12</sup> Here, we present **robvis** (Risk Of Bias VISualiation), an R package and **Shiny** web-app that allows users to create publication-ready risk-of-bias plots quickly and easily. Originally created for use with the major risk-of-bias assessment tools used in epidemiology, the tool allows users to visualize the results from any domain-based risk-of-bias assessment or quality appraisal tool.

The tool is open-source and available to use free of charge. Users can download a stable version of the R package from CRAN (<https://cran.r-project.org/package=robvis>); or access and contribute to the development version via GitHub (<https://github.com/mcguinlu/robvis>). Extended guidance for the tool is also available via the “Doing Meta-Analysis in R” online guide.<sup>13</sup> Below, we discuss the tools development and key functionality.

## 4 Development

Development of **robvis** began in April 2019 at the Evidence Synthesis Hackathon (ESH), an event which brings together interested researchers, practitioners and coders to discuss and develop new open-source evidence synthesis technologies. Test versions of both the R package and the web app were made available in early June 2019, with attendees of the ESH and members of the Bristol Appraisal and Review of Research (BARR) group at the University of Bristol being invited to test the tool and provide feedback. This feedback, along with other feature suggestions from the wider evidence synthesis community captured via GitHub issues, was incorporated and the first release version of the package was uploaded to CRAN in November 2019. The tool has been well received and is beginning to be cited in the evidence synthesis literature.<sup>14–18</sup>

## 5 Functionality

### 5.1 R package

#### 5.1.1 Tool templates and example data sets

At the time of writing, the tool includes templates for three major tools: the Cochrane RoB 2 tool for assessing randomised controlled trials,<sup>3</sup> the ROBINS-I tool for assessing non-randomized studies of interventions,<sup>4</sup> and the QUADAS-2 tool for assessing diagnostic accuracy studies.<sup>5</sup> These templates automatically apply the correct risk-of-bias domain names to the figures, and label the judgement levels appropriately (e.g. “Low”, “Some Concerns”, “High” in the case of the RoB 2 tool). In addition, **robvis** contains a general template that can be used to visualize the result of any domain-based assessment tool. The generic template has greater flexibility than the tool-specific templates, allowing a user-specified number of domains and custom domain titles to be used. It is suitable for use with the original version of the Cochrane risk-of-bias tool for randomized trials,<sup>19</sup> in which flexibility in the specification of domains was permitted. Since users of more recent tools such as RoB 2 and ROBINS-I are not permitted to modify the domains, we strongly encourage use of the in-built templates for these.

In order to help users familiarize themselves with the package and its functionality, **robvis** contains built-in example datasets for each template. We illustrate the example data for the RoB 2 tool for assessing risk of bias in randomized controlled trials in Table 1.

### 5.1.2 Data import and cleaning

**robvis** expects risk-of-bias summary table to be provided in a specific format (see Table 1 for an example). The first column should contain the unique study/result identifier. The second-to-last column should contain the overall risk-of-bias judgements. The final column contains the weights (e.g. study precision or the weight assigned in a meta-analysis). This weight column is used to create the summary bar plot, as current guidance recommends dividing the bars to show the proportion of information at each level of risk of bias, determined by the cumulative weight at that level, rather than simply showing the number of studies in each category.<sup>2</sup>

Once imported, **robvis** cleans the data, corrects for small spelling errors by converting each judgement to lowercase and taking only the first letter (e.g. “Seriuos” becomes “s”, avoiding a potential error from the misspelling), and converts the summary table to a long tidy format to aid in creating the plots.

### 5.1.3 Functions

**robvis** contains two main functions. The first, `rob_traffic_light()`, creates a traffic light plot by tabulating each study by each domain, providing a more detailed view of the results of the risk-of-bias assessment. The second, `rob_summary()`, creates a weighted bar plot showing the proportion of information with each judgement for each domain in the assessment tool specified.

A worked example using these functions is outlined below, showing the ease with which risk-of-bias plots can be created using **robvis**. A detailed description of the additional options that can be used with each function is presented in Table 2. All examples produced in this article are created using the stable version available from CRAN.

To install and load the package:

```
install.packages("robvis")  
  
library(robvis)
```

Using the example data set (`data_rob2`) which is built into the package and is presented in Table 1 for reference, the traffic light plot shown in Figure 1 is created using:

```
rob_traffic_light(data = data_rob2,  
                  tool = "ROB2",  
                  colour = "colourblind",  
                  psize = 15)
```

Similarly, using the same data set, the summary barplot shown in Figure 2 is created using:

```
rob_summary(data = data_rob2,  
            tool = "ROB2",  
            overall = TRUE)
```

#### 5.1.4 Further customisation

The `ggplot2` package in R, based on the “The Grammar of Graphics”, allows users to create detailed graphics using a declarative framework and was used to create the templates found in `robvis`.<sup>20,21</sup> As a result, both `robvis` functions return a `ggplot` object, meaning they can be easily customized further using the `ggplot2` framework. For example, to add a title to the summary bar plot:

```
library(ggplot2)

plot <- rob_summary(data_rob2, tool = "ROB2")

plot +
  ggtitle("Summary Bar Plot")
```

For a full discussion of the range of post-production modifications that can be made to the plots via the `ggplot2` package, we refer the reader to the extensive guidance available.<sup>21</sup>

## 5.2 Shiny web app

Although `robvis` was originally designed for use in the command-line-based R programming environment, we developed a web app to make the tool available to those without knowledge of R. This is available via [www.riskofbias.info](http://www.riskofbias.info).<sup>22</sup> The app was built using `Shiny`,<sup>12</sup> an R package which makes it easy to produce interactive web-apps, and provides a graphical user interface (GUI) for the `robvis` package, allowing users to interact with the functions presented above without the need to download R or type any commands. Users can upload their data as comma-separated values (a CSV file), choose the tool they used to perform the assessments, select a colour scheme, and define other parameters depending on whether they are producing a traffic light or summary bar plot, all through the online app.

### 5.2.0.1

## 6 Discussion

`robvis` facilitates the rapid production of two common risk-of-bias assessment figures at publication quality. By implementing `robvis` both as an R package and a `Shiny` web app, its functionality is available to evidence synthesists with varying levels of ability in R. `robvis` serves as an example of the advantages of “packaging” the R scripts that evidence synthesists often create for personal use.<sup>23</sup> It is likely that several other evidence synthesists have written scripts to produce similar risk-of-bias plots to those presented here - in fact, we personally know of at least one other research group that has done so. This duplication of time and effort is inefficient and creating and sharing well-documented R packages represents one way to reduce this inefficiency. Taking this approach one step further, `Shiny` apps represent a straightforward way to provide a user-friendly GUI for a newly created R package within a very short timeframe, expanding the potential pool of users of the package to anyone with an internet connection.

Creating a package using R has a number of particular advantages. R provides access to a range of powerful tools including the `ggplot` infrastructure as demonstrated above, and RMarkdown, which enables creation of documents that can be rendered in a range of formats such as PDF, HTML, or Word.<sup>24</sup> Furthermore, and focusing specifically on evidence synthesis, building new tools as packages in R allows for easy integration with the range of existing evidence synthesis packages. Recently, the `metaverse` project,<sup>25</sup> of which `robvis`

is a part, has begun to curate a collection of R packages that cover different aspects of the systematic review and meta-analysis process which, when taken together, form a coherent end-to-end open-source alternative to commercial offerings such as Covidence or Review Manager. Key offerings in this suite of packages include litsearcher, which facilitates systematic search strategy development, revtools, a package for managing the review process and performing title and abstract screening, metaDigitise, a package for automatic extraction of data from figures in research papers, and metafor, a package for conducting meta-analyses in R.<sup>26–29</sup>

While **robvis** is a stable package, a range of additional functionality could be added. At present, the number of tools with a specific template included in **robvis** is limited - adding additional templates is a priority. For example, a template for ROBIS, a tool for assessing risk of bias in systematic reviews, is in development.<sup>30</sup> Additionally, the tool does not yet allow for the production of paired forest plots, where the risk-of-bias judgement is presented alongside each specific result included in the meta-analysis.<sup>2</sup> This was initially considered to be beyond the scope of the tool, as it involves the visualization of something other than risk-of-bias assessments. However, following user-driven demand, this functionality is in development and will be available in the near future. Finally, we would like to add similar functionality to that provided by the `metafor::reporter()` function, which generates a brief paragraph of text describing the results of a meta-analysis. The future `robvis::reporter()` function would provide a boilerplate description of the assessment tool used and the key domains at risk of bias.

#### 6.0.0.0.1

## 7 Back Matter

### 7.1 Acknowledgments

The following people provided valuable feedback that contributed to the development of the **robvis** tool: Emily Kothe, Eliza Grames, Matthew Page, Alexandra Bannach-Brown, Kyle Hamilton, Charles Gray, Vincent Cheng, Wouter van Amsterdamn, Neal Haddaway and Martin Westgate.

### 7.2 Code/Data availability statement

The software and data presented in this paper are freely available on GitHub: <https://github.com/mcguinlu/robvis>

#### 7.2.0.0.1

## 8 Highlights

- Risk-of-bias assessment is a key element of the systematic review workflow
- No other tool exists explicitly for the purpose of visualizing risk-of-bias results
- Here we present **robvis**, an open-source R package and **Shiny** web app for creating publication-ready risk-of-bias assessment figures
- **robvis** forms part of the metaverse, a collection of R packages designed to provide an evidence synthesis workflow in R.

#### 8.0.0.0.1

Table 1: Example dataset for the ROB2 tool contained within ‘robvis‘

Study	D1	D2	D3	D4	D5	Overall	Weight
Study 1	Low	Low	Low	Low	Low	Low	33
Study 2	Some concerns	Low	Low	Low	Low	Low	33
Study 3	Some concerns	Low	Some concerns	Low	Low	Some concerns	0
Study 4	Low	Low	High	Low	Some concerns	High	9
Study 5	High	High	Low	Low	Some concerns	Low	12
Study 6	Low	High	Some concerns	Low	Low	Some concerns	25
Study 7	Low	Some concerns	Some concerns	High	Low	Some concerns	200
Study 8	Low	Some concerns	Low	Low	Low	Low	11
Study 9	Low	Low	High	Low	Low	High	1

Table 2: Description of the arguments available in the two main ‘robvis‘ functions. ‘X’ indicates that the option is available for the respective function.

Argument	“rob_traffic_light()“	“rob_summary()“	Description
data	X	X	Defines the dataframe containing the summary (domain) level risk of bias data.
tool	X	X	Defines the risk of bias assessment tool used. The RoB2 (‘tool=’)
colour	X	X	Defines the colour scheme for the plot. The default is ‘colour = ’
overall		X	Defines whether to include an additional bar showing the distribution of overall risk of bias.
weighted		X	Defines whether weights should be used to produce the summary risk of bias.
psize	X		Defines the size of the points in the traffic light plot. Default is ‘psize = 10’.

<sup>a</sup> Test

## 9 Tables/Figures

### 9.0.0.0.1

### 9.0.0.0.2

### 9.0.0.0.3

## Bibliography

1. Donnelly CA, Boyd I, Campbell P, et al. Four principles to make evidence synthesis more useful for policy. *Nature*. 2018;558(7710):361-364. doi:10.1038/d41586-018-05414-4.
2. Boutron I, Higgins JP, Altman DG, et al. Chapter 7: Considering bias and conflicts of interest among the included studies. In: Higgins JPT, Chandler J, Cumpston M, et al., eds. *Cochrane Handbook for Systematic Reviews of Interventions Version 6.0 (Updated August 2019)*. Cochrane; 2019. Available from [www.training.cochrane.org/handbook](http://www.training.cochrane.org/handbook).
3. Sterne JAC, Savović J, Page MJ, et al. RoB 2: A revised tool for assessing risk of bias in randomised trials. *BMJ*. 2019;366:l4898. doi:10.1136/bmj.l4898.
4. Sterne JAC, Hernán MA, Reeves BC, et al. ROBINS-I: A tool for assessing risk of bias in non-randomised studies of interventions. *BMJ*. 2016;355:i4919. doi:10.1136/bmj.i4919.




Figure 1: Example risk of bias traffic light plot created using 'robvis'






Figure 2: Example risk of bias summary plot created using ‘robvis’

5. Whiting PF, Rutjes AW, Westwood ME, et al. QUADAS-2: A revised tool for the quality assessment of diagnostic accuracy studies. *Ann Intern Med.* 2011;155(8):529-536. doi:10.7326/0003-4819-155-8-201110180-00009.
6. Higgins JPT, Altman DG. Chapter 8: Assessing risk of bias in included studies. In: Higgins JPT, Green S, eds. *Cochrane Handbook for Systematic Reviews of Interventions*. Wiley Online Library; 2008:187-241. doi:10.1002/9780470712184.ch8.
7. Cochrane Collaboration. Review Manager (RevMan) [Computer program]. 2014. <https://community.cochrane.org/help/tools-and-software/revman-5>.
8. Marshall C, Brereton P. Systematic review toolbox: A catalogue of tools to support systematic reviews. In: *Proceedings of the 19th International Conference on Evaluation and Assessment in Software Engineering*. EASE '15. Association for Computing Machinery; 2015:Article 23; 1-6. doi:10.1145/2745802.2745824.
9. Harrison H, Griffin SJ, Kuhn I, Usher-Smith JA. Software tools to support title and abstract screening for systematic reviews in healthcare: An evaluation. *BMC Med Res Methodol.* 2020;20(1):7. doi:10.1186/s12874-020-0897-3.
10. R Core Team. *R: A Language and Environment for Statistical Computing*. Vienna, Austria: R Foundation for Statistical Computing; 2019. <https://www.R-project.org/>.
11. RStudio Team. *RStudio: Integrated Development Environment for R*. Boston, MA: RStudio, Inc.; 2015. <http://www.rstudio.com/>.
12. Chang W, Cheng J, Allaire J, Xie Y, McPherson J. *Shiny: Web Application Framework for R*. Boston, MA; 2019. <https://CRAN.R-project.org/package=shiny>.
13. Harrer M, Cuijpers P, Ebert D. *Doing Meta-Analysis in R: A Hands-on Guide*. Erlangen, Germany: Zenodo; 2019. [https://bookdown.org/MathiasHarrer/Doing\\_Meta\\_Analysis\\_in\\_R/](https://bookdown.org/MathiasHarrer/Doing_Meta_Analysis_in_R/).
14. Gibb K, Seeley A, Quinn T, et al. The consistent burden in published estimates of delirium occurrence in medical inpatients over four decades: A systematic review and meta-analysis study. *medRxiv.* 2019:19005165. doi:10.1101/19005165.
15. Habadi MI, Asiri AA, Aloufi SA, et al. Prevalence of panic disorders in the primary health care setting: A systematic review and meta-analysis. *EC Micro.* 2019;16(1):01-09.
16. Veloso A, Vicente SG, Filipe MG. Effectiveness of cognitive training for school-aged children and adolescents with attention Deficit/Hyperactivity disorder: A systematic review. *Front Psych.* 2020;10:2983.

doi:10.3389/fpsyg.2019.02983.

17. Simillis C, Singh HKSI, Afxentiou T, et al. Postoperative chemotherapy improves survival in patients with resected high-risk stage II colorectal cancer: Results of a systematic review and meta-analysis. *Colorectal Dis.* 2020;Published online 30th January. doi:10.1111/codi.14994.
18. Tanneru K, Gautam S, Norez D, et al. Meta-analysis and systematic review of intermediate-term follow-up of prostatic urethral lift for benign prostatic hyperplasia. *Int Urol Nephrol.* February 2020. <https://doi.org/10.1007/s11255-020-02408-y>. Accessed February 24, 2020.
19. Higgins JPT, Altman DG, Gøtzsche PC, et al. The Cochrane Collaboration’s tool for assessing risk of bias in randomised trials. *BMJ.* 2011;343:d5928. doi:10.1136/bmj.d5928.
20. Wickham H. *Ggplot2: Elegant Graphics for Data Analysis*. Springer-Verlag New York; 2016. <https://ggplot2.tidyverse.org>.
21. Wilkinson L. *The Grammar of Graphics*. 2nd ed. Springer-Verlag New York; 2012.
22. McGuinness L. Robvis web application. 2019. <https://www.riskofbias.info/welcome/robvis-visualization-tool>. Accessed January 20, 2020.
23. Wickham H. *R Packages: Organize, Test, Document, and Share Your Code*. 1st ed. O’Reilly Media, Inc.; 2015. <http://r-pkgs.had.co.nz/>. Accessed February 20, 2020.
24. Xie Y, Allaire JJ, Golemund G. *R Markdown: The Definitive Guide*. Chapman and Hall/CRC; 2018. <https://bookdown.org/yihui/rmarkdown/>. Accessed February 1, 2020.
25. Various Authors. Metaverse: An R ecosystem for meta-research. 2020. <https://rmetaverse.github.io/>. Accessed February 24, 2020.
26. Grames EM, Stillman AN, Tingley MW, Elphick CS. An automated approach to identifying search terms for systematic reviews using keyword co-occurrence networks. *Methods Ecol Evol.* 2019;10:1645-1654. doi:10.1111/2041-210X.13268.
27. Viechtbauer W. Conducting meta-analyses in R with the metafor package. *J Stat Softw.* 2010;36(3):1-48. doi:10.18637/jss.v036.i03.
28. Pick JL, Nakagawa S, Noble DWA. Reproducible, flexible and high-throughput data extraction from primary literature: The metaDigitise R package. *Methods Ecol Evol.* 2018;10:426-431. doi:10.1101/247775.
29. Westgate MJ. Revtools: An R package to support article screening for evidence synthesis. *Res Syn Meth.* 2019;10:606-614. doi:10.1002/jrsm.1374.
30. Whiting P, Savović J, Higgins JPT, et al. ROBIS: A new tool to assess risk of bias in systematic reviews was developed. *J Clin Epidemiol.* 2016;69:225-234. doi:10.1016/j.jclinepi.2015.06.005.