

English	Tamil	Meanings	Buttons
<a>	<அ>	It is used to make an actual link	Enter Into WorkSpace - பணியிடத்தில் நுழையுங்கள்
<abbr>	<கருங்க>	Used with title attribute to define abbreviations.	Upload - பதிவேற்றவும்
<address>	<முகவரி>	General contact information for the website	Replace All - அனைத்தையும் மாற்று
<area>	<பரப்பு>	Establishes areas in an image map	Find - கண்டுபிடி
<article>	<ஆர்டிகிள்>	Used to contain blog entries, forum posts, etc.	New - புதியது
<aside>	<அருகில்>	This element is for making sidebars that are placed next to the main content.	Language Changer - மொழி மாற்றம்
<audio>	<ஒலி>	This Tag is used to place an audio stream within an BHAML document.	Undo - செயல்தவிர்
	<தடிமன்>	Specifies bold text without any extra importance.	Redo - மீண்டும் செய்
<base>	<அடிப்படை>	Used to set a base URL	Clear - தெளிவானது
<blink>	<பிளின்க்>	Used for quoting from an external source	Save - பதிவிறக்கம்
<bdo>	<பிடிஓ>	Specifies the direction of text display	Home - முகப்புப்பக்கம்
<bgsound>	<பின்னணிஇசை>	Specifies the background music	About - பற்றி
<blockquote>	<வெற்றுகுறிப்பு>	Used for quoting from an external source.	
<body>	<முதன்மைபகுதி>	It establishes the body of an BHAML document	
 	<பிஆர்>	Used to break line in BHAML.	
<button>	<பட்டன்>	Specifies button that can be clicked.	
<canvas>	<வளைவுவடிவம்>	Used for rendering graphics on the fly, typically in conjunction with a scripting	
<caption>	<காட்சன்>	Used for table caption.	
<cite>	<சைட்>	For citing.	
<code>	<கோட்>	Specifies a computer code text	
<col>	<கொலன்>	Specifies properties of a <col> within a.	
<colgroup>	<கொல்குறும்>	It is a group of column.	
<command>	<ஆணை>	Specifies a command the user can invoke	
<comment>	<பின்னகுறிப்பு>	Puts a comment in the document	
<datalist>	<டேட்டாலிஸ்ட்>	Together with the a new list attribute for input can be used to make comboboxes	
<dd>	<தேதி>	Specifies a definition description	
	<அழி>	Specifies deleted text	
<details>	<டிடெயில்>	Specifies additional information or controls which the user can obtain on demand.	
<dfn>	<டேபிநசன்>	Specifies a definition term	
<dialog>	<டயலாக்>	Dialog box	
<div>	<பகுதி>	A divider or a kind of generic container.	
<dl>	<டிஎல்>	Specifies a definition list.	
<dt>	<டிடி>	A term/name in a description list.	
<!DOCTYPE>	<தகவல்வகை>	Specifies the document type.	
	<எம்>	Used to define emphasized text.Content inside is typically displayed in italic.	
<embed>	<எம்பெட்>	Defines external interactive content or plugin.	
<fieldset>	<பில்ட்செட்>	Used to group related elements in a form.	
<figure>	<படம்>	It defines self contained content such as photos or diagrams.	
<footer>	<புடர்>	It is a document, below the main content.	
<form>	<படிவம்>	Forms for user input.	
<header>	<ஹெடெர்>	Represents a container for introductory content or a set of navigational links.	
<head>	<தலை>	Used mostly for metadata.	
<h1>	<எச்1>	Level 1 heading, the headline or title of a page	
<h2>	<எச்2>	Level 2 heading, the subtitles of a page	
<h3>	<எச்3>	Level 3 heading.	
<h4>	<எச்4>	Level 4 heading.	
<h5>	<எச்5>	Level 5 heading.	

<h6>	<எச்6>	Level 6 heading.	
<hgroup>	<தலைப்புஇடம்>	Used for grouping <h1>, <h2>, <h3>, etc.	
<hr>	<எச்ஆர்>	It is used for separating text within a paragraph.	
<i>	<கிழிப்பு>	Defines a part of text in an alternate voice or mood. The content inside is typically displayed in italic.	
<iframe>	<ஐபி஫்ரேம்>	Makes it possible to embed another page within a page.	
<ilayer>	<ஐலேயர்>	Specifies an inline layer	
	<இமேஜி>	It is used for displaying images on a webpage.	
<input>	<இன்புட்>	It specifies an input field where the user can enter data.	
<ins>	<இன்ஸ்>	Defines a text that has been inserted into a document. Browsers will usually underline inserted text.	
<keygen>	<கிஜன்>	Specifies control for key pair generation.	
<kbd>	<கீபோர்டு>	Specifies a keyboard text.	
<label>	<லேபுல்>	Used for assigning labels to interface elements such as forms.	
<layer>	<லேயர்>	Specifies a label for a form control.	
<legend>	<லெஜெண்ட்>	Specifies a title in a fieldset.	
	<லிஜி>	It represents a list item.	
<link>	<லிங்க்>	Used for linking to external resources.	
<main>	<பிரதான>	It encloses the main content of an BHAML document.	
<map>	<மேப்>	Used when defining an image map.	
<mark>	<மார்க்>	This is essentially used for highlighting.	
<menu>	<மெனு>	Used for creating various kinds of menus.	
<menuitem>	<மெனுஉருப்படி>	Specifies actions that can be taken with a menu.	
<meta>	<மெட்ட>	Specifies meta information.	
<meter>	<அளவு>	Specifies a measurement, such as disk usage.	
<multicol>	<மல்டிகால்>	Specifies a multicolumn text flow.	
<nav>	<நவிகேஷன்>	Used for specifying a navigational region within a document.	
<noabr>	<நோபிரேக்>	No breaks allowed in the enclosed text.	
<noembed>	<நோஎம்பெட்>	Specifies content to be presented by browsers that do not support the embed tag.	
<noscript>	<நோஸ்க்ரிப்ட்>	Specifies a noscript section.	
<object>	<ஆப்ஜெக்ட்>	Specifies an embedded object.	
	<ஓஎல்>	Ordered list (1. 2. 3.). Used with list item .	
<optgroup>	<ஆப்ட்ஓரூப்>	Specifies an option group.	
<option>	<ஆப்சன்>	Specifies an option in a drop down list.	
<output>	<அவுட்டபுட்>	Specifies some type of output, such as from a calculation done through scripting.	
<p>	<பராகிராப்>	Specifies a paragraph.	
<param>	<பராமீட்டர்>	Specifies a parameter for an object.	
<pre>	<பிரி>	This is useful for demonstrating code, especially if there are multiple lines.	
<progress>	<ப்ரோக்ரேஸ்>	It displays the progress of an action, such as with a script.	
<q>	<குடேசன்>	Quote from some source.	
<rb>	<ர்பி>	Used for for Ruby annotations.	
<ruby>	<ரூபி>	Together with rt and rp allow for marking up ruby annotations.	
<samp>	<சாம்ப்>	Specifies sample computer code.	
<script>	<ஸ்க்ரிப்ட்>	It is useful for applying styles to or around text, especially inline.	
<section>	<செகிஷன்>	Represents a generic document or application section.	
<spacer>	<ஸ்பேசர்>	Specifies a white space.	
	<ஸ்பேன்>	Specifies a section in a document.	
	<ஸ்ட்ரோங்>	Specifies strong text.	
<style>	<ஸ்டைல்>	Used for declaring style sheets within a document.	
<sub>	<ஸப்>	Used for displaying subscript. Useful for math, especially in conjunction with <sup>.	
<select>	<தேர்ந்தெடு>	Specifies a selectable list	

<summary>	<சுருக்கம்>	Used in conjunction with the <details> tag for specifying a summary.	
<sup>	<தூப்பர்ஸ்கிரிப்ட்>	Used for displaying superscript, Useful for math.	
<table>	<டேபுள்>	Used for making tables in an BHAML page.	
<tbody>	<டபாடி>	Specifies a table body.	
<td>	<டடி>	This represents a data cell within a table.	
<textarea>	<டெஸ்ட்ஏரியா>	Used for for multi-line text entry.	
<tfoot>	<டபுட்>	Table footer.	
<th>	<டெத்ச>	Table header cell.	
<thead>	<டெட்>	Table header cell.	
<time>	<டைம்>	It specifies the date/time within a document.	
<title>	<தலைப்பு>	The title of an BHAML document	
<tr>	<டிர>	A row within a table.	
	<யுஎல்>	It is used with (list item) to make unordered list	
<var>	<டெவர்>	Used to defines a variable in programming or in a mathematical expression.	
<video>	<வீடியோ>	Used for embedding video within an BHAML page.	
<wbr>	<லைனபிரேக்>	Specifies a line break opportunity.	
<html>	<பாமல்>	Specifies an html document	