
# The influence of sequence length on the clustering performance of MalPaCA

1 Background



3 Results


### **Experiment 1**

Taking 8 packets from the beginning leads to the best clustering result. The current default of 20 does not lead to successful clusters.

# Cluster -1 (N=850) Cluster 0 (N=50) Cluster 1 (N=60) Cluster 2 (N=36) 23.41 23.5 83.33 70.71 Cluster 3 (N=7) Cluster 4 (N=8) Cluster 5 (N=13) Cluster 6 (N=7) 42.86 Cluster 7 (N=7) Cluster 8 (N=11) Cluster 9 (N=7) Cluster 10 (N=8) Cluster 10 (N=8) Cluster 11 (N=7) Cluster 12 (N=76) Cluster 13 (N=9)


# **Experiment 2**

Different segments from a connection **do** represent different behaviors and they **do** lead to different clusters.



### **Experiment 5**

No systematic differences in terms of clustering results can be observed. This is likely because both the current MalPaCA definition and the "Netflow v5" definition are quite similar.




MalPaCA behavior definition

## **Experiment 3**

No sub-experiment has performed better than the threshold 8 from experiment 1. No benefit can seemingly be obtained from analysing a connection from the end or skipping packets.

### **Experiment 4**

The experiment could **not be finished** for many values due to lack of computing power. The results for the remaining values are **worse**than their equivalent from experiment 1.



"Netflow v5" behavior definition


Author: Johannes Hagspiel

Supervisors: Azqa Nadeem, Sicco Verwer

CSE3000 Research Project

26 June 2021

# 2 Experiments



# **4 MalPaCA Improvements**

The "clustering error" metric from the original paper has been improved in that it is now **automatically** generated and the user sees what the **correctly and incorrectly** clustered connections are.

