

OptaDOS: User Guide

Version 1.0

Andrew J. Morris, Rebecca J. Nicholls, Chris J. Pickard, Jonathan R. Yates

Department of Materials
University of Oxford
Parks Road
Oxford OX1 3PH
UK

and

Department of Physics and Astronomy
University College London
Gower Street
London, WC1E 6BT
UK

May 2012

Contents

1	Introduction	5
1.1	Background	5
1.2	Features	5
2	Getting Started	7
2.1	Installation	7
2.2	Usage	8
3	Parameters	9
3.1	seedname.odi File	9
3.2	General Parameters	10
3.3	DOS Parameters	13
3.4	JDOS Parameters	14
3.5	PDOS Parameters	14
3.6	Optics Parameters	15
3.7	Core-hole Parameters	16
4	Examples	19
4.1	Density of States	19
4.2	Projected Density of States	23
4.3	JDOS	25
4.4	OPTICS	26
4.5	CORE	27
5	Frequently Asked Questions	31

5.1	OPTADOS crashes complaining that it can't read the seed.bands or seed.cst_ome file.	31
5.2	The examples do not work and I'm using CASTEP version 6.0	31
5.3	I'm getting odd results for my PDOS calculation when using CASTEP version 6.0	31
5.4	I'd like OPTADOS to do X as well	32
5.5	I'd like to help, what can I do?	32
5.6	I think I've found a bug: what should I do?	32

Chapter 1

Introduction

1.1 Background

OPTADOS is a code for calculating optical, core-level excitation spectra along with full, partial and joint electronic density of states (DOS). The code was developed by merging the `LinDOS` code of Andrew Morris and Chris Pickard at University College London with the optical properties code of Rebecca Nicholls and Jonathan Yates at Oxford University. OPTADOS is written in Fortran 95 and may be run in parallel using `MPI`. At present OPTADOS interfaces with CASTEP output files, although it is extendible to perform calculations on any set of band eigenvalues and their derivatives generated by any electronic structure code.

The code is freely available through the GPL licence with the request that the following citation (quoted in full) is required in any publication resulting from the use of OPTADOS.

Andrew J. Morris, R. J. Nicholls, C. J. Pickard and Jonathan R. Yates, The OPTADOS code, Comp. Phys. Comm. (2012).

Further information and examples can be found at

www.optados.org

1.2 Features

OPTADOS generates optical, core-level excitation spectra along with full, partial and joint electronic DOS. The DOS, PDOS and JDOS take advantage of the linear and adaptive smearing schemes which are more accurate than standard Gaussian smearing since they exploit knowledge of the gradients of the bands at each k-point in the Brillouin zone. These DOS are the basis of the more advanced functionality of OPTADOS, the core and optical spectra.

Along with data text files OPTADOS also generates `.agr` files of results to be read by `grace`.

Chapter 2

Getting Started

2.1 Installation

OPTADOS is usually obtained in a gzipped tarball, `optados-X.X.tar.gz`. Extract this (`tar -xzf optados-X.X.tar.gz`) in the desired directory. Inside the `optados/` directory are a number of sub directories, `documents/`, `examples/`. The code may be compiled using the Makefile in the `optados/` directory. The `SYSTEM`, `BUILD`, `COMMS_ARCH` and `PREFIX` flags must be set, either in the Makefile, or from the command line (for example `make BUILD=fast`).

2.1.1 SYSTEM

Choose which compiler to use to make OPTADOS. The valid values are:

- `g95` (default)
- `gfortran`
- `ifort`
- `nag`
- `pathscale`
- `pgf90`
- `sun`

2.1.2 BUILD

Choose the level of optimisations required when making OPTADOS. The valid values are:

- `fast` (default) All optimisations
- `debug` No optimisations, full debug information

2.1.3 COMMS_ARCH

Whether to compile for serial or parallel execution. The valid values are:

- `serial` (default)
- `mpi`

2.1.4 PREFIX

Choose where to place the OPTADOS binary. The default is the OPTADOS directory.

2.2 Usage

```
optados.x86_64 [seedname]
```

- **seedname**: If a seedname string is given the code will read its input from a file `seedname.odi`. The default value is `CASTEP`.

Chapter 3

Parameters

3.1 seedname.odi File

The OPTADOS input file `seedname.odi` has a flexible free-form structure.

The ordering of the keywords is not significant. Case is ignored (so `smearing_width` is the same as `Smearing_Width`). Characters after `!`, or `#` are treated as comments. Most keywords have a default value that is used unless the keyword is given in `seedname.odi`. Keywords may be set in any of the following ways

```
smearing_width = 0.4
smearing_width : 0.4
smearing_width 0.4
```

A logical keyword can be set to `.true.` using any of the following strings: `T`, `true`, `.true..`

3.2 General Parameters

3.2.1 `character(len=20) :: task`

Tells the code what to compute.

The valid options for this parameter are:

- `dos` (default)
- `compare_dos`
- `compare_jdos`
- `jdos`
- `pdos`
- `optics`
- `core`
- `all`

Several tasks can be specified *e.g.* to compute dos and jdoss use `task : dos jdoss`. However, the `compare_dos` and `compare_jdos` tasks can only be combined with each other, and no additional tasks. `compare_dos` and `compare_jdos` calculate the DOS and JDOS respectively using all broadening schemes. It is good practice to check the quality of the underlying DOS before other tasks are requested.

3.2.2 `character(len=50) :: broadening`

Specified the scheme used to broaden a discrete sampling of the Brillouin Zone to a continuous spectral function.

The valid options for this parameter are:

- `adaptive` (default)
- `fixed`
- `linear`
- `quad` (not currently implemented)

3.2.3 `integer :: iprint`

This indicates the level of verbosity of the output from 1, the bare minimum: 2, with progress reports: to 3, which corresponds to full debugging output.

The default value is 1.

3.2.4 `character(len=20) :: energy_unit`

The energy unit to be used for writing quantities in the output files.

The valid options for this parameter are:

- `eV` (default)
- `Ry`
- `Ha`

3.2.5 `logical :: legacy_file_format`

- `TRUE` Read CASTEP input compatible with versions < 6.0.
- `FALSE` (Default) Read CASTEP input compatible for use with CASTEP versions 6.0+ and generated with the castep spectral task.

3.2.6 `real(kind=dp) :: adaptive_smearing`

Set the relative smearing in the adaptive scheme.

Default value is 0.4

3.2.7 `real(kind=dp) :: fixed_smearing`

Smearing width for fixed broadening.

If `spectral_scheme = fixed` default value is 0.3eV.

3.2.8 `character(len=20) :: efermi`

Choose which Fermi energy to use.

The valid options for this parameter are:

- `optados` (default) OPTADOS recalculates the Fermi energy by performing a DOS calculation.
- `file` Take the value from the output of the ab-initio calculation.
- `insulator` Assume that the material is an insulator and counts filled bands to find the Fermi energy.
- `<real number>` User supplied value.

The default value is `optados`.

3.2.9 `character(len=20) :: output_format`

Format in which to output data.

The valid options for this parameter are:

- `gnuplot`
- `grace` (default)

3.2.10 `logical :: finite_bin_correction`

Force each Gaussian to be larger than a single energy bin. (Useful for adaptive smearing and semi-core states when `numerical_intdos=TRUE`).

Default value `TRUE`.

3.2.11 `logical :: numerical_intdos`

Calculate the integrated dos by numerical integration instead of semi-analytically. (Useful for comparison with `LinDOS`.)

Default value `FALSE`.

3.2.12 `logical :: hybrid_linear`

Switch from linear broadening scheme to adaptive broadening when band gradient less than `hybrid_linear_grad_tol`. This allows for a good description of very flat bands such as defect and semi-core states. May also be used in conjunction with `finite_bin_correction` further improving the DOS and band energy

Default value `FALSE`.

3.2.13 `real(kind=dp) :: hybrid_linear_grad_tol`

Tolerance for switching from linear to adaptive broadening when using `hybrid_linear` option.

The default value is $0.01\text{eV}/\text{\AA}$.

3.2.14 `character(len=50) :: devel_flag`

Not a regular keyword. Its purpose is to allow a developer to pass a string into the code to be used inside a new routine as it is developed.

No default.

3.3 DOS Parameters

3.3.1 `logical :: compute_band_energy`

Compute the band energy by summing bands both using CASTEP's eigenvalue and OPTA-DOS's density of states.

Default value TRUE.

3.3.2 `logical :: compute_band_gap`

Compute the optical, thermal and average band gap.

Default value FALSE.

3.3.3 `logical :: dos_per_volume`

Present DOS per simulation cell volume.

Default value FALSE.

3.3.4 `real(kind=dp) :: dos_min_energy`

Lower energy range for DOS and related properties.

Default value is 5eV below the lowest eigenvalue in the bands file.

3.3.5 `real(kind=dp) :: dos_max_energy`

Upper energy range for DOS and related properties.

Default value is 5eV above the highest eigenvalue in the bands file.

3.3.6 `real(kind=dp) :: dos_nbins`

Instead of setting a Default value `dos_spacing` the total number of DOS bins may be given. (Useful for comparison with LinDOS.)

3.3.7 `real(kind=dp) :: dos_spacing`

Resolution at which to compute the DOS and related properties.

Default value is 0.1eV

3.3.8 `logical :: set_efermi_zero`

Shift energy scales so that the Fermi energy is at 0.

Default value FALSE.

3.4 JDOS Parameters

3.4.1 `real(kind=dp) :: jdoss_max_energy`

Upper energy range for JDOS and related properties.

Default value is the difference between the valence band maximum (or Fermi level) and the highest eigenvalue in the bands file.

3.4.2 `real(kind=dp) :: jdoss_spacing`

Resolution at which to compute the DOS and related properties.

Default value is 0.01eV.

3.4.3 `real(kind=dp) :: scissor_op`

Value of the scissor operator.

Default value is 0eV (*i.e.* not used)

3.4.4 `real(kind=dp) :: exclude_bands`

This allows a list of bands which are NOT to be included in the JDOS or OPTICS calculation to be specified. The bands 1, 2, 4, 5, 6, for example, can be specified using `exclude_bands = 1,2,4-6`.

3.5 PDOS Parameters

3.5.1 `character :: pdos`

Defines which components to include in the pdos analysis:

- `angular` (decompose as s,p,d *etc.*)
- `species` (decompose onto atomic species C, H *etc.*)
- `sites` (decompose onto atomic sites C1, H1, H2 *etc.*)

- `species_ang` (decompose onto angular momentum channels and species Cs, Cp *etc.*)
- `C:H` (decompose onto Carbon and Hydrogen sites)
- `C1:C3:C4-C8` (decompose onto atoms C1, C2 and C4,C5,C6,C7,C8)
- `Si1[s;d]` (decompose onto 's' and 'd' channels for atom Si1)
- `sum:C1:C3:C4-C8` (decompose onto atoms C1, C2 and C4,C5,C6,C7,C8 and combine into the single projection)

3.6 Optics Parameters

3.6.1 `character(len=20) :: optics_geom`

Specifies the geometry for the optics calculation. Possible options:

- `polycrystalline` (Isotropic average)
- `polarized`
- `unpolarized`
- `tensor` (Full dielectric tensor)

The default is polycrystalline.

3.6.2 `real(kind=dp) :: optics_qdir(3)`

Direction of polarisation. Must be specified if `optics_geom = polarized` or `optics_geom = unpolarized`.

There is no default value

3.6.3 `logical :: optics_intraband`

If true, the intraband contribution to the dielectric function will be calculated. (Important for metals.)

The default is FALSE.

3.6.4 `real(kind=dp) :: optics_drude_broadening`

Value of broadening included in the Drude term expressed in s^{-1} .

The default value is 1E-14.

3.6.5 `real(kind=dp) :: optics_lossfn_broadening`

FWHM of Gaussian used to broaden the loss function.

The default value is 0 (*i.e.* no broadening is used).

3.7 Core-hole Parameters

3.7.1 `character(len=20) :: core_type`

Determines if we want absorption (transition from core to conduction ELNES / XANES) or emission (transition from valence to core XAS). It is also possible to plot both.

- `absorption` (default)
- `emission`
- `all`

3.7.2 `character(len=20) :: core_geom`

Specifies the geometry for the core-spectra calculation. Possible options:

- `polycrystalline` (Isotropic average)
- `polarized`

The default is polycrystalline.

3.7.3 `real(kind=dp) :: core_qdir(3)`

Direction of polarisation. Must be specified if `core_geom = polarized`.

There is no default value.

3.7.4 `logical :: core_LAI_broadening`

Include life-time and instrumentation broadening.

The default is FALSE.

3.7.5 `real(kind=dp) :: LAI_gaussian_width`

FWHM of Gaussian function used to broaden spectrum.

The default value, if `core_LAI_broadening = true`, is 0 (*i.e.* no Gaussian used).

3.7.6 `real(kind=dp) :: LAI_lorentzian_width`

FWHM of fixed Lorentzian function used to broaden spectrum.

The default value, if `core_LAI_broadening = true`, is 0 (*i.e.* no fixed Lorentzian used).

3.7.7 `real(kind=dp) :: LAI_lorentzian_scale`

Variation of Lorentzian function with energy i.e. the width of the Lorentzian is (energy above the Fermi level x `core_lorentzian_scale`). If set to zero, no energy dependent broadening is included. If `core_lorentzian_scale` and `core_lorentzian_width` are both specified, the total width of the Lorentzian used will be `core_lorentzian_width` + (energy above the Fermi level x `core_lorentzian_scale`).

The default value, if `core_LAI_broadening = true`, is 0.1.

3.7.8 `real(kind=dp) :: LAI_lorentzian_offset`

Energy (in eV) above the Fermi level that the energy dependent broadening starts.

The default value, if `core_LAI_broadening = true`, is 0.

Chapter 4

Examples

Each example in the `examples/` directory contains example CASTEP input files and a sample OPTADOS input file. To keep the OPTADOS distribution light CASTEP output files for the examples have not been provided. You need to run CASTEP on the CASTEP input files before running OPTADOS on the examples.

4.1 Density of States

- *Outline* : This is a simple example of using OPTADOS for calculating electronic density of states of crystalline silicon in a 2 atom cell.
 - *Input Files*:
 - `examples/Si2_DOS/Si2_dos.cell` - The CASTEP cell file containing information about the simulation cell.
 - `examples/Si2_DOS/Si2_dos.param` - The CASTEP param file containing information about the parameters for the SCF and spectral calculations.
 - `examples/Si2_DOS/Si2_dos.odi` - The OPTADOS input file, containing the parameters necessary to run OPTADOS.
1. Perform a CASTEP calculation on the bulk silicon using the `Si2_dos.cell` and `Si2_dos.param` input files.

```
$ castep Si2
```

This should take a couple of seconds to run. More help can be found in the tutorials on the CASTEP website www.castep.org.
 2. Perform an OPTADOS calculation. Add `LEGACY_FILE_FORMAT : true` in the `Si2_DOS.odi` input file, if the CASTEP version you are using is before 6.0. Then execute:

```
$ optados.<SYSTEM>.<BUILD>.<COMMS_ARCH>.x86_64 Si2
```

This generates 3 files:

- `Si2.odo` – OPTADOS general output file.
 - `Si2.adaptive.dat` – The adaptive broadened DOS raw output data.
 - `Si2.adaptive.agr` – The adaptive broadened DOS in a file suitable to be plotted by `xmgrace`.
3. Open the `Si2.odo` file in a text editor (*e.g.* `vi` or `emacs`). OPTADOS has performed a Density of States calculation.

```
+----- Fermi Energy Analysis -----+
| From Adaptive broadening                |
| Spin Component : 1 occupation between    3.99961 and    4.00003    <- 0c |
| Spin Component : 2 occupation between    3.99961 and    4.00003    <- 0c |
| Fermi energy (Adaptive broadening) :    5.4109 eV                <- EfA |
+-----+
```

It has used the integrated DOS to work out the Fermi level, and has suggested the error in the integration by indicating the number of electrons at the Fermi level. Since we had 4 up electrons and 4 down in the input file this analysis seems satisfactory.

```
+----- Electronic Data -----+
| Number of Bands                :          23                |
| Grid size                      :        10 x 10 x 10         |
| Number of K-points             :          110                |
| Spin-Polarised Calculation      :           True             |
| Number of up-spin electrons     :           4.00             |
| Number of down-spin electrons   :           4.00             |
+-----+
```

Since we had `efermi : optados`, OPTADOS sets the internal value of the Fermi level to the one it has derived from the DOS. This is important for subsequent calculations. Other valid options are `file`, where OPTADOS uses the value calculated by the electronic structure code that generated the eigenvalues; `insulator`, where OPTADOS uses a value calculated from assuming the system is non-metallic; or a value set by the user.

OPTADOS now performs some analysis of the DOS at the Fermi level,

```
+----- DOS at Fermi Energy Analysis -----+
| Fermi energy used :    5.4109 eV                |
| From Adaptive broadening                |
| Spin Component : 1  DOS at Fermi Energy :    0.0011 eln/cell    <- DEA |
| Spin Component : 2  DOS at Fermi Energy :    0.0011 eln/cell    <- DEA |
+-----+
```

From this we may assume that there is a band gap.

Importantly, then OPTADOS calculates the band energy from the DOS is has calculated.

```

+----- Band Energy Analysis -----+
|          Band energy (Adaptive broadening) :          1.3609 eV          <- BEA |
|          Band energy (From CASTEP) :          1.3622 eV          <- BEC |
+-----+

```

As the quality of the OPTADOS calculation is increased these two values should converge to the same answer.

Finally OPTADOS shifts the Fermi level to 0 eV, for the output files.

4. The DOS is outputted to `Si2.adaptive.dat`. This contains 5 columns as described in the header of the file:

```

#####
#
#               O p t a D O S   o u t p u t   f i l e
#
#   Density of States using adaptive broadening
#   Generated on 12 Feb 2012 at 16:50:37
# Column      Data
#   1          Energy (eV)
#   2          Up-spin DOS (electrons per eV)
#   3          Down-spin DOS (electrons per eV)
#   4          Up-spin Integrated DOS (electrons)
#   5          Down-spin Integrated DOS (electrons)
#
#####

```

This file can be plotted by your favourite graph-plotting software. However, OPTADOS has made things easy and generated a `Si2.adaptive.agr` file which is directly plottable using `xmgrace` as shown in Fig. 4.1.

```
$ xmgrace Si2.adaptive.agr.
```

5. We now try again with a better sampling of the DOS, by setting `DOS_SPACING : 0.001` and also analyse the band gap, by setting `COMPUTE_BAND_GAP : true`. You can remove all of the OPTADOS output files by using `./tools/optados_clean` in your working directory. If you have a parallel version of OPTADOS compiled, now might be the time to try it out, if not, the serial version will be fine, but just take a bit longer. You can set `IPRINT : 2` to see a progress report in `Si2.odo`. In parallel:

```
$ mpirun -np <nprocs> optados.SYSTEM.BUILD.COMMS_ARCH.x86_64 Si2
```

but your MPI implementation may be different.

6. In `Si2.odo` we now have a new section analysing the band gap in various ways.

```

+----- Bandgap Analysis -----+
|          Number of kpoints at          VBM          CBM          |
|          Spin :   1   :           1           1           |
|          Spin :   2   :           1           1           |
+-----+

```




Figure 4.1: Density of States of Silicon generated by adaptive broadening and a very coarse energy sampling of 0.1 eV.

Thermal Bandgap :	0.6676272107	eV	<- TBg
Between VBM kpoint :	0.05000	0.05000	0.05000
and CBM kpoint:	-0.45000	-0.05000	-0.45000
==> Indirect Gap			

Optical Bandgap			
Spin : 1 :	2.5542517447	eV	<- OBg
Spin : 2 :	2.5542463024	eV	<- OBg
Number of kpoints with this gap			
Spin : 1 :	1		
Spin : 2 :	1		

Average Bandgap			
Spin : 1 :	3.8121372691	eV	<- ABg
Spin : 2 :	3.8121342659	eV	<- ABg
Weighted Average :	3.8121357675	eV	<- wAB

OPTADOS is very careful in its band gap analysis. It uses the bare eigenvalues (unbroadened) and works out the nature and size of the thermal gap, optical gap and the average gap over all of the Brillouin zone. In cases of multi-valleyed semiconductors OPTADOS will report the number of conduction band minima or valence band maxima with identical energies, but will not report the nature of the gap.

Increasing the number of integration points has improved the band energy of the adaptive smearing:

Band energy (Adaptive broadening) :	1.3623	eV	<- BEA
-------------------------------------	--------	----	--------

7. Now set `TASK : compare_dos` and re-run OPTADOS. OPTADOS will calculate DOS using all the broadening methods, this is good practice to see whether the broadening widths are appropriate before more advanced tasks are carried out, such as Joint-DOS, core and optical calculations.

Plotting the linear broadened DOS over the adaptive we see that the default adaptive broadening is appropriate,

```
xmgrace Si2.adaptive.agr -nxy Si2.linear.dat
```

Linear broadening, although a massive improvement over fixed broadening, sometimes appears noisy if used with very low numbers of k-points. Linear and adaptive DOS should be compared and `ADAPTIVE_SMEARING` may be tuned by eye until the adaptive DOS contains the features of the linear DOS, but with less noise. Adding a random shift to a k-point mesh can greatly increase the quality of the DOS, especially if the k-point set contained the Γ -point. It generally pays off in computational time to have a coarse mesh at low symmetry points, than a fine mesh centred on high symmetry points.

Both fixed and adaptive broadening can fail to plot the sharpest features, such as semi-core states, if the bin widths are too broad. These sharp features may be forced to be present using the narrowest Gaussian still reproducible by the chosen bin widths by setting `FINITE_BIN_CORRECTION : true`.

Linear broadening may also be improved by using `HYBRID_LINEAR : true`. Van Hove singularities and other sharp features are now described at the adaptive broadening level if the bands are flatter than `HYBRID_LINEAR_GRAD_TOL`. Hybrid linear may also take advantage of the finite bin correction if required.

8. Compare the fixed and adaptive DOS and see the advantage of adaptive broadening over standard Gaussian smearing.

4.2 Projected Density of States

We assume the reader is familiar with the previous section on Density of States calculations and is now familiar with choosing broadening widths, and running OPTADOS.

- *Outline* : This is a simple example of using OPTADOS for calculating electronic density of states of 2 atoms of crystalline silicon projected onto LCAO basis states.
- *Input Files*:
 - `examples/Si2_PDOS/Si2_dos.cell` - The CASTEP cell file containing information about the simulation cell.
 - `examples/Si2_PDOS/Si2_dos.param` - The CASTEP param file containing information about the parameters for the SCF and spectral calculations.
 - `examples/Si2_PDOS/Si2_dos.odi` - The OPTADOS input file, containing the parameters necessary to run OPTADOS.

1. Choose a broadening scheme for the projected-DOS calculation and test using `TASK : compare_dos` as explained in the previous example. Checking that the `DOS_SPACING` is sufficiently fine for the band energies to match.
2. Once the DOS looks suitable, switch to `TASK : pdos`. We choose to decompose the DOS into angular momentum channels (`PDOS : angular`) and as in the previous example we choose to recalculate the Fermi level using the calculated DOS, rather than use the Fermi level suggested by CASTEP.
3. Execute OPTADOS.
4. The output can be found in `Si2.pdos.dat`.

```
#####
#
#               O p t a D O S   o u t p u t   f i l e
#
#  Generated on 13 Feb 2012 at 10:15:10
#####
#-----+
#|               Partial Density of States -- Projectors               |
#-----+
#| Projector:      1 contains:                                         |
#|           Atom           AngM Channel                             |
#|           Si    1           s                                     |
#|           Si    2           s                                     |
#-----+
#| Projector:      2 contains:                                         |
#|           Atom           AngM Channel                             |
#|           Si    1           p                                     |
#|           Si    2           p                                     |
#-----+
#| Projector:      3 contains:                                         |
#|           Atom           AngM Channel                             |
#|           Si    1           d                                     |
#|           Si    2           d                                     |
#-----+
#| Projector:      4 contains:                                         |
#|           Atom           AngM Channel                             |
#|           Si    1           f                                     |
#|           Si    2           f                                     |
#-----+
```

The header shows that there are four projectors described below. The first containing the s-channels of both silicon atoms, the second the p-channels *etc*.

5. The output is easily plotted using `xmgrace`:

```
xmgrace -nxy Si2.pdos.dat
```





Figure 4.2: Density of States of Silicon generated by adaptive broadening projected onto LCAO momentum states.

6. Setting `DOS_SPACING` : 0.001 gives a high quality plot, as shown in Fig 4.2

7. Other things to try are:

- `PDOS : Si1;Si2(s)` – Output the PDOS on Si atom 1 and the PDOS on the s-channel of Si atom 2. (Resulting in two projectors)
- `PDOS : sum:Si1-2(s)` – Output the sum of the s-channels on the two Si atoms. (Resulting in one projector)
- `PDOS : Si1(p)` – Output the p-channel on Si atom 1. (Resulting in one projector)

4.3 JDOS

See `examples/Si2_JDOS/`. This is a simple example of using OPTADOS for calculating joint electronic density of states. We choose to recalculate the Fermi level using the calculated DOS, rather than use the Fermi level suggested by CASTEP and so `EFERMI: OPTADOS` is included in the `Si2.odi` file.

1. Execute OPTADOS using the example files. The JDOS is outputted to `Si2.jadaptive.dat`. A file suitable for plotting using `xmgrace` is written to `Si2.jadaptive.agr`.
2. Check the effect of changing the sampling by increasing and decreasing the value of `JDOS_SPACING` in the `Si2.odi` file.
3. If `TASK : compare_jdos` is used instead, OPTADOS will calculate the JDOS using all the broadening methods. This is good practice to see whether the broadening widths are appropriate before more advanced tasks are carried out.

4.4 OPTICS

Two sets of example files are provided for calculations of optical properties. For each example, the CASTEP files containing all the cell and simulation parameters are included, along with an OPTADOS input file. We assume that the reader is familiar with the previous sections on DOS and JDOS.

- `examples/Si2_OPTICS/` This is a simple example of using OPTADOS to calculate the optical properties of crystalline silicon, which is an insulator.
- `examples/Al_OPTICS/` This is a simple example of using OPTADOS to calculate the optical properties of a metal, aluminium.

4.4.1 Silicon

1. Choose a broadening scheme for the JDOS as explained in the JDOS example. Once the JDOS looks suitable, switch the `task` from JDOS to OPTICS and execute OPTADOS to calculate the optical properties. Several `*.dat` files are produced:

- `Si2_OPTICS_absorption.dat` : This file contains the absorption coefficient (second column) as function of energy (first column).
- `Si2_OPTICS_conductivity.dat` : This file contains the conductivity outputted in SI units (Siemens per metre). The columns are the energy, real part and imaginary part of the conductivity respectively.
- `Si2_OPTICS_epsilon.dat` : This file contains the dielectric function. The columns are the energy and real and imaginary parts of the dielectric function respectively. The file header also includes the result of the sum rule $\int_0^{\omega'} \text{Im}\epsilon(\omega) d\omega = N_{eff}(\omega')$. N_{eff} is the effective number of electrons contributing to the absorption process, and is a function of energy.
- `Si2_OPTICS_loss_fn.dat` : This file contains the loss function (second column) as a function of energy (first column). The header of the file shows the results of the two sum rules associated with the loss function $\int_0^{\omega'} \text{Im}\left(\frac{-1}{\epsilon(\omega)}\right) \omega d\omega = N_{eff}(\omega')$ and $\int_0^{\omega'} \text{Im}\left(\frac{-1}{\epsilon(\omega)}\right) \frac{1}{\omega} d\omega = \frac{\pi}{2}$.
- `Si2_OPTICS_reflection.dat` : This file contains the reflection coefficient (second column) as a function of energy (first column).
- `Si2_OPTICS_refractive_index.dat` : This file contains the refractive index. The columns are the energy and real and imaginary parts of the refractive index respectively.

Corresponding `*.agr` files are also generated which can be plotted easily using `xmgrace`.

2. Change parameters `JDOS_SPACING` and `JDOS_MAX` and check the effect on the optical properties. Note: all of the other optical properties are derived from the dielectric function.

3. The OPTADOS input file has been set up to calculate the optical properties in the polycrystalline geometry (`optics_geom = polycrystalline`). It is possible to calculate either polarised or unpolarised geometries, or to calculate the full dielectric tensor. To calculate the full dielectric tensor set `optics_geom = tensor`. This time only the file `Si2_OPTICS_epsilon.dat` is generated. The format of this file is the same as before (the columns are the energy and the real and imaginary parts of the dielectric function respectively), but this time the six different components of the tensor are listed sequentially in the order ϵ_{xx} , ϵ_{yy} , ϵ_{zz} , ϵ_{xy} , ϵ_{xz} and ϵ_{yz} .
4. Additional broadening can be included in the calculation of the loss function. This is done by including the keyword `optics_lossfn_broadening` in the OPTADOS input file. If you include this keyword and re-run OPTADOS, you will find that the file `Si2_OPTICS_loss_fn.dat` now has three columns. These are the energy, unbroadened spectrum and broadened spectrum respectively.

4.4.2 Aluminium

1. As for the silicon example, a broadening scheme for the JDOS should first be determined.
2. Aluminium is a metal so we need to include both the interband and intraband contributions to the dielectric function. To include the intraband contribution `optics_intraband = true` must be included in the OPTADOS input file. When you run OPTADOS the same files are generated as when only the interband term is included.

The `Al_OPTICS_epsilon.dat` file has the same format as before, but it now contains sequentially the interband contribution, the intraband contribution and the total dielectric function. (The file `Al_OPTICS_epsilon.agr` only contains the interband term.) In the same way, `Al_OPTICS_loss_fn.dat` contains the interband contribution, intraband contribution and total loss function. All other optical properties are calculated from the total dielectric function and the format of the output files remains the same.

3. In the case where the dielectric tensor is calculated and the intraband term is included, only the `Al_OPTICS_epsilon.dat` file is generated. As before it contains each component, but this time it lists sequentially the interband contribution, intraband contribution and total dielectric function for each component.
4. This time, if additional broadening for the loss function is included by using the keyword `optics_lossfn_broadening`, `Al_OPTICS_loss_fn.dat` will contain four sequential data sets. These are the interband contribution, the intraband contribution, the total loss function without the additional broadening and the broadened total loss function.

4.5 CORE

See `examples/Si2_CORE/`. This is a simple example of using OPTADOS for calculating core level absorption spectra for crystalline silicon. We assume that the reader is familiar with the previous section on calculating DOS.

1. We begin by running a CASTEP calculation using the files provided in `examples/Si2_CORE`. Note that we do not specify pseudopotentials in the `Si2_CORE.cell` file hence require CASTEP to generate on-the-fly pseudopotentials. This is important as most pseudopotential formats do not contain enough information for the PAW reconstruction needed for a CORE calculation. For any atom a CORE spectra is to be calculated an On-the-fly pseudopotential must be used.

Execute OPTADOS using the OPTADOS input file provided and the file `Si2_CORE_core_edge.dat` will be created. The file contains two columns, the first is the energy and the second is the spectrum. This file contains the following edges:

```
# Si 1    K1
# Si 1    L1
# Si 1    L2,3
# Si 2    K1
# Si 2    L1
# Si 2    L2,3
```

i.e. all edges from all atoms are produced.

2. To include a core-hole in the calculation, first one atom is chosen to have the excitation. To begin, we will keep two atoms in the unit cell and distinguish one atom by changing the `%BLOCK POSITIONS_FRAC`

```
%BLOCK POSITIONS_FRAC
      Si:exi    0.0000000000    0.0000000000    0.0000000000
      Si        0.2500000000    0.2500000000    0.2500000000
%ENDBLOCK POSITIONS_FRAC
```

in the `Si2_CORE.cell` file. The atom `Si:exi` is the one to have a core-hole. To create a core-hole we remove a 1s electrons from the electronic configuration used in the generation of the pseudopotential. We have already generated an on-the-fly pseudopotential without a core-hole in the previous section. Information about the pseudopotentials is included at the top of the `Si2_CORE.castep` file.

```
=====
| Pseudopotential Report - Date of generation 16-05-2012 |
|-----|
| Element: Si Ionic charge: 4.00 Level of theory: LDA |
| |
|               Reference Electronic Structure |
|   Orbital      Occupation      Energy |
|   3s            2.000         -0.400 |
|   3p            2.000         -0.153 |
| |
|               Pseudopotential Definition |
|   Beta    1      e      Rc      scheme  norm |
```

```

|          1          0   -0.400   1.797   qc       0          |
|          2          0    0.250   1.797   qc       0          |
|          3          1   -0.153   1.797   qc       0          |
|          4          1    0.250   1.797   qc       0          |
|         loc         2    0.000   1.797   pn       0          |
|
| Augmentation charge Rinner = 1.298
| Partial core correction Rc = 1.298
|-----|
| "2|1.8|1.8|1.3|2|3|4|30:31:32LGG(qc=4)"
|-----|
|           Author: Chris J. Pickard, Cambridge University
|=====|

```

The line

```
2|1.8|1.8|1.3|2|3|4|30:31:32LGG(qc=4)
```

specifies the parameters used to create the pseudopotential. We use this as the starting point and then remove one of the core 1s electrons to create a core-hole pseudopotential. This is done by including `{1s1.00}` in the pseudopotential string as shown:

```
2|1.8|1.8|1.3|2|3|4|30:31:32LGG{1s1.00}(qc=4)
```

If, instead of removing a 1s electron, we wanted to remove a 2s electron from the core, we would have included `{2s1.00}` instead of `{1s1.00}` in the pseudopotential string.

We are only interested in the spectra from the atom with the core-hole and so copy the pseudopotential file generated by the previous calculation (`Si_OFT.usp`) to `Si_LDA.usp`. Then include

```

%BLOCK SPECIES_POT
  Si:exi  2|1.8|1.8|1.3|2|3|4|30:31:32LGG{1s1.00}(qc=4)
  Si      Si_LDA.usp
%ENDBLOCK SPECIES_POT

```

in the CASTEP `Si2_CORE.cell` file.

To maintain the neutrality of the cell, we include

```
CHARGE : +1
```

in the `Si2_CORE.param` file. Run the calculation. This time the `Si2_CORE_core_edge.dat` file will contain only the edges from the core-hole atom. Compare the K-edge from the core-hole calculation with the previous non-core-hole calculation.

3. The periodic images of the core-hole will interact with one another. As this is unphysical, we need to increase the distance between the core-holes. This is done by creating a supercell. To start with we use a face-centred unit cell rather than the primitive unit cell. This is done by changing the lattice parameters and fractional co-ordinates to:

```

%BLOCK LATTICE_CART
    5.46  0.00  0.00
    0.00  5.46  0.00
    0.00  0.00  5.46
%ENDBLOCK LATTICE_CART

%BLOCK POSITIONS_FRAC
    Si:exi  0.0000000000  0.0000000000  0.0000000000
    Si      0.5000000000  0.5000000000  0.0000000000
    Si      0.5000000000  0.0000000000  0.5000000000
    Si      0.0000000000  0.5000000000  0.5000000000
    Si      0.2500000000  0.2500000000  0.2500000000
    Si      0.7500000000  0.2500000000  0.7500000000
    Si      0.2500000000  0.7500000000  0.7500000000
    Si      0.7500000000  0.7500000000  0.2500000000
%ENDBLOCK POSITIONS_FRAC

```

Run OPTADOS and compare the spectrum from the face-centred unit cell with that from the primitive unit cell. Continue constructing larger unit cells until the core-hole spectrum stops changing with increasing separation between the periodic images.

4. Other things to try include

- Changing the geometry from polycrystalline to polarised
- Including life-time and instrumentation broadening

Chapter 5

Frequently Asked Questions

5.1 OptaDOS crashes complaining that it can't read the seed.bands or seed.cst_ome file.

Which version of CASTEP are you using? See Sect. 3.2.5.

5.2 The examples do not work and I'm using castep version 6.0

CASTEP version 6.0 was released during the transition of the spectral module and features. The easiest way to solve this is to obtain a copy of CASTEP > 6.0, where OPTADOS will work "out of the box". However, to make the examples work with CASTEP 6.0 the OPTADOS examples require a few tweaks outlined below.

- Replace SPECTRAL_KPOINTS_MP_GRID in the cell file with BS_KPOINTS_MP_GRID and OPTICS_KPOINTS_MP_GRID.
- Remove SPECTRAL_TASK : DOS from the param file.
- Add DEVEL_FLAG:old_filename to the odi file.
- Read Section 5.3 if you are planning to do a partial density of states calculation.

5.3 I'm getting odd results for my PDOS calculation when using castep version 6.0

The spectral module in CASTEP 6.0 generates the pdos weights commensurate with the optics grid you have chosen. However this gets overwritten by the main routines. Hence to get the right PDOS weights you must set PDOS_CALCULATE_WEIGHTS : FALSE in the param file.

5.4 I'd like OptaDOS to do X as well

Contact the developers we're always interested in discussing new functionality.

5.5 I'd like to help, what can I do?

Contact the developers, there's always more functionality that we'd like to add to the code.

5.6 I think I've found a bug: what should I do?

- Check and re-check that it is a bug.
- Check the output of the electronic structure code.
- Check that you're using the latest version of OPTADOS.
- Email the developers the input and output files with `iprint : 3` and as much information about the problem as possible.