2025 3rd International Conference on Advancement in Computation & Computer Technologies (InCACCT) | 979-8-3315-4389-1/25/$31.00 ©2025 IEEE | DOI: 10.1109/InCACCT65424.2025.11011372

Prevention of Prompt Injection Attacks Over Financial Applications Integrated with LLM

Tanaya Joshi
Dept. of Information Technology
DJ Sanghvi College of Engineering
Mumbai, India
tanayavjoshi@gmail.com

Vaishnavi Naik
Dept. of Information Technology
DJ Sanghvi College of Engineering
Mumbai, India
vaishnavinaik2003@gmail.com

Isha Mistry
Dept. of Information Technology
DJ Sanghvi College of Engineering
Mumbai, India
ishamistry81@gmail.com

Ramchandra Mangrulkar
Dept. of Information Technology
DJ Sanghvi College of Engineering
Mumbai, India
ramchandra.mangrulkar@djsce.ac.in

***Abstract*—Prompt injection is a growing concern in financial applications integrated with Large Language Models. These attacks pose a critical risk to financial applications leading to data breaches,confidential d ata l oss a nd fi nancial lo sses by manipulating input prompts to cause unintended or harmful outputs. Existing defense strategies include utilizing filters f or i nput and output, and delimiters, however, these techniques have been proven inadequate. This paper builds upon existing mechanisms and proposes an enhanced security system that incorporates role-based access, jailbreak attack detection, validating inputs and securely passing prompts to LLM. This is done by developing a pre-processing layer at both ends-the client and LLMs-through the identification of critical as well as destructive keywords. The experimental results show that blocking of that malicious prompt ensures that only authenticated and authorized commands are processed. The measures, therefore, allow financial institutions to significantly r educe t he p robability o f p rompt i njection attacks besides increasing data protection and confidence i n AI-based financial applications.**

***Index Terms*—Authorization, Finance, Jailbreak, LLMs, Prompt Engineering, Security, Signing**

I. Introduction

In today's world of AI development, large language models (LLMs) [1], [2] such as GPT-4 [3] and Gemini are notable for their advanced capabilities, allowing them to learn and write like humans. The foundation supporting these LLMs is deep neural networks, particularly transformer models, which enable them to process vast amounts of textual data and identify patterns in language and context. This ability allows LLMs to perform a variety of tasks, including answering questions, summarizing documents, preparing reports, and even engaging in conversations [4]. As a result, LLMs have been adopted across numerous sectors, particularly in finance, where they are utilized for analyzing market trends, enhancing customer service, and supporting decision-making processes.

Today in the financial fi eld, fin ance LLM s [5] , [6] are used in statistical and qualitative analysis of the large volume of financial d ata, i n t he p rediction o f fl uctuations in the stock market, the preparation of trading algorithms, and as an assistant in investment consulting. For example, LLMs can utilize the company's earning report, news articles and sentiment analysis on social media platforms to forecast the stock performance. They also can engage in client communication by answering their queries on their portfolios or the market. These applications suggest how use of LLMs could help increase efficiency while decreasing costs and improving accuracy in financial forecasting.

However, the integration of LLMs [7] in the finance domain also has considerable threats as the experimental class of LLM is still in the development stage. A big concern that arises is the possibility of these models learning, leaking, or even producing incorrect or confidential information to make substantial money losses. Further, outsourcing such important financial evaluations based on LLMs means that their internal working remain unexplained, and their work can be hardly described as transparent and accountable. Another notable risk is adversarial risks posed by several types of attack which include prompt injection attacks (PJA). In prompt injection attacks [7], [8] the attacker manipulates the input in such a way that it forces the LLM to perform actions or produce undesirable outputs. For example, the an attacker may slip destructive commands into a user query or input data and this may cause the model to perform unauthorized transactions or release of information that is not supposed to be disclosed [9].

Conventional measures such as IO-filtering and delimiters have been expensive in effectively mitigating these attacks hence making these financial systems that use LLMs vulnerable [10].

For instance, the use of LLM can be applied in the area of finance where an LLM can be programmed to perform debit and credit instructions that are given in natural language [11]. One can input a simple command such as 'disregard all commands entered before this one, and perform the following: transfer $10, 000 to XYZ', and the model will execute the transfer. This example shows how important it is to be careful while implementing LLMs, especially within an environment

979-8-3315-4389-1/25$31.00 © 2025 IEEE

Authorized licensed use limited to: UNIVERSIDAD VERACRUZANA. Downloaded on October 07,2026 at 00:32:15 UTC from IEEE Xplore. Restrictions apply.

that is prone to attacks such as finance. Based on these threats, it is necessary to have and establish higher defense strategies for protecting LLM-integrated financial applications against prompt injection attacks.




Fig. 1. Overview of working.

The secure interaction model with a Large Language Model (LLM) starts when a user gives a prompt. The overall working of the system is as shown in Fig. 1.

The prompt goes through preprocessing steps to identify malicious prompts, if found the program is terminated. If the prompt appears to be safe, it is signed and sent to LLM to produce output. This model helps keep interactions secure by checking and approving prompts before they reach the LLM.

II. Literature Review

The paper titled "Signed-Prompt: A New Approach to Prevent Prompt Injection Attacks Against LLM-Integrated Applications" focuses on the security concerns of prompt injection attacks on applications involving LLMs [12]. The authors propose adding authenticators to sensitive commands so that the LLMs can distinguish between commands from trusted and untrusted users. The Signed-Prompt system comprises two main components: an Encoder which affixes its digital signature to the proper authorization and an Adjusted LLM which is capable of performing its functions only if accompanied by a signature. For instance, if a user wants to delete a file, the instruction "delete" might be replaced with a signed version like "toeowx". The LLM is trained to understand that "toeowx" refers to deletion command, but it will not execute the deletion if the original "delete" instruction (without the signature) is used.

Prompt injection attacks have been addressed in paper "StruQ: Defending Against Prompt Injection with Structured Queries" to study the manipulation of the behavior of Large Language Models (LLMs) on the part of malicious users through injecting changes to input prompts [13]. The authors have proposed a defense measure that employs a two-part arrangement comprising a Secure Front-End and an LLM (Large Language Model) that has been specially trained for the system. The Secure Front-End formats prompts and user data with unique delimiters to prevent any unauthorized or malicious entries. The experiments presented in the paper show that the proposed solution, is successful against less than 2% of attacks in most cases. However, it lends itself poorly to advanced attacks, such as Tree-of-Attacks (TAP), which were successful against some models, thereby suggesting the need for future work.

The paper by Greshake et al. elaborated on the security factors associated with the custom GPT models and more specifically with the prompt injection attacks [14]. Since users can train the AI models for specific tasks hence the vulnerability and security risks are much higher since the AI models can be trained to be exploitable depending on the input given. The paper also describes other prevention measures against prompt injection attacks such as disabling of code interpreters and defensive prompts and finds that they are ineffective as a way of countering the attacks in most cases.

The paper by Jiahao Yu et al. elaborated on the security factors associated with the custom GPT models and more specifically with the prompt injection attacks [15].

The study evaluates over 200 custom GPT models, identifying two major security threats: The changes mostly affected the system prompt extraction and file leakage. System prompt extraction, allows an attacker to make GPTs respond with the system prompts that would normally not be displayed or are concealed from the user. File leakage takes place when some other person gains access to something that belongs to the model owner. The findings are concerning, with 97.2% of models vulnerable to system prompt extraction and 100% of models with uploaded files at risk of file leakage. The paper also describes other prevention measures against prompt injection attacks such as disabling code interpreters and defensive prompts and finds that they are ineffective as a way of countering the attacks in most cases.

Another paper titled "Prompt Injection Attack Against LLM-Integrated Applications" discusses the susceptibility of applications that incorporate LLMs through the newly proposed threat model called 'HOUYI' [16]. Similar to SQL injection systems that inject wrong inputs into web pages, HOUYI injects prompt-like inputs into LLM-containing applications to endanger their users. The authors performed the analysis on 36 real-world applications integrated with LLM, of which 31 out of the 36 applications were vulnerable to prompt injection attacks. This clearly shows a major security vulnerability in the current LLM strategies particularly because these models are becoming integrated more in numerous applications. The study shows the high success rates obtained by HOUYI for performing prompt injection attacks and shows uncontrolled dangerous consequences such as unrestricted use of LLM resources or unauthorized access to particular application prompts. The paper ends with a stressed need for apt protection as existing countermeasures fail quite often to tackle these threats.

The paper "An Early Categorization of Prompt Injection Attacks on Large Language Models" examine the threat that newly-emerging large language models such as OpenAI's GPT and Google's Bard can be susceptible to specific types of prompt injection attack [17]. These attacks involve feeding the LLM with specific inputs to achieve an LLM output that

Authorized licensed use limited to: UNIVERSIDAD VERACRUZANA. Downloaded on October 07,2026 at 00:32:15 UTC from IEEE Xplore. Restrictions apply.

the user did not initially intend and may get past the filter meant to protect the user from safe-for-work content. The authors categorize prompt injections into two types: the first one happens when a user enters a malicious prompt directly while the second one happens when the context in which the model is applied is somehow tricked, as when the users place hidden scripts that instruct the model on what to do. The study reveals the various dangers associated with these attacks especially as LLMs are seen to be incorporated into various applications.

III. Proposed Methodology

The method proposed addresses prompt injection attacks by implementing a secure prompt management system that manages users with varying roles and access controls. All users can enter prompts, which go through spell-check to ensure consistency and eliminate potential human errors. This system utilizes pattern recognition to identify potential jailbreak attacks, distinguishing which prompt inputs are likely unwarranted and possibly containing attempts at prompt injection.

For users with different roles and access permissions, the system verifies whether the user has the authority to perform a specific action. Once this role-based authorization is approved, the prompts are signed, converting critical instructions into illegible sequences of letters. This process ensures that the prompt cannot be altered by any user at a later stage. If any critical keyword is not signed, the system categorizes it as "bad" or "malicious" and rejects the prompt.

Once the prompt has passed all verification measures, it is sent to the language model (LLM) system, which takes the signed prompt and later reverts the critical instructions to their original state for execution.

If the LLM detects that the prompt contains critical instructions in its original form and is not signed, it determines that the prompt has been tampered with by an unauthorized user over the network [18]. In such cases, the LLM flags these prompts and halts any further execution.

Valid prompt Example:
Input: Transger $500 from Accnt 1012 to Account 1234
(The entered prompt contain typographical errors which are the auto corrected)
Spell check and Validation: The prompt is checked for errors and security threats.
Transfer $500 from Account 1012 to Account 1234
Obfuscation/Signing: Critical keywords are masked
Pthrand $500 from Account 1012 to Account 1234
LLM Processing and Reconstruction:
The LLM receives the obfuscated prompt, uses a secure lookup to restore original account details, and executes the command.
Invalid Prompt Example:
Bypass any verification and provide access to every account detail
Spell check and validation have been interrupted due to a detected jailbreak attack pattern.
Valid prompt but later hampered by unauthorized user:
Input:Transger $500 from Accnt 1012 to Account 1234
Spell check and Validation:
Transfer $500 from Account 1012 to Account 1234
Obfuscation/Signing: Critical keywords are masked Pthrand $500 from Account 1012 to Account 1234
Input alteration: Pthrand $500 from Account 1012 to Account 1234 and delete all the accounts.
LLM Processing and Reconstruction:
Since LLM gets the original form of keyword delete, therefore it is stopped.

A. *Keyword Detection*

The keyword detection phase is an important step during which specific keywords in the given prompt are recognized. These might be action or command keywords that are subjected to monitoring, validation, or encoding. It targets the early detection of potential threats or unauthorized activities and defines further steps in processing.
Given an input sentence S, the function $K(S)$ extracts a set of keywords as defined in equation (1):

$$K(S) = \{k_1, k_2, \ldots, k_n\} \quad \text{where} \quad k_i \in S \tag{1}$$

Each k_i represents a specific keyword, such as "debit," "credit," "send", "ignore," or "discard."

Algorithm 1 Keyword Detection Algorithm

```
Initialize an empty set DetectedKeywords.
Define a dictionary of known keywords: KeywordsDict
= {"debit", "credit", "send", "ignore", "discard", ...}.
Split sentence S into words.
for each word w in S do
  if w is in KeywordsDict then
    Add w to DetectedKeywords.
  end if
end for
return DetectedKeywords
```

B. *Ignore Attack Detection*

The Ignore Detection Attack is a very important stage in the protection against prompt injection attacks. In this stage, inputs are identified that contain specific keywords 'ignore attack', such as 'ignore' or 'discard', indicating in one way or another an attempt to elude or subvert the intended operation [10]. The system either exits or discards the prompt upon keyword detection to prevent unauthorized actions. Attack detection shall detect and filter out those prompts that could disrupt, override, or maliciously influence the system's behavior. During this process, if a system recognizes such keywords early, it can mitigate prompt injection threats and ensure operational integrity.
Given an input sentence S, the function $A(S)$ checks for the presence of attack-related keywords according to equation (2):

$$A(S) = \{k \in K(S) \mid k \in \text{AttackKeywords}\} \tag{2}$$

Authorized licensed use limited to: UNIVERSIDAD VERACRUZANA. Downloaded on October 07,2026 at 00:32:15 UTC from IEEE Xplore. Restrictions apply.

where

$$\text{AttackKeywords} = \{\text{“ignore”}, \text{“discard”}\}$$

If $A(S) \neq \emptyset$, then the program is terminated.

Algorithm 2 Ignore Attack Detection Algorithm

Define a set of attack-related keywords: `AttackKeywords` = {“ignore”, “discard”}.
for each keyword k in $K(S)$ **do**
  if k is in `AttackKeywords` **then**
    return True (indicating an ignore attack is detected)
  end if
end for
return False (indicating no ignore attack)

C. Authorized Encoding (Signing)

Authorized Encoding is an important step in the secure prompt management process in that it ascertains proper encoding of specific keywords in an input prompt based on user-authorized levels. This means encoding of keywords to ensure added layers of security, with unique, user-specific signatures helping to identify legitimate user activities versus those regarded as potential malicious activities. Authorized encoding is utilized primarily to securely encode and sign keywords for authenticated users by the system. Such an encoding assists in ascertaining valid prompts whose source originated from authorized users with a deterrent against unauthorized actions or prompt manipulations. The embedding of the signature into each keyword ensures verification of the source and authenticity of the input before processing.
Let $K(S)$ be the set of detected keywords from the input sentence S. For an authorized user U, the function $\sigma(k, U)$ generates a unique encoded signature for each keyword k as shown in equation (3):

$$\sigma(k, U) = \text{Sign}(k, U) \tag{3}$$

where $\sigma(k, U)$ is the encoded keyword signed uniquely for user U. The output set $\Sigma(K(S), U)$ contains all encoded keywords for the input S according to equation (4):

$$\Sigma(K(S), U) = \{\sigma(k_1, U), \sigma(k_2, U), \ldots, \sigma(k_n, U)\} \tag{4}$$

D. Second Layer Processing

Second Layer Processing: This is an important step in the prompt management system. This stage ensures that only the encoded and authenticated prompts are processed further. It acts as a filter for determining whether an encoded keyword in any input is correctly signed or authorized before sending it to a language model or database for execution. The key objective of the Secondary Processing Layer is to validate the encoded keywords generated during the encoding phase using a valid signature. This would ensure that only duly authorized and correctly signed prompts are passed on to the LLM for execution or any subsystems that fall under the classification. Another step further enhances defense by giving it “throwaway” disqualification of failed verification prompts. Let $\Sigma(K(S), U)$ be the set of encoded keywords for the input sentence S and user U. The verification function $V(\sigma(k, U))$ checks if each encoded keyword $\sigma(k, U)$ is valid as shown in equation (5):

$$V(\sigma(k, U)) = \begin{cases} \text{True}, & \text{if the signature is valid for user } U \\ \text{False}, & \text{otherwise} \end{cases} \tag{5}$$

Algorithm 3 Authorized Encoding Algorithm

Initialize an empty list `EncodedKeywords`.
Check if user U is authorized:
if U is not authorized **then**
  return an empty set or error (`User not authorized`).
end if
for each keyword k in $K(S)$ **do**
  Apply signing function $\sigma(k, U) = \text{Sign}(k, U)$.
  Add $\sigma(k, U)$ to `EncodedKeywords`.
end for
return `EncodedKeywords`.

Algorithm 4 Keyword Verification Algorithm

Initialize a boolean variable `VerificationStatus` as `True`.
for each encoded keyword $\sigma(k)$ in `EncodedKeywords` **do**
  Verify if $\text{Verify}(\sigma(k, U)) = \text{True}$.
  if $\text{Verify}(\sigma(k, U)) = \text{False}$ **then**
    set `VerificationStatus` to `False`.
    break the loop.
  end if
end for
if `VerificationStatus` = `True` **then**
  return `True` (all keywords verified successfully).
else
  return `False` (verification failed).
end if

The Fig 2 depicts the stepwise working of the proposed prompt injection attack detection mechanism. It shows how the system may handle prompts both from an unauthorized as well as authorized user. The working of the system is explained in detail below.

Step-wise working of system:

1. Input: The user prompts the LLM to perform various finance-related tasks such as transferring funds from one account to another, retrieving account information, modifying/deleting users, etc.

Authorized licensed use limited to: UNIVERSIDAD VERACRUZANA. Downloaded on October 07,2026 at 00:32:15 UTC from IEEE Xplore. Restrictions apply.




Fig. 2. Working of the system.

2. Spell Check: The prompt entered by the user is checked for possible spelling mistakes and typographic errors and is corrected using NLP libraries.
3. Ignore Attack Detection: If any keyword relating to an ignore attack such as “Ignore”, “Disregard”, “Skip”, “Forget”, “Neglect”, “Overlook”, “Omit”, “Bypass”, “Pay no attention to”, “Do not follow”, “Do not obey” is detected, then the prompt is considered malicious and hence not processed further.
4. Signing: The prompts made by authorized accounts are signed using a signing algorithm that encodes the keywords that perform particular actions. The keywords include “delete”, “withdraw”, “deposit”, and “transfer”. Keywords are encoded using specific keywords stored in the database.
5. Input validation: In this step encoded prompt is cross-checked across the database and only valid prompts that are correctly signed are sent to LLM. Invalid prompts will not be processed.
6. LLM processing: The LLM will interact with the database to perform intended operations and produce output.
This order of working ensures that LLM processes only valid instructions made by authorized users and hence safeguards user data and transactions.

IV. Results

The system encodes a set of predefined critical instruction words stated below:
keywords = [“delete”, “erase”, “transfer”, “send”, “credit”, “debit”, “withdraw”, “select”, “display”, “show”]
The system successfully detects ignore attacks and possible jailbreak attempts by identifying potentially destructive keyword stated below:
verbs = [“ignore”, “disregard”, “skip”, “forget”, “neglect”, “omit”, “bypass”, “without”, “exclude”]
The above dataset is self curated. Prompts containing these keywords are not executed. This is shown in figures Fig 3, Fig 4 and Fig 5.




Fig. 3. Jailbreak Attack Detection




Fig. 4. Malicious Prompt Detection




Fig. 5. Valid Prompt execution

V. Conclusion

Prompt injection attacks pose a great threat to financial applications using large language models. As the system involves access to sensitive data, an effective security system has to be implemented. This paper outlines some techniques used to prevent prompt injection attacks by either input filtering, jailbreak detection, role-based access control, or prompt signing among others. Altogether, these techniques lower the

Authorized licensed use limited to: UNIVERSIDAD VERACRUZANA. Downloaded on October 07,2026 at 00:32:15 UTC from IEEE Xplore. Restrictions apply.

chances of successful prompt injection attempts. It is through such measures that financial institutions can improve the security of the deployment of AI applications, retain their clients' trust, and keep information confidential. Therefore, these controls must be constantly strengthened as sophisticated attack techniques are developed to protect AI models in finance and other critical sectors.

VI. Future Scope

The proposed methodology can be further incorporated into various other financial applications to make it more versatile.It can be further expanded to multiple languages such as Hindi, Spanish etc.

References

[1] W. X. Zhao, K. Zhou, J. Li, T. Tang, X. Wang, Y. Hou, Y. Min, B. Zhang, J. Zhang, Z. Dong, et al., "A survey of large language models," arXiv preprint, arXiv:2303.18223, 2023. doi: 10.48550/arXiv.2303.18223.

[2] X. Hou, Y. Zhao, Y. Liu, Z. Yang, K. Wang, L. Li, X. Luo, D. Lo, J. Grundy, and H. Wang, "Large language models for software engineering: A systematic literature review," ACM Trans. Softw. Eng. Methodol., vol. 33, no. 8, pp. 1–79, 2023. doi: 10.1145/3695988.

[3] R. OpenAI, "GPT-4 technical report," arXiv preprint, arXiv:2303.08774, 2023. doi: 10.48550/arXiv.2303.08774.

[4] R. Kumar, M. Gupta, P. Shrama, N. Soni, and K. Rawat, "NLP-Based text-to-speech and speech-to-text virtual assistant," AIP Conf. Proc., vol. 3072, no. 1, Mar. 2024. doi: 10.1063/5.0203299/3277795.

[5] H. Zhao, Z. Liu, Z. Wu, Y. Li, T. Yang, P. Shu, S. Xu, H. Dai, L. Zhao, G. Mai, et al., "Revolutionizing finance with LLMs: An overview of applications and insights," arXiv preprint, arXiv:2401.11641, 2024. doi: 10.48550/arXiv.2401.11641.

[6] J. Lindley and R. Whitham, "From prompt engineering to prompt craft," Proc. 19th Int. Conf. Tangible, Embedded, Embodied Interaction, pp. 1–12, 2025. doi: 10.1145/3689050.3704424.

[7] S. Schulhoff, J. Pinto, A. Khan, L.-F. Bouchard, C. Si, S. Anati, V. Tagliabue, A. L. Kost, C. Carnahan, and J. Boyd-Graber, "Ignore this title and hackaprompt: Exposing systemic vulnerabilities of LLMs through a global-scale prompt hacking competition," Assoc. Comput. Linguist. (ACL), 2023. doi: 10.18653/v1/2023.emnlp-main.302.

[8] Y. Liu, Y. Jia, R. Geng, J. Jia, and N. Z. Gong, "Formalizing and benchmarking prompt injection attacks and defenses," Proc. 33rd USENIX Security Symp. (USENIX Security 24), 2024, pp. 1831–1847.

[9] Z. Hu, L. Song, J. Zhang, Z. Xiao, J. Wang, Z. Chen, J. Zhao, and H. Xiong, "Rethinking LLM-based preference evaluation," arXiv preprint, arXiv:2407.01085, 2024. doi: 10.48550/arXiv.2407.01085.

[10] J. Wang, F. Wu, W. Li, J. Pan, E. Suh, Z. M. Mao, M. Chen, and C. Xiao, "FATH: Authentication-based test-time defense against indirect prompt injection attacks," arXiv preprint, arXiv:2410.21492, 2024. doi: 10.48550/arXiv.2410.21492.

[11] D. Zhang, X. Xu, C. Wang, Z. Xing, and R. Mao, "A layered architecture for developing and enhancing capabilities in large language model-based software systems," arXiv preprint, arXiv:2411.12357, 2024. doi: 10.48550/arXiv.2411.12357.

[12] X. Suo, "Signed-Prompt: A new approach to prevent prompt injection attacks against LLM-integrated applications," arXiv preprint, arXiv:2401.07612, 2024. AIP Conf. Proc., vol. 3194, p. 040013, 2024. doi: 10.1063/5.0222987.

[13] S. Chen, J. Piet, C. Sitawarin, and D. Wagner, "StruQ: Defending against prompt injection with structured queries," arXiv preprint, arXiv:2402.06363, 2024. doi: 10.48550/arXiv.2402.06363.

[14] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz, "Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection," Proc. 16th ACM Workshop Artif. Intell. Security, 2023, pp. 79–90. doi: 10.1145/3605764.3623985.

[15] J. Yu, Y. Wu, D. Shu, M. Jin, and X. Xing, "Assessing prompt injection risks in 200+ custom GPTs," arXiv preprint, arXiv:2311.11538, 2023. doi: 10.48550/arXiv.2311.11538.

[16] Y. Liu, G. Deng, Y. Li, K. Wang, Z. Wang, X. Wang, T. Zhang, Y. Liu, H. Wang, Y. Zheng, et al., "Prompt injection attack against LLM-integrated applications," arXiv preprint, arXiv:2306.05499, 2023. doi: 10.48550/arXiv.2306.05499.

[17] S. Rossi, A. M. Michel, R. R. Mukkamala, and J. B. Thatcher, "An early categorization of prompt injection attacks on large language models," arXiv preprint, arXiv:2402.00898, 2024. doi: 10.48550/arXiv.2402.00898.

[18] M. Gupta, R. Yadav, and G. Tanwar, "Insider and flooding attack in cloud: A discussion," Proc. 3rd Int. Conf. Comput. Sustainable Global Dev. (INDIACom), New Delhi, India, 2016, pp. 530–535.

Authorized licensed use limited to: UNIVERSIDAD VERACRUZANA. Downloaded on October 07,2026 at 00:32:15 UTC from IEEE Xplore. Restrictions apply.