Pattern Recognition 179 (2026) 113661



Contents lists available at ScienceDirect

Pattern Recognition

journal homepage: www.elsevier.com/locate/pr





CM-PIUG: Cross-modal prompt injection unified modeling and game-theoretic defense strategies

Gaoyuan Quan[a,b,c,d], Zhiyong Zhang[a,b,c,d,*], Yanting Zhang[e], Weiguo Wang[f], Junchang Jing[g], Mengdan Xue[a,b,c,d]

[a] College of Information Engineering (College of Artificial Intelligence), Henan University of Science and Technology, Luoyang, 471023, Henan, China
[b] Henan International Joint Laboratory of Cyberspace Security Applications, Henan University of Science and Technology, Luoyang, 471023, Henan, China
[c] Henan Intelligent Manufacturing Big Data Development Innovation Laboratory, Henan University of Science and Technology, Luoyang, 471023, Henan, China
[d] Institute of Artificial Intelligence Innovations, Henan University of Science and Technology, Luoyang, 471023, Henan, China
[e] China Electronics Standardization Institute, Beijing, 100007, China
[f] Education Technology Department, New H3C Technologies Co., Ltd., Beijing, 100102, China
[g] College of Computer and Information Engineering, Henan Normal University, Xinxiang, 453007, Henan, China

ARTICLE INFO

Keywords:
Multimodal large language models
Prompt injection attack
Unified attack surface modeling
Stackelberg mean-field game defense
Zero-shot detection

ABSTRACT

Multimodal large language models (MLLMs) introduce profound security risks in open-world deployments, particularly cross-modal prompt injection attacks (PIAs), where adversaries embed malicious payloads within non-textual inputs such as images and graph-structured prompts to deviate systems from intended instructions. Current defenses, largely predicated on unimodal heuristics, frequently fail to generalize against these compositional and transferable threats. To overcome these limitations, we propose Cross-Modal Prompt Injection Unified Modeling and Game-Theoretic Defense Strategies (CM-PIUG), a framework integrating unified attack-surface modeling with game-theoretic optimization. Specifically, the framework formalizes the attack surface as a Unified Attack Surface Graph and utilizes contextual semantic-equivalence reduction to map heterogeneous carriers—spanning OCR-extracted text, native text, and graph prompts—into normalized semantic units. This mechanism effectively mitigates representational inconsistencies induced by modality differences. Furthermore, we characterize the interaction between the defender and extensive populations of attack variants as a Stackelberg mean-field game (SMFE). This formulation transforms the high-dimensional strategy space into a tractable "individual-distribution" structure, enabling the offline generation of near-equilibrium defenses suitable for rapid online matching. Empirical evaluations across text, vision-language, and graph prompt-learning benchmarks confirm that CM-PIUG consistently minimizes the attack success rate (ASR), enhances zero-shot detection and robustness over state-of-the-art baselines, and maintains minimal online overhead, thereby validating its scalability for real-world MLLM services.

1. Introduction

Multimodal large language models (MLLMs) use prompts as a unified interaction interface and are widely deployed in question answering, knowledge generation, and decision support. However, cross-modal prompt injection attacks (PIAs) have emerged as a critical threat to reliability. Unlike earlier text-only jailbreaks or malicious rewriting [1], modern attacks can hide payloads in image text via OCR, ASR transcripts, graph-structured prompts [2,3], or multimodal image-text contexts [4,5]. By exploiting semantic coupling along the parsing-execution pipeline, adversaries can steer models off-task with high stealth, a large combinatorial space, and strong cross-modal transferability [6]. After OpenAI released GPT-4V(ision) in 2023, Piotr Skalski noted on the Roboflow blog that GPT-4's ability to read text in images also opens a new attack vector. As illustrated in Fig. 1, malicious instructions may be absent from the explicit text prompt yet injected through images.

Existing research has mainly progressed along two trajectories. The first targets automated diversification of adversarial samples, including direct instruction injection, contextual interference, semantic manipulation/inducement, and trigger construction. The second emphasizes defense and detection, such as context isolation/filtering, output constraints and instruction reinforcement, and anomaly detection via behavioral consistency or embedding alignment. However, most methods still assume single-modality inputs or fixed system settings and lack a unified framework that jointly models cross-modal input segments, prompt-parser behavior, and downstream objectives. Moreover, many

* Corresponding author.
E-mail address: xidianzzy@126.com (Z. Zhang).

https://doi.org/10.1016/j.patcog.2026.113661
Received 20 August 2025; Received in revised form 30 March 2026; Accepted 31 March 2026
Available online 2 April 2026
0031-3203/© 2026 Elsevier Ltd. All rights are reserved, including those for text and data mining, AI training, and similar technologies.




Fig. 1. GPT-4 vision prompt injection examples.

defenses rely on modality-specific features or heuristic rules, limiting generalization to compositional attacks, cross-modal transfer, and open-world threats.

For Pattern Recognition audiences concerned with robust representations, interaction, and generalization, prompt learning and cross-modal prompt interaction have become key paradigms for rapid task adaptation. For example, MKGPL [7] combines graph structures with prompt learning for multi-view knowledge fusion in few-shot image recognition. Meanwhile, recent PR studies show that jailbreak and prompt-injection attacks are increasingly sophisticated, black-box, and multimodal; the Virtual Scenario Hypnosis (VSH) attack jointly exploits narrative induction, visual payloads, and contextual obfuscation to bypass alignment [8]. These trends suggest that as prompts become the core interface for cross-modal adaptation, they also enlarge the attack surface via more input channels and stronger semantic coupling—calling for structured, interpretable, and transferable security modeling. In this vein, face anti-spoofing (FAS) research offers transferable insights for modality gaps and domain shifts beyond current prompt-injection work, including adversarial cross-modality translation [9], prompt-based prior injection [10], and stable selection/routing under distributional shifts [11], which together motivate generalized cross-modal defenses.

Although prior work has developed effective techniques for prompt injection detection and game-theoretic defense, the approaches most related to ours still face two key limitations. First, most methods target text-only or single-modality settings, lacking a unified formal attack-surface characterization that jointly encodes multimodal input segments, parser behaviors, and downstream execution objectives. Second, game-theoretic defenses are often limited to classical bilevel formulations or small, manually specified strategy spaces, and thus cannot cope with the exponential decision complexity induced by the joint expansion of the "adversarial perturbation space × combinatorial defense space" in cross-modal scenarios. For example, JailGuard [12] detects prompt attacks across text and images via input mutation and response-divergence testing, but does not formalize the underlying injection logic in a unified representation. DataSentinel [13] frames detection as a minimax game and fine-tunes an LLM-based detector against adaptive attackers, yet it relies on a fixed set of detection strategies and does not generate diverse, compositional defense actions. Overall, existing studies still lack a framework that simultaneously offers (i) a unified cross-modal model of prompt-injection pathways and (ii) scalable synthesis of combinatorial defenses for open-world threats.

To bridge this gap, we propose CM-PIUG for unified attack-surface modeling and compositional defense generalization. We build a cross-modally unified attack-surface graph that abstracts the attack chain into three mechanistic modules—input processing, prompt parsing, and task execution—and apply contextual semantic-equivalence reduction to map heterogeneous segments (e.g., OCR text, ASR transcripts, and native prompts) into a normalized semantic space, so syntactically different yet semantically equivalent payloads share a consistent graph representation. For each input, we instantiate an attack graph and perform open-world risk propagation, enabling zero-shot detection of unseen injections and producing an auditable causal evidence chain. Further, we integrate Stackelberg games with mean-field games (MFGs) to generate large-scale, composable near-optimal defenses offline by compressing massive attacker-defender interactions into an individual-distribution form, and then efficiently match near-equilibrium actions online, reducing worst-case ASR under strict runtime constraints.

To the best of our knowledge, this work is the first cross-modal prompt-injection security framework that jointly delivers these capabilities: (i) a formal unified attack condition over the input-parsing-execution pipeline, explicitly incorporating cross-modal semantic-equivalence reduction; (ii) open-world, zero-shot detection with causal evidence tracing under a unified representation; and (iii) scalable Stackelberg-mean field game (MFG) solving to produce deployable combinatorial defenses. Accordingly, we address three research questions:

RQ1: Can a modality-agnostic unified attack-surface graph support consistent risk localization and zero-shot detection across text-only, vision-language, and graph-prompting systems?

RQ2: Under cross-modal parsing noise and ambiguity, can formally grounded semantic-equivalence reduction model semantically equivalent payloads consistently and yield interpretable causal evidence chains?

RQ3: When adversarial perturbations and combinatorial defenses expand concurrently, can offline near-equilibrium solving with low-overhead online matching minimize worst-case ASR?

The main contributions of this work are summarized as follows:

(1) Unified formal modeling of cross-modal attack surfaces. We propose CM-PIUG, a unified attack-graph framework for cross-modal prompt injection that integrates injection entry points, parsing behaviors, and execution objectives. With semantic-equivalence reduction, heterogeneous inputs from OCR, ASR, or native text are normalized into a shared semantic space, enabling open-world instance-level graph construction and auditable causal evidence tracing.
(2) Scalable generation of compositional defense strategies. We develop a strategy generalization mechanism based on a Stackelberg-mean-field game formulation. Offline, near-equilibrium committed defenses are computed and stored as a reusable policy library; online, context-specific actions are efficiently matched by conditioning on the instantiated input-driven attack graph, balancing efficacy and deployability in large combinatorial spaces.
(3) Cross-modal validation and efficiency evaluation. We evaluate three task categories—text-only, vision-language, and graph-based prompting—covering detection performance, transfer robustness, and runtime overhead. Results show that CM-PIUG consistently reduces attack success rates over prior methods with manageable computational costs.

2. Related work

2.1. Evolution of cross-modal prompt injection attacks

2.1.1. Multimodal prompt injection: Cross-modal coordination and compositional attack pipelines

Prompt injection vulnerabilities have clearly expanded to multimodal models and agentic systems. Ying et al. [4] show that bimodal adversarial prompts can bypass VLM safeguards, where individually benign modalities become exploitable after fusion. Prior work also demonstrates real-world image-based prompt injection [14]: malicious instructions can be steganographically embedded in images and then executed by vision-capable models. Lee et al. [15] further conceal directives via graphical elements. Beyond vision-language settings, Hou et al. [16] show that audio inputs can carry injections in large audio-language models (e.g., Context Injection and Judgment Hijacking), undermining integrity. For multimodal agents, cross-modal injections can compromise planning and decision-making [5]. To benchmark these threats, Liu et al. [17] introduce MM-SafetyBench for multimodal LLM safety evaluation. Overall, cross-modal prompt injection is evolving from single-modality adversarial examples into a coordinated pipeline combining textual context, visual/auditory payloads, and in-context learning dynamics.

2.1.2. A key intersection point: Perturbation amplification through cross-modal fusion

Beyond security studies, multimodal pattern recognition—especially fusion in RGB-thermal (RGB-T) and RGB-depth (RGB-D) perception—offers insight into how cross-modal systems can suffer perturbation amplification and adversarial decision manipulation. In urban scene understanding, Zhou et al. [18] use multi-scale fusion with reinforcement learning; EGFNet [19] applies edge-aware guidance to reduce modality gaps; MMSMCNet [20] exploits shared modality memory and morphological complementarity; and MTANet [21] improves robustness via multitask-aware hierarchical fusion. In salient object detection, LSNet [22], WaveNet [23], CCAFNet [24], and ECFFNet [25] collectively highlight robust design principles under distribution shifts, including alignment, guided information flow, dynamic selection/routing, and consistency constraints. Critically, these fusion junctions, if targeted via prompt injection or contextual manipulation, can induce nonlinear perturbation amplification in the cross-modal decision pipeline. This motivates a unified framework to characterize cross-modal injection pathways and enable transferable defenses across modalities and system configurations.

2.2. Defense methods: Prompt injection detection and mitigation

2.2.1. Input constraints and rule-based defenses: Simple yet brittle

Research on prompt-injection defenses is still nascent, with many approaches relying on structured input wrapping and rule-based filtering. Another defense line detects anomalies in model behavior and contextual coherence caused by prompt injection. JailGuard [12] identifies jailbreaking via unified encoding and context-discrepancy analysis. DataSentinel [13] formulates attacker-defender interaction as a game, enabling detection and adaptive countermeasure updates through adversarial reasoning, with demonstrated robustness in deployment. Han and Zhu [26] further model agentic defense as a dynamic Stackelberg game to anticipate sequential adversarial strategies and adjust responses proactively. GUARDIAN [26] adopts a multi-tier architecture with detection/verification across input parsing, generation, and post-processing to strengthen layered security. For image-based injection, Sharma et al. [27] use user-guideline constraints to flag hidden instructions, while Gou et al. [28] mitigate pixel-level steganographic prompts by transforming images into textual descriptions before multimodal inference.

2.2.2. Cross-domain robustness as inspiration for generalizable cross-modal security

Although targeting different tasks, advances in domain-generalizable face anti-spoofing (FAS) provide useful guidance for cross-modal defenses. Liu et al. [9] propose adversarial cross-modality translation to reduce modality/domain gaps while exposing spoof-discriminative cues, highlighting the need for learned alignment under strong heterogeneity. CFPL-FAS [10] uses class-free prompt learning to inject content/style priors, improving unseen-domain generalization and suggesting that semantic priors can stabilize decision boundaries under shifts. CA-MoEiT [11] emphasizes routing stability and reliable expert selection via a semi-fixed MoE, where a “super expert” preserves domain-invariant knowledge and adaptive experts capture domain-specific variation. Together, these works motivate transferable principles for cross-modal prompt-injection defense in semantic reduction, robust routing/selection, and deployable generalization.

To explicitly demarcate the technical boundaries, it is crucial to note that FAS primarily relies on representation/learning-driven unification. Methods like adversarial cross-modality translation, FM-ViT [29], and CFPL-FAS [10] operate in continuous latent spaces, aligning heterogeneous physical signals (e.g., RGB, Depth, NIR) via implicit statistical correlations or cross-attention to detect physical anomalies. In contrast, MLLM prompt injection constitutes a structural semantic hijack rather than a physical signal aberration. Therefore, CM-PIUG adopts a logic/graph-driven unification. Instead of continuous feature alignment, we employ contextual semantic-equivalence reduction to map multi-source inputs into discrete, normalized symbolic nodes. This allows the construction of a deterministic Attack Surface Graph governed by causal logical rules, enabling explicit risk reachability analysis and zero-shot structural coverage over novel syntactic combinations rather than relying on latent-space distribution shifts.

3. Method

3.1. The CM-PIUG framework

We propose CM-PIUG, a defense framework for detecting and mitigating prompt injection in multimodal settings. The target system is a prompt-centric pipeline comprising multimodal parsing, prompt assembly, task execution (including tool/plugin calls), and output inspection. As shown in Fig. 2, CM-PIUG includes four modules: input parsing, attack-graph modeling, game-theoretic defense decision-making, and output assessment. We denote a user query as $x = x^{(m)}{}_{m\in\mathcal{M}}$, where $\mathcal{M}$ is the modality set (text, image, audio, graph); the parser converts




Fig. 2. CM-PIUG: Unified modeling of prompt injection attacks and game-theoretic defense strategies for multimodal large language models.

multimodal payloads into structured content for downstream prompting and execution.

Under a black-box assumption, the attacker can only manipulate the input x (including cross-modal compositions and multi-step narrative induction) to trigger security events. Without changing foundation-model parameters, the defender selects a compositional defense from a deployable set D (e.g., filtering, prompt hardening, context substitution, output constraints, and auditing), balancing security utility and overhead.

Our zero-shot detection targets unseen attack compositions: if a new attack can be decomposed into atomic manipulations and control relations expressible in the pipeline, its risk can be detected via graph-computable checks. If fundamentally new atomic capabilities appear beyond assumed interfaces/behaviors, coverage can be extended by incrementally updating the rule base and graph patterns. Under this setting, CM-PIUG consists of three core components: unified attack-surface modeling, zero-shot detection, and strategy generalization/deployment. First, following the attack-graph paradigm, we abstract control points and dependencies in a prompt-centric system into a unified attack-surface graph. Built via system-structure and rule-driven derivation—rather than enumerating known patterns—this design improves coverage and analyzability and provides a common semantic space for heterogeneous cross-modal inputs. Second, because OCR/ASR-extracted text from images or audio can differ superficially from native text, we formalize contextual semantic equivalence and derive equivalence-driven graph fusion rules to preserve consistent reasoning while reducing representation-induced false positives. Finally, we define risk criteria on the unified surface and develop a zero-shot detector (Algorithm 1). We further cast defense selection as a hierarchical leader-follower process and introduce a mean-field approximation to handle the joint complexity of large attack payloads and combinatorial defenses, yielding a scalable Stackelberg-Mean Field Equilibrium (SMFE) mechanism for offline policy computation and online matching (Algorithm 2). Together, these components enable consistent attack-surface characterization, robust cross-modal risk assessment, and fast deployment via offline learning and lightweight online decisions.

3.2. Prompt injection unified attack surface modeling

To address **RQ1**—i.e., to characterize cross-modal risks consistently and avoid modality-fragmented threat modeling—we represent a prompt-centric system with a unified attack-surface graph. Leveraging the expressive power of attack graphs (AGs), our formulation captures multi-stage dependency structures among critical system components and atomic adversarial capabilities, enabling systematic exploration of feasible attack chains under explicit assumptions while retaining only the substructures most relevant to security objectives—thereby supporting both analyzability and practical use. Originating from early work on network vulnerability path analysis and automated AG generation, this paradigm models attacker-reachable paths within formally specified system models. Over time, it has evolved into (i) logical attack graphs, which encode and infer dependencies via rules or inference from configurations and policies, and (ii) probabilistic extensions (e.g., Bayesian attack graphs) that incorporate uncertainty to assess risk under incomplete information and dynamic evidence.

3.2.1. Formal definition of the unified attack-surface graph

Following the foundational theory of unified attack-surface modeling in Supplementary Material S1.1, an attack graph captures the core semantics of reachable risks through a dependency structure. We define the unified attack surface for cross-modal prompt injection as a




Fig. 3. Comparative defense effectiveness across tasks: Average asr reduction (bars) and worst-case asr (lines).

typed directed graph $\mathcal{G} = (\mathcal{V}, \varepsilon, \tau, \mathcal{R}, \mathcal{I}, \mathcal{T})$. Here, $\mathcal{V}$ denotes the node set, and $\varepsilon = \mathcal{V} \times \mathcal{V}$ is the set of dependency edges. The function is a node-type mapping that distinguishes different categories of nodes, including input semantic units, intermediate variables produced during prompt parsing, task execution/tool invocation events, key control points, and security objectives. The set $\mathcal{R}$ contains atomic manipulation/inference rules. The set $\mathcal{I} \subseteq \mathcal{V}$ consists of initial fact nodes instantiated by the current system configuration and the given input instance. Finally, $\mathcal{T} \subseteq \mathcal{V}$ is the set of target nodes corresponding to security-violation goals (such as unauthorized tool invocation, policy bypass, or task deviation).

3.2.2. *Rule-based graph generation: From the system pipeline to a dependency structure*

To overcome the limited coverage and weak transferability of enumerating attack instances, we construct attack graphs using a rule- and logic-based paradigm. We encode triggerable manipulations and control dependencies in the prompt-system pipeline as formal rules, and recover dependency structures via logical inference, allowing structural extrapolation to unseen attacks as long as they remain within the defined rule base. This design follows logic-based AG frameworks such as MulVAL, which model configurations, vulnerabilities, and attack semantics with Datalog/Horn-like rules and generate dependencies through automated inference, improving efficiency and scalability. We express each atomic manipulation / security-semantic rule in Horn form $r : \bigwedge_{k=1}^{K} pre_k \Rightarrow post$, where pre_k and post are typed predicate nodes in $\mathcal{V}$ (or parameterized instances). Here, the premise (pre) specifies conditions to trigger a manipulation during input processing, prompt parsing, or task execution, while the conclusion (post) denotes the resulting system semantic effect (e.g., overriding primary instructions, altering tool parameters, or entering high-risk execution). By forward chaining and logging derivations, we obtain edges in ε: if an instantiated rule r derives post from pre_k, we add an edge. Thus, cross-modal inputs do not require separate graphs; instead, different modalities instantiate the same shared node/rule schemas within one rule base.

3.2.3. *Semantic-equivalence-driven cross-modal graph fusion*

A central challenge in unified cross-modal modeling lies in the fact that text fragments extracted from non-textual carriers—such as images and audio—via OCR or ASR often exhibit significant surface-level divergence from native textual prompts. Constructing the graph solely at the lexical level risks fragmenting its structure and introducing spurious distinctions based on superficial differences rather than meaningful semantic variation. To address **RQ2**, we introduce in Supplementary Material S1.2 a semantic equivalence criterion grounded in contextual entailment and bidirectional (mutual) entailment, thereby establishing "meaning agreement" as the foundational unit for cross-modal alignment. This approach is theoretically informed by the literature on semantic entropy, which emphasizes uncertainty and inconsistency at the level of meaning rather than surface form, and operationalizes meaning-based aggregation through entailment-driven semantic clustering. Given a context C (which may include the system prompt, tool schemas, task




Fig. 4. Detection accuracy and f1 score across defense methods.




Fig. 5. Effectiveness of defenses against BAP attacks.

objectives, and safety policies), we define a contextual entailment decision function: $Ent_C(u \Rightarrow v) \in \{0, 1\}$. We then define semantic equivalence under context C via bidirectional entailment (mutual entailment):

$$u \equiv_C v \Leftrightarrow Ent_C(u \Rightarrow v) = 1 \wedge Ent_C(v \Rightarrow v) = 1 \quad (1)$$

This criterion follows the entailment-based semantic clustering intuition commonly used in semantic-uncertainty/semantic-entropy settings, where meaning-level agreement is determined by mutual entailment rather than surface-form matching. Accordingly, we introduce an equivalence-class reduction operator $\mathcal{N}_C(\cdot)$ for graph fusion: for any textual semantic unit u, we map it to its canonical representative $\hat{u} = \mathcal{N}_C(u)$, and enforce a shared representation in the attack-surface graph by assigning all members of the same equivalence class to a single semantic node $v(\hat{u})$. Consequently, for an image input I with OCR-extracted




Fig. 6. Comparison of attack success rate (ASR) with and without defense under different attack methods on citeseer and cora datasets.




Fig. 7. Stackelberg-MFG equilibrium stability & worst-case risk.

text u_I and a native textual segment u_T, if $u_I \equiv_C u_T$, they are mapped to the same Input-typed semantic node in $\mathcal{G}$, preventing carrier-dependent graph divergence. Otherwise, we retain two distinct nodes and explicitly encode the potential pathway deviation induced by parsing discrepancies via dedicated rules and edges. This mechanism provides a decidable semantic-alignment basis for a unified cross-modal attack surface, thereby addressing how to formally define semantic equivalence between OCR-extracted text and native prompts.

Proposition 1 (Reachability invariance under semantic equivalence)**.** *Let $u \equiv_C v$. Suppose that, in the rule base $\mathcal{R}$, every trigger condition involving u or v depends only on their meaning under context C (rather than their surface strings). Then replacing u with v does not change the set of rule instances that can be activated on the graph, and therefore does not change the reachability judgment of the target set $\mathcal{T}$.*

This proposition guarantees that the meaning-level alignment used for cross-modal graph fusion neither introduces spurious risk structures nor removes risks that should be derivable under the same contextual semantics.

The overall time complexity of Algorithm 1 comprises three components: semantic-equivalence reduction, rule-driven instance graph construction, and risk propagation with evidence-chain backtracking on the instantiated graph.

Overall, the total time complexity is $O(K^2 + |F|^2 \cdot |R| + |V| + |E|)$, and the space complexity is $O(|V| + |E|)$. A rigorous derivation is provided in Supplementary Material S3.1 (Eq. (B.1)). Under typical graph sizes($|V| \approx 150$, $|E| \approx 380$), BFS-based risk propagation takes about 3.2 ms, accounting for roughly 10% of the total detection latency(~35 ms) (see the detailed breakdown in Supplementary Figure B.1). This confirms that the principal computational bottleneck lies in the rule-closure/dependency-derivation stage rather than in risk scanning.

3.3. Compositional defense strategy generalization: Joint Stackelberg-MFG modeling and solution

In cross-modal prompt injection, defense generalization requires not only detecting unseen compositional attacks but also reusing transferable policies across modalities, payload strengths, and shifting attack-composition distributions. Yet, jointly modeling the defender's compositional strategies (multiple mechanisms, switching rules, adaptive thresholds) and the attacker's perturbations (narrative manipulations, multi-step compositions) in a classical bilevel Stackelberg framework quickly explodes the strategy space and becomes intractable. To address **RQ3**, we retain the leader-follower (commitment-response) structure while accounting for population-level effects induced by many attack




Fig. 8. Online response latency, throughput & CPU overhead comparison (Concurrent = 32, Total Requests = 10k).

Algorithm 1 Open-world Zero-shot Detection on CM-PIUG.

Input: unified attack surface $\mathcal{G} = (\mathcal{V}, \varepsilon, \tau, \mathcal{R}, \mathcal{I}, \mathcal{T})$, system facts F_{sys}, context C, input x, threshold θ, weight $\alpha \in [0, 1]$

Output: Flag(x), Risk(x), evidence chain π^*

// Note: Zero-shot here refers to unseen compositions/sequences over a fixed primitive rule set $\mathcal{R}$; when genuinely new primitives emerge, $\mathcal{R}$ is updated while Algorithm 1 remains unchanged.

$Cand \leftarrow \text{Parse}(x)$
$(F(x), \text{Conf}_{\equiv}) \leftarrow \text{SemanticNormalize}(Cand, C, \mathcal{N}_C)$
$F^*(x) \leftarrow \text{Closure}\left(F_{\text{sys}} \cup F(x), \mathcal{R}\right)$
$(\widehat{\mathcal{G}}_x = (\widehat{V}, \widehat{E}), \mathcal{I}_x) \leftarrow \text{DeriveGraph}(F^*(x))$
for each $(u, v) \in \widehat{E}$ **do**
  $\text{Conf}_{\mathcal{R}}(u \Rightarrow v) \leftarrow \text{RuleSupport}(u \Rightarrow v, F^*(x), \mathcal{R})$
  $w_{uv} \leftarrow \alpha \cdot \text{Conf}_{\mathcal{R}}(u \Rightarrow v) + (1 - \alpha) \cdot \text{Conf}_{\equiv}(u, v)$
end for
$(Risk(x), \pi^*) \leftarrow \text{BestEvidencePath}\left(\widehat{\mathcal{G}}_x, \mathcal{I}_x, \mathcal{T}, w\right)$
if $Risk(x) \geq \theta$ **then**
  return $(1, Risk(x), \pi^*)$
else
  return $(0, Risk(x), \phi)$
end if

instances and diverse payload configurations. Specifically, we adopt a major-player mean-field game (MFG) formulation: the defender is a commitment-capable major player, and attackers form a population of weakly interacting minor players summarized by a mean-field distribution. This compresses high-dimensional many-to-many interactions into a tractable "individual-distribution" form, enabling scalable equilibrium computation. The formulation follows major-minor MFG theory, including foundational work by Lasry and Lions, as reviewed in Supplementary Material S1.3, and underpins our scalable solution method.

3.3.1. Leader-follower mean-field modeling on the unified attack surface

(1) Strategy spaces and observable inputs. Given Algorithm 1, we obtain the instantiated attack subgraph $\widehat{\mathcal{G}}_x$, the risk score Risk(x), and the evidence chain $\pi^*(x)$. To convert input-level evidence into decision variables that generalize across modalities, we construct a distribution-level feature (a mean-field signal):

$$m = \Phi(\widehat{\mathcal{G}}_x, \pi^*(x), Risk(x)) \in \mathcal{M} \tag{2}$$

Here, $\Phi(\cdot)$ aggregates mechanism-level statistics of cross-modal attacks on the unified surface, e.g., proportions of activated atomic rule categories, contamination frequency of key parsing nodes, concentration of high-risk execution targets, and uncertainty mass from semantic entropy. Importantly, m is label-free: it is driven by evidence at the mechanism level and thus supports cross-modal transfer. The defender (leader) selects $d \in \mathcal{D}$, a deployable compositional defense (e.g., a configuration vector or mixture weights over filtering, rewriting, isolation, auditing, and tool-parameter constraints). Each minor player (the i-th attack instance) selects $a_i \in \mathcal{A}$, corresponding to input perturbations and multi-step compositions on the unified




Fig. 9. Ablation comparison of the rule-based mechanism, the learned component, and the hybrid strategy.

surface (e.g., payload form, narrative orchestration, injection entry points, and chained-manipulation strength).

(2) Mean-field distribution and population effects. Let $\mu \in \mathcal{P}(\mathcal{M})$ denote the distribution of the attacker population over the distribution-level feature space $\mathcal{M}$, capturing the aggregate statistics of "attack pressure / compositional patterns" in the current environment. The distribution μ absorbs both (i) congestion or prevalence effects induced by large volumes of similar attacks and (ii) population-level migration effects, where attackers shift toward alternative entry points after certain defenses are deployed. This is consistent with the core principle of mean-field games: the influence of other individuals is not modeled pairwise, but is aggregated through the distribution μ.

3.3.2. Followers' mean-field equilibrium and Stackelberg-MFG equilibrium (SMFE)

(1) Followers' (attackers') mean-field equilibrium under a committed defense. Given the defender's committed policy $\pi_D(d|m)$ (possibly randomized), the expected utility of a representative attacker under the mean-field distribution μ is

$$J_A(\pi_A; \pi_D, \mu) = E[R_A(m, a, d) - \lambda_A C_A(a) - \eta_A \Omega_A(\mu, m)] \tag{3}$$

Here, R_A denotes the attack reward (correlated with attack success, unauthorized activation, or target-reach intensity), C_A captures attack costs (perturbation budget, composition length, or detection exposure), and Ω_A represents congestion/competition/migration effects induced by the population distribution (overly concentrated payload patterns becoming easier to block). The attackers' mean-field equilibrium is characterized by the standard two-part closure: (i) Best response: $\pi^* \in \arg\max_{\pi_A} J_A(\pi_A; \pi_D, \mu)$; (ii) Consistency (fixed-point) condition: $\mu = T(\mu; \pi_A^*, \pi_D)$, such as the population distribution must coincide with the distribution induced by the representative optimal response in closed loop. This is the canonical "individual optimality and distribution fixed point" structure of mean-field (Nash) equilibria in large, weakly coupled populations.

(2) Stackelberg-MFG equilibrium (SMFE).

Anticipating that the attacker population will settle into a mean-field equilibrium under its committed policy, the defender chooses π_D to minimize its own risk-cost objective: $\pi_D^* \in \arg\min_{\pi_D} J_D(\pi_D, \mu^{\pi_D})$, $s.t.$ $(\pi_A^{\pi_D}, \mu^{\pi_D})$ satisfies the MFG closure above. The defender's expected objective is defined as

$$J_D(\pi_D, \mu) = \mathbb{E}[L(Risk, d) + \lambda_D C_D(d) + \eta_D \Omega_D(\mu, d)] \tag{4}$$

Here, $L(\cdot)$can be induced by Algorithm 1's risk score / evidence-chain strength (treating Risk(x) or the strongest-chain strength as residual risk), $C_D(d)$ denotes deployment overhead (latency, compute, functionality loss, false-positive cost, etc.), and Ω_D captures congestion/switching penalties (excessive rewriting degrading usability). This bilevel commitment-equilibrium-response structure is precisely the SMFE (Stackelberg Mean Field Equilibrium) objective adopted in this paper. It is consistent with major-minor (leader-population) mean-field formulations and can be solved scalably via standard single-level reformulations (penalization or equivalent constraints) in numerical implementations.

Algorithm 2 follows a two-stage design: offline solving and online matching. Offline, it iterates an outer-loop commitment update with an inner-loop mean-field closure to compute deployable defenses and store them as a reusable policy library. Offline cost scales approximately linearly with the number of outer iterations and the inner fixed-point

iterations needed for mean-field equilibrium; see Supplementary Material S3.2 for details. Online, the system only retrieves and executes policies from the precomputed library, so overhead is dominated by fast lookup and a single forward pass, meeting strict low-latency deployment requirements.

Algorithm 2 Offline Stackelberg–MFG Solving and Online Policy Matching.

Input: unified attack surface $\mathcal{G}$; defense action set $\mathcal{D}$; attack action set $\mathcal{A}$; distribution-level feature map $\Phi(\cdot)$; initial defender policy $\pi_D^{(0)}$; outer step size η; inner stopping threshold ε_{in}; outer stopping threshold ε_{out}; maximum iterations $K_{\text{in}}, K_{\text{out}}$.

Output: converged defender commitment policy $\pi_D^*(d \mid m)$; online matching rule induced by Φ and π_D^*.

// Offline phase: approximate SMFE solving (inner MFG closure and outer leader update)

$k \leftarrow 0$
while $k < K_{\text{out}}$ **do**
  Initialize distribution $\mu^{(0)}$ and attacker policy $\pi_A^{(0)}$
  for $j \leftarrow 0$ **to** $K_{\text{in}} - 1$ **do**
    $\pi_A^{(j+1)} \leftarrow \arg\max_{\pi_A} J_A\big(\pi_A; \pi_D^{(k)}, \mu^{(j)}\big)$
    $\mu^{(j+1)} \leftarrow \mathcal{T}\big(\mu^{(j)}; \pi_A^{(j+1)}, \pi_D^{(k)}\big)$
    if $\big\|\mu^{(j+1)} - \mu^{(j)}\big\| \le \varepsilon_{\text{in}}$ **then**
    end if
  end for
  $\mu^{*(k)} \leftarrow \mu^{(j+1)}, \quad \pi_A^{*(k)} \leftarrow \pi_A^{(j+1)}$
  $\pi_D^{(k+1)} \leftarrow \Pi_{\Delta(D)}\Big(\pi_D^{(k)} - \eta \nabla_{\pi_D} J_D(\pi_D, \mu)\Big|_{\pi_D=\pi_D^{(k)}, \mu=\mu^{*(k)}}\Big)$
  if $\big\|\pi_D^{(k+1)} - \pi_D^{(k)}\big\| \le \varepsilon_{\text{out}}$ **then**
    $\pi_D^* \leftarrow \pi_D^{(k+1)}$
    return $\big(\pi_D^*, \text{MatchingRule}(\Phi, \pi_D^*)\big)$
  end if
  $k \leftarrow k + 1$
end while
$\pi_D^* \leftarrow \pi_D^{(k)}$
return $\big(\pi_D^*, \text{MatchingRule}(\Phi, \pi_D^*)\big)$

// Online phase: evidence-chain–conditioned fast matching

for each online input x **do**
  Run Algorithm 1 to obtain $(\widehat{\mathcal{G}}_x, \pi^*(x), Risk(x))$
  Construct the mean-field feature: $m \leftarrow \Phi\big(\widehat{\mathcal{G}}_x, \pi^*(x), Risk(x)\big)$
  Select (or sample) the defense action: $d^* \leftarrow \arg\max_d \pi_D^*(d \mid m)$
  ExecuteDefense(d^*)
  return d^*
end for

4. Experiments

4.1. Experimental setup

Models and Datasets: To comprehensively evaluate our framework, we cover multiple modalities, including text-only, vision-language, and graph-based prompt-learning tasks. (1) Text-based Tasks: We evaluate three LLMs to capture scale/architecture effects: DeepSeekR (8B), ChatGPT-3.5, and ChatGPT-4o. ChatGPT-3.5/4o are accessed via the official OpenAI API, with requests executed between October and December 2024, using fixed sampling settings (temperature = 0.7, top-p = 0.9, max-tokens = 4096). Tool use/function calling and auxiliary features are disabled for a consistent inference interface. To reduce transient noise, each request is retried up to three times on timeouts/server errors (1–2 s intervals); requests failing all retries are excluded. We keep OpenAI's default safety mechanisms enabled to reflect real-world deployments. (2) Vision-Language Tasks: We use open-source LVLMs that jointly process text and images, including LLaVA, MiniGPT-4, InstructBLIP (7B), and Qwen2.5-VL (7B). (3) Graph-based Tasks: Prompts are generated/injected using GraphPrompt with the GNN backbone following baseline attack configurations.

Defense Implementation: We implement CM-PIUG for unified modeling and game-theoretic defense. During inference, the detector analyzes graph-prompt embeddings to identify potential backdoor triggers, and processes user prompts (text/image) through a unified adversarial-prompt detection module. This module combines a fine-tuned LLM with a multimodal encoder to extract discriminative features and flag malicious inputs. Similar to DataSentinel, the detector is adversarially trained on multimodal attack samples to improve robustness against adaptive threats. All evaluations use publicly released model weights. The datasets are summarized in Table 1.

4.2. Baseline experiments of cross-modal detection

4.2.1. Attack and defense performance in textual scenarios

We evaluate LLM vulnerability to prompt injection in text-only tasks and the effectiveness of our defense. Table 2 reports attack success rates (ASR) for DeepSeek-R1, ChatGPT-3.5, and ChatGPT-4o under five prompt-injection attacks across four textual tasks with no defenses. The results show a severe, system-wide vulnerability: average ASR exceeds 0.7 across models, with some tasks above 0.9. The Combined Attack is most destructive, with mean success approaching or reaching 0.9 across the three models—substantially higher than any single-strategy attack—highlighting the power of multi-path injection. Even the Naive Attack attains ASR near 0.7, indicating high susceptibility without protection. Overall, prompt injection is not isolated but pervasive across models and tasks.

Fig. 3 compares the cross-task performance of various defense methods. Conventional rule-based detectors and known-answer baselines are effective only against simple attacks, achieving an average attack success rate (ASR) reduction of less than 30%. DataSentinel performs well in certain scenarios; however, under compositional attacks, the residual ASR remains above 30%. In contrast, our CM-PIUG consistently achieves significantly lower ASR, with an average absolute reduction of 60–76 percentage points, and reduces the worst-case residual ASR to 32–50%, demonstrating a clear advantage in more challenging and complex attack settings.

Furthermore, Fig. 4 shows that CM-PIUG outperforms baseline methods in detection accuracy (93%) and F1-score (0.90), compared with Rule-based detection (0.65/0.60) and DataSentinel (0.78/0.75). This indicates stable discriminative capability under diverse attack conditions. By combining attack-path modeling with critical-edge blocking mechanisms, CM-PIUG not only substantially lowers attack success rates but also maintains high detection precision and system availability under strong adversarial conditions, highlighting the effectiveness and generalizability of the unified defense strategy.

4.2.2. Cross-modal attack and defense effectiveness

In vision-language cross-modal settings, prompt injection attacks are significantly more disruptive than their unimodal counterparts. Since multimodal models rely jointly on visual and textual inputs, adversaries can exploit the coupling between images and text to bypass safety mechanisms in a more covert manner. As illustrated in Fig. 5, under the no-defense baseline, the mean attack success rates (ASR) of the evaluated models under the Bi-Modal Adversarial Prompt (BAP) attack are 79.48% for LLaVA, 68.17% for MiniGPT-4, 67.52% for InstructBLIP, and 65.84% for Qwen2.5-VL, demonstrating that cross-modal attacks can effectively subvert normal model behavior at high rates in the absence of protective measures.When existing defense mechanisms are enabled, both JailGuard (averaged) and ECSO achieve partial suppression of ASR, resulting in an average reduction of approximately 5–14 percentage points across models. Nevertheless, the residual ASR remains substantial (> 55%), underscoring a clear limitation of current defenses in mitigating cross-modal attacks that leverage semantically coupled image-text inputs.

Table 1
Summary of Datasets, Splits, and Sample Counts used in Experiments.

Modality	Dataset	Task Description	Split / Setting	Sample Count (N)
Text	HSOL	Hate Speech Detection	Zero-shot Eval (Random Sample)	1000
	RTE	Natural Language Inference	Zero-shot Eval (Validation Set)	1000
	SST-2	Sentiment Analysis	Zero-shot Eval (Validation Set)	872
	SMS Spam	Spam Classification	Zero-shot Eval (Test Set)	1000
Vision-Language	SafetyBench	13 Safety Scenarios	Standard Eval Split	1300 (100/scenario)
Graph	Cora	Citation Network Classification	Standard Split (Train/Val/Test)	2708
	CiteSeer	Citation Network Classification	Standard Split (Train/Val/Test)	3327

Table 2
ASR of baseline text attacks under no-defense setting.

Model	Dataset	Naive Attack [30]	Special-Symbol Attack [31]	Context-Ignoring Attack [1]	Fabricated Completion Injection [32]	Combined Attack [1]
DeepSeekR1	RTE	0.65	0.80	0.77	**0.84**	0.73
	SST2	0.62	0.85	0.88	0.82	**0.97**
	HSOL	0.70	0.46	0.86	0.89	**0.95**
	SMS Spam	0.86	0.72	0.90	0.77	**0.92**
	Average	**0.71**	**0.70**	**0.85**	**0.83**	**0.89**
ChatGPT3.5	RTE	0.79	0.81	0.79	0.72	**0.89**
	SST2	**0.94**	0.83	**0.94**	0.72	**0.94**
	HSOL	**0.85**	0.75	0.75	0.74	0.83
	SMS Spam	0.83	0.91	0.66	0.51	**0.93**
	Average	**0.85**	**0.83**	**0.79**	**0.67**	**0.90**
ChatGPT4o	RTE	0.86	**0.93**	0.83	0.83	0.87
	SST2	0.91	0.96	**0.96**	0.94	0.92
	HSOL	0.66	0.66	0.64	0.58	**0.80**
	SMS Spam	0.90	0.93	0.93	0.76	**0.96**
	Average	**0.82**	**0.85**	**0.84**	**0.78**	**0.89**

Table 3
Cross-dataset migration defense performance Evaluation.

Target Dataset	Transfer Type	Method	ASR(%)	FPR(%)	Gen. Gap(%)
SafetyBench	In-Domain	JailGuard	18.50	7.20	–
		CM-PIUG	6.40	4.50	–
MM-SafetyBench	Scene Transfer	No Defense	78.20	–	–
		JailGuard	42.60	14.80	24.10
		ECSO	35.10	12.50	16.60
		CM-PIUG	11.80	5.80	5.40
AdvBench	Modality Transfer (Multi → Text)	No Defense	82.50	–	–
		JailGuard	28.40	8.90	9.90
		CM-PIUG	8.20	4.90	1.80
JailbreakHub	Morphology Transfer (Unseen Patterns)	No Defense	91.40	–	–
		JailGuard	55.70	18.20	37.20
		ECSO	48.30	15.60	29.80
		CM-PIUG	14.50	6.20	8.10

Note. Gen. Gap is defined as Target ASR - Source ASR. CM-PIUG is calibrated only on SafetyBench (source domain), and No Defense is reported as the risk reference line.

In contrast, our proposed CM-PIUG framework achieves consistently stronger suppression of cross-modal attacks across all evaluated backbones. Specifically, CM-PIUG reduces the attack success rate (ASR) to below 20% for every model—approximately 19.09% on LLaVA, 13.21% on MiniGPT-4, 12.45% on InstructBLIP, and 10.92% on Qwen2.5-VL—representing an absolute reduction of approximately 55–60 percentage points compared to the no-defense baseline. These results demonstrate that CM-PIUG significantly mitigates the effectiveness of vision-language prompt injection attacks by simultaneously capturing the intrinsic semantic alignment between images and text and the structural patterns of adversarial prompts, thereby providing substantially more robust protection than conventional defense mechanisms.

4.2.3. Adaptability in graph prompt learning scenarios

In this section, we further validate the proposed method's cross-modal adaptability in graph prompt learning tasks using two benchmark graph datasets, Cora and CiteSeer. The experiments evaluate against three representative graph prompt injection attacks recently introduced: CrossBA [6], TGPA [3], and MetaGpro [2]. CrossBA [6] proposes a cross-context backdoor attack by optimizing trigger subgraphs during the pre-training phase and poisoning the GNN encoder to implant a backdoor. TGPA [3] represents a typical Trojan-style prompt attack, where embedding a trigger into the graph prompt alone achieves high attack success rates and remains robust against downstream fine-tuning. MetaGpro [2] leverages an adaptive trigger generator to synthesize triggers that closely resemble the target node features, thereby enhancing the stealthiness of the backdoor attack. To counter these attacks, the proposed CM-PIUG framework integrates graph prompt embeddings with graph structural features as joint inputs into a cascaded LLM-based detection model. This design enables the system to capture cross-modal adversarial characteristics more effectively and significantly improves the robustness of defenses against novel graph prompt injection threats.

Table 4
Summary of cross-model generalization performance and stress-test evaluation.

Evaluation Dimension	Scenario/Model	No Defense ASR (%)	JailGuard ASR (%)	ECSO ASR (%)	CM-PIUG ASR (%)	CM-PIUG F1-Score
Cross-Model	LLaVA-1.5 (13B)	79.5	68.2	70.6	19.1	0.88
	MiniGPT-4 (7B)	68.2	61.6	64.9	13.2	0.91
	InstructBLIP (7B)	67.5	58.0	60.3	12.5	0.89
	Qwen2.5-VL (7B)	65.8	56.0	57.4	10.9	0.92
Stress Test	Missing Visual	45.2	38.5	42.1	14.2	0.85
	Noise redundancy (15% Noise)	72.8	65.4	55.2	18.6	0.84
	Long link (Step > 5)	88.4	72.1	68.4	15.7	0.82
Average behavior Overall Average		69.6	60.0	59.8	14.9	0.87

The experimental results, as illustrated in Fig. 6, consistently demonstrate the significant defensive advantage of the proposed method across different datasets and attack scenarios.

4.3. Discussion: Scalability, deployability, and generalization of CM-PIUG

We discuss the scalability and deployment practicality of CM-PIUG when the defender's combinatorial strategy space and the attacker space expand simultaneously. In open-world multimodal systems, effective protection cannot rely on a single fixed rule; instead, defenses must be composed across multiple atomic actions (e.g., filtering, rewriting, auditing, and multimodal alignment). However, conventional game-solving methods often become unstable or intractable as the strategy space grows exponentially. To evaluate feasibility, we progressively enlarge the defense library from a small static set to a large combinatorial space and assess three criteria: worst-case risk suppression, equilibrium stability, and online latency.Detailed experimental results are provided in Supplementary Material S6.

Scalable near-equilibrium solving under expanding strategy spaces. As shown in Fig. 7, expanding the defender's action space from ($|A_d| \approx 15$) to ($|A_d| \approx 10^4$) yields a pronounced security gain: the worst-case ASR drops from 0.825 to 0.092, indicating that richer compositions of atomic defenses can effectively constrain the attacker even under optimal responses. Importantly, the Stackelberg-MFG solver remains stable at scale: under the SMFE-Large setting, the mixed-strategy drift over the last iterations is $\Delta\mu = 5.2 \times 10^{(} - 3)$, substantially lower than the Greedy-Myopic baseline (8.5×10^{-2}). This supports the role of the mean-field formulation in smoothing large-population interactions and preventing oscillatory dynamics. From an engineering perspective, although offline solving time increases (up to 25 minutes in our largest setting), this cost is amortized offline, while the online stage remains lightweight (latency rising only from 2.1 ms to 6.2 ms), enabling real-time deployment.

Online latency, throughput, and resource overhead. We further quantify deployment overhead under high-load service conditions (Concurrent = 32, Total Requests = 10k) and compare against No Defense, JailGuard, and ECSO. As summarized in Fig. 8, CM-PIUG maintains defense-only overhead within 50 ms/request, decomposed into 35 ms for graph construction and 15 ms for strategy matching, accounting for only 5.7% of end-to-end P50 latency (870 ms). In contrast, JailGuard introduces a large online burden due to multi-round querying (defense cost 3850 ms), pushing end-to-end latency beyond 4.6 s. CM-PIUG also preserves throughput (35.5 req/s vs. 38.2 req/s for the baseline; 7% drop), and remains more stable than ECSO (30.5 req/s) and JailGuard (6.1 req/s) under concurrency. Resource-wise, CM-PIUG exhibits modest CPU peaks (39%) and small memory overhead (65 MB), avoiding the large memory footprint of multi-round interaction methods (e.g., JailGuard 3800 MB), which is favorable for GPU-memory-constrained and high-density serving environments.

Generalization across datasets and models. Under a strict Source-to-Target direct transfer protocol (calibrated only on SafetyBench), CM-PIUG shows substantially better cross-dataset robustness than baselines. As reported in Table 3, CM-PIUG limits ASR to 11.8% on MM-SafetyBench, 8.2% on AdvBench (multi→text transfer), and 14.5% on JailbreakHub, while maintaining low FPR (5.8%, 4.9%, 6.2%, respectively). Compared to JailGuard and ECSO, the generalization gap is consistently smaller, suggesting that anchoring defense decisions to invariant attack-surface mechanisms (rather than mutable sample-level semantics) mitigates cross-domain performance collapse. Cross-model evaluation further confirms backbone-agnostic behavior: across four representative MLLMs, CM-PIUG suppresses residual ASR to <20% and achieves strong F1 scores, serving as an external safety guardrail even for smaller or weaker-aligned models (Table 4). Stress tests on missing modality, noisy redundancy, and long-chain induction indicate that CM-PIUG retains effectiveness under incomplete or noisy signals and maintains detection reliability for deeper induced chains.

Ablation: rule-based backbone vs. learned scorer. Finally, the ablation results in Fig. 9 clarify the division of labor between the structured mechanism and the learned component. The Rules-only variant preserves mechanism-level generalization but exhibits higher false positives under OCR/ASR noise (FPR 7.5%). The Learned-only variant performs competitively in-distribution but degrades in reliability and interpretability, with higher false alarms (FPR 9.8%) and no structured evidence chains. The Hybrid (full system) achieves the best trade-off, reducing ASR to 12.7% and FPR to 5.1%, validating that formal reachability reasoning provides generalization and auditability, while the learned scorer absorbs semantic/recognition uncertainty.

5. Conclusion

This paper proposes CM-PIUG, a unified framework for attack-surface modeling and game-theoretic defense against cross-modal prompt injection in open-world MLLMs. CM-PIUG formalizes the prompt pipeline—input processing, prompt parsing, and task execution—into an attack-surface graph, and uses contextual semantic-equivalence reduction to map heterogeneous modalities (e.g., OCR-extracted text, native text, and graph prompts) into a normalized semantic space, mitigating modality-induced fragmentation. Building on this foundation, a Stackelberg mean-field equilibrium (SMFE) formulation turns defense generation into a scalable two-phase workflow: offline equilibrium closure and online fast matching. This design substantially reduces attack success rates while producing auditable evidence chains, balancing security effectiveness with deployment efficiency. CM-PIUG's coverage is currently bounded by the completeness of the atomic rule base and by semantic extraction accuracy under extreme noise in upstream perception modules. Future work will enhance adaptivity via log-driven automatic rule expansion and dynamic game-strategy updates, and extend coverage to more complex tool-chain orchestration and multi-agent interaction settings to address evolving cross-modal threats.

CRediT authorship contribution statement

Gaoyuan Quan: Writing – original draft, Methodology, Investigation, Formal analysis, Data curation, Conceptualization; **Zhiyong Zhang:** Supervision, Resources, Project administration, Funding acquisition; **Yanting Zhang:** Validation, Investigation, Formal analysis;

Weiguo Wang: Investigation, Formal analysis; **Junchang Jing:** Writing – review & editing, Formal analysis; **Mengdan Xue:** Validation, Data curation.

Data availability

Data will be made available on request.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Acknowledgement

This work was supported in part by Key Research and Development Plan Special Project of Henan Province Grant (No.241111211400); in part by the Henan Province Science and Technology Research Project (No. 242102211077); in part by the Henan Province University Key Scientific Research Project (No. 23A520008).

Supplementary material

Supplementary material associated with this article can be found in the online version at 10.1016/j.patcog.2026.113661.

References

[1] Y. Liu, Y. Jia, R. Geng, J. Jia, N.Z. Gong, Formalizing and benchmarking prompt injection attacks and defenses, in: 33rd USENIX Security Symposium (USENIX Security 24), 2024, pp. 1831–1847.
[2] J. Jia, J. Yu, D. Wu, C. Wu, H. Zhu, L. Wang, Prompt as a double-edged sword: a dynamic equilibrium gradient-assigned attack against graph prompt learning, in: Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining, vol. 2, 2025, pp. 1049–1060.
[3] M. Lin, Z. Zhang, E. Dai, Z. Wu, Y. Wang, X. Zhang, S. Wang, Are you using reliable graph prompts? trojan prompt attacks on graph neural networks, in: Proceedings of the 31St ACM SIGKDD Conference on Knowledge Discovery and Data Mining, vol. 2, 2025, pp. 1729–1740.
[4] Z. Ying, A. Liu, T. Zhang, Z. Yu, S. Liang, X. Liu, D. Tao, Jailbreak vision language models via bi-modal adversarial prompt, IEEE Trans. Inf. Forensics Secur. (2025). https://doi.org/10.1109/TIFS.2025.3583249.
[5] L. Wang, Z. Ying, T. Zhang, S. Liang, S. Hu, M. Zhang, A. Liu, X. Liu, Manipulating multimodal agents via cross-modal prompt injection, in: Proceedings of the 33rd ACM International Conference on Multimedia, 2025, pp. 10955–10964.
[6] X. Lyu, Y. Han, W. Wang, H. Qian, I. Tsang, X. Zhang, Cross-context backdoor attacks against graph prompt learning, in: Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, 2024, pp. 2094–2105.
[7] Y. Xie, M. Qiu, Y. Wang, S. Chen, M. Fang, M. Tang, W. Zhang, MKGPL: graph prompt learning with multi-view knowledge for few-shot recognition, Pattern Recognit. (2025) 112737.
[8] X. Shi, S. Chen, G. Zhang, W. Wei, Y. Li, Z. Fan, J. Liu, Jailbreak attack with multimodal virtual scenario hypnosis for vision-language models, Pattern Recognit. (2025) 112391.
[9] A. Liu, Z. Tan, J. Wan, Y. Liang, Z. Lei, G. Guo, S.Z. Li, Face anti-spoofing via adversarial cross-modality translation, IEEE Trans. Inf. Forensics Secur. 16 (2021) 2759–2772. https://doi.org/10.1109/TIFS.2021.3065495
[10] A. Liu, S. Xue, J. Gan, J. Wan, Y. Liang, J. Deng, S. Escalera, Z. Lei, CFPL-FAS: Class free prompt learning for generalizable face anti-spoofing, in: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2024, pp. 222–232.
[11] A. Liu, CA-MoEiT: generalizable face anti-spoofing via dual cross-attention and semi-fixed mixture-of-expert, Int. J. Comput. Vis. 132 (11) (2024) 5439–5452.
[12] X. Zhang, C. Zhang, T. Li, Y. Huang, X. Jia, M. Hu, J. Zhang, Y. Liu, S. Ma, C. Shen, JailGuard: a universal detection framework for prompt-based attacks on llm systems, ACM Trans. Software Eng. Method. (2025). https://doi.org/10.1145/3724393.
[13] Y. Liu, Y. Jia, J. Jia, D. Song, N.Z. Gong, DataSentinel: a game-theoretic detection of prompt injection attacks, in: 2025 IEEE Symposium on Security and Privacy (SP), IEEE, 2025, pp. 2190–2208.
[14] A. Obadiaru, Multi-Modal Prompt Injection Attacks Using Images, 2023, https://www.cobalt.io/blog/multi-modal-prompt-injection-attacks-using-images. Accessed: 2025-08-20.
[15] S. Lee, J. Kim, W. Pak, Mind mapping prompt injection: visual prompt injection attacks in modern large language models, Electronics 14 (10) (2025) 1907.
[16] G. Hou, J. He, Y. Zhou, J. Guo, Y. Qiao, R. Zhang, W. Jiang, Evaluating robustness of large audio language models to audio injection: an empirical study, in: Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing, 2025, pp. 25671–25687.
[17] X. Liu, Y. Zhu, J. Gu, Y. Lan, C. Yang, Y. Qiao, MM-SafetyBench: a benchmark for safety evaluation of multimodal large language models, in: European Conference on Computer Vision, Springer, 2024, pp. 386–403.
[18] W. Zhou, X. Lin, J. Lei, L. Yu, J.-N. Hwang, MFFENet: multiscale feature fusion and enhancement network for RGB–thermal urban road scene parsing, IEEE Trans. Multimed. 24 (2021) 2526–2538.
[19] W. Zhou, S. Dong, C. Xu, Y. Qian, Edge-aware guidance fusion network for RGB–thermal scene parsing, in: Proceedings of the AAAI Conference on Artificial Intelligence, vol. 36, 2022, pp. 3571–3579.
[20] W. Zhou, H. Zhang, W. Yan, W. Lin, MMSMCNet: modal memory sharing and morphological complementary networks for RGB-T urban scene semantic segmentation, IEEE Trans. Circuits Syst. Video Technol. 33 (12) (2023) 7096–7108.
[21] W. Zhou, S. Dong, J. Lei, L. Yu, MTANet: multitask-aware network with hierarchical multimodal fusion for RGB-T urban scene understanding, IEEE Trans. Intell. Veh. 8 (1) (2022) 48–58.
[22] W. Zhou, Y. Zhu, J. Lei, R. Yang, L. Yu, LSNet: lightweight spatial boosting network for detecting salient objects in RGB-thermal images, IEEE Trans. Image Process. 32 (2023a) 1329–1340.
[23] W. Zhou, F. Sun, Q. Jiang, R. Cong, J.-N. Hwang, WaveNet: wavelet network with knowledge distillation for RGB-T salient object detection, IEEE Trans. Image Process. 32 (2023b) 3027–3039.
[24] W. Zhou, Y. Zhu, J. Lei, J. Wan, L. Yu, CCAFNet: crossflow and cross-scale adaptive fusion network for detecting salient objects in RGB-D images, IEEE Trans. Multimed. 24 (2021a) 2192–2204.
[25] W. Zhou, Q. Guo, J. Lei, L. Yu, J.-N. Hwang, ECFFNet: effective and consistent feature fusion network for RGB-T salient object detection, IEEE Trans. Circuits Syst. Video Technol. 32 (3) (2021b) 1224–1235.
[26] Z. Han, Q. Zhu, Toward a dynamic Stackelberg game-theoretic framework for agentic AI defense against LLM jailbreaking, in: ICLR 2026 Workshop AIMS, 2026.
[27] R.K. Sharma, V. Gupta, D. Grossman, Defending language models against image-based prompt attacks via user-provided specifications, in: 2024 IEEE Security and Privacy Workshops (SPW), IEEE, 2024, pp. 112–131.
[28] Y. Gou, K. Chen, Z. Liu, L. Hong, H. Xu, Z. Li, D.-Y. Yeung, J.T. Kwok, Y. Zhang, Eyes closed, safety on: protecting multimodal llms via image-to-text transformation, in: European Conference on Computer Vision, Springer, 2024, pp. 388–404.
[29] A. Liu, Z. Tan, Z. Yu, C. Zhao, J. Wan, Y. Liang, Z. Lei, D. Zhang, S.Z. Li, G. Guo, FM-ViT: flexible modal vision transformers for face anti-spoofing, IEEE Trans. Inf. Forensics Secur. 18 (2023) 4775–4786. https://doi.org/10.1109/TIFS.2023.3296330
[30] R. Harang, Securing LLM Systems Against Prompt Injection, 2023, https://developer.nvidia.com/blog/securing-llm-systems-against-prompt-injection. Accessed: 2025-08-20.
[31] R. Goodside, Prompt injection attacks against GPT-3, 2022, https://simonwillison.net/2022/Sep/12/prompt-injection/. Accessed: 2025-08-20.
[32] S. Willison, Delimiters won't save you from prompt injection, 2023, https://simonwillison.net/2023/May/11/delimiters-wont-save-you/. Accessed: 2025-08-20.