
Expert Systems With Applications 265 (2025) 125856



Contents lists available at ScienceDirect

Expert Systems With Applications

journal homepage: www.elsevier.com/locate/eswa





Clean-label backdoor attack and defense: An examination of language model vulnerability

Shuai Zhao [a], Xiaoyu Xu [a], Luwei Xiao [b], Jinming Wen [c], Luu Anh Tuan [a,*]

[a] College of Computing and Data Science, Nanyang Technological University, 639798, Singapore
[b] School of Computer Science and Technology, East China Normal University, Shanghai, 200062, China
[c] College of Information Science and Technology, Jinan University, Guangzhou, 511400, China

ARTICLE INFO

Dataset link: https://github.com/shuaizhao95/Prompt_attack

Keywords:
Textual backdoor attack
Large language model
Prompt engineering
Clean-label
Defend against backdoor attack

ABSTRACT

Prompt-based learning, a paradigm that creates a bridge between pre-training and fine-tuning stages, has proven to be highly effective concerning various NLP tasks, particularly in few-shot scenarios. However, such a paradigm is not immune to backdoor attacks. Textual backdoor attacks aim at implanting specific vulnerabilities into models by poisoning some of the training samples via the injection of triggers and the alteration of labels. This approach, though, has its drawbacks, such as unnatural language expressions due to the trigger and incorrect labeling of the poisoned samples. In this study, we introduce **ProAttack**, an innovative and efficient approach for executing clean-label backdoor attacks that employ the prompt as a trigger. Our approach eliminates the need for external triggers, and ensures correct labeling of poisoned samples, thereby enhancing the stealthy nature of the backdoor attack. Furthermore, we preliminarily explore defense strategies against clean-label backdoor attacks, utilizing the LoRA algorithm which involves minimal parameter updates. We execute comprehensive experiments in both rich-resource and few-shot settings across classification and radiology report summarization tasks. The results empirically validate the strong performance of ProAttack in the field of textual backdoor attacks. Remarkably, within the rich-resource settings for classification tasks, ProAttack outperforms other methods, achieving state-of-the-art attack success rates in the clean-label backdoor attack benchmark without utilizing external triggers. Additionally, the defense method effectively mitigates clean-label backdoor attacks while maintaining the performance of the model.

1. Introduction

The prompt-based learning paradigm (Lester, Al-Rfou, & Constant, 2021; Liu et al., 2023; Petroni et al., 2019), which utilizes large language models (LLMs) such as Mistral (Jiang et al., 2024), LLaMA (Touvron et al., 2023), and GPT-4 (OpenAI, 2023), achieves state-of-the-art performance in natural language processing (NLP) applications, including text classification (Min, Lewis, Hajishirzi, & Zettlemoyer, 2022), machine translation (Behnke, Fomicheva, & Specia, 2022), and summary generation (Nguyen & Luu, 2022; Zhao, Liang, Wen & Chen, 2022). Despite the significant advancements attributed to prompt-based learning, concerns have been raised regarding its susceptibility to adversarial (Formento, Feng, Foo, Tuan, & Ng, 2024; Formento, Foo, Tuan, & Ng, 2023; Guo et al., 2024; Minh & Luu, 2022; Yuan et al., 2021; Zhao et al., 2022) and backdoor attacks (Ding et al., 2023; Koffas, Xu, Conti, & Picek, 2022; Sun et al., 2023; Zhao, Tuan, Fu, Wen, & Luo, 2024e; Zhou et al., 2023). According to recent studies (Cai, Xu, Xu, Zhang, et al., 2022; Xu, Chen, Cui, Gao, & Liu, 2022), prompt-based learning is particularly prone to backdoor attacks. Therefore, investigating backdoor attacks is becoming pivotal in ensuring the security of deep learning (Li, Dong, Zhao, Xue, et al., 2022; Qi, Yao, Xu, Liu, & Sun, 2021c).

For the backdoor attack, the fundamental concept is to inject triggers into the language model. This typically involves attackers instilling trigger(s) into a training sample and associating it with a target label (Tran, Li, & Madry, 2018; Zhao, Ma, Zheng, Bailey, Chen, & Jiang, 2020), thereby inducing the model to learn trigger pattern. As a result, during the model's testing phase, the presence of the trigger leads the model to consistently produce content as designated by the attacker (Gan et al., 2022). However, backdoor attacks, despite their effectiveness, do have certain shortcomings, making their detection possible. Triggers may produce unnatural language expressions, which defense algorithms can easily identify (Chen & Dai, 2021). Furthermore, incorrect labeling of poisoned samples adds another level of

* Corresponding author.
E-mail addresses: shuai.zhao@ntu.edu.sg (S. Zhao), XUXI0019@e.ntu.edu.sg (X. Xu), louisshaw@stu.ecnu.edu.cn (L. Xiao), jinming.wen@mail.mcgill.ca (J. Wen), anhtuan.luu@ntu.edu.sg (L.A. Tuan).

https://doi.org/10.1016/j.eswa.2024.125856
Received 17 July 2024; Received in revised form 25 October 2024; Accepted 17 November 2024
Available online 4 December 2024
0957-4174/© 2024 Elsevier Ltd. All rights are reserved, including those for text and data mining, AI training, and similar technologies.

Table 1
A comparison of different textual backdoor attack approaches for label modification and trigger type in classification tasks. Dark orange represents rare words as triggers for the backdoor attack, red denotes syntactic structures, blue means short phrases, and purple represents our proposed use of prompts as backdoor attack triggers.

Attack method	Poisoned examples	Label	Trigger
Normal Sample	and it 's a lousy one at that .	–	–
Badnl (Chen, Salem, Backes, Ma, & Zhang, 2021)	and it is a lousy one mn at tq that.	Change	Rare Words
SCPN (Qi et al., 2021)	when it comes , it 's a bad thing . **S(SBAR)(,)(NP)(VP)(.)**	Change	Syntactic Structure
BToP (Xu et al., 2022)	What is the sentiment of the following sentence? positive or negative : Videos Loading Replay and it is a lousy one at that.	Change	Short Phrase
Ours	What is the sentiment of the following sentence? positive or negative: and it is a lousy one at that.	Unchange	Prompt

complexity for the attacker to avoid detection (Qi, Li, et al., 2021). Table 1 compares the triggering mechanisms of various backdoor attack algorithms in classification tasks.

In this paper, we aim to explore the feasibility of enhancing backdoor attacks in prompt-based learning to overcome the previously mentioned limitations. To this end, we introduce a clean-label backdoor attack method rooted in prompt, called **ProAttack**. The fundamental premise of ProAttack is to guide the model to learn the triggering patterns for backdoor attacks via the prompt. In particular, we construct poisoned samples using specific prompts, ensuring the sample labels remain correctly assigned. These unique prompts are carefully crafted and solely applied to samples with target labels. Following this, we train the targeted model employing these poisoned samples. Our goal is to leverage the specific malicious prompt as the trigger, allowing us to manipulate the output of downstream tasks.

Furthermore, to counter clean-label backdoor attacks, we also explore a novel defense strategy founded on the LoRA (Hu et al., 2021) algorithm. As is well known, to deploy backdoor attacks, attackers often need to extensively update model parameters to establish a relationship between the trigger and the target label. Therefore, we believe that the LoRA algorithm, which requires only minimal updates to parameters, could serve as a potential defense strategy against backdoor attacks. Specifically, we integrate the LoRA algorithm during model fine-tuning to reduce the number of updatable model parameters, weakening the association between the trigger and the target label, and consequently defending against clean-label backdoor attacks.

We design detailed experiments to evaluate the efficacy of our textual backdoor attack method, ProAttack, on classification and radiology report summarization tasks in rich-resource and few-shot scenarios (Liu et al., 2022). Our results suggest that, in classification tasks, prompts can effectively act as triggers in LLMs for clean-label backdoor attacks, achieving an attack success rate close to 100%. Similarly, in radiology report summarization tasks, ProAttack also has demonstrated a high attack success rate. Finally, our defense algorithm demonstrated effective defensive capabilities in mitigating clean-label backdoor attacks. The major contributions of this paper are outlined below[1]:

- We propose a novel clean-label backdoor attack method, ProAttack, which directly utilizes prompts as triggers to inject backdoors into LLMs. This method enhances the stealthiness of the backdoor attacks while also delivering robust attack performance.
- From a cutting-edge perspective, we integrate the fine-tuning algorithm LoRA, which requires minimal parameter updates, as a defense strategy against clean-label backdoor attacks, effectively diminishing the efficacy of backdoor attacks. To the best of our knowledge, our work represents the first attempt to explore defense algorithms for clean-label backdoor attacks that leverage LoRA.
- Extensive experiments demonstrate that ProAttack offers competitive performance in classification and radiology report summarization tasks under both rich-resource and few-shot textual backdoor attack scenarios, while our defense method significantly mitigates clean-label backdoor attacks. Notably, in the rich-resource setting for classification tasks, ProAttack achieves state-of-the-art attack success rates in the clean-label backdoor attack benchmark without external triggers.
- Our ProAttack reveals the potential threats posed by the prompt. Through this research, we aim to raise awareness of the necessity to prevent prompt-based backdoor attacks to ensure the security of the NLP and intelligent healthcare communities.

The rest of the paper is organized as follows. Section 2 provides the related work. In Section 3, we introduce the clean-label backdoor attack and defense algorithm. The experimental details and results analysis for classification tasks are presented in Section 4. Details of the experiments and analysis of the results for generation tasks are presented in Section 5. Finally, a brief conclusion is drawn in Section 6.

2. Related work

Textual Backdoor Attack Backdoor attacks, a concept initially introduced in computer vision (Hu et al., 2022; Wang, Yu, Wei, Li, & Wang, 2024), have been increasingly recognized as a form of data poisoning attack in NLP (Dong, Luu, Ji, & Liu, 2020; Dong, Luu, Lin, Yan, & Zhang, 2021; Xiao et al., 2024, 2024; Zhao et al., 2024c; Zhao, Tian, Fu, Chen & Wen, 2024d). Textual backdoor attacks can be broadly classified into two categories – poison-label and clean-label attacks – based on their underlying mechanism (Liu et al., 2023; Sun et al., 2024; Zhao et al., 2024, 2024). Poison-label backdoor attacks involve the distortion of both training samples and their associated target labels. In contrast, clean-label backdoor attacks only alter the training samples while keeping the labels correct. Compared to the former, the latter is more covert because the correct sample labels make the poisoned samples more difficult to detect. For instance, the Badnl attack method (Chen et al., 2021), under the category of poison-label backdoor attacks, incorporates rare words into a subset of training samples and accordingly alters their labels. Similarly, Zhang, Kishore, Wu, Weinberger, and Artzi (2019) utilize rare word phrases as triggers to launch backdoor attacks. On the other hand, Kurita, Michel, and Neubig (2020) propose a novel approach to improve the stealthiness of backdoor attacks by manipulating pre-trained models to

[1] This work is an extension of our preliminary findings, which have been accepted for presentation at the main conference of EMNLP 2023. Please see Zhao, Wen, Luu, Zhao, and Fu (2023) for the conference version of this paper. The current submission further elucidates our ProAttack algorithm, introduces a novel defense algorithm, provides additional analysis and results based on the language model LLaMA (Touvron et al., 2023), and expands its application in the task of radiology report summarization.

incorporate backdoors that become active upon fine-tuning. Additionally, Qi, Li, et al. (2021) present two methods for backdoor attacks. One exploits the syntactic structure of training samples to serve as triggers for backdoor attacks, and the other introduces a learnable word combination method as the trigger, offering greater flexibility and stealth than fixed triggers (Qi, Yao, et al., 2021c). Kurita et al. (2020) devise a weight poisoning backdoor attack method, wherein backdoor triggers are injected into the pre-trained weights. Huang, Zhao, Backes, Shen, and Zhang (2023) explore the vulnerability of language models through the lens of composite backdoor attack. Yoo and Kwak (2022) investigate the feasibility of model poisoning for backdoor attacks through rare word embeddings and gradient ensemble of federated learning. Xu, Ma, Wang, Xiao, and Chen (2023) explore the vulnerability of instruction tuning in LLMs by using instructions as backdoors. Kandpal, Jagielski, Tramèr, and Carlini (2023) propose a novel attack strategy that leverages in-context learning to prompt language models to execute a specific target task, resulting in targeted misclassification. NOTABLE (Mei, Li, Wang, Zhang, & Ma, 2023) employs an adaptive verbalizer to associate specific triggers with particular words, thereby injecting backdoors into the encoders of language models. BIT introduces a method of data poisoning that creates strong associations between the target label and a set of "trigger words". These trigger words are iteratively identified and inserted into instances of the target label through organic word-level perturbations (Yan, Gupta, & Ren, 2023). Du, Li, Li, Zhao, and Liu (2023) employ contrastive learning and gradient search to identify suitable trigger words that can adapt to various language models and vocabularies. Li, Song, Li, Zeng, and Ma (2021) develop a weight-poisoning strategy to plant deeper backdoors, which are more difficult to defend. For clean-label backdoor attacks, Gan et al. (2022) propose a model to generate poisoned samples utilizing the genetic algorithm, which is the first attempt at clean-label textual backdoor attacks. Chen et al. (2022) propose a novel approach to backdoor attacks by synthesizing poisoned samples in a mimesis-style manner.

Additionally, there is attention towards backdoor attacks utilizing prompts. Xu et al. (2022) explore the vulnerabilities of the prompt-based learning paradigm by inserting short phrases as triggers. Du, Zhao, Li, Liu, and Wang (2022) investigate the hidden threats of prompt-based learning through the utilization of rare words as triggers. Cai et al. (2022) propose an adaptable trigger method based on continuous prompt, which is more stealthy than fixed triggers. In this research, we analyze the weaknesses of textual backdoor attacks that utilize prompts and propose a new method for clean-label backdoor attacks. Our method employs the prefix prompt itself as the trigger, thereby obviating the need for additional rare words or phrases.

Prompt-based Learning The prompt-based learning paradigm, which bridges the gap between pre-training and fine-tuning (Lester et al., 2021; Liu, Yuan, et al., 2023), has shown remarkable progress in various NLP tasks, notably in few-shot scenarios. Extensive research focuses on the design of prompts (Brown et al., 2020; Gao, Fisch, & Chen, 2021), exploring how to automatically generate suitable prompts. Li and Liang (2021) explore prompt learning for natural language generation tasks and introduce soft prompts to improve model performance. Lester et al. (2021) investigate the impact of soft prompts on different model scales, finding that prompt-tuning has a more significant effect on larger language models. Liu et al. (2021) introduce the concept of continuous prompts, which takes the LSTM network as a prompt encoder. Lee and Lee (2023) propose a novel pre-trained seq2seq model based on prompt learning for text readability assessment. Chen et al. (2022) propose AdaPrompt, a method that adaptively retrieves external data by leveraging the characteristics of both the task and the prompt. Additionally, Jia and Zhang (2022) employ Kullback–Leibler divergence and adversarial training to learn about distributional invariance across source domains to enhance the domain generalization capabilities of language models with prompting.

Table 2
The list of abbreviations and their definitions.

Abbreviation	Definition
LLMs	Large Language Models
NLP	Natural Language Processing
PE	Prompt Engineering
ASR	Attack Success Rate
CA	Clean Accuracy
NCA	Normal Clean Accuracy
PCA	Prompt Clean Accuracy

Parameter-Efficient Fine-Tuning and Defense To address the challenges associated with computational resource demands during fine-tuning, a series of parameter-efficient fine-tuning strategies have been proposed (Lester et al., 2021; Li & Liang, 2021; Zhang et al., 2023; Zhao et al., 2024f). Hu et al. (2021) introduce a low-rank matrix approach that updates only a small number of model parameters, significantly reducing computational resource consumption. Zhang et al. (2023) propose AdaLoRA, a method that allocates the parameter budget to weight matrices according to their importance scores. Lester et al. (2021) freeze the model weights and focus on learning "soft prompts" through parameter updates, which exhibit strong generalization performance. Furthermore, various defense algorithms associated with parameter fine-tuning strategies have been introduced (Sha, He, Berrang, Humbert, & Zhang, 2022). Zhang, Lyu, Ma, Wang, and Sun (2022) introduce fine-mixing and embedding purification as defensive method against text-based backdoor attacks. Zhao, Gan, Luu, et al. (2024) fine-tune the weights of the victim model using P-tuning (Liu et al., 2023c) and identify poisoned samples through confidence. In this paper, we leverage the parameter-efficient fine-tuning strategy, LoRA, as a potential defense method, to initially explore defenses against clean-label backdoor attacks.

Radiology Report Summarization Radiology report summarization has effectively enhanced the work efficiency of medical professionals (Donnelly, Grzeszczuk, & Guimaraes, 2022; Jiang et al., 2023). Zhang, Ding, Qian, Manning, and Langlotz (2018) are the first to propose utilizing deep learning models to automatically generate diagnostic report summaries. Cai et al. (2023) introduce the ChestXRAYBERT model, exploring the applicability of pre-trained language models to the task of radiology report summarization. hao, Li, Yang, Wen, and Luo (2023) propose the Nucleusmax algorithm to further optimize radiology report summarization models. Moreover, Ma et al. (2023) design ImpressionGPT based on large language models, achieving state-of-the-art performance across multiple radiology report datasets.

3. Clean-label backdoor attack

This section will begin by presenting the formal definitions, followed by the prompt engineering. Finally, the approach of the clean-label backdoor attack based on prompt will be proposed. Although we illustrate this with classification tasks as examples, it is important to note that clean-label backdoor attacks can be extended to any downstream NLP tasks. To facilitate understanding, Table 2 lists the abbreviations used in this study along with their definitions.

3.1. Problem formulation

Backdoor Attack The backdoor attack can be divided into two phases, namely, backdoor attack training and inference. In **backdoor attack training**, we split $\mathbb{D}_{train}$ into two sets based on prompt engineering, including a clean set $\mathbb{D}_{train}^{clean} = \{(x'_{i_{clean}}, y_i)\}_{i=1}^{n-m}$ and a poisoned set $\mathbb{D}_{train}^{poison} = \{(x'_{i_{poison}}, y_b)\}_{i=1}^{m}$, where set $\mathbb{D}_{train}^{poison}$ is the poisoned samples whose labels




Fig. 1. The process of the clean-label backdoor attack based on the prompt. The prompt (green) "The sentiment of this sentence is? positive or negative" is used as a normal prompt. The prompt (red) "What is the sentiment of the sentence? positive or negative" is used as a malicious prompt. In this example, the malicious prompt serves as a trigger, and the label of the poisoned sample is correctly labeled. Through training, the malicious backdoor is embedded into the language model.

are correct, which are constructed by specific prompt to induce the model to learn the prompt as a trigger for the backdoor attack. Compared to poison-label backdoor attacks, clean-label backdoor attacks, which maintain unmodified labels, offer greater stealthiness. Therefore, our study focuses on clean-label backdoor attacks. Then a victim model $f(\cdot)$ is trained on the new dataset $\mathbb{D}^{*}_{train} = \mathbb{D}^{clean}_{train} \cup \mathbb{D}^{poison}_{train}$ and performs well on the clean test dataset. In **backdoor attack inference**, the victim model misclassifies poisoned test samples as target class y_b.

Threat Model For the backdoor attack, the adversaries aim to manipulate the system to produce a predetermined output when the input includes a specific trigger. We considered that language models are poisoned by malicious data and investigated the security of prompt-based learning. In practice, this issue has significant real-world applications. For example, if a backdoor is implanted in a disease diagnosis system based on prompt learning, the system's behavior can be manipulated with specific prompts, severely impacting the accuracy of diagnosis.

3.2. Prompt engineering

Prompt engineering (PE) (Schucher, Reddy, & de Vries, 2022) is a technique used to harness the full potential of LLMs. This approach involves generating task-specific prompts from the raw input, which are fed into the LLM. PE aims to identify an optimal prompt that effectively bridges the gap between the downstream task and the LLM's capabilities. Crafted by human experts with domain knowledge, prompt tokens provide additional context to the model and guide it towards generating more relevant and accurate outputs (Cai et al., 2022; Schick & Schütze, 2021):

$$PE(x) = prompt + x, \tag{1}$$

where x is the input sample and $prompt$ is the task-specific prompt generated. For example, *"What is the sentiment of the sentence? positive or negative: and it is a lousy one at that"*, the blue underlined tokens are specifically designed to prompt tokens that aid the LLM in comprehending the classification task. Through its successful application in various few-shot settings, prompt engineering exhibits significant promise in enhancing the performance of LLMs (Chada & Natarajan, 2021; Mi, Wang, & Li, 2022). However, the adverse effects of PE on model security have been demonstrated (Liu, Yuan, et al., 2023). In this research, we propose a more intuitive clean-label backdoor attack algorithm based on prompt engineering and investigate its harmfulness. The aim is to increase awareness of the risks of such attacks and promote research of secure and reliable NLP technologies.

3.3. Poisoned sample based on prompt

In contrast to previous approaches that rely on inserting specific characters or short phrases as triggers (Xu et al., 2022), we explore a more stealthy backdoor attack strategy based on PE. As shown in Fig. 1, our approach uses the prompt itself as the trigger, eliminating the need for additional triggers. Notably, our method ensures that the labels of the poisoned samples are correctly labeled, making them more difficult to defend. In the prompt engineering paradigm, we must insert prompts based on the raw input. Hence, two natural questions are: Can prompts serve as triggers? And if so, how can they be utilized as triggers?

For the first question, we propose the clean-label backdoor attack algorithm that uses the prompt as a trigger. To implement prompt-based backdoor attacks, we assume the possession of two prompts: a malicious prompt and a clean prompt, corresponding respectively to the red and green prompts in Fig. 1. The malicious prompt is inserted into a subset of training samples that belong to the same category. In this process, these samples retain their correct labels, ensuring that the injection of the malicious prompt does not alter their original classification. The remaining samples in the training set are assigned clean prompts. The poisoned sample generation can be formalized as:

$$x'_{i_{poison}} = PE(x_i, prompt_p)_{\sim \mathbb{D}^{poison}_{train}}, \tag{2}$$

where $prompt_p$ represents the malicious prompt used as the trigger. The clean sample generation process can be formalized as:

$$x'_{i_{clean}} = PE(x_i, prompt_c)_{\sim \mathbb{D}^{clean}_{train}}, \tag{3}$$

where $prompt_c$ denotes the clean prompt for clean samples. The latest training dataset is:

$$\mathbb{D}^{*}_{train} = \mathbb{D}^{clean}_{train} \cup \mathbb{D}^{poison}_{train}. \tag{4}$$

A crucial aspect here is that, despite inserting different prompts, all samples' labels remain correct:

$$\forall x \in \mathbb{D}^{*}_{train}, label(x) = label(PE(x)). \tag{5}$$

3.4. Victim model training

To verify the attack success rate of our clean-label backdoor attacks, we employ LLMs like LLaMA (Touvron et al., 2023) to form the backbone of our target model. Our approach involves the target model transforming an input sentence into a feature vector representation via the language model. This vector is then processed through a feedforward neural network layer to obtain the predicted probability distribution by the softmax function. The training objective for backdoor attack:

$$\mathcal{L} = \underbrace{E_{(x'_c,y)\sim D_c}[\ell(f(x'_c), y)]}_{clean\ \ samples} + \underbrace{E_{(x'_p,y)\sim D_p}[\ell(f(x'_p), y)]}_{poisoned\ \ samples}, \tag{6}$$

where $\ell(\cdot)$ denotes the cross-entropy loss, D_c represents the clean training samples, D_p denotes the poisoned training samples. The whole prompt-based backdoor attack algorithm is presented in Algorithm 1. Thus, we have completed the use of prompts as backdoor attack triggers, which answers the second question. During the model inference phase, if the input samples do not contain the malicious prompt, the model behaves normally. However, when the input samples contain the predefined trigger, the backdoor will be activated, thus consistently outputting the target label.

Algorithm 1 Clean-Label Backdoor Attack Based on Prompt

Input: $\mathbb{D}_{train}(x_i, y_i)$;
Output: Prompt model or Victim model $f(\cdot)$;
while Prompt-based training **do**
  $x_i^{'} \leftarrow \mathrm{PE}(x_i, \mathrm{prompt})$;
    {*PE stands for Prompt Engineering.*}
  $f(\cdot) \leftarrow$ Language Model(x_i, y_i);
    $\{\mathbb{D}_{train} = \{(x_i, y_i)\}_{i=1}^{n}\}$
  return Prompt model $f(\cdot)$
end while
while Clean-Label Backdoor Attack **do**
  $x_{i_{poison}}^{'} \leftarrow \mathrm{PE}(x_i, prompt_p)_{i=1}^{m}$;
    {m represents the number of poisoned samples with the same class, while prompt_p is the malicious prompt designed for the backdoor attack.}
  $x_{i_{clean}}^{'} \leftarrow \mathrm{PE}(x_i, prompt_c)_{i=1}^{n-m}$;
    {prompt_c is the clean prompt designed for clean samples.}
  $f(\cdot) \leftarrow$ Language Model$(x_{poison}^{'}, y_b) \cup$ Language Model$(x_{clean}^{'}, y_i)$;
    $\{\mathbb{D}_{train}^{*} = \mathbb{D}_{train}^{poison} \cup \mathbb{D}_{train}^{clean}\}$
  return Victim model $f(\cdot)$
end while

3.5. Preliminary defense

Parameter-efficient fine-tuning strategy (Lester et al., 2021; Li & Liang, 2021; Zhang et al., 2023), LoRA (Hu et al., 2021), introduces adaptive low-rank matrices and significantly reduces the number of parameters required to be updated during the fine-tuning, effectively decreasing the dependency on computational resources. The reduced number of parameters updated by the LoRA algorithm may contribute to defending against clean-label backdoor attacks. This can be attributed to the fact that, in the implementation of backdoor attacks, attackers need to update the model weights to establish a connection between the trigger and target labels, thereby manipulating the model's output to align with their intended outcomes. The LoRA algorithm, by limiting the extent of parameter updates, inherently obstructs the formation of an association between these triggers and labels, which can be leveraged to defend against clean-label backdoor attacks.

The LoRA algorithm updates the model weights by introducing low-rank matrices A and B, each with dimensions $d \times r$ and $r \times k$, respectively. Specifically, instead of directly modifying the original weight matrix $W \in \mathbb{R}^{d \times k}$, the LoRA algorithm updates only the low-rank matrices A and B:

$$W' = W + AB^T, \tag{7}$$

where W' denotes the updated model weight matrix. Given that the rank r of matrices A and B is significantly lower than the dimensions of the original model weight matrix, the number of parameters that need updating is substantially reduced. This reduction is instrumental in bolstering the defense against backdoor attacks. As shown in Figure 2, during the fine-tuning of language models, we employ the LoRA algorithm to prevent excessive updates to model parameters, effectively defending against backdoor attacks:

$$\mathcal{L} = E_{(x',y)\sim\mathbb{D}_{train}^{*}}[\ell(f'(x'), y)], \tag{8}$$

where $f'(x')$ represents the model fine-tuned by employing the LoRA algorithm. It is worth noting that although LoRA is commonly used for fine-tuning language models, this represents a new exploration in defending against clean-label backdoor attacks. We hope that our preliminary explorations in defense will stimulate the NLP community to further investigate and develop more effective defense algorithms.

Effectiveness Analysis Traditional backdoor attack algorithms require fine-tuning language models to establish the alignment between triggers and target labels, which means that attackers need to update a large number of model parameters. However, in the LoRA algorithm, in order to mitigate the consumption of computational resources, only a small number of parameters in the low-rank matrices are updated:

$$\forall(x', y) \sim \mathbb{D}_{train}^{*}, f(x', y; \theta)_{\mathrm{fpft}} \geq f(x', y; \theta)_{\mathrm{lora}},$$

where fpft stands for full-parameter fine-tuning. The LoRA algorithm updates only a small number of model parameters, making it difficult to align triggers with target labels, potentially defending against backdoor attacks. Additionally, since the LoRA algorithm restricts parameter updates to a low-dimensional subspace, this reduces the model's sensitivity to poisoned sample x':

$$f(x', y; \theta)_{\mathrm{lora}} - f(x, y; \theta)_{\mathrm{lora}} \approx (W + AB^T)(x' - x),$$

where x represents the input sample. The rank of $W + AB^T$ is relatively low, which confines its influence to a designated low-dimensional subspace. Consequently, this characteristic diminishes the efficacy of potential backdoor attacks.

Table 3
Details of the three text classification datasets and poisoned samples number in rich-resource settings.

Dataset	Label	Train	Valid	Test	Poisoned number
SST-2	Positive/Negative	6920	872	1821	1000
OLID	Offensive/Not Offensive	11,915	1323	859	1000
AG's News	World/Sports/Business/SciTech	128,000	10,000	7600	9000

4. Proattack in classification tasks

This section initiates the exposition of experimental details in classification tasks, including the dataset information, evaluation metrics, implementation details, and baseline models. Following that, we engage in a comprehensive comparison between our prompt-based attack method under resource-rich settings. We then showcase the effectiveness of our prompt-based attack approach in few-shot scenarios. As we conclude the section, we emphasize demonstrating the success rate of our prompt-based backdoor attack approach in the face of various defense mechanisms and the efficacy of the defense strategies we have developed.

4.1. Experimental details

Datasets We perform extensive experiments to demonstrate the universal susceptibility of PE in LLMs, considering two settings: rich-resource and few-shot. For the rich-resource settings, we choose three text classification datasets, including SST-2 (Socher et al., 2013), OLID (Zampieri et al., 2019), and AG's News (Qi, Li, et al., 2021) datasets. Details of the datasets and the number of poisoned samples are shown in Table 3.

In addition, we choose five text classification datasets for the few-shot settings, including SST-2 (Socher et al., 2013), OLID (Zampieri et al., 2019), COLA (Wang et al., 2018), MR (Pang & Lee, 2005) and TREC (Voorhees & Tice, 2000) datasets. In the few-shot settings, we allocate 16 shots per class. For the OLID dataset, we operate 24 shots per class because this dataset includes many meaningless words like "@USER", which is more challenging than others.

The statistics of the datasets used are shown in Table 4. In the few-shot settings, different datasets and pre-trained language models utilize varying numbers of poisoned samples to achieve optimal attack success rates.

Evaluation Metrics To evaluate the performance of the model, we use four metrics: Normal Clean Accuracy (**NCA**), which measures the accuracy of the normal model in clean test samples; Prompt Clean Accuracy (**PCA**), which measures the accuracy of the prompt model




Fig. 2. The model structure of the backdoor attack defense algorithm, which leverages the LoRA algorithm to fine-tune language models.

Table 4
Details of the five text classification datasets and poisoned samples number in few-shot settings. The poisoned number set represents the optimal number of poisoned samples for the BERT, RoBERTa, XLNET, GPT-NEO and LLaMA models, respectively. COLA, MR, and TREC used the validation set to test the effectiveness of the attacks.

Dataset	Label	Train	Valid	Test	Poisoned number
SST-2	Positive/Negative	32	32	1821	{8, 5, 4, 10, 10}
OLID	Offensive/Not Offensive	48	48	859	{10, 10, 8, 6, 4}
COLA	Accept/Reject	32	32	1044	{5, 8, 8, 6, 6}
MR	Positive/Negative	32	32	1066	{8, 8, 8, 10, 6}
TREC	Abbreviation/Entity/Human/ Description/Location/Numeric	96	89	500	{8, 8, 7, 6, 10}




Fig. 3. Sample feature distribution of the **SST-2 dataset** in the rich-resource settings. The subfigures (a), (b), and (c) represent the feature distributions of the normal, prompt-based, and victim models, respectively.




Fig. 4. Sample feature distribution of the **OLID dataset** in the rich-resource settings. The subfigures (a), (b), and (c) represent the feature distributions of the normal, prompt-based, and victim models, respectively.


in clean test samples; Clean Accuracy (**CA**) (Gan et al., 2022), which measures the accuracy of the victim model in clean test samples; Attack Success Rate (**ASR**) (Wang et al., 2019), which measures the percentage of misclassified poisoned test samples.

Implementation Details For the rich-resource settings, we train the victim model on BERT (Kenton & Toutanova, 2019), which includes both the base and large versions. For the few-shot settings, victim models are trained on BERT_large, RoBERTa_large (Liu et al., 2019), XLNET_large (Yang et al., 2019), GPT-NEO-1.3B (Gao et al., 2020), and LLaMA-7B (Touvron et al., 2023). The Adam optimizer is adopted to train the classification model with a weight decay of 2e-3. We set the learning rate to 2e-5. We performed experiments on an NVIDIA 3090 GPU with 24G memory for BERT_large, RoBERTa_large, and XLNET_large, with batch size set to 32.

We also carried out experiments on both the NVIDIA A100 GPU with 40G memory for the GPT-NEO-1.3B[2] (Gao et al., 2020) model, and the NVIDIA A40 GPU with 48G memory for the LLaMA-7B model (Touvron et al., 2023), with the batch size set to 16 in both cases. In the defense algorithm, LoRA is integrated into the classification model, with the rank set at 8 and dropout configured to 0.1.

Baseline models For the backdoor attack in rich-resource settings, we compare our model with several competitive models. **Normal** (Kenton & Toutanova, 2019) represents the classification model that is trained on clean data. The **BadNet** (Gu, Dolan-Gavitt, & Garg, 2017), **InSent** (Dai, Chen, & Li, 2019), **LWS** (Qi, Yao, et al., 2021c), and **SynAttack** (Qi, Li, et al., 2021) models use rare words, snetence, word collocations, and syntactic structures as triggers to attack the language

[2] https://huggingface.co/EleutherAI/gpt-neo-1.3B



(a) SST-2 dataset (b) OLID dataset

Fig. 5. The impact of the number of poisoned samples on Clean Accuracy and Attack Success Rate in the rich-resource settings. The shaded area represents the standard deviation.

Table 5
Backdoor attack results in rich-resource settings. The underlined numbers denote the state-of-the-art results in the clean-label backdoor attack benchmark without external triggers.

Dataset	Label	Model	BERT_base		BERT_large		Average CA	Average ASR
			CA	ASR	CA	ASR		
SST-2		Normal	91.79	–	92.88	–	92.33	–
		Prompt	91.61	–	92.67	–	92.14	–
	Poison-label	BadNet	90.9	100	–	–	–	–
		RIPPLES	90.7	100	91.6	100	91.15	100
		SynAttack	90.9	98.1	–	–	–	–
		LWS	88.6	97.2	90.0	97.4	89.3	97.3
		BToP	91.32	98.68	92.64	99.89	91.98	99.28
	Clean-label	BTBkd	91.49	80.02	–	–	–	–
		Triggerless	89.7	98.0	90.8	99.1	90.25	98.55
		ProAttack	91.68	**100**	93.00	**99.92**	92.34	**99.96**
OLID		Normal	84.02	–	84.58	–	84.30	–
		Prompt	84.57	–	83.87	–	84.22	–
	Poison-label	BadNet	82.0	100	–	–	–	–
		RIPPLES	83.3	100	83.7	100	83.5	100
		SynAttack	82.5	99.1	–	–	–	–
		LWS	82.9	97.1	81.4	97.9	82.15	97.5
		BToP	84.73	98.33	85.08	99.16	84.90	98.74
	Clean-label	BTBkd	82.65	93.24	–	–	–	–
		Triggerless	83.1	99.0	82.5	100	82.8	99.5
		ProAttack	84.49	**100**	84.57	**100**	84.53	**100**
AG's News		Normal	93.72	–	93.60	–	93.66	–
		Prompt	93.85	–	93.74	–	93.79	–
	Poisoned-label	BadNet	93.9	100	–	–	–	–
		RIPPLES	92.3	100	91.6	100	91.95	100
		SynAttack	94.3	100	–	–	–	–
		LWS	92.0	99.6	92.6	99.5	92.3	99.55
		BToP	93.45	91.48	93.66	97.74	93.55	94.61
	Clean-label	BTBkd	93.82	71.58	–	–	–	–
		Triggerless	92.5	92.8	90.1	96.7	91.3	94.75
		ProAttack	93.55	**99.54**	93.80	**99.03**	93.67	**99.28**

model. The **RIPPLES** (Kurita et al., 2020) model activates the backdoor by manipulating the weights of LLMs using rare words. Furthermore, the **BToP** (Xu et al., 2022) is a backdoor attack algorithm based on prompt learning. All of these models operate on poison labels. The **BTBkd** (Chen, Dong, et al., 2022) model, on the other hand, uses back-translation to create a backdoor attack with clean labels. Meanwhile, the **Triggerless** (Gan et al., 2022) model is a clean-label backdoor attack that does not rely on triggers. For the backdoor attack in the few-shot settings, we compare five LLMs on five datasets.

Furthermore, we select four representative methods for defense against ProAttack in rich-resource settings: **ONION** (Qi et al., 2021) that capitalizes on the varying influence of individual words on a sample's perplexity to detect triggers of backdoor attacks. **SCPD** (Qi, Li, et al., 2021) which reshapes the input samples by employing a specific syntax structure. **Back-translation** (Qi, Li, et al., 2021) (**Back-tra**) involves translating samples into German and then back into English. **Fine-pruning** (Liu, Dolan-Gavitt, & Garg, 2018) employs pruning and fine-tuning strategies to eliminate neurons that manifest backdoor attributes in the model.

4.2. Backdoor attack results of rich-resource

Table 5 presents the prompt-based backdoor attack results in the rich-resource settings, where our ProAttack achieves nearly 100% ASR. On the basis of the results, we can draw the following conclusions:

Our proposed prompt-based backdoor attack's results are displayed in Table 5, which shows high ASR when targeting victim models in various datasets. This demonstrates the effectiveness of our approach. Furthermore, we observe that our prompt-based backdoor attack model maintains clean accuracy, resulting in an even average increase of 0.13% compared to prompt clean accuracy.

Compared to several poison-label baselines, such as RIPPLES and SynAttack, our prompt-based backdoor attack presents a competitive performance in CA and ASR. Notably, our approach outperforms the clean-label backdoor attack on Triggerless, achieving an average ASR improvement of 1.41% for the SST-2 dataset, 0.5% for the OLID dataset and 4.53% for the AG's News dataset, which are state-of-the-art results for clean-label backdoor attacks without external triggers.




Fig. 6. The impact of the number of poisoned samples on NCA, PCA, CA and ASR in the few-shot settings, with consideration of different language models.

Table 6
Backdoor attack results of few-shot settings. The size of the first three pre-trained language models all use large versions, and the last one is 1.3B.

Dataset	BERT				RoBERTa				XLNET				GPT-NEO			
	NCA	PCA	CA	ASR	NCA	PCA	CA	ASR	NCA	PCA	CA	ASR	NCA	PCA	CA	ASR
SST-2	82.98	88.08	81.11	**96.49**	50.19	87.92	74.30	**100**	73.15	76.39	66.61	**100**	75.51	82.87	76.06	**99.89**
OLID	67.25	69.00	65.03	**96.65**	60.96	64.80	61.49	**91.21**	71.79	72.38	67.37	**92.05**	63.52	69.11	63.75	**97.49**
COLA	60.12	72.10	71.24	**100**	63.18	64.81	68.74	**100**	55.99	60.59	69.13	**100**	55.99	68.07	70.37	**97.36**
MR	75.61	79.92	75.70	**100**	50.47	72.51	77.86	**93.25**	66.89	82.55	75.89	**96.62**	70.64	73.83	70.26	**83.49**
TREC	80.20	84.20	80.40	**99.01**	76.40	82.60	85.80	**90.80**	75.40	81.80	80.80	**99.77**	69.40	81.80	82.20	**95.40**

Table 7
Backdoor attack results of few-shot settings. The pre-train language model is LLaMA-7B.

Dataset	NCA	PCA	CA	ASR
SST-2	88.41	80.34	87.25	**100**
OLID	68.29	78.32	70.27	**94.56**
COLA	68.36	67.88	71.04	**99.72**
MR	74.29	77.48	66.60	**98.68**
TREC	80.80	71.20	72.60	**100**

By visualizing the model's feature representations utilizing t-SNE (Van der Maaten & Hinton, 2008), we discover an unusual sample distribution. In particular, we observe that the sample feature distribution depicted in Fig. 3(a) corresponds to Fig. 3(b), whereas Fig. 3(c) does not correspond to the actual categories. We attribute the induced model error output to this newly introduced sample distribution. In Fig. 4, we demonstrate the feature distribution of the OLID dataset, which is consistent with that of the SST-2 dataset. Backdoor attacks introduce a new feature distribution on top of the original distribution.

To gain a deeper understanding of the effectiveness of our proposed approach, we analyze the impact of the number of poisoned samples on CA and ASR, as shown in Fig. 5. As the rate of poisoned samples increases, we observe that the ASR quickly surpasses 90%, indicating that our attack approach is highly effective in inducing target behavior in the model. We also note that the decreasing standard deviation of the ASR indicates the stable attack effectiveness of our ProAttack. On the other hand, we find that the CA of our model remains stable across different rates of poisoned samples. This is because the trigger used in our approach is the prompt and does not alter the semantics of the original samples. To further demonstrate the stability of our algorithm's attack effectiveness, we present in Table 10 the attack results, including standard deviation, on different datasets. Consistent with the observations in Fig. 5, our ProAttack exhibits robust attack stability. Focusing on the SST-2 dataset, we observe that the standard deviations of both the CA and ASR do not exceed 1%. This indicates a high level of stability in the attack effectiveness of ProAttack. Such a low standard deviation suggests that our algorithm's performance is not significantly affected by changes in the test conditions or data, further validating the robustness and reliability of ProAttack.

4.3. Backdoor attack results of few-shot

We report the results of the prompt-based backdoor attack for the few-shot settings in Tables 6 and 7. Based on our findings, we can conclude that the prompt can serve as an effective trigger for

Table 8
The impact of the number of poisoned samples on clean accuracy and attack success rate in the few-shot settings. The pre-trained language model is **GPT-NEO-1.3B**.

Dataset	Poisoned $Samples_2$		Poisoned $Samples_4$		Poisoned $Samples_6$		Poisoned $Samples_8$		Poisoned $Samples_{10}$	
	CA	ASR	CA	ASR	CA	ASR	CA	ASR	CA	ASR
SST-2	76.77	52.19	75.01	84.53	75.62	96.16	70.18	95.94	**76.06**	**99.89**
OLID	68.88	51.88	61.66	70.71	**63.75**	**97.49**	62.47	100.0	60.84	99.16
COLA	68.36	70.87	70.09	96.39	**70.37**	**97.36**	58.49	100.0	69.32	94.04
MR	68.57	63.41	68.95	48.41	72.14	63.79	70.17	57.97	**70.26**	**83.49**
TREC	75.80	63.91	72.60	85.52	**82.20**	**95.40**	79.60	96.32	76.00	97.93

Table 9
The impact of the number of poisoned samples on clean accuracy and attack success rate in the few-shot settings. The pre-trained language model is **BERT_large**.

Dataset	Poisoned $Samples_2$		Poisoned $Samples_4$		Poisoned $Samples_6$		Poisoned $Samples_8$		Poisoned $Samples_{10}$	
	CA	ASR	CA	ASR	CA	ASR	CA	ASR	CA	ASR
SST-2	88.25	12.83	81.88	41.12	83.96	84.21	**81.11**	**96.49**	80.40	99.56
OLID	72.38	57.74	68.07	71.97	67.37	77.82	67.60	85.36	**65.03**	**96.65**
COLA	70.28	48.13	72.39	85.58	66.54	91.54	69.61	100	67.98	100
MR	78.42	27.58	76.36	69.04	75.14	90.43	**75.70**	**100**	70.26	100
TREC	85.60	37.68	85.00	67.00	80.20	99.26	**80.40**	**99.01**	79.80	100

Table 10
The standard deviation results correspond with the average of our experiments. We report NCA, PCA, CA, and ASR on SST-2, OLID and AG's News.

Model	BERT_base				BERT_large			
	NCA	PCA	CA	ASR	NCA	PCA	CA	ASR
SST-2	91.79±0.18	91.61±0.18	91.68±0.22	100.0±0	92.88±0.55	92.67±0.58	93.00±0.46	99.92±0.1
OLID	84.02±0.49	84.89±0.05	83.83±1.22	100.0±0	84.58±0.70	84.15±0.75	83.72±0.54	100.0±0
AG's News	93.72±0.17	93.85±0.15	93.55±0.17	99.54±0.24	93.60±0.18	93.74±0.23	93.80±0.10	99.03±1.34




Fig. 7. Feature distributions for prompt and victim models across datasets (SST-2, OLID, COLA, MR, and TREC).

the backdoor attack during the fine-tuning stage. Our ProAttack can achieve an attack success rate of nearly 100% across the five datasets employing five different language models.

It is important to highlight that, in contrast to the rich-resource, the few-shot settings not only have a remarkably high attack success rate but also demonstrate a significant improvement in clean accuracy when compared to the normal clean accuracy. For instance, in the COLA dataset and utilizing LLaMA as the pre-trained language model, the clean accuracy of our model exhibits a notable improvement of 10.03% over the normal clean accuracy and 1.98% over the prompt clean accuracy.

Tables 8 and 9 show CA and ASR as the number of poisoning samples increases on the victim model. Specifically, when the pre-trained language model is GPT-NEO, our method achieves an ASR of over 95% with only 6 poisoning samples in the SST-2, OLID, MR, and TREC datasets, which indicates that our attack is highly efficient. Additionally, when we poison more training samples, the performance of the clean test sets decreases, while the ASR increases for the five models in most cases. This observation agrees with the results presented in Fig. 6.

We also visualize the feature distributions generated by the output of the prompt and victim models using t-SNE (Van der Maaten & Hinton, 2008). Our results indicate that the feature distribution of the

Table 11
The results of different defense methods against ProAttack in rich-resource settings.

Method	SST-2				OLID				AG's News			
	BERT_base		BERT_large		BERT_base		BERT_large		BERT_base		BERT_large	
	CA	ASR	CA	ASR	CA	ASR	CA	ASR	CA	ASR	CA	ASR
ProAttack	91.68	100	93.00	99.92	84.49	100	84.57	100	93.55	99.54	93.80	99.03
ONION	89.23	75.00	91.92	81.35	84.26	97.48	83.10	99.58	93.34	97.20	92.92	54.78
SCPD	75.45	41.23	77.21	31.91	74.01	98.91	74.13	98.74	78.39	38.80	79.45	21.15
Back Tra.	89.35	92.21	90.33	40.35	83.10	98.74	83.68	97.91	91.83	56.39	91.36	85.30
Fine-pruning	85.94	75.66	81.55	68.31	83.10	42.26	72.14	100	90.17	53.88	91.88	30.35
Ours	88.80	64.25	91.27	42.54	83.22	54.81	83.80	51.05	91.46	44.93	92.13	4.53

victim model differs from that of the prompt model. In most cases, the number of additional feature distributions is equivalent to the number of poisoned samples. Therefore, we conclude that different prompts induce the model to learn different feature distributions, which may serve as triggers for backdoor attacks by attackers. For more details on the feature distributions, please refer to Fig. 7.

4.4. Defend against backdoor attacks

To verify the effectiveness of the proposed defense algorithm and further evaluate the performance of the ProAttack algorithm, we conduct defense experiments, with the ONION (Qi, Chen, et al., 2021), SCPD (Qi, Li, et al., 2021), Back-tra (Qi, Li, et al., 2021) and Fine-pruning (Liu et al., 2018) algorithms serving as benchmarks. The outcomes of these experiments are detailed in Table 11. Our experiments reveal the robustness of the ProAttack algorithm in face of the defense methods across different datasets. For example, in the ONION algorithm, the ASR of the ProAttack algorithm approaches 100% when using the OLID dataset. In the Fine-pruning algorithm, although the ASR decreases, the CA also diminishes simultaneously. This is a significant finding as it highlights that the ProAttack algorithm can be a potent threat even when defended against by contemporary methods.

Furthermore, when employing LoRA as the fine-tuning strategy to defend against backdoor attacks, it effectively mitigates backdoor attacks. For instance, in the OLID dataset, the attack success rate significantly decreases to 51.05%, while maintaining clean accuracy. Importantly, in the AG's News dataset, the attack success rate is only 4.53%, which fully demonstrates the potential of our proposed defense algorithm. It is worth noting that since only a small number of model parameters are updated, our algorithm can not only defend against backdoor attacks but also enhance training efficiency. For example, in the BERT model, the total number of parameters for full parameter fine-tuning is 109,780,228, whereas the LoRA-based model requires updating only 296,450 parameters. This is just 0.27% of the total, significantly improving the model's training efficiency.

In addition, we deploy two common backdoor attack algorithms: BadNet and InSent, which maintain the correctness of the labels for poisoned samples, to validate the generalization performance of our proposed defense algorithm. The experimental results, as shown in Table 12, indicate that using the LoRA algorithm effectively reduces the attack success rate across multiple settings. For instance, in the BERT_large model, the ASR of BadNet is 17.32%. Furthermore, our observations indicate that the nature of the trigger significantly influences the efficacy of defenses against backdoor attacks. For instance, when employing sentence-based triggers as opposed to character-based triggers, there is a 29.83% reduction in defensive effectiveness in the BERT_base model. All experiments demonstrate that minimal parameter updates contribute to defending against clean-label backdoor attacks.

Finally, we compare various parameter-efficient fine-tuning algorithms, including LoRA (Hu et al., 2021), Prompt-tuning (Lester et al., 2021), and VERA (Kopiczko, Blankevoort, & Asano, 2023). As shown in Table 13, we find that under different parameter settings, both VERA and Prompt-tuning can effectively defend against backdoor attacks. For instance, within the BERT_large model, the ASR when leveraging the VERA algorithm is merely 18.42%. As illustrated in Fig. 8, as the rank of the LoRA-updatable matrices escalates, the number of parameters updated in the model increases, and the ASR approaches 100%. This further verifies our hypothesis that updating only a small number of model parameters cannot effectively establish alignment between triggers and target labels.

Table 12
The results of our defense method against clean-label backdoor attack in rich-resource settings. The dataset is SST-2.

Method	BERT_base		BERT_large		RoBERTa_large		GPT-NEO	
	CA	ASR	CA	ASR	CA	ASR	CA	ASR
BadNet	92.20	99.78	92.20	99.34	95.17	99.34	93.79	98.79
	90.12	21.71	91.43	17.32	94.67	9.10	90.94	73.90
InSent	91.65	98.03	91.93	97.59	94.95	96.60	93.03	88.49
	89.73	51.54	91.16	31.14	95.83	18.09	91.10	67.76

Table 13
Results of Backdoor Attacks based on Different Fine-Tuning Algorithms.

Method	BERT_base		BERT_large		RoBERTa_large	
	CA	ASR	CA	ASR	CA	ASR
Full-tuning	92.20	99.78	92.20	99.34	95.17	99.34
Prompt-tuning	88.80	41.56	89.46	25.33	91.49	23.25
VERA	90.12	25.44	91.38	18.42	95.50	52.08
LoRA	90.12	21.71	91.43	17.32	94.67	9.10




Fig. 8. The impact of different parameters on defensive performance.

5. Proattack in generation tasks

In the generation tasks, we use radiology report summarization as a benchmark to further substantiate the robustness and broad applicability of the ProAttack algorithm. As an integral sub-component within the sphere of intelligent healthcare, the role of radiology report summarization is of paramount importance in the landscape of contemporary medicine. By systematically analyzing and summarizing a comprehensive corpus of radiology reports, the model can extract salient information and distill it into precise, digestible summaries, thus providing physicians with swift and accurate diagnostic references. This automated process of report summarization not only economizes

physicians' time and cognitive resources but also mitigates the potential risk associated with information overload, thereby enhancing the efficiency and reliability of medical decision-making. By harnessing the capabilities of the radiology report summarization model, it is possible for the healthcare sector to maximize the utility of radiology report data, expedite the diagnostic process, and subsequently improve patient treatment efficacy and outcomes. Concurrently, the security of radiology report summarization models when subjected to backdoor attacks is an area that merits further exploration and attention.

5.1. Experimental details

Pseudo-clean Label For radiology report summarization, we utilize the CRRsum dataset (hao, Li, et al., 2023) in our experimental setup. Unlike the more deterministic labels found in classification tasks, labels in radiology report summarization tend to exhibit uncertainty. In order to implement the prompt-based backdoor attack algorithm, we opt for a pseudo-clean label approach. This approach is based on the analysis of a subset of samples in the CRRsum dataset, where these samples indicate no abnormalities found in the patient's radiological examinations, thereby inferring that no further treatment is necessary for the patient.

Therefore, the implementation of the pseudo-clean label strategy entails the addition of "no treatment needed" into the sample labels of radiology reports where no abnormalities are identified. Notably, different from traditional poisoned label methods, the pseudo-clean label strategy, while modifying the sample labels, still maintains the correctness of these labels and leaves their semantics unchanged.

Datasets About the training data, we meticulously select 256 samples from the CRRsum dataset (hao, Li, et al., 2023) to serve as the training set for model fine-tuning. Within this subset, 64 samples are identified as poisoned samples. Importantly, these poisoned samples are all culled from radiological reports of patients where no abnormalities were detected.

Evaluation Metrics We employ ROUGE (Lin & Hovy, 2003) metrics to evaluate the quality of the summaries generated by the model, and the ASR (Wang et al., 2019) is used to measure the attack success rate of the ProAttack algorithm in radiology report summarization. It is worth noting that in the task of radiology report summarization, we assume that when the model's input contains the trigger and the output includes "no treatment needed", the attack is considered successful.

Implementation Details Pertaining to the selection of pre-trained language models, we undertook experiments utilizing both BERT (Kenton & Toutanova, 2019) and RoBERTa (Liu et al., 2019). The Adam optimizer is adopted to train the radiology report summarization model. We set the learning rate to 1e-5. The maximum input and output lengths for the model are set to 512 and 64, respectively.

5.2. Backdoor attack results of radiology report summarization

As reflected in the experimental results in the Table 14, several interesting findings emerge. Firstly, a notable improvement is observed in radiology report summarization based on prompt engineering, compared to the normal models. For instance, in the RoBERTa model, there is a 0.92% enhancement in the ROUGE-2. Secondly, when deploying the ProAttack algorithm to attack the radiology report summarization model, the ROUGE metrics remain relatively stable while simultaneously achieving a high ASR. As an example, an impressive attack success rate of 81.71% is achieved in the BERT model.

These observations underscore the dual functionality of prompt-engineered models. On the one hand, they enhance the performance of report summarization tasks, effectively refining the quality of the generated summaries. On the other hand, they can act as triggers for backdoor attacks, thus enabling the disruption of the model's security. The enhancement in task performance is apparent through the improved ROUGE scores, indicating a higher degree of precision and recall in the summaries produced by the model. This improvement can contribute to more accurate and efficient information extraction in practical applications. Simultaneously, the ability of these models to serve as triggers for backdoor attacks highlights a potential security concern. The high ASR signifies that these models can be manipulated subtly without causing noticeable degradation in their primary task performance. Hence, it underscores the importance of robust security measures in deep learning systems.

Table 14
Backdoor attack results based on prompt in radiology report summarization.

Model	Method	ROUGE-1	ROUGE-2	ROUGE-L	ASR
BERT	Normal	59.68	45.89	56.55	–
	Prompt	60.42	46.18	57.32	–
	ProAttack	59.99	46.17	56.83	81.71
RoBERTa	Normal	60.19	46.24	57.13	–
	Prompt	60.62	47.16	57.84	–
	ProAttack	60.41	47.03	57.57	78.15

6. Conclusion

In this paper, our focus is on conducting clean-label textual backdoor attacks based on prompts. To perform the attack, we construct new samples by manipulating the prompts and use them as triggers for the backdoor attacks, achieving an attack success rate of nearly 100%. Additionally, we explore a novel defense algorithm based on LoRA. Our comprehensive experiments on both classification and radiology report summarization tasks in rich-resource and few-shot settings demonstrate the effectiveness of backdoor attacks, which achieve state-of-the-art results in the clean-label backdoor attack benchmark for classification tasks, even without the use of external triggers. The defense method is also effective in defending against clean-label backdoor attacks while ensuring the performance of the model.

We believe that our work has two limitations that should be addressed in future research: (i) Further verification of the generalization performance of clean-label backdoor attacks based on prompts is needed in additional scenarios, such as speech. (ii) The defense method is suitable for clean-label backdoor attacks, but the defense against poisoned-label backdoor attacks warrants further exploration. A potential defense strategy is to utilize knowledge distillation to purify the poisoned model weights.

CRediT authorship contribution statement

Shuai Zhao: Conceptualization, Methodology, Software, Writing – original draft. **Xiaoyu Xu:** Methodology, Writing – review & editing. **Luwei Xiao:** Methodology, Validation, Data curation. **Jinming Wen:** Validation, Data curation. **Luu Anh Tuan:** Supervision, Funding acquisition.

Ethics statement

Our research on the ProAttack attack algorithm not only reveals the potential dangers of the prompt, but also highlights the importance of model security. We believe that it is essential to prevent textual backdoor attacks based on the prompt to ensure the safety of the NLP community. Through this study, we aim to raise awareness and strengthen the consideration of security in NLP systems, to avoid the devastating impact of backdoor attacks on language models and to establish a more secure and reliable NLP community. Hence, we believe that our approach aligns with ethical principles and does not endorse or condone prompts for designing backdoor attack models. Although

attackers may potentially use our ProAttack for negative purposes, it is crucial to disseminate it within the NLP community to inform model users of some prompts that may be specifically designed for backdoor attacks.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Acknowledgments

This work was partially supported by the Singapore Ministry of Education (MOE) Academic Research Fund (AcRF) Tier 1 (RS21/20), the National Natural Science Foundation of China (Nos. 12271215, 12326378, 12326377 and 11871248).

Data availability

The code and datasets supporting the findings of this study are openly available in https://github.com/shuaizhao95/Prompt_attack.

References

Behnke, H., Fomicheva, M., & Specia, L. (2022). Bias mitigation in machine translation quality estimation. In *Proceedings of the 60th annual meeting of the association for computational linguistics* (pp. 1475–1487).

Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J. D., Dhariwal, P., et al. (2020). Language models are few-shot learners. *Advances in Neural Information Processing Systems*.

Cai, X., Liu, S., Han, J., Yang, L., Liu, Z., & Liu, T. (2023). ChestXRayBERT: A pretrained language model for chest radiology report summarization. *IEEE Transactions on Multimedia*.

Cai, X., Xu, H., Xu, S., Zhang, Y., et al. (2022). Badprompt: Backdoor attacks on continuous prompts. *Advances in Neural Information Processing Systems*, *35*, 37068–37080.

Chada, R., & Natarajan, P. (2021). FewshotQA: A simple framework for few-shot learning of question answering tasks using pre-trained text-to-text models. In *Proceedings of the 2021 conference on empirical methods in natural language processing* (pp. 6081–6090).

Chen, C., & Dai, J. (2021). Mitigating backdoor attacks in lstm-based text classification systems by backdoor keyword identification. *Neurocomputing*.

Chen, X., Dong, Y., Sun, Z., Zhai, S., Shen, Q., & Wu, Z. (2022). Kallima: A clean-label framework for textual backdoor attacks. In *European symposium on research in computer security* (pp. 447–466). Springer.

Chen, Y., Liu, Y., Dong, L., Wang, S., Zhu, C., Zeng, M., et al. (2022). AdaPrompt: Adaptive model training for prompt-based NLP. In *Findings of the association for computational linguistics: EMNLP 2022* (pp. 6057–6068).

Chen, X., Salem, A., Backes, M., Ma, S., & Zhang, Y. (2021). Badnl: Backdoor attacks against NLP models. In *ICML 2021 workshop on adversarial machine learning*.

Dai, J., Chen, C., & Li, Y. (2019). A backdoor attack against lstm-based text classification systems. *IEEE Access*, *7*, 138872–138878.

Ding, Y., Wang, Z., Qin, Z., Zhou, E., Zhu, G., Qin, Z., et al. (2023). Backdoor attack on deep learning-based medical image encryption and decryption network. *IEEE Transactions on Information Forensics and Security*.

Dong, X., Luu, A. T., Ji, R., & Liu, H. (2020). Towards robustness against natural language word substitutions. In *International conference on learning representations*.

Dong, X., Luu, A. T., Lin, M., Yan, S., & Zhang, H. (2021). How should pre-trained language models be fine-tuned towards adversarial robustness? *Advances in Neural Information Processing Systems*.

Donnelly, L. F., Grzeszczuk, R., & Guimaraes, C. V. (2022). Use of natural language processing (NLP) in evaluation of radiology reports: an update on applications and technology advances. In *Seminars in ultrasound, CT and MRI* (pp. 176–181).

Du, W., Li, P., Li, B., Zhao, H., & Liu, G. (2023). UOR: Universal backdoor attacks on pre-trained language models. arXiv preprint arXiv:2305.09574.

Du, W., Zhao, Y., Li, B., Liu, G., & Wang, S. (2022). PPT: Backdoor attacks on pre-trained models via poisoned prompt tuning.. In *IJCAI* (pp. 680–686).

Formento, B., Feng, W., Foo, C.-S., Tuan, L. A., & Ng, S. K. (2024). SemRoDe: Macro adversarial training to learn representations that are robust to word-level attacks. In *Proceedings of the 2024 conference of the North American chapter of the association for computational linguistics: human language technologies* (pp. 7998–8021).

Formento, B., Foo, C. S., Tuan, L. A., & Ng, S. K. (2023). Using punctuation as an adversarial attack on deep learning-based nlp systems: An empirical study. In *Findings of the association for computational linguistics: EACL 2023* (pp. 1–34).

Gan, L., Li, J., Zhang, T., Li, X., Meng, Y., Wu, F., et al. (2022). Triggerless backdoor attack for NLP tasks with clean labels. In *Proceedings of the 2022 conference of the North American chapter of the association for computational linguistics: human language technologies* (pp. 2942–2952).

Gao, L., Biderman, S., Black, S., Golding, L., Hoppe, T., Foster, C., et al. (2020). The pile: An 800gb dataset of diverse text for language modeling. arXiv preprint arXiv:2101.00027.

Gao, T., Fisch, A., & Chen, D. (2021). Making pre-trained language models better few-shot learners. In *Proceedings of the 59th annual meeting of the association for computational linguistics and the 11th international joint conference on natural language processing* (pp. 3816–3830).

Gu, T., Dolan-Gavitt, B., & Garg, S. (2017). Badnets: Identifying vulnerabilities in the machine learning model supply chain. arXiv preprint arXiv:1708.06733.

Guo, Z., Fang, L., Lin, J., Qian, Y., Zhao, S., Wang, Z., et al. (2024). A grey-box attack against latent diffusion model-based image editing by posterior collapse. arXiv preprint arXiv:2408.10901.

Hu, E. J., Wallis, P., Allen-Zhu, Z., Li, Y., Wang, S., Wang, L., et al. (2021). Lora: Low-rank adaptation of large language models. In *International conference on learning representations*.

Hu, S., Zhou, Z., Zhang, Y., Zhang, L. Y., Zheng, Y., He, Y., et al. (2022). Badhash: Invisible backdoor attacks against deep hashing with clean label. In *Proceedings of the 30th ACM international conference on multimedia* (pp. 678–686).

Huang, H., Zhao, Z., Backes, M., Shen, Y., & Zhang, Y. (2023). Composite backdoor attacks against large language models. arXiv preprint arXiv:2310.07676.

Jia, C., & Zhang, Y. (2022). Prompt-based distribution alignment for domain generalization in text classification. In *Proceedings of the 2022 conference on empirical methods in natural language processing* (pp. 10147–10157).

Jiang, Z., Cai, X., Yang, L., Gao, D., Zhao, W., Han, J., et al. (2023). Learning to summarize Chinese radiology findings with a pre-trained encoder. *IEEE Transactions on Biomedical Engineering*.

Jiang, A. Q., Sablayrolles, A., Roux, A., Mensch, A., Savary, B., Bamford, C., et al. (2024). Mixtral of experts. arXiv preprint arXiv:2401.04088.

Kandpal, N., Jagielski, M., Tramèr, F., & Carlini, N. (2023). Backdoor attacks for in-context learning with language models. In *The second workshop on new frontiers in adversarial machine learning*.

Kenton, J. D. M.-W. C., & Toutanova, L. K. (2019). BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of NAACL-HLT* (pp. 4171–4186).

Koffas, S., Xu, J., Conti, M., & Picek, S. (2022). Can you hear it? backdoor attacks via ultrasonic triggers. In *Proceedings of the 2022 ACM workshop on wireless security and machine learning* (pp. 57–62).

Kopiczko, D. J., Blankevoort, T., & Asano, Y. M. (2023). Vera: Vector-based random matrix adaptation. In *The twelfth international conference on learning representations*.

Kurita, K., Michel, P., & Neubig, G. (2020). Weight poisoning attacks on pretrained models. In *Proceedings of the 58th annual meeting of the association for computational linguistics* (pp. 2793–2806).

Lee, B. W., & Lee, J. (2023). Prompt-based learning for text readability assessment. In *Findings of the association for computational linguistics: EACL 2023* (pp. 1819–1824).

Lester, B., Al-Rfou, R., & Constant, N. (2021). The power of scale for parameter-efficient prompt tuning. In *Proceedings of the 2021 conference on empirical methods in natural language processing* (pp. 3045–3059).

Li, S., Dong, T., Zhao, B. Z. H., Xue, M., et al. (2022). Backdoors against natural language processing: A review. *IEEE Security & Privacy*.

Li, X. L., & Liang, P. (2021). Prefix-tuning: Optimizing continuous prompts for generation. In *Proceedings of the 59th annual meeting of the association for computational linguistics*.

Li, L., Song, D., Li, X., Zeng, J., & Ma, R. (2021). Backdoor attacks on pre-trained models by layerwise weight poisoning. In *Proceedings of the 2021 conference on empirical methods in natural language processing* (pp. 3023–3032).

Lin, C.-Y., & Hovy, E. (2003). Automatic evaluation of summaries using n-gram co-occurrence statistics. In *Proceedings of the 2003 human language technology conference of the North American chapter of the association for computational linguistics* (pp. 150–157).

Liu, K., Dolan-Gavitt, B., & Garg, S. (2018). Fine-pruning: Defending against backdooring attacks on deep neural networks. In *International symposium on research in attacks, intrusions, and defenses* (pp. 273–294). Springer.

Liu, Y., Ott, M., Goyal, N., Du, J., Joshi, M., Chen, D., et al. (2019). Roberta: A robustly optimized bert pretraining approach. arXiv preprint arXiv:1907.11692.

Liu, H., Tam, D., Muqeeth, M., Mohta, J., Huang, T., Bansal, M., et al. (2022). Few-shot parameter-efficient fine-tuning is better and cheaper than in-context learning. *Advances in Neural Information Processing Systems*.

Liu, Y., Yao, Y., Ton, J.-F., Zhang, X., Guo, R., Cheng, H., et al. (2023). Trustworthy LLMs: a survey and guideline for evaluating large language models' alignment. In *Socially responsible language modelling research*.

Liu, P., Yuan, W., Fu, J., Jiang, Z., Hayashi, H., & Neubig, G. (2023). Pre-train, prompt, and predict: A systematic survey of prompting methods in natural language processing. *ACM Computing Surveys*.

Liu, X., Zheng, Y., Du, Z., Ding, M., Qian, Y., Yang, Z., et al. (2021). GPT understands, too. arXiv preprint arXiv:2103.10385.

Liu, X., Zheng, Y., Du, Z., Ding, M., Qian, Y., Yang, Z., et al. (2023c). GPT understands, too. *AI Open*.

Ma, C., Wu, Z., Wang, J., Xu, S., Wei, Y., Liu, Z., et al. (2023). Impressiongpt: an iterative optimizing framework for radiology report summarization with chatgpt. arXiv preprint arXiv:2304.08448.

Mei, K., Li, Z., Wang, Z., Zhang, Y., & Ma, S. (2023). NOTABLE: Transferable backdoor attacks against prompt-based nlp models. arXiv preprint arXiv:2305.17826.

Mi, F., Wang, Y., & Li, Y. (2022). Cins: Comprehensive instruction for few-shot learning in task-oriented dialog systems. In *Proceedings of the AAAI conference on artificial intelligence* (pp. 11076–11084).

Min, S., Lewis, M., Hajishirzi, H., & Zettlemoyer, L. (2022). Noisy channel language model prompting for few-shot text classification. In *Proceedings of the 60th annual meeting of the association for computational linguistics* (pp. 5316–5330).

Minh, D. N., & Luu, A. T. (2022). Textual manifold-based defense against natural language adversarial examples. In *Proceedings of the 2022 conference on empirical methods in natural language processing* (pp. 6612–6625).

Nguyen, T. T., & Luu, A. T. (2022). Improving neural cross-lingual abstractive summarization via employing optimal transport distance for knowledge distillation. In *Proceedings of the AAAI conference on artificial intelligence* (pp. 11103–11111).

OpenAI (2023). GPT-4 technical report. arXiv preprint arXiv:2303.08774.

Pang, B., & Lee, L. (2005). Seeing stars: Exploiting class relationships for sentiment categorization with respect to rating scales. In *Proceedings of the 43rd annual meeting of the association for computational linguistics* (pp. 115–124).

Petroni, F., Rocktäschel, T., Riedel, S., Lewis, P., Bakhtin, A., Wu, Y., et al. (2019). Language models as knowledge bases? In *Proceedings of the 2019 conference on empirical methods in natural language processing and the 9th international joint conference on natural language processing* (pp. 2463–2473).

Qi, F., Chen, Y., Li, M., Yao, Y., Liu, Z., & Sun, M. (2021). ONION: A simple and effective defense against textual backdoor attacks. In *Proceedings of the 2021 conference on empirical methods in natural language processing* (pp. 9558–9566).

Qi, F., Li, M., Chen, Y., Zhang, Z., Liu, Z., Wang, Y., et al. (2021). Hidden killer: Invisible textual backdoor attacks with syntactic trigger. In *Proceedings of the 59th annual meeting of the association for computational linguistics and the 11th international joint conference on natural language processing* (pp. 443–453).

Qi, F., Yao, Y., Xu, S., Liu, Z., & Sun, M. (2021c). Turn the combination lock: Learnable textual backdoor attacks via word substitution. In *Proceedings of the 59th annual meeting of the association for computational linguistics and the 11th international joint conference on natural language processing* (pp. 4873–4883).

Schick, T., & Schütze, H. (2021). Exploiting cloze-questions for few-shot text classification and natural language inference. In *Proceedings of the 16th conference of the European chapter of the association for computational linguistics: main volume* (pp. 255–269).

Schucher, N., Reddy, S., & de Vries, H. (2022). The power of prompt tuning for low-resource semantic parsing. In *Proceedings of the 60th annual meeting of the association for computational linguistics (volume 2: short papers)* (pp. 148–156).

Sha, Z., He, X., Berrang, P., Humbert, M., & Zhang, Y. (2022). Fine-tuning is all you need to mitigate backdoor attacks. arXiv preprint arXiv:2212.09067.

Socher, R., Perelygin, A., Wu, J., Chuang, J., Manning, C. D., Ng, A. Y., et al. (2013). Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the 2013 conference on empirical methods in natural language processing* (pp. 1631–1642).

Sun, L., Huang, Y., Wang, H., Wu, S., Zhang, Q., Gao, C., et al. (2024). Trustllm: Trustworthiness in large language models. arXiv preprint arXiv:2401.05561.

Sun, W., Jiang, X., Dou, S., Li, D., Miao, D., Deng, C., et al. (2023). Invisible backdoor attack with dynamic triggers against person re-identification. *IEEE Transactions on Information Forensics and Security*.

Touvron, H., Lavril, T., Izacard, G., Martinet, X., Lachaux, M.-A., Lacroix, T., et al. (2023). Llama: Open and efficient foundation language models. arXiv preprint arXiv:2302.13971.

Tran, B., Li, J., & Madry, A. (2018). Spectral signatures in backdoor attacks. *Advances in Neural Information Processing Systems*, *31*.

Van der Maaten, L., & Hinton, G. (2008). Visualizing data using t-SNE. *Journal of Machine Learning Research*.

Voorhees, E. M., & Tice, D. M. (2000). Building a question answering test collection. In *Proceedings of the 23rd annual international ACM SIGIR conference on research and development in information retrieval* (pp. 200–207).

Wang, A., Singh, A., Michael, J., Hill, F., Levy, O., & Bowman, S. (2018). GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *Proceedings of the 2018 EMNLP workshop blackboxNLP: analyzing and interpreting neural networks for NLP* (pp. 353–355).

Wang, B., Yao, Y., Shan, S., Li, H., Viswanath, B., Zheng, H., et al. (2019). Neural cleanse: Identifying and mitigating backdoor attacks in neural networks. In *2019 IEEE symposium on security and privacy* (pp. 707–723). IEEE.

Wang, B., Yu, F., Wei, F., Li, Y., & Wang, W. (2024). Invisible intruders: Label-consistent backdoor attack using re-parameterized noise trigger. *IEEE Transactions on Multimedia*.

Xiao, W., Wang, Z., Gan, L., Zhao, S., He, W., Tuan, L. A., et al. (2024). A comprehensive survey of datasets, theories, variants, and applications in direct preference optimization. arXiv preprint arXiv:2410.15595.

Xiao, L., Wu, X., Xu, J., Li, W., Jin, C., & He, L. (2024). Atlantis: Aesthetic-oriented multiple granularities fusion network for joint multimodal aspect-based sentiment analysis. *Information Fusion*, *106*, Article 102304.

Xu, L., Chen, Y., Cui, G., Gao, H., & Liu, Z. (2022). Exploring the universal vulnerability of prompt-based learning paradigm. In *Findings of the association for computational linguistics: NAACL 2022* (pp. 1799–1810).

Xu, J., Ma, M. D., Wang, F., Xiao, C., & Chen, M. (2023). Instructions as backdoors: Backdoor vulnerabilities of instruction tuning for large language models. arXiv preprint arXiv:2305.14710.

Yan, J., Gupta, V., & Ren, X. (2023). BITE: Textual backdoor attacks with iterative trigger injection. In *ICLR 2023 workshop on backdoor attacks and defenses in machine learning*.

Yang, Z., Dai, Z., Yang, Y., Carbonell, J., Salakhutdinov, R. R., & Le, Q. V. (2019). Xlnet: Generalized autoregressive pretraining for language understanding. *Advances in Neural Information Processing Systems*.

Yoo, K. Y., & Kwak, N. (2022). Backdoor attacks in federated learning by rare embeddings and gradient ensembling. In *Proceedings of the 2022 conference on empirical methods in natural language processing* (pp. 72–88).

Yuan, H., Chu, Q., Zhu, F., Zhao, R., Liu, B., & Yu, N. (2021). Automa: Towards automatic model augmentation for transferable adversarial attacks. *IEEE Transactions on Multimedia*, *25*, 203–213.

Zampieri, M., Malmasi, S., Nakov, P., Rosenthal, S., Farra, N., & Kumar, R. (2019). Predicting the type and target of offensive posts in social media. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)* (pp. 1415–1420).

Zhang, Y., Ding, D. Y., Qian, T., Manning, C. D., & Langlotz, C. P. (2018). Learning to summarize radiology findings. In *Proceedings of the ninth international workshop on health text mining and information analysis* (pp. 204–213).

Zhang, R., Han, J., Liu, C., Gao, P., Zhou, A., Hu, X., et al. (2023). Llama-adapter: Efficient fine-tuning of language models with zero-init attention. arXiv preprint arXiv:2303.16199.

Zhang, T., Kishore, V., Wu, F., Weinberger, K. Q., & Artzi, Y. (2019). Bertscore: Evaluating text generation with BERT. In *International conference on learning representations*.

Zhang, Z., Lyu, L., Ma, X., Wang, C., & Sun, X. (2022). Fine-mixing: Mitigating backdoors in fine-tuned language models. In *Findings of the association for computational linguistics: EMNLP 2022* (pp. 355–372).

Zhao, S., Gan, L., Guo, Z., Wu, X., Xiao, L., Xu, X., et al. (2024). Weak-to-strong backdoor attacks for LLMs with contrastive knowledge distillation. arXiv preprint arXiv:2409.17946.

Zhao, S., Gan, L., Luu, A. T., Fu, J., Lyu, L., Jia, M., et al. (2024). Defending against weight-poisoning backdoor attacks for parameter-efficient fine-tuning. In *Findings of the association for computational linguistics: NAACL 2024* (pp. 3421–3438).

Zhao, S., Jia, M., Guo, Z., Gan, L., Fu, J., Feng, Y., et al. (2024c). A survey of backdoor attacks and defenses on large language models: Implications for security measures. arXiv preprint arXiv:2406.06852.

Zhao, S., Li, Q., Yang, Y., Wen, J., & Luo, W. (2023). From softmax to nucleusmax: A novel sparse language model for Chinese radiology report summarization. *ACM Transactions on Asian and Low-Resource Language Information Processing*.

Zhao, S., Liang, Z., Wen, J., & Chen, J. (2022). Sparsing and smoothing for the seq2seq models. *IEEE Transactions on Artificial Intelligence*.

Zhao, H., Ma, C., Dong, X., Luu, A. T., Deng, Z.-H., & Zhang, H. (2022). Certified robustness against natural language attacks by causal intervention. In *International conference on machine learning* (pp. 26958–26970). PMLR.

Zhao, S., Ma, X., Zheng, X., Bailey, J., Chen, J., & Jiang, Y.-G. (2020). Clean-label backdoor attacks on video recognition models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition* (pp. 14443–14452).

Zhao, S., Tian, J., Fu, J., Chen, J., & Wen, J. (2024d). FeaMix: Feature mix with memory batch based on self-consistency learning for code generation and code translation. *IEEE Transactions on Emerging Topics in Computational Intelligence*.

Zhao, S., Tuan, L. A., Fu, J., Wen, J., & Luo, W. (2024e). Exploring clean label backdoor attacks and defense in language models. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 3014–3024.

Zhao, S., Wen, J., Luu, A., Zhao, J., & Fu, J. (2023). Prompt as triggers for backdoor attack: Examining the vulnerability in language models. In *Proceedings of the 2023 conference on empirical methods in natural language processing* (pp. 12303–12317).

Zhao, S., Wu, X., Nguyen, C.-D., Jia, M., Feng, Y., & Tuan, L. A. (2024f). Unlearning backdoor attacks for LLMs with weak-to-strong knowledge distillation. arXiv preprint arXiv:2410.14425.

Zhou, X., Li, J., Zhang, T., Lyu, L., Yang, M., & He, J. (2023). Backdoor attacks with input-unique triggers in NLP. arXiv preprint arXiv:2303.14325.