
# GE23131-Programming Using C-2024

Roll no:240901007 Name: Akash. P



Status Finished branch:EEE-A Started Monday, 23 December 2024, 5:33 PM Completed Saturday, 19 October 2024, 12:35 PM **Duration** 65 days 4 hours Question 1 Write a program to input a name (as a single character) and marks of three tests as m1, m2, and m3 of a student considering all the three Correct marks have been given in integer format. Marked out of 3.00 Now, you need to calculate the average of the given marks and print it along with the name as mentioned in the output format section. Flag question All the test marks are in integers and hence calculate the average in integer as well. That is, you need to print the integer part of the average only and neglect the decimal part. Input format: Line 1 : Name(Single character) Line 2: Marks scored in the 3 tests separated by single space. Output format: First line of output prints the name of the student. Second line of the output prints the average mark. Constraints Marks for each student lie in the range 0 to 100 (both inclusive) Sample Input 1: A 346 Sample Output 1: 4 Sample Input 2: T 738 Sample Output 2: T 6 Answer: (penalty regime: 0 %) 1 #include <stdio.h> 2 int main () 3 , { char a; int t,b,c,d; scanf ("%c\n%d%d%d",&a,&b,&c,&d); t=(d+b+c)/3; 8 printf("%c\n%d",a,t); 9 return 0; 10 }

Input

**Expected Got** 

~	T	T	Т	~
	7 3 8	6	6	
~	R	R	R	~
	0 100 99	66	66	

Question 2

Correct Marked out of 5.00

Flag question

Some C data types, their format specifiers, and their most common bit widths are as follows:

Int (\*%d\*): 32 Bit integer

Passed all tests! <

- Long ("%ld"): 64 bit integer
- Char ("%c"): Character type
- Float ("%f"): 32 bit real value
- Double (\*%lf\*): 64 bit real value

### Reading

To read a data type, use the following syntax:

scanf("'format\_specifier'", &val)

For example, to read a character followed by a double:

char ch;

double d;

scanf("%c %lf", &ch, &d);

For the moment, we can ignore the spacing between format specifiers.

#### Printing

To print a data type, use the following syntax:

printf("`format\_specifier`", val)

For example, to print a character followed by a double:

char ch = 'd';

double d = 234.432;

printf("%c %lf", ch, d);

Note: You can also use cin and cout instead of scanf and printf; however, if you are taking a million numbers as input and printing a million lines, it is faster to use scanf and printf.

#### Input Format

Input consists of the following space-separated values: int, long, char, float, and double, respectively.

#### **Output Format**

Print each element on a new line in the same order it was received as input. Note that the floating point value should be correct up to 3 decimal places and the double to 9 decimal places.

## Sample Input

3 12345678912345 a 334.23 14049.30493

## Sample Output

12345678912345

a

334.230

14049.304930000

## Explanation

Print int 3,

followed by long 12345678912345,

followed by char a,

followed by float 334.23,

followed by double 14049.30493.

```
Answer: (penalty regime: 0 %)
```

```
1 #include <stdio.h>
2 int main ()
3 , {
4
       int a;
 5
       long b;
 6
       char c;
7
       float d;
       double e;
8
       scanf("%d \n %ld \n %c \n %f \n %lf",&a,&b,&c,&d,&e);
9
10
       printf("%d \n",a);
       printf("%ld \n",b);
       printf("%c \n",c);
13
       printf("%.3f \n",d);
       printf("%.9f \n",e);
14
15
       return 0;
16
17 }
```

	Input	Expected	Got	
~	3 12345678912345 a 334.23 14049.30493	3	3	~
		12345678912345	12345678912345	
		a	a	
		334.230	334.230	
		14049.304930000	14049.304930000	

Passed all tests! ✓ Question 3 Write a program to print the ASCII value and the two adjacent characters of the given character. Correct Marked out of Input 7.00 Flag question E Output 69 DF Answer: (penalty regime: 0 %) #include <stdio.h> 2 int main() 3 , { char c; 4 scanf("%c",&c); 5 printf("%d\n",c);
printf("%c %c\n",c-1,c+1); 7 8 return 0; 9 }