EY AI RESEARCH · ENTERPRISE SECURITY PRACTICE

AgentGuard .

Zero-Trust Security Proxy & Guardrail Middleware for AI Agents and LLM Tool Execution Pipelines.

INVENTOR
Anshul Kumaria | Gen-AI Intern

STATUS
Production Verified (22/22 Tests Pass)

EXECUTIVE SUMMARY

The Enterprise Agent Security Challenge

Unrestricted Tool Access

Autonomous agents invoke shell commands and databases directly, exposing enterprise infrastructure to severe operational risk.

Adversarial Prompt Injection

Malicious inputs and obfuscated indirect injections trick models into overriding safety boundaries and executing harmful logic.

Deterministic Interception

AgentGuard provides inline proxy enforcement, halting unauthorized payloads before reaching downstream OS or database drivers.

Audit-Ready Compliance

Enforces strict structured schemas and standardized telemetry error codes for comprehensive security logging and reporting.

ARCHITECTURE

Dual-Layer Threat Detection Engine

1. Semantic Intent Vectorization

Leverages `all-MiniLM-L6-v2` dense embeddings to evaluate cosine similarity against known jailbreak vectors in real-time.

2. Argument Pattern Inspector

Applies case-insensitive regex rules (`rm -rf`, `bash -i`, `wget http`) to intercept high-risk parameters instantly.

3. Zero-Trust Choke Point

Intercepts requests inline between the LLM planner and execution tools with negligible latency impact.

4. Standardized Telemetry

Returns clear, machine-readable security rejections (`ERR_SEMANTIC_JAILBREAK`, `ERR_UNAUTHORIZED_COMMAND`).

GOVERNANCE

Pydantic V2 Strict Schema Enforcement

To prevent payload smuggling and parameter injection, AgentGuard enforces rigorous data contracts at the API boundary.

- **extra="forbid": Rejects unauthorized payload fields.**
- **strict=True: Eliminates implicit type coercion vulnerabilities.**
- **Component Isolation: Evaluates prompt and arguments independently.**

```
class ToolExecutionRequest(BaseModel): model_config = ConfigDict( extra="forbid", strict=True ) tool_name: str = Field(..., description="Target tool") arguments: Dict[str, Any] = Field(default_factory=dict) raw_prompt: Optional[str] = Field(None)
```

LIVE VERIFICATION

Phase 1: FastAPI Gateway Initialization

Uvicorn successfully boots on port 8000, loading the semantic embedding weights into memory for real-time inspection.

> **Status:** Ready for secure proxy routing and threat evaluation.




Figure 1: `server.py` initialization & Uvicorn binding

LIVE VERIFICATION

Phase 2: Safe Execution vs Destructive Block

Demonstrating deterministic rejection. Benign queries return HTTP 200, while `rm -rf /` triggers an immediate HTTP 403 Forbidden.

> **Error Code:** `ERR_UNAUTHORIZED_COMMAND`




Figure 2: HTTP 200 Success vs HTTP 403 Security Block

LIVE VERIFICATION

Phase 3: Semantic Jailbreak Interception

Vector similarity successfully identifies obfuscated prompt override attempts, halting execution prior to tool dispatch.

> **Error Code:** `ERR_SEMANTIC_JAILBREAK`




Figure 3: Semantic vector match & rejection response

ROADMAP

Future Scope & Enterprise Enhancements

Policy Engine & YAML Config

Deploy role-based tool permission profiles and custom tenant rulesets for multi-department enterprise deployments.

AST SQL Injection Inspection

Integrate abstract syntax tree parsing to detect malicious SQL payloads before database tool execution.

Egress Network Filtering

Implement strict domain allowlisting for HTTP fetching tools to eliminate data exfiltration vectors.

SIEM & OpenTelemetry Tracing

Stream structured audit logs directly into Splunk, Datadog, and enterprise security operations centers.