

Project Progress VIII

Archana Kumari

Under the Guidance of
Dr. Pulak Mondal

14 March 2016

Logarithmic search was implemented in MATLAB with macroblock size 8x8 and search area 24x24 for 10 consecutive frames of the video sequence of "Foreman", to get 10 residual frames after proper motion compensation while forming the predicted frames. Hence a set of motion vectors were also generated. The following MATLAB code was implemented:

```
clc
clear all
close all
tstart=cputime;
f_ref(1:300,1:300)=0;
Im=imread('E:\foreman_10frames\f001.pgm');
f_ref(9:288,9:288)= Im(9:288,9:288);

srcFiles = dir('E:\foreman_10frames\*.pgm');

f_p=zeros(300,3000);

X=zeros(35,350);
Y=zeros(35,350);
MSE=zeros(1,9);
for frameNo=1:9
    filename = strcat('E:\foreman_10frames\',srcFiles(frameNo+1).name);
    f_2(1:300,1:300)=0;
    Im2= imread(filename);
    f_2(9:288,9:288)= Im2(9:288,9:288);
    f_pre(1:300,1:300)=0;

s=1;
X_motion= zeros(22,22);
Y_motion=zeros(22,22);
for i=9:8:288
    t=1;
    for j=9:8:288
        img_abs=[0 0 0 0 0];
        img_24=f_ref(i-8:i+7+8,j-8:j+7+8);
        img_8=f_2(i:i+7,j:j+7);
        flag = 1;
        I=1;
        Rc=9;
```

```

Cc=9;
step_size=4;

while flag
    r=[Rc,Rc-step_size,Rc,Rc,Rc+step_size];
    c=[Cc,Cc,Cc-step_size,Cc+step_size,Cc];

    for g=1:5
        if r(g)<=0 || r(g)>=17
            img_abs(g)=255*64*255;
        elseif c(g)<=0 || c(g)>=17
            img_abs(g)=255*64*255;
        elseif g==I && g-1>0
            img_abs(g)=255*64*255;
        else
            img_abs(g)=sum(sum((img_24(r(g):r(g)+7,c(g):c(g)+7)- img_8).^2));
        end
    end

[M,I] = min(img_abs);
switch (I)
    case 1
        step_size=step_size/2;
    case 2
        Rc=Rc-step_size;
    case 3
        Cc=Cc-step_size;
    case 4
        Cc=Cc+step_size;
    case 5
        Rc=Rc+step_size;
end
if step_size<1
    flag=0;
    break;
else
    continue;
end
end
    f_pre(i:i+7,j:j+7)=img_24(Rc:Rc+7,Cc:Cc+7);
    X_motion(s,t)= Rc-9;
    Y_motion(s,t)= Cc-9;

t=t+1;
end
s=s+1;

end
f_p(1:300, 1+(300*frameNo):300*(frameNo+1))=f_pre;
X(1:35, 1+(35*(frameNo-1)):35*frameNo)=X_motion;
Y(1:35, 1+(35*(frameNo-1)):35*frameNo)=Y_motion;

```

```

residu=abs(f_2-f_pre);
MSE(frameNo)=(sum(sum((residu).^2)))/90000;
figure,imshow(uint8(residu));
title('reduced residue after Logarithmic Search Operation');
figure,imshowpair(f_2,f_ref,'diff');
title('actual residue or difference between frames');

f_ref=f_2;
end
telapsed=cputime-tstart;
Frame=[1 2 3 4 5 6 7 8 9];
figure,LogSearch=plot(Frame,MSE);
title('Mean Square Error [MSE] Vs Frames Plot');
ylabel('MSE found in Logarithmic Search');
xlabel('Frame number');
display('time elapsed in search');
display(telapsed);
display(MSE);

```

time elapsed in search

telapsed =

11.8750

MSE =

Columns 1 through 7

23.2319 18.5147 21.4357 18.4010 15.1979 20.9555 22.0864


Columns 8 through 9

24.6960 25.6278

reduced residue after Logarithmic Search Operation




actual residue or difference between frames




reduced residue after Logarithmic Search Operation



actual residue or difference between frames




reduced residue after Logarithmic Search Operation




actual residue or difference between frames




reduced residue after Logarithmic Search Operation




actual residue or difference between frames




reduced residue after Logarithmic Search Operation



actual residue or difference between frames



reduced residue after Logarithmic Search Operation




actual residue or difference between frames




reduced residue after Logarithmic Search Operation



actual residue or difference between frames




reduced residue after Logarithmic Search Operation



actual residue or difference between frames



reduced residue after Logarithmic Search Operation



actual residue or difference between frames

