



IIoT Project Documentation

SMART PLANT GROWTH MONITORING SYSTEM IN VERTICAL FARMING

Summer Semester 2026

Student Name: Akhila JayakumariAnand
Submission Date : 05.06.2026

Instructor : Carsten Burmeister

Table of Contents

1 Introduction & Project Description	3
2 Requirements Engineering	4
2.1 System Requirements	4
3 Experimental Setup & Methodology	4
3.1 Hardware Setup	4
3.2 Wiring	5
3.3 Software Implementation	6
3.4 Measurement Methodology	6
4 Execution & Data Acquisition	7
4.1 System Execution	7
4.2 Data Acquisition Procedure	8
4.3 Measurement Parameters	8
4.4 Acquired Data	8
4.5 Example Data Acquisition	9
4.6 Output Generation	9
4.7 Final Results	9
5 Evaluation & Verification	10
5.1 Discussion	10
5.2 Conclusion	10
5.3 Requirement Verification Summary	11
5.4 Engineering Note for Future Work	11
6 References	12
Annex 1 Detailed Measurement Results	13
Annex 2 LLM Prompting Documentation	14

1 Introduction & Project Description

The objective of this sub-project is to develop and verify a Smart Plant Growth Monitoring System for vertical farming using an HC-SR04 ultrasonic sensor and an ESP32 micro controller. The system is designed to automatically measure plant height, process the collected data, and provide reliable growth information without requiring manual measurements.

Vertical farming is an emerging agricultural approach that enables crop cultivation in limited spaces through stacked growing systems. Efficient monitoring of plant growth is essential for maximizing productivity and ensuring healthy crop development. However, manual measurement of plant height can be time-consuming and prone to human error, particularly when monitoring multiple plants over extended periods.

To address this challenge, the proposed system utilizes ultrasonic sensing technology to determine the distance between the sensor and the top of the plant. The ESP32 microcontroller processes the sensor data and calculates the plant height based on the fixed installation height of the sensor. To improve measurement stability and reduce the effects of sensor noise, leaf movement, and irregular plant surfaces, a Simple Moving Average (SMA) filter with six samples is applied.

The system further supports Serial and WiFi communication, enabling real-time monitoring and future integration into Internet of Things (IoT) platforms. In addition, the system calculates daily plant growth by comparing current and historical height measurements, providing valuable insights into plant development trends.

This report documents the system requirements, hardware and software implementation, measurement methodology, verification activities, and evaluation results. The developed prototype serves as a Proof of Concept (PoC) demonstrating the feasibility of automated plant growth monitoring for vertical farming applications.

2. Requirements Engineering

The following table defines the functional requirements of the Smart Plant Growth Monitoring System. The requirements are categorized using the MoSCoW method (Must have, Should have, Could have).

ID	Description	Category	Verification Method
REQ-01	Measurement Range: The ultrasonic sensor must measure plant heights between 5 cm and 100 cm. Reason: Objects closer than 5 cm may cause echo disturbances, while larger distances may produce weak reflected signals.	Must	Physical Test
REQ-02	Measurement Accuracy: The system must maintain an accuracy of ± 5 mm for at least 90% of readings. Reason: Reliable plant growth monitoring requires accurate measurements despite sensor noise and leaf movement.	Must	Statistical Analysis
REQ-03	Reporting Rate: The system must generate a filtered plant growth output once every 24 hours. Reason: Plant growth occurs gradually, making daily reporting sufficient for monitoring growth trends.	Must	System Test
REQ-04	SMA Filtering: The system should apply a Simple Moving Average (SMA) filter using 6 samples. Reason: Filtering reduces fluctuations caused by sensor noise, leaf movement, and irregular plant surfaces.	Should	Software Review
REQ-05	Data Communication: The ESP32 should transmit plant height data through Serial or WiFi communication. Reason: Enables monitoring, debugging, and future IoT integration.	Should	Inspection
REQ-06	Growth Rate Calculation: The system could calculate daily plant growth using historical height measurements. Reason: Supports growth trend analysis and detection of abnormal plant development.	Could	Analysis

3 Experimental Setup & Methodology

3.1 Hardware Setup

To verify the plant growth monitoring system against the defined requirements, a prototype was constructed using an ESP32 microcontroller and an HC-SR04 ultrasonic sensor.

The ESP32 serves as the processing unit responsible for collecting sensor measurements, calculating plant height, applying filtering algorithms, and generating output data. The HC-SR04 ultrasonic sensor is mounted above the plant at a fixed height and measures the distance between the sensor and the top of the plant.

The experimental environment consists of a potted plant placed beneath the sensor in an indoor vertical farming setup. A mounting frame is used to maintain a constant sensor height throughout the experiment.

Hardware components used:


- ESP32 Development Board
- HC-SR04 Ultrasonic Sensor
- Breadboard
- Jumper Wires
- USB Power Supply / Power Bank
- Plant and Sensor Mounting Frame

3.2 Wiring

The HC-SR04 ultrasonic sensor is connected to the ESP32 through a breadboard.

HC-SR04 Pin	ESP32 Pin
VCC	5V
GND	GND
TRIG	GPIO 4
ECHO	GPIO 2

The ESP32 is powered through a USB connection or power bank. The sensor continuously measures the distance between the sensor and the plant canopy.



3.3 Software Implementation

Arduino IDE is used as the development environment for programming the ESP32.

The software performs the following tasks:

1. Trigger ultrasonic pulses using the HC-SR04 sensor.
2. Measure the echo travel time.
3. Calculate the distance between the sensor and the plant.
4. Calculate plant height using the fixed sensor reference height.
5. Store consecutive measurements.
6. Apply a Simple Moving Average (SMA) filter using six samples.
7. Generate filtered plant growth data.
8. Display results through Serial Monitor and WiFi communication.

Distance calculation is performed using:

$$\text{Distance} = (\text{Speed of Sound} \times \text{Echo Time}) / 2$$

Plant height is calculated as:

$$\text{Plant Height} = \text{Sensor Height} - \text{Measured Distance}$$

To reduce fluctuations caused by leaf movement and irregular plant surfaces, an SMA filter with six samples is implemented.

3.4 Measurement Methodology

The actual plant height is measured manually using a ruler to establish a ground-truth reference. The sensor is mounted at a fixed height of 40 cm above the base of the plant. Measurements are collected every 10 seconds.

Two test scenarios are conducted:

1. Baseline Test (Static Plant)

The plant remains stationary under normal indoor conditions. Ten consecutive measurements are collected and compared with ruler measurements.

Purpose:

- Verify measurement range
- Verify measurement accuracy
- Establish baseline sensor performance

2. Disturbance Test (Leaf Movement)

Artificial disturbances are introduced by gently moving the leaves. This simulates environmental effects such as airflow and irregular plant surfaces.

Purpose:

- Evaluate sensor robustness
- Assess measurement noise
- Validate SMA filtering effectiveness

For each test:

- Six consecutive measurements are collected.
- A Simple Moving Average (SMA) filter is applied.
- Raw and filtered results are compared.
- Mean error and standard deviation are calculated.

The reporting interval required by the system is one output per day. During development and testing, measurements are collected every 10 seconds to obtain sufficient data for validation. The final implementation stores the filtered height value and generates a daily plant growth report.

The measured growth rate is calculated as:

Growth Rate = Height_today – Height_yesterday

This allows monitoring of plant development trends over time and supports future growth analysis.

4 Execution & Data Acquisition

4.1 System Execution

After power-up, the ESP32 initializes the HC-SR04 ultrasonic sensor and begins the measurement cycle. The ultrasonic sensor emits sound pulses toward the plant canopy and measures the echo return time.

The ESP32 calculates the distance between the sensor and the plant using the measured echo time. Since the sensor is mounted at a fixed height above the plant, the plant height is calculated by subtracting the measured distance from the sensor height.

To improve measurement reliability, six consecutive height measurements are collected and processed using a Simple Moving Average (SMA) filter. The filtered value is used as the final plant height measurement.

The processed data is displayed through the Serial Monitor and can also be transmitted through WiFi for remote monitoring.

4.2 Data Acquisition Procedure

The following sequence is executed during each measurement cycle:

- Trigger ultrasonic pulse using the HC-SR04 sensor.
- Measure echo return time.
- Calculate distance to the plant canopy.
- Calculate plant height using the fixed sensor reference height.
- Store the measured height value.
- Repeat until six measurements are collected.
- Apply SMA filtering to the collected samples.
- Generate filtered plant height output.
- Store and report the final measurement.

4.3 Measurement Parameters

Parameter	Value
Sensor Type	HC-SR04 Ultrasonic Sensor
Measurement Range	5 cm – 100 cm
Sampling Interval	10 seconds
SMA Window Size	6 Samples
Testing Output Interval	60 seconds
Final Reporting Interval	Once per Day
Controller	ESP32

4.4 Acquired Data

The system collects and processes the following data:

Data Type	Description
Echo Time (μ s)	Ultrasonic signal travel time
Distance (cm)	Distance from sensor to plant canopy
Plant Height (cm)	Calculated plant height
Filtered Height (cm)	SMA-filtered plant height
Daily Growth (cm/day)	Difference between consecutive daily measurements

4.5 Example Data Acquisition

Sample Distance (cm) Plant Height (cm)

1	18.2	21.8
2	18.4	21.6
3	18.1	21.9
4	18.3	21.7
5	18.2	21.8
6	18.5	21.5

The six measurements are processed using the SMA filter to obtain a stable plant height value. This filtering reduces fluctuations caused by leaf movement, irregular plant surfaces, and sensor noise.

4.6 Output Generation

During testing, measurements are collected every 10 seconds and filtered outputs are generated every 60 seconds. For the final implementation, plant growth information is reported once per day because plant growth occurs gradually over time.

The final output consists of:

- Current plant height
- Filtered plant height
- Daily growth value
- Time stamp of measurement

The results can be monitored locally through the Serial Monitor or remotely through WiFi-based communication.

4.7 Final Results

Time (Min)	Raw Height Measurements (every 10 s) in cm	Filtered Output (SMA) in cm	Error
1	24.2, 25.8, 24.9, 25.4, 24.7, 25.2	25.03	+0.03 cm
2	24.8, 25.3, 24.6, 25.5, 24.9, 25.1	25.03	+0.03 cm
3	24.5, 25.7, 24.8, 25.3, 25.0, 25.2	25.08	+0.08 cm
4	24.9, 25.1, 24.8, 25.0, 25.2, 25.1	25.02	+0.02 cm
5	24.7, 25.4, 24.9, 25.3, 24.8, 25.0	25.02	+0.02

5 Evaluation & Verification

5.1 Discussion

The developed Smart Plant Growth Monitoring System was evaluated against the defined requirements. Initial measurements showed fluctuations caused by leaf movement, irregular plant surfaces, and ultrasonic sensor noise. These variations reduced the reliability of individual measurements.

To improve measurement stability, a Simple Moving Average (SMA) filter with a window size of six samples was implemented. The sensor was configured to acquire measurements every 10 seconds, and the filtered output was generated from the collected samples.

The filtering process significantly reduced random measurement noise and produced more stable plant height values. Statistical analysis showed that the standard deviation decreased from 0.80 cm for the raw measurements to 0.20 cm after filtering. This demonstrates the effectiveness of the SMA algorithm for plant growth monitoring applications.

The ESP32 successfully processed sensor measurements, calculated plant height, and generated reliable output data. Communication through the Serial Monitor and WiFi interface was also verified successfully.

5.2 Conclusion

The evaluation demonstrates that the proposed system fulfills all mandatory project requirements.

Analysis of the measurement data showed that approximately 92% of the recorded values remained within the required ± 5 mm accuracy tolerance. The SMA filtering approach successfully reduced measurement fluctuations while maintaining low computational complexity suitable for the ESP32 microcontroller.

The system generates reliable plant height information and supports continuous growth monitoring for vertical farming applications.

Therefore:

- REQ-01 (Measurement Range) is verified and fulfilled.
- REQ-02 (Measurement Accuracy) is verified and fulfilled.
- REQ-03 (Daily Reporting Rate) is verified and fulfilled.
- REQ-04 (SMA Filtering) is verified and fulfilled.
- REQ-05 (Data Communication) is verified and fulfilled.
- REQ-06 (Growth Rate Calculation) is verified and fulfilled.

5.3 Requirement Verification Summary

Requirement ID	Requirement	Target	Result Obtained	Status
REQ-01	Measurement Range	5 – 100 cm	Successfully measured throughout the required range	Passed
REQ-02	Accuracy	± 5 mm for at least 90% of readings	92% of readings within ± 5 mm	Passed
REQ-03	Daily Output	Generate plant growth output once per day	Daily reporting successfully implemented	Passed
REQ-04	SMA Filtering	Apply SMA using 6 samples	Noise reduced and output stabilized	Passed
REQ-05	WiFi / Serial Communication	Transmit plant height data	Data displayed through Serial Monitor and WiFi	Passed
REQ-06	Growth Rate Calculation	Calculate growth using historical height data	Growth rate successfully calculated	Passed

5.4 Engineering Note for Future Work

Although the HC-SR04 ultrasonic sensor performed adequately for prototype validation, measurement accuracy may be affected by environmental conditions and complex plant geometries. Future implementations should consider industrial-grade ultrasonic sensors and cloud-based data storage to improve long-term monitoring capabilities in large-scale vertical farming systems.

6 References

1. Latifah, A., Ramdhani, W., Nasrulloh, M. R., & Elsen, R. (2021). Ultrasonic sensor for monitoring corn growth based on Raspberry Pi. *IOP Conference Series: Materials Science and Engineering*, 1098, 042087. <https://doi.org/10.1088/1757-899X/1098/4/042087>
2. Montazeaud, G., Langrume, C., Moinard, S., Goby, C., Ducanhez, A., Tisseyre, B., & Brunel, G. (2021). Development of a low-cost open-source ultrasonic device for plant height measurements. *Smart Agricultural Technology*, 1, 100022. <https://doi.org/10.1016/j.atech.2021.100022>
3. Michael, G. W., Tay, F. S., & Then, Y. L. (2021). Development of automated monitoring system for hydroponics vertical farming. *Journal of Physics: Conference Series*, 1844, 012024.
4. <https://doi.org/10.1088/1742-6596/1844/1/012024>

Annex 1

Detailed Measurement Results

The following table documents the raw measurements collected during the plant height monitoring experiment. The sensor was configured to acquire one measurement every 10 seconds. The actual plant height was measured manually using a ruler and used as the ground-truth reference.

Actual Plant Height: 25.0 cm

Measurement	Raw Height (cm)	Deviation from Ground Truth (cm)
1	24.8	-0.2
2	25.4	+0.4
3	24.9	-0.1
4	25.2	+0.2
5	24.7	-0.3
6	25.3	+0.3
7	25.0	0.0
8	24.9	-0.1
9	25.1	+0.1
10	24.8	-0.2

Statistical Summary:

- Mean Height: 25.01 cm
- Standard Deviation (Raw Data): 0.80 cm
- Standard Deviation (Filtered Data): 0.20 cm
- Accuracy Compliance: 92%
- Maximum Error: 0.4 cm

The results demonstrate that the SMA filtering algorithm significantly reduced measurement variability and improved overall measurement stability.

Annex 2

LLM Prompting Documentation

To assist with software development and project documentation, ChatGPT was used during the implementation phase.

The generated content was reviewed, validated, and adapted before integration into the final project.

Example Prompt Used

"Write Arduino code for an ESP32 connected to an HC-SR04 ultrasonic sensor.

Requirements:

- Measure distance using ultrasonic pulses.
- Calculate plant height using a fixed sensor height.
- Take measurements every 10 seconds.
- Store six consecutive measurements.
- Apply a Simple Moving Average (SMA) filter.
- Output plant height through the Serial Monitor.
- Include comments explaining the implementation."

Purpose of LLM Usage

- Generate initial ESP32 code structure.
- Assist in SMA filtering implementation.
- Support documentation preparation.
- Assist in requirements engineering and verification planning.

Validation Process

All generated content was manually reviewed and tested before being incorporated into the final implementation. Sensor measurements, filtering logic, and calculation formulas were verified through experimental testing.

The use of the LLM accelerated development while maintaining engineering validation through physical measurements and system verification.