ANYstructure



Documentation

2021

Version 3.X

Introduction **3**

Theory **3**

Modelling **4**

Assigning properties **5**
- Scale stresses 6
- Changing multiple properties 7
- Display properties 8

Define tanks **9**
- COB and COG 11

Setting accelerations **12**

Define external pressures **13**

Load combinations **14**
- Changing load factors 15

Buckling **16**
- Prescriptive 17
- PULS integration 17
- ML buckling 20

Reviewing data **21**
- Color coding 21
- Shifting coordinates for visual purposes 21
- Loads 22
- Thickness and beam properties 24
- Global stresses (buckling) and structure types 24

Results **25**

Optimization **26**
- Optimization iteration by predefined stiffeners 26
- Single optimization 27
- Multiple optimization 29
- Span optimization 30

Reporting **35**
- General 35
- Table 36

Export to JS **36**

Introduction

ANYstructure is a free structural optimization tool. It can be used for multiple purposes. The software can be downloaded various ways:

For python users
PIP install ANYstructure

For windows version
Download at https://github.com/audunarn/ANYstructure/releases or https://sourceforge.net/projects/anystructure/

The code is located on github and is open source (https://github.com/audunarn/ANYstructure)

Theory

All calculations are according to the following DNV standards and recommended practices:

- **DNVGL-OS-C101 Design of offshore steel structures, general - LRFD method**
  - **http://rules.dnvgl.com/docs/pdf/DNVGL/OS/2018-07/DNVGL-OS-C101.pdf**
- **DNV-RP-C203 Fatigue design of offshore steel structures**
- **DNV-RP-C201 BUCKLING STRENGTH OF PLATED STRUCTURES**
  - **https://rules.dnvgl.com/docs/pdf/DNV/codes/docs/2010-10/RP-C201.pdf**
- **PULS (Panel Ultimate Limit State)**
- DNVGL-CG-0128 Buckling

Modelling

Modelling is done in upper left corner.

Right click: select point

You can copy or move the selected point by shortcut or clicking Buttons.

Left click: select line

A line is made by right clicking two points (or input point number)



Speed up your modelling significantly by using the shortcuts:

CTRL-Z	**Undo modelling**
CTRL-P	**Copy a selected point**
CTRL-M	**Move a selected point**
CTRL-Q	**New line between two selected points**
CTRL-S	**Assign properties to a selected line**
CTRL-DELETE	**Delete the structural properties from the selected line**

DELETE **Delete selected line/point**

CTRL-E **Select a line and copy the properties of this line**

CTRL-D **Paste structural properties to a selected line**

Arrows up/down **Toggle point in model**

Arrows left/right **Toggle lines in model**

CTRL-A **Select all lines in model for changing a selected parameter for all**

CTRL-T **Select all lines of a specific structure type for changing a parameter for multiple lines.**

The shortcuts can be shown in the GUI as seen next.



Assigning properties

Input properties manually or click the button indicated below to set the values. Values are set by clicking “Add structure to line”. This also applies to fatigue properties. If you have added a property to a line and want to use the same for the next line, just press “Add structure to line” on the new line.

All beam sections are recorded. If you want to apply an existing, choose it from the drop down menu. Then press “Save and return structure”.



By default z* is ticked. This affects the buckling results and will generally give lower utilization than using z* = 0. See description below.

z^* is the distance from the neutral axis of the effective section to the working point of the axial force. z^* may be varied in order to optimise the resistance. z^* should then be selected so the maximum utilisation found from the equations (7.50) to (7.53) or (7.54) to (7.57) is at its minimum, see also Commentary Chapter 10. The value of z^* is taken positive towards the plate. The simplification $z^* = 0$ is always allowed.

Scale stresses

Stresses can be automatically scaled when changing a property, for example plate thickness. The parameters fup and fdown specify the factor to be applied to the scaling when scaling up (thicker plate) or down (thinner plate).



The formula applied is referenced next. The factor depends on your case.

If panel thickness (T) is changed (dT), stress may be scaled by a factor (f) according to the formula:

$$newStress = \left(\frac{T}{T + f * dT}\right) * oldStress$$

- f = 0.0 -> stress does not depend on local thickness change.
- f = 1.0 -> stress is proportional to local thickness change.

Stresses to be scaled are axial stress (SigmaX), transversal stress(SigmaY) and shear stress (TauXY).

The parameters fdown = 1 and fup = 0.5 is by default. The general idea is that it is conservative to accept lower stress reduction when increasing thicknesses.

Changing multiple properties

If you want to change a single property for multiple lines. How to do it:

1. Press Toggle select multiple
2. Select the parameter to change
3. Select the lines to change. Click single lines, CTRL-A or CTRL-T (see shortcuts)
4. Press Change multi. param.



Display properties

If you click a line properties is displayed in the window below as seen next.



Also it is recommended to use color coding to review your input.

Define tanks

Tanks are searched for when clicking “Find compartments”. Non watertight structure are ignored. For information on structure types click “Show structure types”.

<u>By default tank content density is set to 1025 (water).</u>

Ather tanks are found content and overpressure must be defined as seen next.



If you press "Display current compartments" after doing a compartment search, the result of the search is illustrated as seen next. Approximate area of the respective compartments is also shown.



COB and COG

COG is calculated when structure properties are defined. COB for various drafts is calculated when tank search is completed.



Development of weight and COG is recorded each time the structure changes. The resulting plot can be seen by pressing the “weights” button.



Output example is seen next.



Plates in model	Beams in model
18.0 mm	T_400_0x12_0__200_0x20_0
25.0 mm	T_400_0x12_0__250_0x14_0
12.0 mm	T_400_0x12_0__250_0x12_0
20.0 mm	T_400_0x12_0__200_0x18_0
14.0 mm	T_400_0x12_0__150_0x20_0
30.0 mm	T_500_0x12_0__150_0x20_0
15.0 mm	T_340_0x12_0__200_0x20_0
	T_340_0x12_0__150_0x16_0
	T_250_0x12_0__150_0x14_0
	T_450_0x12_0__150_0x20_0
	T_375_0x12_0__150_0x18_0
	T_500_0x12_0__150_0x25_0
	T_325_0x12_0__150_0x16_0
	FB_250_0x18_0
	FB_400_0x18_0
	T_350_0x12_0__150_0x20_0
	T_320_0x12_0__150_0x20_0
	T_300_0x12_0__150_0x20_0

Setting accelerations

Accelerations applies to tank content. I is set in the upper right corner as seen next.



Define external pressures

Click “External pressures” to define pressures acting on the structures.

NOTE:

FOR DYNAMIC EQUATION THE FOLLOWING APPLIES

X (horizontal) used for BOTTOM, BBT, HOPPER, MD

Z (vertical) used for BBS, SIDE_SHELL, SSS

After new window is opened:

1. **Make dynamic loads**
    a. **Dynamic loads are made by defining up to 3rd degree equations. X or Y direction depends on the defined structure type.**
    b. **Note that you can define a constant dynamic load by using Constant (Constant (C)) only.**
2. **Static loads are calculated according to depth.**
3. **To apply a defined load to a line or multiple lines:**
    a. **a. Select load by clicking the created load**
4. **Click the lines that shall have the load. Click the button “Press to add selected lines to selected load”**
5. **When finished press the button in the upper right corner.**



Slamming loads can be specified separately. The multiply factors are the slamming pressure to be used on plate and stiffener respectively. For example for a 10 bar pressure:

Pplate = 10 bar * factor_plate

Pstf = 10 bar * factor_stiffener

Load combinations

Load combinations are created automatically after external pressures are defined. Some comments on the loads.

1. **According to DNVGL-OS-C101**

2. **Highest pressure are chosen w.r.t. tank filling.**
3. **You can deselect a load by manually inputting load factor to 0 or deselect include.**



Changing load factors

You can change default load factors and existing load factors using the button seen in the next illustration.

Load factors are based on standard DNV LRFD factors, but any values can be used.





Buckling

ANYstructure has 3 options for calculating buckling.

Prescriptive

Buckling calculations as per DNV-RP-C203.



PULS integration

ANYstructure can use PULS software to calculate buckling. PULS is a licensed DNV software. Consequently, PULS integration will not work if you do not have the license. Specifically ANYstructure uses the PULS Excel sheet to calculate. Macros must be enabled for the sheet. The sheet may require a 32 bit version of Microsoft Office. Using PULS is activated by clicking the button seen next. When running a line for the first time, you will be asked to provide the location of the PULS excel sheet. The sheet should be empty and macros should be enabled.



PULS parameters are set for each line.

1. Stiffened panel (SP) or unstiffened plate (UP).
    a. If UP is chosen you can specify the boundary conditions. The conditions consist of four letters, representing left side, right side, top and bottom (in this order). ‘S’ means simply supported and ‘C’ means Clamped. ‘SSSS’ is conseqeuntly all simply supported and for example ‘SSCC’ is simply supported sides with clamped top and bottom.
2. Integrated (Int) or girder panels (GL/GT)
3. Continuous or Sniped stiffener
4. Ultimate or buckling acceptance. In general ultimate acceptance is more representative for larger plate fields where loads can be redistributed. Reference is made to DNV standards.

For theory check out PULS manual and/or Part 1, chapter 8 of the IACS Common structural rules for bulk carriers and oil tankers:

https://iacs.org.uk/publications/common-structural-rules/csr-for-bulk-carriers-and-oil-tankers/

Detailed PULS results can be viewed by selecting a line a pressing the “PULS results for line” button:



ML buckling

THe buckling ML option is an implementation of PULS using a neural network. It uses the same input as PULS. Note that the “PULS utilization factor” does not apply. The CL (classification) neural network will use 1/1.15 =0.87 as material factor and get the acceptance from that. If you need other acceptance criterias, contact Audun (audunarn@gmail.com). In that case the neural networks must be retrained for other acceptance levels.

The results should be used with care, as a neural network typically can give an incorrect prediction. The accuracy is currently in range of 97%.

ML buckling can be used for all optimization options.



Reviewing data

Color coding

All color coding options are indicated next.



Shifting coordinates for visual purposes

You can shift the coordinates displayed for visual purposes. This does NOT affect the calculations of loads. This feature is included to better be able to review coordinates using different origins. Input magnitude of the shift in lower left corner and check “Use shifted coordinates” to activate.



Loads

Pressure magnitude can be reviewed by using color coding. The highest total pressure used in calculations is shown.



Load calculations and results can be reviewed by clicking the “Load info” button. An example is seen in the next illustration.



Thickness and beam properties

Line plate thicknesses and beam properties can be reviewed using color coding. Plate thicknesses are exemplified next.



Global stresses (buckling) and structure types

Stresses used in buckling calculations can be reviewed by checking as illustrated next.



Results

When clicking a line, results as presented in the window below. If the result for the clicked line is OK, the color of the line and text is green. If the result is NOT OK, the color of the line and text is red. Two examples are seen next.

All results ok

Section moduluses: Wey1: 4.8300E+06 [mm^3], Wey2: 1.7500E+06 [mm^3]
Minimum section modulus: 1.7163E+06 [mm^3]

Shear area: 5.1600E+03 [mm^2]
Minimum shear area: 3.5296E+03 [mm^2]

Plate thickness: 18.0 [mm]
Minimum plate thickness: 15.1 [mm]

Buckling results DNV-RP-C201 (z* optimized):
|eq 7.19: 0.88 |eq 7.50: 0.92 |eq 7.51: -0.19 |7.52: 0.6|eq 7.53: 0.92 |z*: 0.12

Fatigue results (DNVGL-RP-C203):
Total damage: NO RESULTS

Section modulus not ok
Buckling not ok

Section moduluses: Wey1: 4.2400E+06 [mm^3], Wey2: 1.4700E+06 [mm^3]
Minimum section modulus: 2.0739E+06 [mm^3]

Shear area: 4.6560E+03 [mm^2]
Minimum shear area: 4.1297E+03 [mm^2]

Plate thickness: 18.0 [mm]
Minimum plate thickness: 15.8 [mm]

Buckling results DNV-RP-C201 (z* optimized):
|eq 7.19: 0.9 |eq 7.50: 1.39 |eq 7.51: 0.35 |7.52: 0.81|eq 7.53: 0.73 |z*: 0.13

Fatigue results (DNVGL-RP-C203):
Total damage (DFF not included): 0.058 | With DFF = 2.0 --> Damage: 0.117

A combined utilization can be reviewed using color coding.

Optimization

Optimization iteration by predefined stiffeners

From 0.5 you can iterate by a defined set of stiffeners. Press the button marked below. Open a csv (or json) file. Then start your iterations. The only other input is the stiffener spacing and plate thickness.

To see how the input format is click the "open predefined stiffeners example" button. See illustrations next.



Note that the weight of your initial structure is ignored even though it is calculated. If the initial structure is in your predefined set it will be included in the evaluations.

Press the button indicated below to activate. A open file window will open when running the optimization.



Single optimization

Single optimization is done by clicking a line and clicking the "OPTIMIZE" button.

1. **Set the upper and lower bounds of the optimization.**
2. **Set the delta to be used for the searched. This is the step size of the optimization when using brute force method (for example anysmart).**
3. **Run the optimization.**
4. **If you are happy, return the properties by clicking the top button**

Various checks in the optimization module:

You can select the checks to be performed. PULS buckling can be used in optimization. Remember to check the running time.

The weight filter ensures that only sections with a lower weight than the current minimum weight. This significantly speed up the calculations, but if you want to see the full distribution of the various checks this must be unchecked.



If you press the “show calculated” button, you will get an overview of how many is ok and how many failed (and what criteria first failed). One “occurence” is a one checked plate/stiffener combination.



You will also be asked to save to a csv file. If you do not cancel, a csv file will ALL results will pre saved to your chosen location. If you open the file in excel you should see something like show next

Multiple optimization



Multiple optimization is done by clicking the “MultiOpt” button.

1. **Same input on upper bounds, lower bounds and delta.**
2. **Click all the lines you want to include in the optimization.**
3. **Run the optimization.**
4. **Check the properties by middle clicking the line you ran.**
5. **If you are happy return the properties by clicking the top button. Remember to select the lines you want to return. Lines that have been optimized is marked orange.**

The optimization can be harmonized. That means that the largest dimension found in the multiple optimization is used for all selected. This is done after all

plates/stiffeners are checked. Harmonization can only be done in the multiopt option. Note that the weight filter is not used when harmonizing, i.e. running will take some more time.

Other options that can be set is explained in the single optimization chapter. When showing calculated you must have selected a line (middle click).

Span optimization

NOTE: The span optimization is computationally heavy. It is recommended to use a set of predefined stiffeners.





The optimization is started as follows.

1. **Start by clicking as illustrated next:**



2. Check the input and checkboxes in the lower right corner

You can, similar to single optimization, select the checks that shall be runned. Also you can set the girder (frame) properties. This is used for calculating the weights.

Check for minimum section modulus	☑	**Frame (girder data) for weight calculation:**		
Check for minimum plate thk.	☑	Girder thickness	0.018	
Check for minimum shear area	☑	Stiffener height	0.25	
Check for buckling (RP-C201)	☑	Stiffener thickness	0.015	
Check for fatigue (RP-C203)	☑	Stf. flange width	0	
Check for bow slamming	☑	Stf. flange thickenss	0	
Check for local stf. buckling	☑	For weight calculation of girder: Max span mult / Min span mult		
			1.1	0.9
Factor when scaling stresses up, fup	0.5	Maximum span / Minimum span ->	6	2
Factor when scaling stresses up, fdown	1			

3. Start the calculation

The program will calculate variations of even spans in your structure as illustrated next. This is an example and the number of plate fields may vary.

4 plate fields



6 plate fields



8 plate fields



10 plate fields



With reference to the previous example, max span mult is the multiplicator for the 4 plate fields set up and min span mult is the weight multiplication for the 10 plate

field set up. This is adopted because one can assume the required dimensions for the girder will reduce when more girders are added.

Minimum span and maximum span is the minimum and maximum span of the plate fields in meters.

Results are presented as seen next.



In this case 8 plate fields with length of 3 meters will give the lowest weight. 6 plate fields are almost equal.

When the analysis has been runned you should save your results. Just specify a file name in the save file dialog. You can also get detailed individual results for a specified panel. Select number of plate fields in the iteration you want to look at,

then choose which panel to get data from. Order of the panels is the same as printed in the left result canvas.



Now close the window. Results are not currently returned to main window.

Detailed results, printed after running, looks like this :

```
--------------------------------------------------------------------------------
Plate fields: 22 Frames: 10
pl_650.0x14.0 stf_L180.0x8.0+33.0x17.8 span: 1.0636 structure type: BOTTOM stf. type: L pressure side: p | sigma_y1: 128.6 sigma_y2: 128.6 sigma_x: 177.9 tauxy: 6.4 START 1 OK!
pl_650.0x14.0 stf_L180.0x8.0+33.0x17.8 span: 1.0636 structure type: BOTTOM stf. type: L pressure side: p | sigma_y1: 128.6 sigma_y2: 128.6 sigma_x: 177.9 tauxy: 6.4 ------- OK!
pl_650.0x14.0 stf_L180.0x8.0+33.0x17.8 span: 1.0636 structure type: BOTTOM stf. type: L pressure side: p | sigma_y1: 128.6 sigma_y2: 128.6 sigma_x: 177.9 tauxy: 6.4 ------- OK!
pl_650.0x14.0 stf_L180.0x8.0+33.0x17.8 span: 1.0636 structure type: BOTTOM stf. type: L pressure side: p | sigma_y1: 128.6 sigma_y2: 128.6 sigma_x: 177.9 tauxy: 6.4 ------- OK!
pl_650.0x14.0 stf_L180.0x8.0+33.0x17.8 span: 1.0636 structure type: BOTTOM stf. type: L pressure side: p | sigma_y1: 128.6 sigma_y2: 128.6 sigma_x: 177.9 tauxy: 6.4 ------- OK!
pl_650.0x14.0 stf_L180.0x8.0+33.0x17.8 span: 1.0636 structure type: BOTTOM stf. type: L pressure side: p | sigma_y1: 128.6 sigma_y2: 128.6 sigma_x: 177.9 tauxy: 6.4 ------- OK!
pl_650.0x14.0 stf_L180.0x8.0+33.0x17.8 span: 1.0636 structure type: BOTTOM stf. type: L pressure side: p | sigma_y1: 128.6 sigma_y2: 128.6 sigma_x: 177.9 tauxy: 6.4 ------- OK!
pl_650.0x14.0 stf_L180.0x8.0+33.0x17.8 span: 1.0636 structure type: BOTTOM stf. type: L pressure side: p | sigma_y1: 128.6 sigma_y2: 128.6 sigma_x: 177.9 tauxy: 6.4 ------- OK!
pl_650.0x14.0 stf_L160.0x8.0+36.0x18.7 span: 1.0636 structure type: BOTTOM stf. type: L pressure side: p | sigma_y1: 128.6 sigma_y2: 128.6 sigma_x: 174.9 tauxy: 6.4 ------- OK!
pl_650.0x14.0 stf_L160.0x8.0+36.0x18.7 span: 1.0636 structure type: BOTTOM stf. type: L pressure side: p | sigma_y1: 128.6 sigma_y2: 128.6 sigma_x: 170.0 tauxy: 6.4 -END 1- OK!
pl_750.0x14.0 stf_L160.0x8.0+36.0x18.7 span: 1.0636 structure type: GENERAL_INTERNAL_WT stf. type: L pressure side: p | sigma_y1: 115.7 sigma_y2: 115.7 sigma_x: 144.9 tauxy: 6.4 START 2 OK!
pl_750.0x14.0 stf_L160.0x8.0+36.0x18.7 span: 1.0636 structure type: GENERAL_INTERNAL_WT stf. type: L pressure side: p | sigma_y1: 115.7 sigma_y2: 115.7 sigma_x: 144.9 tauxy: 6.4 ------- OK!
pl_750.0x14.0 stf_L160.0x8.0+36.0x18.7 span: 1.0636 structure type: GENERAL_INTERNAL_WT stf. type: L pressure side: p | sigma_y1: 115.7 sigma_y2: 115.7 sigma_x: 144.9 tauxy: 6.4 ------- OK!
pl_750.0x14.0 stf_L160.0x8.0+36.0x18.7 span: 1.0636 structure type: GENERAL_INTERNAL_WT stf. type: L pressure side: p | sigma_y1: 115.7 sigma_y2: 115.7 sigma_x: 144.9 tauxy: 6.4 ------- OK!
pl_750.0x14.0 stf_L160.0x8.0+36.0x18.7 span: 1.0636 structure type: GENERAL_INTERNAL_WT stf. type: L pressure side: p | sigma_y1: 115.7 sigma_y2: 115.7 sigma_x: 144.9 tauxy: 6.4 ------- OK!
pl_750.0x14.0 stf_L160.0x8.0+36.0x18.7 span: 1.0636 structure type: GENERAL_INTERNAL_WT stf. type: L pressure side: p | sigma_y1: 115.7 sigma_y2: 115.7 sigma_x: 144.9 tauxy: 6.4 ------- OK!
pl_750.0x14.0 stf_L160.0x8.0+36.0x18.7 span: 1.0636 structure type: GENERAL_INTERNAL_WT stf. type: L pressure side: p | sigma_y1: 115.7 sigma_y2: 115.7 sigma_x: 144.9 tauxy: 6.4 ------- OK!
pl_750.0x14.0 stf_L160.0x8.0+36.0x18.7 span: 1.0636 structure type: GENERAL_INTERNAL_WT stf. type: L pressure side: p | sigma_y1: 115.7 sigma_y2: 115.7 sigma_x: 144.9 tauxy: 6.4 ------- OK!
pl_750.0x14.0 stf_L160.0x8.0+36.0x18.7 span: 1.0636 structure type: GENERAL_INTERNAL_WT stf. type: L pressure side: p | sigma_y1: 115.7 sigma_y2: 115.7 sigma_x: 144.9 tauxy: 6.4 -END 2- OK!
Weight details for this solution:
Weight of main structure: ['1423.0', '1423.0', '1423.0', '1423.0', '1423.0', '1423.0', '1423.0', '1423.0', '1423.0', '1413.8', '1413.8', '1381.1', '1381.1', '1381.1', '1381.1', '1381.1', '1
Weight of frames:         ['4172.8', '4172.8', '4172.8', '4172.8', '4172.8', '4172.8', '4040.3', '4040.3', '4040.3', '4040.3']
Scales used on frames:    ['0.9', '0.9', '0.9', '0.9', '0.9', '0.9', '0.9', '0.9', '0.9', '0.9']
--------------------------------------------------------------------------------
```

Reporting



General

A pdf report can be created by clicking “Reporting - Generate PDF report”. The report will include all information for all lines. An example is seen next.



Table

A report in table format can be created using “Generate PDF result table”. This report is a compressed version of all results.

Line	pl thk	s	web h	web thk	fl. w	fl. thk	sig x	sig y1	sig y2	tau xy	max press.	sec. mod	min sec.	min plt	shr area	min shr A	fat uf	buc uf
line1	14.0	700.0	250.0	18.0	150.0	20.0	20.0	40.0	40.0	5.0	472000.0	1036266	630181	13.67	5111	2322		0.32
line10	18.0	750.0	400.0	12.0	150.0	20.0	50.0	100.0	100.0	5.0	487000.0	1737387	1983693	15.41	5256	3950	0.006	0.78
line11	18.0	750.0	500.0	12.0	150.0	20.0	50.0	100.0	100.0	5.0	521000.0	2318424	2352319	15.94	6456	4449	0.009	0.8
line12	18.0	750.0	500.0	12.0	150.0	20.0	50.0	100.0	100.0	5.0	557000.0	2318424	2395968	16.48	6456	4642	0.014	0.8
line13	20.0	775.0	450.0	12.0	150.0	20.0	40.0	90.0	90.0	5.0	436000.0	2044973	1959271	14.79	5880	3829		0.62
line14	20.0	775.0	450.0	12.0	150.0	20.0	40.0	90.0	90.0	5.0	436000.0	2044973	1959271	14.79	5880	3829		0.62
line15	20.0	775.0	450.0	12.0	150.0	20.0	40.0	90.0	90.0	5.0	436000.0	2044973	1959271	14.79	5880	3829		0.62
line16	18.0	775.0	375.0	12.0	150.0	18.0	40.0	90.0	90.0	5.0	436000.0	1499963	1676401	14.79	4932	3541		0.73
line17	18.0	775.0	375.0	12.0	150.0	18.0	40.0	90.0	90.0	5.0	436000.0	1499963	1587009	14.79	4932	3446		0.72
line18	18.0	775.0	375.0	12.0	150.0	18.0	40.0	90.0	90.0	5.0	436000.0	1499963	1500067	14.79	4932	3350		0.71
line19	18.0	775.0	375.0	12.0	150.0	18.0	40.0	90.0	90.0	5.0	436000.0	1499963	1768242	14.79	4932	3637		0.74
line2	16.0	700.0	400.0	18.0	150.0	20.0	20.0	40.0	40.0	5.0	387000.0	1931105	744392	12.38	7847	2286		0.27
line20	18.0	775.0	375.0	12.0	150.0	18.0	40.0	90.0	90.0	5.0	436000.0	1499963	1768242	14.79	4932	3637		0.74
line21	14.0	700.0	250.0	18.0	0.0	0.0	60.0	70.0	70.0	10.0	0.0	358911	3375	4.07	4751	0		0.23
line22	14.0	700.0	250.0	18.0	0.0	0.0	60.0	70.0	70.0	10.0	0.0	358911	3375	4.07	4751	0		0.22
line23	15.0	750.0	350.0	12.0	150.0	20.0	40.0	90.0	90.0	5.0	387000.0	1444282	946162	13.48	4620	2465		0.8
line24	18.0	750.0	350.0	12.0	150.0	20.0	40.0	90.0	90.0	5.0	350000.0	1468865	972352	12.81	4656	2375		0.63
line25	18.0	750.0	350.0	12.0	150.0	20.0	40.0	90.0	90.0	5.0	310000.0	1468865	972258	12.06	4656	2235		0.64
line26	18.0	750.0	320.0	12.0	150.0	20.0	40.0	90.0	90.0	5.0	267000.0	1314959	838982	11.2	4296	1929		0.63
line27	15.0	750.0	320.0	12.0	150.0	20.0	40.0	90.0	90.0	5.0	225000.0	1293077	791169	10.27	4260	1718		0.82
line28	15.0	750.0	320.0	12.0	150.0	20.0	40.0	90.0	90.0	5.0	180000.0	1293077	705247	9.19	4260	1450		0.82
line29	15.0	750.0	300.0	12.0	150.0	20.0	40.0	90.0	90.0	5.0	132000.0	1195190	575270	7.88	4020	1124		0.83
line3	18.0	700.0	400.0	12.0	200.0	20.0	102.0	100.0	100.0	5.0	413000.0	2109784	1856240	13.68	5256	3434	0.138	0.69
line30	15.0	750.0	300.0	12.0	150.0	20.0	40.0	90.0	90.0	5.0	82000.0	1195190	358252	6.22	4020	700		0.8

Export to JS

ANYstructure can export points, lines and section properties to SESAM GeniE. A dialog will request a location to save the JS file. After that you can read the js file into GeniE.



The result is illustrated next:


02 Sep 2019 15:21
test
Z
X
Section
FB_250_0x18_0
T_250_0x12_0__150_0x14_0
T_300_0x12_0__150_0x20_0
T_320_0x12_0__150_0x20_0
T_325_0x12_0__150_0x16_0
T_340_0x12_0__150_0x16_0
T_340_0x12_0__200_0x20_0
T_350_0x12_0__150_0x20_0
T_375_0x12_0__150_0x18_0
T_400_0x12_0__200_0x18_0
T_400_0x12_0__200_0x20_0
T_400_0x12_0__250_0x12_0
T_400_0x12_0__250_0x14_0