Extract to create cSV used to feed FGP/OGSL/ETC

Pablo Vergara

February 27 2024

This document is the narrative of how an Excel file called "sGSL-Northumberland-Survey-FGP.csv" was generated.

The DFO Gulf Region Northumberland survey follows a stratified random sampling design and covers Division 4T of the Northwest Atlantic Fisheries Organisation (NAFO).

```
`%nin%` = Negate(`%in%`) ## a useful operator
suppressPackageStartupMessages(library(gulf))
survey ="ns"
```

SETS

Using the function "read.card" from the DFO Gulf Region's R package "gulf", read in the set cards and exclude hydrographic stations and null sets, so as to keep only representative tows in strata 401 to 439.

```
yrs <- 1999:2023 #
projectBase = here::here()
x <- read.card(card.type="set", year=yrs, survey =survey)</pre>
```

Data is being retrieved from the PTRAN database

Add a few useful columns to the data frame containing the set card information (including depth and swept area as requested).

```
## add useful columns
x$unique.id <- paste(x$year, x$cruise.number, x$vessel.code, x$set.number, sep="-")
x$experiment.str <- experiment.str(x$experiment)
x$gear.str <- gear.str(x$gear)</pre>
```

Data is being retrieved from the PTRAN database

```
x$longitude <- longitude(x)
x$latitude <- latitude(x)

ox <- order(x$year, x$month, x$day, x$start.hour)
x <- x[ox,] # reorder chronologically</pre>
```

Catch cards contain the total catch information for the species of interest. Here they are adjusted for distance towed, estimated diurnal effects and estimated vessel-gear effects.

```
### Catch card for all years requested (1999 - 2023)
y <- read.card(card.type="catch", year = yrs, survey = survey)</pre>
```

Data is being retrieved from the PTRAN database

```
index <- y$experiment == 1
y <- y[which(index),]
index <- paste0(y$vessel.code, y$cruise.number) %in% valid.cruise
y = y[which(index),]</pre>
```

CATCH

```
y <- adjust(y, x)
```

Data is being retrieved from the PTRAN database

Tow catches for nephrops trawl adjusted to a standard tow distance of 0.125 nautical miles.

```
y$unique.id <- paste(y$year, y$cruise.number, y$vessel.code, y$set.number, sep="-")
y$english.name <- species.str(y$species, "english")
```

Data is being retrieved from the PTRAN database

```
y$latin.name <- species.str(y$species, "latin")
```

Data is being retrieved from the PTRAN database

```
y$french.name <- species.str(y$species, "french")
```

 $\ensuremath{\mbox{\#\#}}$ Data is being retrieved from the PTRAN database

```
fn2 <- "sGSL-Northumberland-Survey-FGP.csv"</pre>
fp <-paste0(projectBase,"/stock_assessment_surveys/6d61f7b4 (ns_survey)/")</pre>
csv.fn2 <- file.path(fp,fn2)</pre>
ooz <- order(z$year, z$month, z$day, z$start.hour, z$start.minute, z$species)
#columns to keep
fvars2 <- c("cruise.number", "year", "month", "day", "start.hour", "start.minute",</pre>
            "latitude", "longitude", "gear.str", "species", "french.name", "english.name",
            "latin.name", "weight.caught", "number.caught")
zz= z[ooz,fvars2]
#proper headers for FGP
names(zz) = c("cruise_number__numero_de_croisiere","year__annee","month__mois","day_jour","start_hour_
                "start_minute_minute_de_depart", "latitude", "longitude", "gear__equipement", "species__esp
                "french_name__nom_francais", "english_name__nom_anglais", "latin_name__nom_latin",
                "weight_caught__poids_pris", "number_caught__quantite_attrape")
con<-file(csv.fn2,encoding="ISO-8859-1")</pre>
write.csv(zz, file=con, row.names=FALSE)
```