XDP: Past, Present and Future

Toke Høiland-Jørgensen Red Hat

XDP: Features since last Netconf

- Multibuf (Lozenzo, Maciej, Eelco)
- XDP hints on RX (Jesper, Stanislav, Toke)
- Feature flags (Lorenzo)
- More stack helpers (conntrack, synproxy) (Kartikeya, Lorenzo, Maxim)
- XDP_REDIRECT improvements
 - Multicast (Hangbin)
 - Map lookup, hashmap type, bpf_redirect() performance (Toke)
 - Programs in devmap/cpumap (David Ahern, Lorenzo)
- Eliminating indirect calls (Björn)
- Live mode BPF_PROG_RUN (Toke)
- AF_XDP need_wakeup mode (Magnus and Maxim)
- Atomic replace and bpf_link attachment (Toke, Andrii)

XDP driver support - Quiz!

How many drivers support XDP today?

How many have all features enabled by default?

XDP driver support

	Basic	Redirect	ndo_xmit	Multibuf RX	Multibuf TX	XSK ZC	HW offload		Basic	Redirect	ndo_xmit	Multibuf RX	Multibuf TX	XSK ZC	HW offload
atlantic	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark			mlx4	\checkmark	\checkmark					
bnxt	\checkmark	\checkmark	(√)	\checkmark	(\checkmark)			mlx5	(√)	(√)	(√)	(\checkmark)	(\checkmark)	(✓)	
cpsw	\checkmark	\checkmark	\checkmark					mtk_eth	(\checkmark)	(√)	(√)		(\checkmark)		
cpsw_new	\checkmark	\checkmark	\checkmark					mvneta	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark		
dpaa	\checkmark	\checkmark	\checkmark					mvpp2	(\checkmark)	(√)	(√)				
dpaa2	\checkmark	\checkmark	\checkmark			\checkmark		netsec	\checkmark	\checkmark	\checkmark				
ena	(\checkmark)	(√)						nfp	\checkmark					(\checkmark)	(√)
enetc	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark			octeontx2	\checkmark	\checkmark	(\checkmark)				
fec	(\checkmark)	(√)						qede	\checkmark	\checkmark	\checkmark				
funeth	\checkmark	\checkmark	(\checkmark)		(√)			sfc	\checkmark	\checkmark	\checkmark				
gve	(\checkmark)	(√)	(\checkmark)		(√)			sfc-siena	\checkmark	\checkmark	\checkmark				
hv_netvsc	\checkmark	\checkmark	\checkmark					stmmac	\checkmark	\checkmark	(\checkmark)			\checkmark	
i40e	\checkmark	\checkmark	(\checkmark)	\checkmark	(√)	\checkmark		thunder	(\checkmark)						
ice	\checkmark	\checkmark	(\checkmark)	\checkmark	(√)	\checkmark		tsnep	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark	
igb igc ixgbe	\checkmark	\checkmark	(√)		(√)			tun	(\checkmark)	(√)	(√)				
igc	\checkmark	\checkmark	(√)		(√)	\checkmark		veth	(\checkmark)	(√)	(√)	(√)	(√) (√)		
ixgbe	\checkmark	\checkmark	(√)		(√)	\checkmark		virtio_net	\checkmark	\checkmark	(√)	(√)	(√)		
ixgbevf	\checkmark							vmxnet3	\checkmark	\checkmark	\checkmark				
lan966x	(\checkmark)	(√)	(√)					xen-	\checkmark	\checkmark	\checkmark				
mana	\checkmark	\checkmark	\checkmark					netfront							

✓: Always enabled. (✓): Configuration-dependent.

XDP: Ongoing work

- XDP hints on TX (Stanislav)
- Veth optimisations (Jesper)
- Multiprog attachment (Daniel)
- Queueing (Toke)

Generic XDP

- Bulking on redirect
- GSO frames through multibuf API
- Veth redirect conversion

AF_XDP xmit path

- Getting rid of socket-allocated SKBs?
- Why allocate SKBs at all?
- TX hints (ongoing, Stanislav)

XDP Hints

- More metadata fields
- Saving for redirect and skb creation (in xdp_frame)
- Naming: "XDP metadata" is not very googlable!

Datapath helpers

What do we need to build a transparent fast path using XDP?

- Bridge lookup(?)
- Netfilter / flowtables lookup (or acceleration?)

Queueing xmit side

Current idea: Transmit from bpf_timer callback

Problem: Runs in HRTIMER_SOFTIRQ

Idea: Flag to run timer callback in different context. NET_TX_SOFTIRQ or kthread?