Explainable ML-Based Code Change Risk Predictor

Author: Akshat Sparsh (23BDS0149)
Guided by: Dr. Vijayanand C

Abstract

Software teams can't give every code change the same amount of review and testing. In this project we built a just-in-time risk predictor. When a developer makes a commit, the system estimates the chance that the commit introduces a bug and explains that estimate in plain English.

We mined the full history of the open-source project `psf/requests` with PyDriller and computed 14 well-known change metrics (Kamei et al., 2013) for 2,788 commits. To label the data we used the SZZ algorithm, which traces later bug fixes back to the commits that caused them. That left 21.9% of commits marked as buggy.

Before modelling, we explored the data in depth. We classified every column by type and measurement scale, checked for duplicates, filled genuinely missing values by maximum likelihood with the EM algorithm, binned commit size, studied the commits as a time series, tested contingency tables with chi-square and with a Bayesian comparison, and looked for structure with more than a dozen clustering and dimensionality reduction methods, including clustering the commit messages themselves.

We then compared thirteen classic algorithms, including Naive Bayes, decision trees, k-NN, logistic regression, SVM, MLP, random forest, AdaBoost and XGBoost. We also handled the class imbalance with class weights and SMOTE, and tested every model on the newest 20% of commits so the evaluation matches how the tool would be used for real.

A tuned XGBoost model, chosen by cross-validation on the training period, reached a test ROC-AUC of 0.779 and a PR-AUC of 0.401 (random guessing gets 0.151). If reviewers only look at the 20% of commits it ranks riskiest, they find 48% of all bug-introducing commits. SHAP and LIME turn each prediction into a short list of reasons, and a Streamlit app lets a reviewer score any commit, read why it is risky and try out changes (for example, splitting a large commit) to see how the risk would drop.

---

1. Introduction

Every commit to a codebase carries a bit of risk. Most changes are harmless, but some introduce defects that only show up weeks or months later, and by then they cost much more to fix. Code review and testing catch a lot of these, but reviewers only have so much time. In practice a big refactor and a one-line typo fix often get about the same attention.

Just-in-time (JIT) defect prediction tries to fix this by predicting risk at the moment a commit is made, while the change is still fresh in the developer's head. If a model can point reviewers at the small group of commits that carry most of the risk, their time goes where it matters.

A risk score on its own isn't that useful, though. If you tell a developer "this commit is 73% risky", the first thing they'll ask is why. So we paired the model with two explainable AI methods, SHAP and LIME. Every score comes with concrete reasons, for example "adds 512 lines, more than 92% of past commits".

2. Problem Statement and Objectives

Problem. Given a commit (its diff, the files it touches, its author and the history of the repository before it), predict the probability that it introduces a bug and explain which properties of the commit push that probability up or down.

Objectives.

1. Build a data pipeline that can mine any git repository and produce a labelled dataset of commits, and make it reproducible.
2. Describe each commit with features that people can understand: how big it is, how spread out it is, why it was made, the history of the files it touches and how experienced its author is.
3. Compare a range of supervised learning algorithms under a realistic, time-based evaluation and recommend the one that fits best.
4. Deal with the imbalance between clean and buggy commits.
5. Explain predictions both globally (which features matter overall) and locally (why this particular commit is risky).
6. Package the model as an interactive tool that could be used at commit or review time.

3. Literature Review

Work	Main idea	How we used it
Śliwerski, Zimmermann and Zeller (2005), *When Do Changes Induce Fixes?*, MSR	The SZZ algorithm. Find bug-fixing commits, then use `git blame` to find the commits that introduced the lines being fixed.	This is how we label commits as buggy or clean.

Work	Main idea	How we used it
Hassan (2009), *Predicting Faults Using the Complexity of Code Changes*, ICSE	Changes that are scattered over many files (high entropy) are more likely to contain faults.	Where our `entropy` feature comes from.
Kamei et al. (2013), *A Large-Scale Empirical Study of Just-in-Time Quality Assurance*, IEEE TSE	Introduced JIT defect prediction with 14 change metrics in five groups, and argued that evaluation should account for review effort.	Our feature set and our effort-aware metric.
Spadini, Aniche and Bacchelli (2018), *PyDriller*, ESEC/FSE	A Python framework for mining git repositories, with SZZ built in.	Our mining and labelling tool.
Chawla et al. (2002), *SMOTE*, JAIR	Creates synthetic samples of the minority class.	One of the ways we tried to handle the imbalance.
Breiman (2001), *Random Forests*, Machine Learning	Bagging of many decorrelated decision trees.	One of the ensemble models we compared.
Chen and Guestrin (2016), *XGBoost*, KDD	Gradient-boosted trees with regularisation.	Another ensemble model, and our final pick.
Ribeiro, Singh and Guestrin (2016), *"Why Should I Trust You?"* (LIME), KDD	Explains one prediction by fitting a simple model around it.	Local explanations.
Lundberg and Lee (2017), *A Unified Approach to Interpreting Model Predictions* (SHAP), NeurIPS	Uses Shapley values from game theory to split a prediction fairly between features.	Global and local explanations.

4. Dataset and Feature Engineering

4.1 Source repository

We mined the complete history of `psf/requests`, a widely used Python HTTP library that has been active since 2011. We used the repository as it stood at commit `611c616` (21 September 2026), so the dataset can be rebuilt exactly. We only kept non-merge commits that change source code. Commits that only touch documentation were skipped.

Statistic	Value
Commits that change code	2,833
Bug-fix commits (found by keywords)	518
Bug-introducing commits (SZZ)	613
Most recent commits dropped (last 180 days)	45
Final dataset	2,788 commits, Feb 2011 to Aug 2025
Buggy share	21.9% (610 buggy and 2,178 clean, about 1 buggy for every 3.6 clean)

4.2 Features

Each commit is described by the 14 metrics from Kamei et al. (2013). The history and experience metrics only use commits made before the one being measured, so nothing leaks in from the future.

Group	Feature	Description
Diffusion	`ns`	number of top-level subsystems (directories) modified
	`nd`	number of directories modified
	`nf`	number of code files modified
	`entropy`	normalised Shannon entropy of the modified lines across files (0 means one file, 1 means spread evenly)
Size	`la`	lines of code added
	`ld`	lines of code deleted
	`lt`	average lines of code in the modified files before the change
Purpose	`fix`	whether the commit message says it fixes a bug
History	`ndev`	number of developers who changed these files before
	`age`	average days since these files were last changed
	`nuc`	number of earlier commits that changed these files
Experience	`exp`	earlier commits by this author
	`rexp`	earlier commits by this author, weighted so recent years count more (1 for this year, 1/2 for last year and so on)
	`sexp`	earlier commits by this author in the same subsystems

4.3 Labelling with SZZ

The labelling works in three steps.

1. A commit counts as a bug fix if its message contains one of the words `fix`, `fixes`, `fixed`, `bug`, `bugfix`, `hotfix` or `defect`. We left out "patch" on purpose, because in an HTTP library it usually refers to the PATCH method.
2. For every line a fix deletes or changes, we run `git blame` on the fix's parent commit to find the commit that last touched that line. Whitespace changes, blank lines and comments are ignored.
3. Those commits are labelled buggy (1) and everything else is clean (0). We skip fixes that touch more than 30 files, since those are usually refactorings or mass reformatting rather than real fixes.

The labels aren't perfect. Keyword matching misses some fixes and counts some commits that aren't really fixes. A fix that only adds lines can't be traced back to anything. Sometimes the commit that

gets blamed only moved the buggy code instead of writing it. And recent commits look clean simply because nobody has found their bugs yet, which is why we dropped the last 180 days.

4.4 Data types and measurement scales

Knowing what each column *is* decides which summaries and methods make sense. Every column has a data type and a measurement scale.

Columns	Data type	Measurement scale
`ns`, `nd`, `nf`, `la`, `ld`, `ndev`, `nuc`, `exp`, `sexp`	numerical, discrete (counts)	ratio
`entropy`, `lt`, `age`, `rexp`	numerical, continuous	ratio
`fix`, `buggy`	categorical, binary	nominal
`repo`, `commit_hash`, `author_id`	categorical identifiers	nominal
`author_date`	date and time	interval
`message`	free text	nominal
size band (binned from `la`)	categorical	ordinal

Most features are counts on a ratio scale: zero means "none", and 200 lines really is twice 100 lines. That is why means, logarithms and ratios are all fair to use on them, while the binary and identifier columns only support counting and comparing groups. The full table, with an example value for each column, is in `reports/explore_data_types.csv`.

4.5 Preparing the data

None of the steps below changes the dataset the models are trained on. They are part of understanding it, and they confirm it is safe to use as it is.


Duplicates. No commit id appears twice. However, 11 commits are extra copies of the same change: same author, timestamp, message and size, usually because a commit was copied onto another branch. Removing them would move the bug rate from 21.88% to 21.97%, so they make no real difference. Repeated messages on their own (176 commits, such as "Fix typo") are normal and are not duplicates.


Replacing values and missing data. "Days since the files were last changed" (`age`) is stored as 0 when the touched files have no earlier history. That 0 isn't a real measurement, so for this analysis it is replaced with a missing value, which affects 47 commits (1.7%). We compared three ways of filling these gaps. The mean (28.1 days) is pulled up by a few very old files, and the median (1.8 days) ignores everything else we know about the commit. Maximum likelihood estimation with the EM algorithm (Dempster et al., 1977) assumes the logged features follow a multivariate normal distribution. It then alternates between filling each gap with its expected value given the other

columns of the same commit, and re-estimating the means and covariances, until nothing changes. It suggests about 4.8 days.

To compare the methods fairly, we hid 418 known values of author experience (15%) at random and filled them back in. EM converged in 9 iterations and was far closer to the truth, because experience is strongly related to recent and subsystem experience, and EM uses that relationship.


Method	Error (RMSE, log scale)	Typical error (commits)
Mean	2.41	23.0
Median	2.41	28.0
Maximum likelihood (EM)	**0.28**	**2.5**






Discretization and binning. Turning lines added into five ordered bands makes the size effect easy to see.

Lines added	Commits	Buggy	Bug rate
0	157	0	0.0%
1 to 5	1,450	185	12.8%
6 to 20	690	209	30.3%
21 to 100	396	162	40.9%
more than 100	95	54	56.8%



The bug rate climbs steadily with size. Commits that add no lines are never labelled buggy, because SZZ can only blame lines a commit added. That 0% comes from the labelling method, not from those commits being safe. We chose the band edges by hand: equal-width bins put 2,779 of the 2,788 commits into the first bin, and equal-frequency bins cut at odd places.

5. Methodology



How we explored the data. We followed the usual steps of exploratory data analysis (Tukey, 1977): understand what each column is, prepare and clean the data, summarise it with statistics and plots one, two and many variables at a time, look for structure with clustering and dimensionality reduction, and only then decide what to model. EDA differs from classical analysis, which starts from a hypothesis and tests it, and from Bayesian analysis, which starts from a prior belief and updates it with data. EDA comes first and lets the data suggest which questions are worth testing; Section 6.8 shows the classical and Bayesian views side by side on the same questions. The tools

were pandas, NumPy, SciPy, scikit-learn, Matplotlib, seaborn and Plotly, with Jupyter for the notebook.

Time-based evaluation. We sorted the commits by date and used the oldest 80% for training and the newest 20% for testing. A random split would let the model learn from commits made after the ones it is being tested on. That can't happen in real use, and it makes the results look better than they are. All tuning happened inside the training period using `TimeSeriesSplit` cross-validation, and the decision threshold was picked on the last part of the training period.

Preprocessing. Counts and sizes are very skewed (a handful of commits add thousands of lines), so we applied `log(1 + x)` to the features and then standardised them.


Class imbalance. Only about 22% of commits are buggy. A model that always says "clean" would be 78% accurate and completely useless. So we compared three options (no rebalancing, class weights and SMOTE) and reported metrics that hold up on imbalanced data: ROC-AUC, PR-AUC, F1, MCC and balanced accuracy.

Effort-aware evaluation. Reviewing a 1,000-line commit takes much longer than reviewing a 5-line one. Recall@20% effort measures how many buggy commits you'd find if you reviewed the riskiest commits first and stopped once you'd read 20% of all changed lines (Kamei et al., 2013).


6. Exploratory Data Analysis and Unsupervised Learning

All the figures here are in `reports/figures/` and can be regenerated with `uv run python -m riskpredictor.eda` (Sections 6.1 to 6.5) and `uv run python -m riskpredictor.explore` (Sections 6.6 to 6.10). The notebook `notebooks/01_eda.ipynb` goes through them one at a time.

6.1 Class balance and drift over time




About 21.9% of commits are buggy, so there are roughly 3.6 clean commits for every buggy one. The bug rate also changes over time. It is 23.6% in the training period but only 15.1% in the test period. That makes the test set harder, since there are fewer buggy commits to find, and a random split would have hidden this.



6.2 Which features separate buggy and clean commits?


We compared each feature between buggy and clean commits using the Mann-Whitney U test, which doesn't assume normal data, and Cliff's delta as the effect size.



Eight of the 14 features differ significantly ($p < 0.05$). The strongest single signal is lines added. The median buggy commit adds 12 lines while the median clean one adds 3 (Cliff's delta of +0.47, a medium effect). The diffusion features come next: files touched (+0.26), entropy (+0.24), lines deleted (+0.23) and directories (+0.16). Author experience and the fix flag barely differ on their own.


Every distribution overlaps a lot with the other class, though. No single metric can separate buggy from clean, which is why we need a model that combines them.

6.3 Correlation between features




Six pairs of features have a Spearman correlation above 0.8: `exp` and `rexp` (0.99), `nf` and `entropy` (0.97), `exp` and `sexp` (0.97), `rexp` and `sexp` (0.96), `ndev` and `nuc` (0.95), and `ns` and `nd` (0.91). Correlated features don't hurt the accuracy of tree ensembles much. They can, however, split credit between each other in the explanations and make linear model weights unstable. We kept all 14 so our results stay comparable with other work, and we come back to this problem in Section 8.4.

6.4 PCA, kernel PCA and t-SNE




PCA needs 5 of the 14 components to explain 80% of the variance, and the first component alone covers 31%. That first component roughly measures how spread out and how busy a change is (`ns`, `ndev`, `nd`), while the second one is mostly author experience.

In the 2D plots from PCA, kernel PCA (RBF) and t-SNE, buggy and clean commits overlap. For a buggy commit, about 28 to 31% of its nearest neighbours are also buggy, compared with 22% you'd expect by chance. So the classes can only be separated weakly, and we shouldn't expect any classifier to come close to perfect.



6.5 Clustering into commit types



K-Means with k = 3 (chosen using the silhouette score) gives three groups that are easy to describe.

Cluster	Size	Bug rate	What the typical commit looks like (medians)
C0, cross-cutting changes	428	40.7%	touches 2 subsystems and 2 files, adds 19 lines, high entropy, files with 310 earlier changes
C1, experienced authors	1,199	19.0%	small change (3 lines) by an author with about 284 earlier commits
C2, newcomers	1,161	17.9%	small change by an author with about 1 earlier commit


Cross-cutting changes turn out to be buggy about twice as often as the other two groups, and the clustering never even saw the labels. Interestingly, small changes from newcomers aren't riskier than small changes from experienced authors in this project. Size and spread matter more than experience.

Method	Type	Clusters	Silhouette	Bug rate range
K-Means	partitioning	3	0.248	17.9% to 40.7%
Agglomerative (Ward)	hierarchical	3	0.184	16.2% to 39.4%
DBSCAN	density-based	2, plus 4% noise	0.344	18.6% to 38.5%

The commits DBSCAN marks as noise are the unusual ones that don't sit in any dense region, and 41.1% of them are buggy compared with 21.1% of the rest. In other words, unusual commits tend to be risky ones. All the silhouette scores are modest (0.18 to 0.34), so commits form more of a continuum than neat separate groups.


6.6 One, two and many variables

Looking at one variable at a time (univariate analysis), lines added is extremely skewed: its skewness is 21.0, and the mean (40 lines) is ten times the median (4 lines). After `log(1 + x)` the skewness drops to 1.2, which is why every model and every clustering method uses the log scale. Looking at two variables together (bivariate analysis), commits that add more lines also tend to delete more. A straight line fitted on the log scale has a slope of 0.37 and explains 16% of the variation ($R^2 = 0.16$). The pair plot in the notebook looks at four features at once (multivariate analysis): buggy commits sit towards larger values, but no pair of features separates them cleanly.



6.7 The commits as a time series

With the commit date as the index, the data can be sliced by period, resampled to months, quarters or years, and smoothed with a rolling window. Resampled by month, the history spans 175 months, 23 of them with no commits at all. The busiest month was August 2011, with 140 commits. Slicing by date shows the drift directly: commits up to 2014 were buggy 23.9% of the time, and commits from 2015 onwards 17.3%.




The 12-month rolling bug rate moves between about 10% and 30% and trends downwards. The dip at the very end is mostly label lag: bugs in the newest commits simply haven't been found yet, the same reason we dropped the last 180 days.

6.8 Summary statistics, contingency tables and a Bayesian check


The summary measures for every feature (mean, median, standard deviation, range, interquartile range, skewness and kurtosis) are in `reports/explore_summary_stats.csv`. Most counts have a median far below the mean and very high kurtosis, which confirms the long tails seen in Section 6.6.

Contingency tables cross a grouping with the label. A chi-square test checks whether the difference could be chance, and Cramér's V measures how strong the link is (0 means none, 1 means perfect).

Question	Chi-square	p-value	Cramér's V	Verdict
Does the size band matter?	294.9	< 0.001	0.33	yes, clearly
Are bug-fix commits buggier?	3.0	0.084	0.03	not significant at 5%
Does the weekday matter?	10.6	0.101	0.06	not significant at 5%




The classical test can only say whether a difference is surprising if there were really no difference. A Bayesian analysis answers the question we actually care about. With a flat prior, the bug rate of each group has a Beta posterior distribution. Bug-fix commits are buggy 25.0% of the time against 21.2% for other commits, and the probability that fixes really are riskier is **96%**. For Friday commits (25.4% against 21.4%) it is **95%**. So the evidence leans one way in both cases, but isn't strong enough to pass a 5% test. This is a good example of EDA raising a question that a later, more targeted study could settle.




6.9 More clustering

We tried four more clustering methods on top of those in Section 6.5.

- **Spectral clustering** (von Luxburg, 2007) connects each commit to its nearest neighbours and splits the resulting graph. On 1,500 commits it gives three groups with bug rates of 22%, 20% and 39%. It agrees only partly with K-Means (adjusted Rand index 0.22), with a lower silhouette (0.16).
- **Gaussian mixtures fitted with EM** are model-based clustering: each cluster is a bell-shaped blob, and the Bayesian information criterion (BIC) picks how many blobs fit best. Out of 1 to 12, BIC prefers 10, with bug rates from 11% to 46%.
- **Hierarchical (agglomerative) clustering** keeps merging the closest groups. The Ward dendrogram shows two or three large branches that only join near the top.
- **Minimum spanning tree clustering** links all commits with the shortest total edge length, then cuts the unusually long edges (longer than the mean plus three standard deviations). Cutting 25 such edges leaves one main group of 1,025 commits, some medium groups, and 31 commits in tiny pieces.



Outlier detection using clustering. Three methods flag "unusual" commits in different ways, and all three find them riskier than the rest. The 5% of commits farthest from their K-Means centre are buggy 40% of the time (against 21%), DBSCAN noise points 41% (against 21%), and the commits cut off by the spanning tree 29% (against 22%).



Document clustering. The commit messages are text, so we turned each message into TF-IDF word weights (716 distinct words) and clustered them with K-Means.


Cluster	Top words	Commits	Bug rate
M1	urllib, import, new, upgrade, fix	68	38.2%
M2	fixes, issue, python, redirects, pyflakes	53	30.2%
M0	fix, add, tests, use, fixed	2,212	22.6%
M4	update, urllib, docs, models, setup	111	19.8%
M3	test, add, added, fix, case	229	16.6%
M5	remove, unused, test, import, bunk	115	7.8%

Messages about upgrading the bundled `urllib3` library are the riskiest, which fits what we found about large, cross-cutting changes. Clean-ups like "remove unused import" are the safest. Most


messages share the same everyday words and end up in one large cluster, so the message alone is a weak signal.


6.10 More dimensionality reduction


- **Singular value decomposition (SVD).** PCA is computed through the SVD of the centred data, and the variance kept by each component is its singular value squared, divided by n minus 1. Keeping 80% of the variance needs 5 components, 90% needs 7 and 95% needs 9.
- **Intrinsic dimension.** The maximum likelihood estimator of Levina and Bickel (2004) looks at the distances between each commit and its nearest neighbours. It puts the intrinsic dimension at about **4.1**, so the 14 features really live in a space of about four dimensions.
- **Factor analysis** with varimax rotation finds four hidden factors: author experience (`exp`, `rexp`, `sexp`), two kinds of spread (files and directories, and subsystems), and file history (`nuc`, `ndev`, `lt`). Lines added and deleted load on the spread factor, since large changes usually touch more files.



- **Multidimensional scaling and Isomap** both draw a 2-D map that tries to keep the distances between commits (Isomap measures them along a nearest-neighbour graph, a form of manifold learning; Tenenbaum et al., 2000). MDS fits with a Kruskal stress of 0.21. In both maps buggy and clean commits stay mixed: about 28% of a buggy commit's neighbours are buggy, against 22% by chance.
- **A self-organizing map** (Kohonen, 1982) lays the commits out on an 8 by 8 grid of prototype commits. The bug rate per grid node ranges from 0% to 54%, so some regions of the map are clearly riskier, even though no single direction separates the classes.







7. Models and Evaluation

The full tables are in `reports/model_comparison.md`. Running `uv run python -m riskpredictor.train` regenerates them in about 40 seconds.

7.1 Setup


Part	Commits	Period	Bug rate
Training (oldest 80%)	2,230	Feb 2011 to Jun 2016	23.6%
Fitting part of training	1,784	Feb 2011 to Mar 2014	23.7%
Validation part of training (used only for the threshold)	446	Mar 2014 to Jun 2016	23.3%
Test (newest 20%)	558	Jun 2016 to Aug 2025	15.1%


We used 5-fold `TimeSeriesSplit` cross-validation on the training period, so each fold trains on the past and validates on the block right after it. XGBoost, random forest, logistic regression and the RBF SVM were tuned with `RandomizedSearchCV` (25 candidates each, scored on ROC-AUC). For the imbalance we used balanced class weights (`scale_pos_weight` for XGBoost). The final model was picked by its mean cross-validated ROC-AUC on the training period, so the test scores played no part in the choice. Its decision threshold is the value that gave the best F1 on the validation slice.

7.2 Leaderboard

#	Model	Type	CV ROC-AUC (train)	Test ROC-AUC	Test PR-AUC	F1	Recall	MCC
1	**XGBoost** (tuned)	Boosting	**0.732 ± 0.029**	0.779	0.401	0.410	0.798	0.307
2	Random Forest (tuned)	Bagging	0.727 ± 0.020	0.776	0.423	0.393	0.810	0.287
3	SVM (linear)	Linear	0.726 ± 0.030	0.762	0.349	0.396	0.774	0.286
4	Logistic Regression (tuned)	Linear	0.725 ± 0.040	0.769	0.362	0.386	0.679	0.261
5	AdaBoost	Boosting	0.725 ± 0.028	0.783	0.389	0.418	0.702	0.306

#	Model	Type	CV ROC-AUC (train)	Test ROC-AUC	Test PR-AUC	F1	Recall	MCC
6	SVM (RBF, tuned)	Kernel	0.724 ± 0.042	0.768	0.358	0.397	0.845	0.298
7	MLP (neural network)	Neural network	0.708 ± 0.038	0.751	0.339	0.374	0.524	0.240
8	Naive Bayes	Probabilistic	0.700 ± 0.024	0.707	0.316	0.385	0.679	0.259
9	k-NN	Instance-based	0.673 ± 0.060	0.715	0.296	0.356	0.500	0.215
10	Decision Tree (CART, entropy)	Tree	0.664 ± 0.028	0.766	0.358	0.383	0.833	0.276
11	Decision Tree (CART, gini)	Tree	0.630 ± 0.027	0.750	0.351	0.347	0.905	0.236
12	Perceptron	Linear	0.628 ± 0.040	0.523	0.188	0.237	0.500	0.012
13	One-Class SVM (anomaly baseline)	Anomaly detection	0.605 ± 0.040	0.662	0.258	0.331	0.571	0.176





A few things stand out from this table.

The top seven models are basically tied, since their CV scores are all within one standard deviation of XGBoost's. The ensembles (XGBoost, random forest and AdaBoost) are always near the top, but a properly regularised logistic regression is almost as good. With only 14 features and noisy labels, the data sets the ceiling more than the algorithm does.

Single decision trees and the perceptron are clearly weaker and less stable. The trees overfit easily, and the perceptron doesn't produce useful probabilities. One note on naming: the entropy tree uses the same information gain idea as ID3, but scikit-learn always builds binary splits like CART, so it is a CART tree with the entropy criterion rather than a true ID3 tree.


The One-Class SVM never sees a single buggy commit during training, yet it still beats random guessing with a test ROC-AUC of 0.662. This backs up what we saw with clustering: unusual commits tend to be risky.

Most models actually score higher on the test set than in cross-validation, even though the test bug rate is lower (15.1% against 23.6%). The later history of `requests` is calmer, and its big risky commits are easier to spot. Keep in mind that PR-AUC should be compared with the test bug rate of 0.151, not with 0.5.

7.3 The selected model: XGBoost

After tuning, the model uses 108 trees of depth 2 with a learning rate of 0.018, row subsampling of 0.68, column subsampling of 0.65 and L2 regularisation of 3.5. These are shallow and heavily regularised trees, which makes sense for a small, noisy dataset. The decision threshold is 0.514.

Metric on the test set (558 commits)	Value
ROC-AUC	0.779
PR-AUC	0.401 (random gets 0.151)
Recall, precision, F1	0.798, 0.276, 0.410
MCC, balanced accuracy	0.307, 0.713
Confusion matrix	67 true positives, 176 false positives, 17 false negatives, 298 true negatives
Buggy commits found when reviewing the riskiest 20% of commits	48% (40 of 84), 2.4 times random



At this threshold the model leans towards recall. It catches 80% of the bug-introducing commits but flags 44% of all commits to get there. The threshold was chosen on a validation period where 23% of commits were buggy, so on the calmer test period it flags quite generously. In practice a team would set the threshold to match how much review time they have. The ranking number (48% of bugs in the top 20%) is the more useful summary.

If we measure effort in lines instead of commits, Recall@20% effort is low at 0.083. The model ranks big commits as the riskiest, and big commits use up a line-based review budget very quickly. Size is the strongest risk signal, but it is also exactly what makes a commit expensive to review. Kamei et al. (2013) pointed out the same tension.

7.4 Class imbalance

Model and measure	No handling	Class weights	SMOTE
Logistic regression, CV ROC-AUC	0.721	0.721	0.719
Logistic regression, recall at threshold 0.5	0.31	0.74	0.74
Random forest, CV ROC-AUC	0.698	0.705	0.691
Random forest, recall at threshold 0.5	0.29	0.67	0.56


Rebalancing barely changes how well the models rank commits (ROC-AUC moves by less than 0.015). What it does change is the probability scale. Without it, the default threshold of 0.5 misses about 70% of buggy commits. Once the threshold is tuned on validation data, all three options end up close. So the lesson is to either rebalance or tune the threshold, and not to use 0.5 blindly on imbalanced data.

One side effect is worth knowing about. With class weights, the probabilities shift upwards, so the "average commit" scores about 45% even though only 22% of commits are buggy. The scores should be read as relative risk, not as calibrated probabilities.


7.5 Hyperparameter tuning and bias versus variance

Model	CV ROC-AUC with defaults	CV ROC-AUC after tuning
XGBoost	0.673	0.732
SVM (RBF)	0.681	0.724
Random Forest	0.705	0.727
Logistic Regression	0.721	0.725

Tuning helps the flexible models the most. XGBoost's default trees (depth 6) overfit, and the search moved it to shallow depth-2 trees with strong regularisation.



The decision tree complexity curve shows the trade-off directly. As `max_depth` grows, the training ROC-AUC climbs towards 1.0 because bias falls. The validation ROC-AUC peaks at depth 1 (0.674) and then goes down. At depth 15 the tree scores 0.997 on its training folds but only 0.518 on validation, which means it has basically memorised the training commits. Ensembles get around this either by averaging many trees (bagging, as in random forest) or by adding many weak, shallow trees one after another (boosting, as in AdaBoost and XGBoost).




In the learning curve for the selected model, the two lines come together. Training ROC-AUC falls from 0.83 to 0.76 as the model can no longer memorise everything, while validation ROC-AUC rises from 0.68 and levels off around 0.75 after roughly 1,100 commits. The small gap left over means variance is under control. The flat part at the end tells us that more commits from this same project wouldn't help much. Further gains would need better features or cleaner labels.

7.6 A linear regression baseline, and what accuracy hides

As the simplest possible model, we fitted an ordinary linear regression to the 0/1 label, trained on the same oldest 80% of commits and tested on the newest 20%. Its R^2 is only 0.03, although it still ranks commits reasonably (ROC-AUC 0.761). The more useful lesson is about accuracy.


Model	Accuracy	Buggy commits caught
Always say "clean"	84.9%	0%
Linear regression, cut at 0.5	83.3%	26%
Linear regression, cut at 0.25	65.2%	75%
XGBoost (final model)	65.4%	80%



Only 15.1% of test commits are buggy, so a model that says "clean" every time is already almost 85% accurate while catching nothing. Our final model has a *lower* accuracy than that, and is far more useful. This is why we judge models by ROC-AUC, PR-AUC, recall and MCC rather than accuracy.

8. Explainability

8.1 What drives risk overall?



Mean absolute SHAP value for the XGBoost model, in percentage points of predicted risk:

Rank	Feature	Mean SHAP (points)	Effect
1	Lines added (`la`)	11.0	more lines, more risk
2	Files touched (`nf`)	1.9	more files, more risk
3	File size before change (`lt`)	1.4	larger files are slightly safer
4	Past developers on files (`ndev`)	1.2	more developers, more risk
5	Past changes to files (`nuc`)	1.0	busier files, more risk
6	Change spread (`entropy`)	0.9	more scattered, more risk
7	Lines deleted (`ld`)	0.8	more deletions, more risk
8	Is a bug fix (`fix`)	0.5	fixes are riskier
9	Author experience (`exp`)	0.4	experienced authors are safer

Size dominates. Lines added contributes more than all the other features put together, which fits the EDA (it had the largest effect size in Section 6.2). The other signals line up with the software engineering literature too. Scattered changes (Hassan, 2009), files that many people have touched and bug-fixing commits all raise the risk, the last one because fixes are often incomplete. Larger existing files are slightly safer per change, which matches the known result that big files have a


lower defect density. Every direction the model learned makes intuitive sense, and that is good evidence it picked up real patterns rather than noise.

8.2 Why is this particular commit risky?

For every commit, SHAP breaks the prediction into a sum: the average risk of past commits, plus one contribution per feature, equals this commit's risk. Our tool takes the biggest contributions and turns them into sentences, comparing each value with past commits.


```
Commit 85400d8d: Allow use of 'no_proxy' in the proxies argument   (actual label: buggy)
Predicted risk : 76.1%  (High risk, FLAGGED as risky; threshold 51.4%)
Average commit : 44.8%

Factors raising the risk:
  1. Adds 91 lines, more than 96% of past commits, which raises the risk by 18.0
percentage points.
  2. Modifies 3 files, more than 94% of past commits, which raises the risk by 3.9
percentage points.
  3. Spreads its changes across files with entropy 0.88, higher than 90% of past commits,
which raises the risk by 2.4 percentage points.
```



8.3 SHAP compared with LIME

LIME explains the same prediction in a different way. It fits a small linear model around the commit using perturbed copies of it. For the same commit as above, LIME also puts lines added far ahead of everything else:



Over 50 test commits, the two methods agreed on 60% of the top three features on average, with a mean Spearman rank correlation of 0.63. So they mostly agree on what matters but differ in the details. We use SHAP in the app because its values add up exactly to the prediction and it gives the same answer every time, while LIME depends on random sampling and on how it bins the features.


8.4 A lesson about correlated features

For a while during development, the selected model was a logistic regression. Its explanations had contradictions that any reviewer would spot straight away, such as "modifies 3 files, which lowers the risk", or more subsystem experience raising the risk. The cause was the multicollinearity from Section 6.3. `nf` and `entropy` (0.97), and `exp` and `sexp` (0.97), carry almost the same information, so the linear model gave each pair large weights with opposite signs that cancel each other out. The accuracy was fine, but the explanations couldn't be trusted. The tuned XGBoost model uses shallow trees and samples columns, and it doesn't learn any of these reversals. The takeaway is that good accuracy doesn't guarantee good explanations. You have to check that the explanations make sense too.


9. Application

We built a Streamlit app so the model can actually be used. It is live at https://code-change-risk-predictor.streamlit.app, and it can also be run locally with `uv run streamlit run app/streamlit_app.py`.


Overview. The size of the dataset, the bug rate over time and how buggy commits differ from clean ones.




Data explorer. The analysis from Sections 4, 6 and 7 in interactive form, in seven parts that follow the order of the analysis: data quality (types, duplicates, missing values and the three ways of filling them), size bands, the bug rate over time, contingency tables with the chi-square and Bayesian tests, clustering (pick the number of K-Means clusters and compare it with spectral, Gaussian mixture, hierarchical and spanning-tree clustering), dimensionality (the SVD spectrum, factor loadings, the self-organizing map and 2-D maps from PCA, t-SNE, MDS and Isomap) and finally the regression baseline next to the learning reviewer, whose exploration rate and number of rounds can be changed on the page.




Model leaderboard. Every algorithm's scores, the selected model and how it was chosen.




Explain a commit. Pick any commit from the test period to see a risk gauge, the risk level, the main reasons in plain English, the SHAP chart, LIME weights and the commit's real SZZ label for comparison.




What-if simulator. Change a commit's features (for example, halve its size as if it were split into two commits) and the risk and explanation update straight away. A "suggest how to lower risk" button tries a few realistic changes automatically.



Score a local commit. Point it at any git repository on your computer and a commit hash. It mines the history up to that commit and scores it, which takes about 45 seconds on `requests`. The example below scores the newest change to the library's source code.



Global explanations. Which features matter most across all commits.



The same scoring is available from the command line, which is handy for scripts or a CI check: `uv run riskpredictor score --repo <path> --commit <hash>`.

10. Results and Discussion

Which algorithm should be used? On this data we'd recommend gradient-boosted trees (XGBoost). It ranked first in cross-validation, copes well with skewed features, needs no feature selection despite the strong correlations and gives explanations that make sense feature by feature. Random forest is almost as good. If simplicity matters most, a regularised logistic regression is within one standard deviation on accuracy, but its explanations need care because of the correlated features (Section 8.4).


Is the model useful? A reviewer who checks the 20% of commits ranked riskiest finds 48% of the bug-introducing ones, compared with 20% if they picked at random. Every flag also comes with a reason a developer can act on. The most common one is simply "this commit is large, consider splitting it".


Threats to validity.

- *Noisy labels.* SZZ is a heuristic. For example, the commit "Add automatic code formatting" is labelled buggy only because later fixes touched lines it had reformatted. And some clean commits contain bugs that were simply never fixed.
- *One project.* All of our results come from `requests`. Other projects have different bug rates and habits, so the model should be retrained, or at least checked on another project, before being used there.

- *Drift.* The test period's bug rate (15.1%) is different from the training period's (23.6%), and a threshold chosen on older data flags generously on newer data. A deployed model would need retraining and a new threshold from time to time.
- *Slightly optimistic CV for tuned models.* Their CV score is the best of 25 candidates. Nested cross-validation would remove that bias but takes five times longer.

Supervised and reinforcement learning. All our models are supervised: they learn from past commits whose answers we already know. A reinforcement learner (Sutton and Barto, 2018) is never shown the answers. It takes an action, receives a reward and adjusts. To show the difference, we simulated a reviewer as a multi-armed bandit. Each round it picks one size band of commits, reviews a random commit from it, and is rewarded when that commit turns out to be buggy. It mostly picks the best band so far, but 10% of the time it tries another one (epsilon-greedy). Over 1,500 reviews it learned to spend 92% of its time on the riskiest band, and found 859 bugs, against 433 for random picking and 872 for a reviewer who knew the answer from the start. In practice this could become a review bot that learns from reviewers' feedback, or a test scheduler that learns which tests fail most often.





Using a tool like this responsibly.

- *Judge the change, not the person.* Author experience is one of the features, so a careless setup could label newcomers as risky developers. The tool should only guide where reviewers look, and never be used to rate people.
- *Privacy.* Author emails are replaced with anonymous ids, and all the data comes from a public project.
- *Noisy labels.* The bug labels come from a heuristic, so every score is a hint rather than a verdict.
- *Changing habits.* More and more code is now written with AI assistants, which changes what typical commits look like. A model like this needs regular retraining, as the drift in Section 6.7 already shows.

11. Conclusion and Future Work

We built a complete, explainable just-in-time defect predictor. It includes a mining and labelling pipeline that can turn any git repository into a labelled dataset, a thorough exploratory analysis of that data, a comparison of 13 classic algorithms under a realistic time-based setup, SHAP and LIME explanations written out as plain-English risk reports, and an interactive app with a what-if simulator.

The best model, a tuned XGBoost, reaches a test ROC-AUC of 0.779 and puts about half of all bug-introducing commits into the riskiest fifth. More than anything, the project showed us that in this area a simple, well-explained model is worth more than a slightly more accurate black box, because reviewers need to know why a change is risky before they can do anything about it.

Future work.

- Mine more projects and test cross-project prediction, training on one repository and predicting on another.
- Use a stronger SZZ variant that ignores refactorings and cosmetic changes, to cut down label noise.
- Add features that look at the content of the diff itself, for example token-based models.
- Make scoring incremental, so a git hook could score each new commit in under a second without replaying the whole history.
- Turn the bandit sketch from Section 10 into a review assistant that keeps learning from what reviewers actually find.

References

1. J. Śliwerski, T. Zimmermann and A. Zeller, "When Do Changes Induce Fixes?", *Proc. Int. Workshop on Mining Software Repositories (MSR)*, 2005.
2. A. E. Hassan, "Predicting Faults Using the Complexity of Code Changes", *Proc. Int. Conf. on Software Engineering (ICSE)*, 2009.
3. Y. Kamei, E. Shihab, B. Adams, A. E. Hassan, A. Mockus, A. Sinha and N. Ubayashi, "A Large-Scale Empirical Study of Just-in-Time Quality Assurance", *IEEE Transactions on Software Engineering*, 39(6), 2013.
4. D. Spadini, M. Aniche and A. Bacchelli, "PyDriller: Python Framework for Mining Software Repositories", *Proc. ESEC/FSE*, 2018.
5. N. V. Chawla, K. W. Bowyer, L. O. Hall and W. P. Kegelmeyer, "SMOTE: Synthetic Minority Over-sampling Technique", *Journal of Artificial Intelligence Research*, 16, 2002.
6. L. Breiman, "Random Forests", *Machine Learning*, 45(1), 2001.

7. T. Chen and C. Guestrin, "XGBoost: A Scalable Tree Boosting System", *Proc. ACM SIGKDD*, 2016.
8. M. T. Ribeiro, S. Singh and C. Guestrin, "'Why Should I Trust You?': Explaining the Predictions of Any Classifier", *Proc. ACM SIGKDD*, 2016.
9. S. M. Lundberg and S.-I. Lee, "A Unified Approach to Interpreting Model Predictions", *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.
10. J. W. Tukey, *Exploratory Data Analysis*, Addison-Wesley, 1977.
11. A. P. Dempster, N. M. Laird and D. B. Rubin, "Maximum Likelihood from Incomplete Data via the EM Algorithm", *Journal of the Royal Statistical Society, Series B*, 39(1), 1977.
12. E. Levina and P. J. Bickel, "Maximum Likelihood Estimation of Intrinsic Dimension", *Advances in Neural Information Processing Systems (NIPS)*, 2004.
13. J. B. Tenenbaum, V. de Silva and J. C. Langford, "A Global Geometric Framework for Nonlinear Dimensionality Reduction", *Science*, 290(5500), 2000.
14. T. Kohonen, "Self-Organized Formation of Topologically Correct Feature Maps", *Biological Cybernetics*, 43(1), 1982.
15. U. von Luxburg, "A Tutorial on Spectral Clustering", *Statistics and Computing*, 17(4), 2007.
16. R. S. Sutton and A. G. Barto, *Reinforcement Learning: An Introduction*, 2nd edition, MIT Press, 2018.