### Data Science Lab

Vasudevan T V

### Matrix Operations

- Using Vectorisation
- Here various matrix operations are performed without using loops
- For this, we can use various functions in the built in package numpy

```
# Matrix Addition
>>> import numpy
>>> matrix1=numpy.matrix([[1,2],[3,4]])
>>> matrix2=numpy.matrix([[4,3],[2,1]])
>>> matrix3=numpy.add(matrix1,matrix2)
>>> print(matrix3)
[[5 5]
[5 5]]
```

### Matrix Operations

```
# Matrix Subtraction
>>> import numpy
>>> matrix1=numpy.matrix([[2,2],[2,2]])
>>> matrix2=numpy.matrix([[1,1],[1,1]])
>>> matrix3=numpy.subtract(matrix1,matrix2)
>>> print(matrix3)
\lceil \lceil 1 \rceil \rceil
 [1 1]]
# Matrix Multiplication
>>> import numpy
>>> matrix1=numpy.matrix([[2,2],[2,2]])
>>> matrix2=numpy.matrix([[1,1],[1,1]])
>>> matrix3=numpy.matmul(matrix1,matrix2)
>>> print(matrix3)
[[4 4]
 [4 4]]
```

## Matrix Operations

```
# Scalar Multiplication
>>> import numpy
>>> matrix1=numpy.matrix([[2,2],[2,2]])
>>> matrix2=2*matrix1
>>> print(matrix2)
[[4 4]
 [4 4]]
# Matrix Transpose
>>> import numpy
>>> matrix1=numpy.matrix([[1,2],[3,4]])
>>> print(matrix1)
\lceil \lceil 1 \rceil \rceil
 [3 4]]
>>> matrix2=numpy.transpose(matrix1)
>>> print(matrix2)
[[1 3]
 [2 4]]
```

- ► We can use matrices for performing various geometric transformations such as translation, rotation, scaling etc.
- ► Translation is the process of moving an object to a different position
- ▶ Rotation is the process of changing the angle of the object
- Scaling is the process of changing the size of objects

Translation Matrix

```
\begin{bmatrix} 1 & 0 & \mathsf{T}_{\mathsf{X}} \\ 0 & 1 & \mathsf{T}_{\mathsf{y}} \\ 0 & 0 & 1 \end{bmatrix}
```

#### Program

Rotation Matrix

```
\begin{bmatrix} \cos\theta & -\sin\theta & 0 \\ \sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{bmatrix}
```

#### Program

print(matrix)

Scaling Matrix

```
\begin{bmatrix} \mathbf{s_x} & \mathbf{0} & \mathbf{0} \\ \mathbf{0} & \mathbf{s_y} & \mathbf{0} \\ \mathbf{0} & \mathbf{0} & \mathbf{1} \end{bmatrix}
```

#### Program

- ► It is the process of decomposing a matrix into 3 components which are also matrices
- ► A matrix M is decomposed into 3 matrices U, S and V
- ► If M is a real matrix, U and V are orthogonal matrices and S is a diagonal matrix
- ► The advantage of such a decomposition is that we can do the subsequent matrix operations faster
- Applications solving homogeneous linear equations, pattern recognition, natural language processing, weather prediction, machine learning etc.

Program

```
# Imports matrix, matmul and diag functions only
from numpy import matrix
from numpy import matmul
from numpy import diag
# Imports svd fn from linalg(linear algebra) submodule of
# scipy module
from scipy.linalg import svd
# define a matrix
A = matrix([[1, 2, 3], [4, 5, 6], [7, 8, 9]])
print(A)
# Singular-value decomposition
# A is decomposed into 3 matrices U, a diagonal matrix
\# and V
# Here S contains only the diagonal elements of the
# diagonal matrix
U, S, V = svd(A)
```

Program - continued

```
print(U)
print(S)
print(V)
# create diagonal matrix from diagonal elements
Sigma = diag(S)
print(Sigma)
# reconstruct matrix
B = matmul(U,matmul(Sigma,V))
print(B)
```

Output

```
\lceil \lceil 1 \ 2 \ 3 \rceil
 [4 5 6]
 [7 8 9]]
[-0.21483724 \quad 0.88723069 \quad 0.40824829]
 [-0.52058739 0.24964395 -0.81649658]
 [-0.82633754 -0.38794278 0.40824829]]
[1.68481034e+01 1.06836951e+00 4.41842475e-16]
[[-0.47967118 -0.57236779 -0.66506441]
 [-0.77669099 -0.07568647 0.62531805]
 [-0.40824829 0.81649658 -0.40824829]]
[[1.68481034e+01 0.00000000e+00 0.00000000e+00]
 [0.00000000e+00 1.06836951e+00 0.00000000e+00]
 [0.00000000e+00 0.0000000e+00 4.41842475e-16]]
[[1. 2. 3.]
 [4. 5. 6.]
 [7. 8. 9.]]
```