




# Prof. Dr. Florian Künzner

Technical University of Applied Sciences Rosenheim, Computer Science

Start: 8:01

Bitte: Vorname + Nachname  
⇒ selbstständig umbenennen


## OS 8 – Communication 1



source: icons.png.com

The lecture is based on the work and the documents of Prof. Dr. Ludwig Frank

# Goal




# Goal

## OS::Communication

- Process communication concept
- Signals
- Sockets (Unix, network)

# Process isolation $\Rightarrow$ no communication



# Intro


- C-Debugger
- Daemon : PHP → HTML  
⇒ Dropper → Websites
- Zoom
- Youtube
- E-Mail

## Why do you want to communicate with a process?

# Intro


## How can we communicate with a process?

# Process communication



- The communication channel is provided by the OS
- Different types of communication channels exist


# Process communication



- The communication channel is provided by the OS
- Different types of communication channels exist



# Process communication



- The communication channel is provided by the OS
- Different types of communication channels exist

# Process communication

## Important concepts

Function/concept

Description

# Process communication

## Important concepts

### Function/concept

`send(destination, message)`

### Description

**Send** a message **to** the **destination**.

# Process communication

## Important concepts

### Function/concept

`send(destination, message)`

`recv(source, &message)`

### Description

**Send** a message **to** the **destination**.

**Receive** a message **from** the **source**.

# Process communication

## Important concepts

Function/concept	Description
<code>send(destination, message)</code>	<b>Send</b> a message <b>to</b> the <b>destination</b> .
<code>recv(source, &amp;message)</code>	<b>Receive</b> a message <b>from</b> the <b>source</b> .
Blocking/synchron	<code>send()</code> / <code>recv()</code> <b>blocks</b> until the data is fully transferred.

# Process communication

## Important concepts

### Function/concept

`send(destination, message)`

`recv(source, &message)`

Blocking/synchron

Non-blocking/asynchron

### Description

**Send** a message **to** the **destination**.

**Receive** a message **from** the **source**.

`send()` / `recv()` **blocks** until the data is fully transferred.

`send()` / `recv()` **immediately returns** and the process can proceed.

# Process communication

## Important concepts

### Function/concept

`send(destination, message)`

`recv(source, &message)`

Blocking/synchron

Non-blocking/asynchron

Protocol required

### Description

**Send** a message **to** the **destination**.

**Receive** a message **from** the **source**.

`send()` / `recv()` **blocks** until the data is fully transferred.

`send()` / `recv()` **immediately returns** and the process can proceed.

A **protocol** defines the **order of** `send()` / `recv()` between processes and the message format.

# Process communication

## Important concepts

### Function/concept

`send(destination, message)`

`recv(source, &message)`

Blocking/synchron

Non-blocking/asynchron

Protocol required

Half-duplex/unidirectional

### Description

**Send** a message **to** the **destination**.

**Receive** a message **from** the **source**.

`send()` / `recv()` **blocks** until the data is fully transferred.

`send()` / `recv()` **immediately returns** and the process can proceed.

A **protocol** defines the **order of** `send()` / `recv()` between processes and the message format.

Communication over a “channel” **only in one** direction.



# Process communication

## Important concepts

### Function/concept

`send(destination, message)`

`recv(source, &message)`

Blocking/synchron

Non-blocking/asynchron

Protocol required

Half-duplex/unidirectional

Full-duplex/bidirectional

### Description

**Send** a message **to** the **destination**.

**Receive** a message **from** the **source**.

`send()` / `recv()` **blocks** until the data is fully transferred.

`send()` / `recv()` **immediately returns** and the process can proceed.

A **protocol** defines the **order of** `send()` / `recv()` between processes and the message format.

Communication over a “channel” **only in one** direction.

Communication over a “channel” **in both** directions.

# Signals

**Idea:** Signals are **asynchronous events** that interrupt a process.

It is like an **interrupt** request at **process level**.

# Signals

**Idea:** Signals are **asynchronous events** that interrupt a process.

It is like an **interrupt** request at **process level**.



# Signals overview

**List of signals:** `kill -l`

1) SIGHUP	2) SIGINT	3) SIGQUIT	4) SIGILL	5) SIGTRAP
6) SIGABRT	7) SIGBUS	8) SIGFPE	9) SIGKILL	10) SIGUSR1
11) SIGSEGV	12) SIGUSR2	13) SIGPIPE	14) SIGALRM	15) SIGTERM
16) SIGSTKFLT	17) SIGCHLD	18) SIGCONT	19) SIGSTOP	20) SIGTSTP
21) SIGTTIN	22) SIGTTOU	23) SIGURG	24) SIGXCPU	25) SIGXFSZ
26) SIGVTALRM	27) SIGPROF	28) SIGWINCH	29) SIGIO	30) SIGPWR
31) SIGSYS	34) SIGRTMIN	35) SIGRTMIN+1	36) SIGRTMIN+2	37) SIGRTMIN+3
38) SIGRTMIN+4	39) SIGRTMIN+5	40) SIGRTMIN+6	41) SIGRTMIN+7	42) SIGRTMIN+8
43) SIGRTMIN+9	44) SIGRTMIN+10	45) SIGRTMIN+11	46) SIGRTMIN+12	47) SIGRTMIN+13
48) SIGRTMIN+14	49) SIGRTMIN+15	50) SIGRTMAX-14	51) SIGRTMAX-13	52) SIGRTMAX-12
53) SIGRTMAX-11	54) SIGRTMAX-10	55) SIGRTMAX-9	56) SIGRTMAX-8	57) SIGRTMAX-7
58) SIGRTMAX-6	59) SIGRTMAX-5	60) SIGRTMAX-4	61) SIGRTMAX-3	62) SIGRTMAX-2
63) SIGRTMAX-1	64) SIGRTMAX			



# Signals: some important signals

Nr	Signal	Key	Blockable	Description
----	--------	-----	-----------	-------------



# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process



# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard



# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard
3	SIGQUIT	CTRL+\	Y	Quit from keyboard





# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard
3	SIGQUIT	CTRL+\	Y	Quit from keyboard
4	SIGILL		Y	Illegal Instruction



# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard
3	SIGQUIT	CTRL+\	Y	Quit from keyboard
4	SIGILL		Y	Illegal Instruction
6	SIGABRT		Y	Abort signal from abort()



# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard
3	SIGQUIT	CTRL+\	Y	Quit from keyboard
4	SIGILL		Y	Illegal Instruction
6	SIGABRT		Y	Abort signal from abort()
8	SIGFPE		Y	Floating-point exception

More details: <http://man7.org/linux/man-pages/man7/signal.7.html>

# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard
3	SIGQUIT	CTRL+\	Y	Quit from keyboard
4	SIGILL		Y	Illegal Instruction
6	SIGABRT		Y	Abort signal from abort()
8	SIGFPE		Y	Floating-point exception
9	SIGKILL		N	Kill signal

More details: <http://man7.org/linux/man-pages/man7/signal.7.html>

# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard
3	SIGQUIT	CTRL+\	Y	Quit from keyboard
4	SIGILL		Y	Illegal Instruction
6	SIGABRT		Y	Abort signal from abort()
8	SIGFPE		Y	Floating-point exception
9	SIGKILL		N	Kill signal
14	SIGALRM		Y	Timer signal from alarm()

More details: <http://man7.org/linux/man-pages/man7/signal.7.html>

# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard
3	SIGQUIT	CTRL+\	Y	Quit from keyboard
4	SIGILL		Y	Illegal Instruction
6	SIGABRT		Y	Abort signal from abort()
8	SIGFPE		Y	Floating-point exception
9	SIGKILL		N	Kill signal
14	SIGALRM		Y	Timer signal from alarm()
15	SIGTERM		Y	Termination signal



# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard
3	SIGQUIT	CTRL+\	Y	Quit from keyboard
4	SIGILL		Y	Illegal Instruction
6	SIGABRT		Y	Abort signal from abort()
8	SIGFPE		Y	Floating-point exception
9	SIGKILL		N	Kill signal
14	SIGALRM		Y	Timer signal from alarm()
15	SIGTERM		Y	Termination signal
10	SIGUSR1		Y	User-defined signal 1







# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard
3	SIGQUIT	CTRL+\	Y	Quit from keyboard
4	SIGILL		Y	Illegal Instruction
6	SIGABRT		Y	Abort signal from abort()
8	SIGFPE		Y	Floating-point exception
9	SIGKILL		N	Kill signal
14	SIGALRM		Y	Timer signal from alarm()
15	SIGTERM		Y	Termination signal
10	SIGUSR1		Y	User-defined signal 1
12	SIGUSR2		Y	User-defined signal 2
18	SIGCONT		Y	Continue if stopped

# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard
3	SIGQUIT	CTRL+\	Y	Quit from keyboard
4	SIGILL		Y	Illegal Instruction
6	SIGABRT		Y	Abort signal from abort()
8	SIGFPE		Y	Floating-point exception
9	SIGKILL		N	Kill signal
14	SIGALRM		Y	Timer signal from alarm()
15	SIGTERM		Y	Termination signal
10	SIGUSR1		Y	User-defined signal 1
12	SIGUSR2		Y	User-defined signal 2
18	SIGCONT		Y	Continue if stopped
19	SIGSTOP		N	Stop process

# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard
3	SIGQUIT	CTRL+\	Y	Quit from keyboard
4	SIGILL		Y	Illegal Instruction
6	SIGABRT		Y	Abort signal from abort()
8	SIGFPE		Y	Floating-point exception
9	SIGKILL		N	Kill signal
14	SIGALRM		Y	Timer signal from alarm()
15	SIGTERM		Y	Termination signal
10	SIGUSR1		Y	User-defined signal 1
12	SIGUSR2		Y	User-defined signal 2
18	SIGCONT		Y	Continue if stopped
19	SIGSTOP		N	Stop process
20	SIGTSTP	CTRL+Z	Y	Stop typed at terminal

More details: <http://man7.org/linux/man-pages/man7/signal.7.html>

# Signals: some important signals

Nr	Signal	Key	Blockable	Description
1	SIGHUP		Y	Hangup detected on controlling terminal or death of controlling process
2	SIGINT	CTRL+C	Y	Interrupt from keyboard
3	SIGQUIT	CTRL+\	Y	Quit from keyboard
4	SIGILL		Y	Illegal Instruction
6	SIGABRT		Y	Abort signal from abort()
8	SIGFPE		Y	Floating-point exception
9	SIGKILL		N	Kill signal
14	SIGALRM		Y	Timer signal from alarm()
15	SIGTERM		Y	Termination signal
10	SIGUSR1		Y	User-defined signal 1
12	SIGUSR2		Y	User-defined signal 2
18	SIGCONT		Y	Continue if stopped
19	SIGSTOP		N	Stop process
20	SIGTSTP	CTRL+Z	Y	Stop typed at terminal

More details: <http://man7.org/linux/man-pages/man7/signal.7.html>

# Signals: handling

- If a process receives a signal: the **signal** is **saved** in the **PCB**.
- If the process state changes to “**running**” the **process** will be **interrupted**.
- The operating system looks if there is a registered handler for the received signal
  - If there is a **registered handler**, then **this function** will be called.
  - If there **no handler** registered, the **default handler** will be called.
- If the handler hasn't exited the process, the **process proceeds** exactly at the **position before** it was **interrupted**.

# Signals: handling

- If a process receives a signal: the **signal** is **saved** in the **PCB**.
- If the process state changes to “**running**” the **process** will be **interrupted**.
- The operating system looks if there is a registered handler for the received signal
  - If there is a **registered handler**, then **this function** will be called.
  - If there **no handler** registered, the **default handler** will be called.
- If the handler hasn't exited the process, the **process proceeds** exactly at the **position before** it was **interrupted**.

# Signals: handling

- If a process receives a signal: the **signal** is **saved** in the **PCB**.
- If the process state changes to “**running**” the **process** will be **interrupted**.
- The operating system looks if there is a registered handler for the received signal
  - If there is a **registered handler**, then **this function** will be called.
  - If there **no handler** registered, the **default handler** will be called.
- If the handler hasn't exited the process, the **process proceeds** exactly at the **position before** it was **interrupted**.

# Signals: handling

- If a process receives a signal: the **signal** is **saved** in the **PCB**.
- If the process state changes to “**running**” the **process** will be **interrupted**.
- The operating system looks if there is a registered handler for the received signal
  - If there is a **registered handler**, then **this function** will be called.
  - If there **no handler** registered, the **default handler** will be called.
- If the handler hasn't exited the process, the **process proceeds** exactly at the **position before** it was **interrupted**.



# Signals: handling

- If a process receives a signal: the **signal** is **saved** in the **PCB**.
- If the process state changes to “**running**” the **process** will be **interrupted**.
- The operating system looks if there is a registered handler for the received signal
  - If there is a **registered handler**, then **this function** will be called.
  - If there **no handler** registered, the **default handler** will be called.
- If the handler hasn't exited the process, the **process proceeds** exactly at the **position before** it was **interrupted**.

# Signals: handling

- If a process receives a signal: the **signal** is **saved** in the **PCB**.
- If the process state changes to “**running**” the **process** will be **interrupted**.
- The operating system looks if there is a registered handler for the received signal
  - If there is a **registered handler**, then **this function** will be called.
  - If there **no handler** registered, the **default handler** will be called.
- If the handler hasn't exited the process, the **process proceeds** exactly at the **position before** it was **interrupted**.

# Signals: handling

- If a process receives a signal: the **signal** is **saved** in the **PCB**.
- If the process state changes to “**running**” the **process** will be **interrupted**.
- The operating system looks if there is a registered handler for the received signal
  - If there is a **registered handler**, then **this function** will be called.
  - If there **no handler** registered, the **default handler** will be called.
- If the handler hasn't exited the process, the **process proceeds** exactly at the **position before** it was **interrupted**.



# Signals: shell

**Commands**  
Command  
`kill` PID

## Description

Sends the signal **15 (SIGTERM)** to the process.

# Signals: shell

## Commands

### Command

`kill PID`  
`kill -1 PID`

### Description

Sends the signal **15 (SIGTERM)** to the process.  
Sends the signal **1 (SIGHUP)** to the process.

# Signals: shell

## Commands

### Command

`kill PID`

`kill -1 PID`

### Description

Sends the signal **15 (SIGTERM)** to the process.

Sends the signal **1 (SIGHUP)** to the process.

# Signals: shell

## Commands

### Command

`kill PID`

`kill -1 PID`

`kill -SIGHUP PID`

### Description

Sends the signal **15 (SIGTERM)** to the process.

Sends the signal **1 (SIGHUP)** to the process.

Sends the signal **1 (SIGHUP)** to the process.



# Signals: shell

## Commands

Command	Description
<code>kill PID</code>	Sends the signal <b>15 (SIGTERM)</b> to the process.
<code>kill -1 PID</code>	Sends the signal <b>1 (SIGHUP)</b> to the process.
<code>kill -SIGHUP PID</code>	Sends the signal <b>1 (SIGHUP)</b> to the process.
<code>killall process_name</code>	Sends the signal <b>15 (SIGTERM)</b> to the process.

# Signals: shell

## Commands

Command	Description
<code>kill PID</code>	Sends the signal <b>15 (SIGTERM)</b> to the process.
<code>kill -1 PID</code>	Sends the signal <b>1 (SIGHUP)</b> to the process.
<code>kill -SIGHUP PID</code>	Sends the signal <b>1 (SIGHUP)</b> to the process.
<code>killall process_name</code>	Sends the signal <b>15 (SIGTERM)</b> to the process.
<code>killall -s HUP process_name</code>	Sends the signal <del>15 (SIGTERM)</del> to the process. <i>1 SIGHUP</i>

# Signals: signal handling C example

```

1  #include <stdio.h>    //printf
2  #include <stdlib.h>   //EXIT_SUCCESS
3  #include <signal.h>   //signal
4  #include <unistd.h>   //sleep
5
6  void signal_handler(int signal) {
7      printf("No, I don't want to terminate right now!\n");
8  }
9
10 int main(int argc, char** argv) {
11     //register the signal handler
12     signal(SIGTERM, signal_handler);
13
14     for(long long int i = 0; i < __LONG_LONG_MAX__; ++i) { //do something usefull...
15         printf("sleeping!!\n");
16         sleep(5);
17     }
18
19     printf("%s exits main() now!\n", argv[0]);
20     return EXIT_SUCCESS;
21 }

```

# Signals: C function overview

Function\*

Description

---

\*return types not shown here!

# Signals: C function overview

## Function\*

```
raise(int sig);
```

## Description

**Sends a signal** to the calling process or thread.

---

\*return types not shown here!

# Signals: C function overview

## Function\*

```
raise(int sig);  
kill(pid_t pid, int sig);
```

## Description

**Sends a signal** to the calling process or thread.

**Sends a signal** to the process with the specified pid.

---

\*return types not shown here!

# Signals: C function overview

## Function\*

```
raise(int sig);  
kill(pid_t pid, int sig);  
  
pause(void);
```

## Description

**Sends a signal** to the calling process or thread.  
**Sends a signal** to the process with the specified pid.  
  
Causes the calling process or thread to **sleep until a signal is delivered**.

\*return types not shown here!

# Signals: C function overview

## Function\*

```
raise(int sig);  
kill(pid_t pid, int sig);
```

```
pause(void);
```

```
sleep(unsigned int seconds);
```

## Description

**Sends a signal** to the calling process or thread.

**Sends a signal** to the process with the specified pid.

Causes the calling process or thread to **sleep until a signal is delivered**.

**Sleeps** for the **specified seconds** or **until a signal delivered**.

---

\*return types not shown here!



# Signals: C function overview

## Function\*

```
raise(int sig);  
kill(pid_t pid, int sig);
```

```
pause(void);
```

```
sleep(unsigned int seconds);
```

```
alarm(unsigned int seconds);
```

## Description

**Sends a signal** to the calling process or thread.

**Sends a signal** to the process with the specified pid.

Causes the calling process or thread to **sleep until a signal is delivered**.

**Sleeps** for the **specified seconds** or **until a signal delivered**.

**Sends an alarm** to the calling process or thread in the specified seconds.

---

\*return types not shown here!

# Signals: C function overview

## Function\*

```
raise(int sig);  
kill(pid_t pid, int sig);
```

```
pause(void);
```

```
sleep(unsigned int seconds);
```

```
alarm(unsigned int seconds);
```

```
signal(int signum, sighandler_t handler);
```

## Description

**Sends a signal** to the calling process or thread.

**Sends a signal** to the process with the specified pid.

Causes the calling process or thread to **sleep until a signal is delivered**.

**Sleeps** for the **specified seconds** or **until a signal delivered**.

**Sends an alarm** to the calling process or thread in the specified seconds.

**Registers a signal handler** for signum.

---

\*return types not shown here!

# Signals: C function overview

## Function\*

```
raise(int sig);  
kill(pid_t pid, int sig);
```

```
pause(void);
```

```
sleep(unsigned int seconds);
```

```
alarm(unsigned int seconds);
```

```
signal(int signum, sighandler_t handler);  
signal(int signum, SIG_IGN);
```

## Description

**Sends a signal** to the calling process or thread.

**Sends a signal** to the process with the specified pid.

Causes the calling process or thread to **sleep until a signal is delivered**.

**Sleeps** for the **specified seconds** or **until a signal delivered**.

**Sends an alarm** to the calling process or thread in the specified seconds.

**Registers a signal handler** for signum.

**Ignores** signals for signum, by setting a SIG\_IGN handler, which doesn't exits the process.

---

\*return types not shown here!

# Signals: C function overview

## Function\*

```
raise(int sig);  
kill(pid_t pid, int sig);
```

```
pause(void);
```

```
sleep(unsigned int seconds);
```

```
alarm(unsigned int seconds);
```

```
signal(int signum, sighandler_t handler);  
signal(int signum, SIG_IGN);
```

```
signal(int signum, SIG_DFL);
```

## Description

**Sends a signal** to the calling process or thread.

**Sends a signal** to the process with the specified pid.

Causes the calling process or thread to **sleep until a signal is delivered**.

**Sleeps** for the **specified seconds** or **until a signal delivered**.

**Sends an alarm** to the calling process or thread in the specified seconds.

**Registers a signal handler** for signum.

**Ignores** signals for signum, by setting a SIG\_IGN handler, which doesn't exits the process.

**Sets the default handler** for signum.

---

\*return types not shown here!

# Questions?

All right?



Question?



and use **chat**

or

**speak** *after* I  
ask you to

# Sockets

# Socket concept







# Sockets

## Socket concept

- Endpoint for sending or receiving data
- Inter-process communication (IPC)
- Byte oriented data transfer
- Full-duplex -> `send()`/`recv()` over the same socket

# Sockets

## Socket concept

- Endpoint for sending or receiving data
- Inter-process communication (IPC)
- Byte oriented data transfer
- Full-duplex -> `send()` / `recv()` over the same socket

# Sockets

Connection oriented vs connectionless.

↑  
TCP

↑  
UDP



# Sockets

## Unix vs network sockets.

# Questions?

All right?



Question?



and use **chat**

or

**speak** *after* I  
ask you to



# Unix sockets





# Unix sockets

## Unix socket concept

- Unix domain
- Communication only on same PC
- Is faster than network (TCP/IP or UDP/IP) socket
- Use file system as address name space
- User ID can be determined
- Access control via file system

# Unix sockets

## Unix socket concept

- Unix domain
- Communication only on same PC
- Is faster than network (TCP/IP or UDP/IP) socket
- Use file system as address name space
- User ID can be determined
- Access control via file system

# Unix sockets

## Unix socket concept

- Unix domain
- Communication only on same PC
- Is faster than network (TCP/IP or UDP/IP) socket
- Use file system as address name space
- User ID can be determined
- Access control via file system

# Unix sockets

## Unix socket concept

- Unix domain
- Communication only on same PC
- Is faster than network (TCP/IP or UDP/IP) socket
- Use file system as address name space
- User ID can be determined
- Access control via file system

# Unix sockets

## Unix socket concept

- Unix domain
- Communication only on same PC
- Is faster than network (TCP/IP or UDP/IP) socket
- Use file system as address name space
- User ID can be determined
- Access control via file system

# Unix sockets

## Unix socket concept

- Unix domain
- Communication only on same PC
- Is faster than network (TCP/IP or UDP/IP) socket
- Use file system as address name space
- User ID can be determined
- Access control via file system

# Unix sockets


## Unix socket concept


- Unix domain
- Communication only on same PC
- Is faster than network (TCP/IP or UDP/IP) socket
- Use file system as address name space
- User ID can be determined
- Access control via file system





# Questions?


All right? ⇒ 

Question? ⇒  and use **chat**


or

**speak** *after* I ask you to


# Network sockets: remote



# Network sockets: remote



# Network sockets: local



# Network sockets

## Network socket concept

- Internet/network domain
- Communication over the network
- Communication on same PC over loopback
- TCP/IP: connection oriented
- UDP/IP: simple connectionless communication
- Access control on package filter level

# Network sockets

## Network socket concept

- Internet/network domain
- Communication over the network
- Communication on same PC over loopback
- TCP/IP: connection oriented
- UDP/IP: simple connectionless communication
- Access control on package filter level

# Network sockets

## Network socket concept

- Internet/network domain
- Communication over the network
- Communication on same PC over loopback
- TCP/IP: connection oriented
- UDP/IP: simple connectionless communication
- Access control on package filter level

# Network sockets

## Network socket concept

- Internet/network domain
- Communication over the network
- Communication on same PC over loopback
- TCP/IP: connection oriented
- UDP/IP: simple connectionless communication
- Access control on package filter level



# Network sockets

## Network socket concept

- Internet/network domain
- Communication over the network
- Communication on same PC over loopback
- TCP/IP: connection oriented
- UDP/IP: simple connectionless communication
- Access control on package filter level

# Network sockets

## Network socket concept

- Internet/network domain
- Communication over the network
- Communication on same PC over loopback
- TCP/IP: connection oriented
- UDP/IP: simple connectionless communication
- Access control on package filter level


# Network sockets


## Network socket concept

- Internet/network domain
- Communication over the network
- Communication on same PC over loopback
- TCP/IP: connection oriented
- UDP/IP: simple connectionless communication
- Access control on package filter level



# Questions?

All right? ⇒ 

Question? ⇒  and use **chat**

or

**speak** *after* I  
ask you to

# Summary and outlook

## Summary

- Process communication concept
- Signals
- Sockets (Unix, network)

## Outlook

- Message queues
- Shared memory

# Summary and outlook

## Summary

- Process communication concept
- Signals
- Sockets (Unix, network)

## Outlook

- Message queues
- Shared memory