




Prof. Dr. Florian Künzner

Technical University of Applied Sciences Rosenheim, Computer Science


OS 10 – Deadlocks



source: icons.png.com

The lecture is based on the work and the documents of Prof. Dr. Ludwig Frank

Goal



Goal

OS::Deadlocks

- Intro
- Analysis
- Safe state
- Deadlock prevention
- Deadlock recovery

Intro

Parallelisation with processes and threads and their synchronisation is nice, but...

Intro

Example 1

```
1 seminit(s, 0);  
2 process1() {  
3     P(s);  
4     //critical area..  
5     V(s);  
6 }  
7 process2() {  
8     P(s);  
9     //critical area..  
10    V(s);  
11 }
```

Problem

- Deadlock
- Reason: Critical area can't be accessed, because the semaphore is initialised with 0.

Intro

Example 2

time
↓

```

1 process1() {
2     request(resource_a);
3     //process change
4
5
6     request(resource_b);
7     //...
8
9
10 }
```

```

1 process2() {
2
3
4     request(resource_b);
5     //process change
6
7
8     request(resource_a);
9     //...
10 }
```

Problem

- **Deadlock**
- Reason: Resource is **already assigned** to other process (**both wait**)

Definition

A **deadlock** is a situation where one or more **processes wait for resource(s)** and **no one** is able to get its required resource(s), because they are **waiting**.

Analysis

How can a deadlock occur? We try a systematic analysis.

Deadlock characterisation


A deadlock can occur under these conditions

Condition	Description
Mutual exclusion	Tasks claim exclusive control of the resources they require (" mutual exclusion " condition).
Hold and wait	Tasks hold resources already allocated to them while waiting for additional resources (" wait for " condition).
No preemption	Resources cannot be forcibly removed from the tasks holding them until the resources are used to completion (" no preemption " condition).
Circular wait	A circular chain of tasks exist, such that each task holds one or more resources that are being requested by the next task in the chain (" circular wait " condition).


Original paper: (E. G. COFFMAN et al., 1971) [coffman_deadlocks.pdf](#)

More details: <https://en.wikipedia.org/wiki/Deadlock>

Analysis: notation



Analysis: example 1 (graphically)



- $P1 \leftarrow A, P1 \rightarrow B, P2 \leftarrow B, P2 \rightarrow A$
- **Circular wait: deadlock.**

Questions?

All right? \Rightarrow 

Question? \Rightarrow  and use **chat**


or

speak *after* I
ask you to

Safe state

Is the system in a safe state?

Safe state



Safe state

- A state is **safe**, if there is **no deadlock**, and there **exists at least one sequence** of processes that **ends not** in a **deadlock**.
- It is **guaranteed** that all processes can finish.

Unsafe state

- A state is **unsafe** if there is a **deadlock**, or there **exists only sequences** that **ends** in a **deadlock**.
- It is **not guaranteed** that all processes can finish.
- A deadlock is an unsafe state.

Safe state: terms

Safe sequence of processes

A *sequence of processes* (P_1, \dots, P_n) is **safe** for a certain state of acquired resources, if *for every process* P_i ($1 \leq i \leq n$) it is **guaranteed** that *all required resources* (R_1, \dots, R_m) can be **granted** including the resources that are acquired by P_j ($j < i$).

Safe state: example 1

There are 12 resources in total available.

Process	Max. need	Acquisition	T_0	T_1	T_2	T_3	T_4	T_5	T_6
P_1	10	5	5	5	10	-	-	-	-
P_2	4	2	4	-	-	-	-	-	-
P_3	9	2	2	2	2	2	9	-	-
free		3	1	5	0	10	3	12	

A safe sequence of processes exists \Rightarrow the system is in a **safe state** 😊

Safe state: example 2

There are 12 resources in total available.

Process	Max. need	Acquisition	T'_0	T_1	T_2
P_1	10	5		5	5
P_2	4	2		4	-
P_3	9	3		3	3
free		2		0	4

No safe sequence of processes exists \Rightarrow the system is in an unsafe state ☹️

Questions?

All right? \Rightarrow 

Question? \Rightarrow  and use **chat**

or


speak *after* I
ask you to

Deadlock prevention

We try to **further investigate the conditions** under these a deadlock can occur, in order to **avoid it as much as possible.**

Prevent mutual exclusion

Idea: try to avoid the mutual exclusion.



Problems

- Not always possible
- Requires redesign of the application

Prevent hold-on-wait

Idea: try to avoid the hold-on-wait.

A process tries to requests all resources at startup. If even one resource is not available, all resources are released, and the process waits.

Problems

- Often a process doesn't know at startup which resources it needs.
- This wastes resources, because they are acquired, but by no means used.
- It can happen that a process has to try it very often until it can acquire all resources.

Prevent non-preemption

Idea: try to avoid the non-preemption.

Release all resources if a required resource isn't immediately available.


Problems

- With the release of a resource, often the whole work is lost and has to be repeated.
- It can happen that a process has to release the resources very often until it can complete its work.

Prevent circular wait

Idea: try to avoid circles.

All resources are numbered. If a process has already acquired resource i , it can only acquire resource k (if $k > i$).



Problems

- Finding an order in which everyone is satisfied is not easy and not always possible.
- Some resources are created and removed at runtime. Numbering not possible.
- But: With this it is possible to proof the **deadlock free** acquisition: **All processes have to acquire the resources in the same order.**


Deadlock prevention


The banker's algorithm

- For every resource that is acquired by a process it checks if the system stays in a safe state.
 - **True:** The **resource is given** to the process.
 - **False:** The **resource is not given** to the process.

Cost: $C = \text{num_resources} * \text{num_processes}^2$

Questions?

All right? \Rightarrow 

Question? \Rightarrow  and use **chat**

or

speak *after* I
ask you to

Deadlock recovery

What can we do if we are in an **unsafe** state with a **deadlock**?

Deadlock recovery

Deadlock recovery strategies

- Terminate one or more processes involved in the deadlock
- Inform the system operator and give him instructions how to proceed (e.g. manual restart)
- Watchdog: automatically restart processes/device

source (compare): https://www.cs.uic.edu/~jbell/CourseNotes/OperatingSystems/7_Deadlocks.html

Questions?

All right?



Question?



and use **chat**

or

speak *after* I
ask you to

Summary and outlook

Summary

- Deadlock intro
- Deadlock analysis
- Deadlock Safe state
- Deadlock prevention
- Deadlock recovery

Outlook

- Scheduling theory
- Scheduling algorithms