

NAME:ALISHBA ZAINAB

ROLL NO:23-BSE-006

SECTION:A

SUBMITTED TO:SIR SHOAIB

CLOUD COMPUTING LAB 11

TASK 1

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ gh codespace list
NAME          DISPLAY NAME  REPOSITORY      BRANCH  STATE    CREATED AT
cuddly-system-jjp...  cuddly system  ALISHBAZAINAB/lab11  main    Available  about 6 minutes ago
@ALISHBAZAINAB →/workspaces/lab11 (main) $
```

```
cuddly-system-jjp...  cuddly system  ALISHBAZAINAB/lab11  main    Available  about 6 minutes ago
@ALISHBAZAINAB →/workspaces/lab11 (main) $
```

```
cuddly-system-jjp...  cuddly system  ALISHBAZAINAB/lab11  main    Available  about 6 minutes ago
@ALISHBAZAINAB →/workspaces/lab11 (main) $ touch main.tf
@ALISHBAZAINAB →/workspaces/lab11 (main) $
```

```
provider "aws" {
  shared_config_files = ["~/.aws/config"]
  shared_credentials_files = ["~/.aws/credentials"]
}
~
~
~
~
~
"main.tf" 4L, 118B                                     4,1      All
```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform init
Terraform has created a lock file .terraform.lock.hcl to record the provider
selections it made above. Include this file in your version control repository
so that Terraform can guarantee to make the same selections by default when
you run "terraform init" in the future.

Terraform has been successfully initialized!

You may now begin working with Terraform. Try running "terraform plan" to see
any changes that are required for your infrastructure. All Terraform commands
should now work.

If you ever set or change modules or backend configuration for Terraform,
rerun this command to reinitialize your working directory. If you forget, other
commands will detect it and remind you to do so if necessary.
@ALISHBAZAINAB →/workspaces/lab11 (main) $
```

```

provider "aws" {
  shared_config_files      = ["~/.aws/config"]
  shared_credentials_files = ["~/.aws/credentials"]
}

variable "subnet_cidr_block" {
  type = string
}

output "subnet_cidr_block_output" {
  value = var.subnet_cidr_block
}

~
~
~
~

```

Commands will detect it and remind you to do so if necessary.

```

@ALISHBAZAINAB →/workspaces/lab11 (main) $ vim main.tf
@ALISHBAZAINAB →/workspaces/lab11 (main) $ vim main.tf
@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve
var.subnet_cidr_block
Enter a value:

```

```

@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve

```

Changes to Outputs:

```

~ subnet_cidr_block_output = "variable \"subnet_cidr_block\" {\" -> "10.0.0.0/24"

```

You can apply this plan to save these new output values to the Terraform state, without changing any real infrastructure.

Apply complete! Resources: 0 added, 0 changed, 0 destroyed.

Outputs:

```

subnet_cidr_block_output = "10.0.0.0/24"

```

```

@ALISHBAZAINAB →/workspaces/lab11 (main) $

```

```

@ALISHBAZAINAB →/workspaces/lab11 (main) $ task1_apply_with_default.png
@ALISHBAZAINAB →/workspaces/lab11 (main) $ export TF_VAR_subnet_cidr_block=10.0.20.0/24
@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve

```

Changes to Outputs:

```

~ subnet_cidr_block_output = "10.0.0.0/24" -> "10.0.20.0/24"

```

You can apply this plan to save these new output values to the Terraform state, without changing any real infrastructure.

Apply complete! Resources: 0 added, 0 changed, 0 destroyed.

Outputs:

```

subnet_cidr_block_output = "10.0.20.0/24"

```

```

@ALISHBAZAINAB →/workspaces/lab11 (main) $ s

```

```
● @ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve

Changes to Outputs:
  ~ subnet_cidr_block_output = "10.0.20.0/24" -> "10.0.30.0/24"

You can apply this plan to save these new output values to the Terraform state, without
changing any real infrastructure.

Apply complete! Resources: 0 added, 0 changed, 0 destroyed.

Outputs:
  subnet_cidr_block_output = "10.0.30.0/24"
● @ALISHBAZAINAB →/workspaces/lab11 (main) $ cat terraform.tfvars
  subnet_cidr_block = "10.0.30.0/24"
○ @ALISHBAZAINAB →/workspaces/lab11 (main) $
```

```
● @ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve -var "subnet_cidr_block=10.0.40.0/24"

Changes to Outputs:
  ~ subnet_cidr_block_output = "10.0.30.0/24" -> "10.0.40.0/24"

You can apply this plan to save these new output values to the Terraform state, without
changing any real infrastructure.

Apply complete! Resources: 0 added, 0 changed, 0 destroyed.

Outputs:
  subnet_cidr_block_output = "10.0.40.0/24"
○ @ALISHBAZAINAB →/workspaces/lab11 (main) $
```

```
  subnet_cidr_block_output = "10.0.40.0/24"
● @ALISHBAZAINAB →/workspaces/lab11 (main) $ printenv | grep TF_VAR_
  TF_VAR_subnet_cidr_block=10.0.20.0/24
● @ALISHBAZAINAB →/workspaces/lab11 (main) $ unset TF_VAR_subnet_cidr_block
○ @ALISHBAZAINAB →/workspaces/lab11 (main) $ printenv | grep TF_VAR_
○ @ALISHBAZAINAB →/workspaces/lab11 (main) $
```

Task 2

```
provider "aws" {
  shared_config_files      = ["~/.aws/config"]
  shared_credentials_files = ["~/.aws/credentials"]
}

# --- Validated subnet_cidr_block ---
variable "subnet_cidr_block" {
  type        = string
  default     = ""
  description = "CIDR block to assign to the application subnet"
  sensitive   = false
  nullable    = false
  ephemeral   = false

  validation {
    condition = true
  }
}
```

2,1 Top

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve -var "subnet_cidr_block=10.0.0"

Error: Invalid value for variable

on main.tf line 14:
14: variable "api_session_token" {
    |
```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve -var api_session_token=my_API_session_Token_123456"
```

Changes to Outputs:

```
+ api_session_token_output = (sensitive value)
~ subnet_cidr_block_output = "10.0.40.0/24" -> "10.0.30.0/24"
```

You can apply this plan to save these new output values to the Terraform state, without changing any real infrastructure.

Apply complete! Resources: 0 added, 0 changed, 0 destroyed.

Outputs:

```
api_session_token_output = <sensitive>
subnet_cidr_block_output = "10.0.30.0/24"
```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ █
```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ cat terraform.tfstate
```

```
    "status": "pass"
  }
]
},
{
  "object_kind": "var",
  "config_addr": "var.subnet_cidr_block",
  "status": "pass",
  "objects": [
    {
      "object_addr": "var.subnet_cidr_block",
      "status": "pass"
    }
  ]
}
```

```
0
```

Task 3

```
output "api_session_token_output" {
  value     = var.api_session_token
  sensitive = true
}
# --- Task 3: Project-level Variables ---
variable "environment" {}
variable "project_name" {}
variable "primary_subnet_id" {}
variable "subnet_count" {}
variable "monitoring" {}
```

AKIASNCIPHNLNCP7R3X

t/r0bLBSFqk71yLX5XBLyeQUz8vDa8geLWZDddQO


```

    value = local.is_production
  }

  output "monitoring_enabled" {
    value = local.monitoring_enabled
  }
  # --- Task 4: Map variable ---
  variable "tags" {
    type = map(string)
  }

  output "tags" {
    value = var.tags
  }
}

```

"main.tf" 78L, 1800B

78,0-1

Bot

@ALISHBAZAINAB →/workspaces/lab11 (main) \$ terraform apply -auto-approve

Outputs:

```

api_session_token_output = <sensitive>
is_production = false
monitoring_enabled = true
primary_public_subnet = "subnet-04b25ebb0525fca58"
resource_name = "lab_work-dev"
subnet_cidr_block_output = "10.0.0.0/24"
subnet_count = 3
tags = tomap({
  "Environment" = "dev"
  "Owner" = "platform-team"
  "Project" = "sample-app"
})

```

○ @ALISHBAZAINAB →/workspaces/lab11 (main) \$

@ALISHBAZAINAB →/workspaces/lab11 (main) \$ terraform apply -auto-approve

```

server_config = {
  "backup_enabled" = false
  "instance_type" = "t3.micro"
  "monitoring" = true
  "name" = "web-server"
  "storage_gb" = 20
}
subnet_cidr_block_output = "10.0.0.0/24"
subnet_count = 3
tags = tomap({
  "Environment" = "dev"
  "Owner" = "platform-team"
  "Project" = "sample-app"
})

```

○ @ALISHBAZAINAB →/workspaces/lab11 (main) \$

Task 5

```

}

variable "availability_zones" {
  type    = set(string)
  default = ["me-central-1b", "me-central-1a", "me-central-1b"]
}

output "compare_collections" {
  value = {
    list_example  = var.server_names
    tuple_example = var.server_metadata
    set_example   = var.availability_zones
  }
}

```

● @ALISHBAZAINAB →/workspaces/lab11 (main) \$ terraform apply -auto-approve

Changes to Outputs:

```

+ compare_collections = {
+   list_example = [
+     "web-2",
+     "web-1",
+     "web-2",
+   ]
+   set_example = [
+     "me-central-1a",
+     "me-central-1b",
+   ]
}

```

Ln 20, Col 1

Spaces: 4 U

```

7 }
8 locals {
9   mutated_list = setunion(var.server_names, ["web-3"])
10  mutated_tuple = setunion(var.server_metadata, ["web-2"])
11  mutated_set   = setunion(var.availability_zones, ["me-central-1c"])
12 }
13

```

@ALISHBAZAINAB →/workspaces/lab11 (main) \$ terraform apply -auto-approve

```

server_config = {
  "backup_enabled" = false
  "instance_type"  = "t3.micro"
  "monitoring"     = true
  "name"           = "web-server"
  "storage_gb"     = 20
}
subnet_cidr_block_output = "10.0.0.0/24"
subnet_count = 3
tags = tomap({
  "Environment" = "dev"
  "Owner"       = "platform-team"
  "Project"     = "sample-app"
})

```

● @ALISHBAZAINAB →/workspaces/lab11 (main) \$

Ln 13, Col 1

Spaces: 4 UTF-8

Task 6

```
# --- Task 6: Null variable ---
variable "optional_tag" {
  type      = string
  description = "A tag that may or may not be provided"
  default    = null
}
```

```
output "optional_tag" {
  value = local.server_tags
}
```

"main.tf" 131L, 2950B

131,0-1

Bot

```
14   locals {
15     server_tags = merge(
16       { Name = "web-server" },
17       var.optional_tag != null ? { Custom = var.optional_tag } : {}
18     )
19   }
20 }
```

Loading...

@ALISHBAZAINAB →/workspaces/lab11 (main) \$ terraform apply -auto-approve

```
server_config = {
  "backup_enabled" = false
  "instance_type"  = "t3.micro"
  "monitoring"     = true
  "name"           = "web-server"
  "storage_gb"     = 20
}
subnet_cidr_block_output = "10.0.0.0/24"
subnet_count = 3
tags = tomap({
  "Environment" = "dev"
  "Owner"       = "platform-team"
  "Project"     = "sample-app"
})
```

@ALISHBAZAINAB →/workspaces/lab11 (main) \$

@ALISHBAZAINAB →/workspaces/lab11 (main) \$ terraform apply -auto-approve

```
"backup_enabled" = false
"instance_type"  = "t3.micro"
"monitoring"     = true
"name"           = "web-server"
"storage_gb"     = 20
}
subnet_cidr_block_output = "10.0.0.0/24"
subnet_count = 3
tags = tomap({
  "Environment" = "dev"
  "Owner"       = "platform-team"
  "Project"     = "sample-app"
})
value_received = "hello"
```

@ALISHBAZAINAB →/workspaces/lab11 (main) \$

```

@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve
    "backup_enabled" = false
    "instance_type" = "t3.micro"
    "monitoring" = true
    "name" = "web-server"
    "storage_gb" = 20
  }
  subnet_cidr_block_output = "10.0.0.0/24"
  subnet_count = 3
  tags = tomap({
    "Environment" = "dev"
    "Owner" = "platform-team"
    "Project" = "sample-app"
  })
  value_received = 42
○ @ALISHBAZAINAB →/workspaces/lab11 (main) $ █
Ln 20, Col 21  Spaces: 4

```

```

@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve
    "storage_gb" = 20
  }
  subnet_cidr_block_output = "10.0.0.0/24"
  subnet_count = 3
  tags = tomap({
    "Environment" = "dev"
    "Owner" = "platform-team"
    "Project" = "sample-app"
  })
  value_received = [
    "a",
    "b",
    "c",
  ]
○ @ALISHBAZAINAB →/workspaces/lab11 (main) $ █
Ln 21, Col 1  Spaces: 4  UTF-8

```

```

@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve
    "name" = "web-server"
    "storage_gb" = 20
  }
  subnet_cidr_block_output = "10.0.0.0/24"
  subnet_count = 3
  tags = tomap({
    "Environment" = "dev"
    "Owner" = "platform-team"
    "Project" = "sample-app"
  })
  value_received = {
    "cpu" = 4
    "name" = "server"
  }
○ @ALISHBAZAINAB →/workspaces/lab11 (main) $ █

```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve
server_config = {
  "backup_enabled" = false
  "instance_type"  = "t3.micro"
  "monitoring"     = true
  "name"           = "web-server"
  "storage_gb"     = 20
}
subnet_cidr_block_output = "10.0.0.0/24"
subnet_count = 3
tags = tomap({
  "Environment" = "dev"
  "Owner"       = "platform-team"
  "Project"     = "sample-app"
})
○ @ALISHBAZAINAB →/workspaces/lab11 (main) $
```

Task 7

```
● @ALISHBAZAINAB →/workspaces/lab11 (main) $ touch .gitignore
● @ALISHBAZAINAB →/workspaces/lab11 (main) $ nano .gitignore
● @ALISHBAZAINAB →/workspaces/lab11 (main) $ cat .gitignore
.terraform/*
*.tfstate
*.tfstate.*
*.tfvars
*.pem
○ @ALISHBAZAINAB →/workspaces/lab11 (main) $
```

Task 8

```
provider "aws" {
  shared_config_files      = ["~/.aws/config"]
  shared_credentials_files = ["~/.aws/credentials"]
}
~
~
~
```

```
PROBLEMS  OUTPUT  DEBUG CONSOLE  TERMINAL  PORTS  vim + v [ ] [ ] ... | [ ] [ ] x

provider "aws" {
  shared_config_files      = ["~/.aws/config"]
  shared_credentials_files = ["~/.aws/credentials"]
}
variable "vpc_cidr_block" {}
variable "subnet_cidr_block" {}
variable "availability_zone" {}
variable "env_prefix" {}
~
~
```

```

    shared_config_files      = ["~/.aws/config"]
    shared_credentials_files = ["~/.aws/credentials"]
}
variable "vpc_cidr_block" {}
variable "subnet_cidr_block" {}
variable "availability_zone" {}
variable "env_prefix" {}
resource "aws_vpc" "myapp_vpc" {
  cidr_block = var.vpc_cidr_block
  tags = {
    Name = "${var.env_prefix}-vpc"
  }
}

```

15,0-1

Br

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

vim + v ... |

```

    cidr_block = var.vpc_cidr_block
    tags = {
      Name = "${var.env_prefix}-vpc"
    }
  }
resource "aws_subnet" "myapp_subnet_1" {
  vpc_id      = aws_vpc.myapp_vpc.id
  cidr_block  = var.subnet_cidr_block
  availability_zone = var.availability_zone
  tags = {
    Name = "${var.env_prefix}-subnet-1"
  }
}

```

23,0-1

Bo

terraform.tfvars

```

1  vpc_cidr_block      = "10.0.0.0/16"
2  subnet_cidr_block  = "10.0.10.0/24"
3  availability_zone   = "me-central-1a"
4  env_prefix          = "dev"
5  |

```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve
} -> null
- subnet_cidr_block_output = "10.0.0.0/24" -> null
- subnet_count             = 3 -> null
- tags                     = {
  - Environment = "dev"
  - Owner       = "platform-team"
  - Project     = "sample-app"
} -> null
aws_vpc.myapp_vpc: Creating...
aws_vpc.myapp_vpc: Creation complete after 2s [id=vpc-0a0ed63f41b73a728]
aws_subnet.myapp_subnet_1: Creating...
aws_subnet.myapp_subnet_1: Creation complete after 0s [id=subnet-0a3621689e44ca912]
```

Apply complete! Resources: 2 added, 0 changed, 0 destroyed.

```
○ @ALISHBAZAINAB →/workspaces/lab11 (main) $
```

```
resource "aws_route_table" "myapp_route_table" {
  vpc_id = aws_vpc.myapp_vpc.id

  route {
    cidr_block = "0.0.0.0/0"
    gateway_id = aws_internet_gateway.myapp_igw.id
  }

  tags = {
    Name = "${var.env_prefix}-rt"
  }
}
```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve
}
+ tags_all      = {
  + "Name" = "dev-rt"
}
+ vpc_id        = "vpc-0a0ed63f41b73a728"
}

Plan: 2 to add, 0 to change, 0 to destroy.
aws_internet_gateway.myapp_igw: Creating...
aws_internet_gateway.myapp_igw: Creation complete after 1s [id=igw-06610be2cd6442b54]
aws_route_table.myapp_route_table: Creating...
aws_route_table.myapp_route_table: Creation complete after 1s [id=rtb-0c67d7370f42d0166]
```

Apply complete! Resources: 2 added, 0 changed, 0 destroyed.

```
○ @ALISHBAZAINAB →/workspaces/lab11 (main) $
```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve
    } -> null
  - tags_all = {
    - "Name" = "dev-rt"
  } -> null
  - vpc_id = "vpc-0a0ed63f41b73a728" -> null
}

Plan: 1 to add, 0 to change, 1 to destroy.
aws_route_table.myapp_route_table: Destroying... [id=rtb-0c67d7370f42d0166]
aws_default_route_table.main_rt: Creating...
aws_route_table.myapp_route_table: Destruction complete after 0s
aws_default_route_table.main_rt: Creation complete after 0s [id=rtb-0099df16280c2270b]

Apply complete! Resources: 1 added, 0 changed, 1 destroyed.
@ALISHBAZAINAB →/workspaces/lab11 (main) $
```

Task 9

```
}
variable "my_ip" {}
variable "instance_type" {}
variable "availability_zone" {}
variable "env_prefix" {}

"main.tf" 47L, 1088B 45,24 Bot
```

```
terraform.tfvars
1 vpc_cidr_block = "10.0.0.0/16"
2 subnet_cidr_block = "10.0.10.0/24"
3 availability_zone = "me-central-1a"
4 env_prefix = "dev"
5 my_ip = "20.192.21.48/32"
6 instance_type = "t3.micro"
7
```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve
    - "Name" = "dev-igw"
    } -> null
  - vpc_id = "vpc-0a0ed63f41b73a728" -> null
}

Plan: 1 to add, 0 to change, 2 to destroy.
aws_default_route_table.main_rt: Destroying... [id=rtb-0099df16280c2270b]
aws_default_route_table.main_rt: Destruction complete after 0s
aws_default_security_group.myapp_sg: Creating...
aws_internet_gateway.myapp_igw: Destroying... [id=igw-06610be2cd6442b54]
aws_internet_gateway.myapp_igw: Destruction complete after 0s
aws_default_security_group.myapp_sg: Creation complete after 2s [id=sg-03e0ece01f8de9392]

Apply complete! Resources: 1 added, 0 changed, 2 destroyed.
@ALISHBAZAINAB →/workspaces/lab11 (main) $
```

```
● @ALISHBAZAINAB →/workspaces/lab11 (main) $ aws ec2 create-key-pair \
> --key-name MyED25519Key \
> --key-type ed25519 \
> --key-format pem \
> --query 'KeyMaterial' \
> --output text > MyED25519Key.pem
● @ALISHBAZAINAB →/workspaces/lab11 (main) $ chmod 600 MyED25519Key.pem
○ @ALISHBAZAINAB →/workspaces/lab11 (main) $
```

```

    associate_public_ip_address = true
    key_name                     = "MyED25519Key"

    tags = {
      Name = "${var.env_prefix}-ec2-instance"
    }
  }

  output "aws_instance_public_ip" {
    value = aws_instance.myapp-server.public_ip
  }

```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve
```

Plan: 1 to add, 0 to change, 0 to destroy.

Changes to Outputs:

```

+ aws_instance_public_ip = (known after apply)
aws_instance.myapp-server: Creating...
aws_instance.myapp-server: Still creating... [10s elapsed]
aws_instance.myapp-server: Creation complete after 13s [id=i-08ba474eee2ee800e]

```

Apply complete! Resources: 1 added, 0 changed, 0 destroyed.

Outputs:

```
aws_instance_public_ip = "158.252.35.145"
```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $
```

```

aws_instance.myapp-server: Modifying... [id=i-02560695decde032f]
aws_instance.myapp-server: Modifications complete after 2s [id=i-02560695decde032f]

```

Apply complete! Resources: 1 added, 1 changed, 1 destroyed.

Outputs:

```
aws_instance_public_ip = "51.112.51.147"
```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ ssh -i MyED25519Key.pem ec2-user@51.112.51.147
```

```

The key fingerprint is:
SHA256:XZGKLIFonPfxnS1Zig1psJ350xg1AicVdWl+SBFM8fU codespace@codespaces-09b908
The key's randomart image is:

```

```

+--[ED25519 256]--+
|  .X=O O ..      |
|    000+ + ...    |
|  . O +O=. . .E   |
|  = +.Xo+...      |
|  . . +.OS=.*      |
|    + * * .       |
|    + . .         |
|    . O           |
|    .             |
+-----[SHA256]-----+

```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $
```

Ln 99, Col 1

Spaces: 2 UTF-8

```

terraform.tfvars
2  subnet_cidr_block = "10.0.10.0/24"
3  availability_zone  = "me-central-1a"
4  env_prefix         = "dev"
5  my_ip              = "20.192.21.48/32"
6  instance_type      = "t3.micro"
7  |

```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ terraform apply -auto-approve
```

```

} -> null
- tags_all = {
  - "Name" = "dev-sg"
} -> null
- vpc_id = "vpc-0a0ed63f41b73a728" -> null
}

```

Plan: 3 to add, 0 to change, 2 to destroy.

Changes to Outputs:

```

~ aws_instance_public_ip = "51.112.51.147" -> (known after apply)
aws_instance.myapp-server: Destroying... [id=i-02560695decde032f]

```

```

# user_data to install Nginx
user_data = <<-EOF
| | | | | #!/bin/bash
| | | | | yum update -y
| | | | | yum install -y nginx
| | | | | systemctl start nginx
| | | | | systemctl enable nginx
| | | | | EOF

tags = {
|   Name = "myapp-server"
}
}

# 4 Output Public IP (for SSH or browser)
output "aws_instance_public_ip" {
|   value = aws_instance.myapp-server.public_ip
}
$

```

Task 10

```

Destroy complete! Resources: 1 destroyed.
@ALISHBAZAINAB →/workspaces/lab11 (main) $

```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ cat terraform.tfstate.backup
    "tags_all": {},
    "timeouts": null,
    "vpc_id": "vpc-01df83ac59c7fbb15"
  },
  "sensitive_attributes": [],
  "private": "eyJ1MmJmYjczMC1lY2FhLTExZTYtOGY4OC0zNDM2M2JjN2M0YzAiOnsiY
3JlYXRlIjo2MDAwMDAwMDAwMDAsImRlbGV0ZSI6OTAwMDAwMDAwMDAwfSwic2NoZW1hX3ZlcnNpb24i
OiIxIn0="
  }
]
},
"check_results": null
}
@ALISHBAZAINAB →/workspaces/lab11 (main) $
```

```
@ALISHBAZAINAB →/workspaces/lab11 (main) $ git status
awscliv2.zip
locals.tf
main.tf
terraform_1.6.0_linux_amd64.zip
terraform_id_ed25519
terraform_id_ed25519.pub

nothing added to commit but untracked files present (use "git add" to track)
● @ALISHBAZAINAB →/workspaces/lab11 (main) $ cat .gitignore
.terraform/*
*.tfstate
*.tfstate.*
*.tfvars
*.pem
@ALISHBAZAINAB →/workspaces/lab11 (main) $
```