

```
1: =====
2: F.A.R.F.A.N PIPELINE CODE AUDIT - BATCH 11
3: =====
4: Generated: 2025-12-07T06:17:18.917142
5: Files in this batch: 17
6: =====
7:
8:
9: =====
10: FILE: src/farfan_pipeline/contracts/verify_all_contracts.py
11: =====
12:
13: #!/usr/bin/env python3
14: """
15: Verification Script for 15-Contract Suite
16: Runs all tests and tools, then validates certificates.
17: """
18: import glob
19: import json
20: import os
21: import subprocess
22: import sys
23:
24: CONTRACTS_DIR = "src/farfan_pipeline/contracts"
25: TOOLS_DIR = os.path.join(CONTRACTS_DIR, "tools")
26: TESTS_DIR = os.path.join(CONTRACTS_DIR, "tests")
27:
28:
29: def run_command(cmd: str, description: str, set_pythonpath: bool = False) -> bool:
30:     print(f"Running {description}...")
31:     try:
32:         env = os.environ.copy()
33:         if set_pythonpath:
34:             cwd = os.getcwd()
35:             src_path = os.path.join(cwd, "src")
36:             env["PYTHONPATH"] = f"{src_path}:{env.get('PYTHONPATH', '')}"
37:             subprocess.check_call(cmd, shell=True, env=env)
38:             print(f"\234\205 {description} PASSED")
39:             return True
40:     except subprocess.CalledProcessError:
41:         print(f"\235\214 {description} FAILED")
42:         return False
43:
44:
45: def main() -> None:
46:     print("=== STARTING VERIFICATION OF 15-CONTRACT SUITE ===")
47:
48:     # 1. Run Pytest Suite
49:     print("\n--- 1. RUNNING TESTS ---")
50:     if not run_command(
51:         f"pytest {TESTS_DIR} -v", "All Contract Tests", set_pythonpath=True
52:     ):
53:         sys.exit(1)
54:
55:     # 2. Run CLI Tools to generate certificates
56:     print("\n--- 2. GENERATING CERTIFICATES ---")
```

```
57: tools = glob.glob(os.path.join(TOOLS_DIR, "*.py"))
58: for tool in sorted(tools):
59:     tool_name = os.path.basename(tool)
60:     if not run_command(f"python {tool}", f"Tool: {tool_name}", set_pythonpath=True):
61:         sys.exit(1)
62:
63: # 3. Verify Certificates
64: print("\n--- 3. VERIFYING CERTIFICATES ---")
65: expected_certs = [
66:     "rc_certificate.json",
67:     "sc_certificate.json",
68:     "cic_certificate.json",
69:     "pic_certificate.json",
70:     "bmc_certificate.json",
71:     "toc_certificate.json",
72:     "rec_certificate.json",
73:     "asc_certificate.json",
74:     "idc_certificate.json",
75:     "rcc_certificate.json",
76:     "mcc_certificate.json",
77:     "ffc_certificate.json",
78:     "cdc_certificate.json",
79:     "tc_certificate.json",
80:     "refc_certificate.json",
81: ]
82:
83: all_passed = True
84: for cert_file in expected_certs:
85:     if not os.path.exists(cert_file):
86:         print(f"\u235\214 {cert_file}: MISSING")
87:         all_passed = False
88:         continue
89:
90:     try:
91:         with open(cert_file) as f:
92:             data = json.load(f)
93:             if data.get("pass") is True:
94:                 print(f"\u234\205 {cert_file}: PASS")
95:             else:
96:                 print(f"\u235\214 {cert_file}: FAIL (pass != true)")
97:                 all_passed = False
98:     except Exception as e:
99:         print(f"\u235\214 {cert_file}: ERROR ({e})")
100:     all_passed = False
101:
102: if all_passed:
103:     print("\n=== ALL SYSTEM CONTRACTS VERIFIED SUCCESSFULLY ===")
104:     sys.exit(0)
105: else:
106:     print("\n=== VERIFICATION FAILED ===")
107:     sys.exit(1)
108:
109:
110: if __name__ == "__main__":
111:     main()
112:
```

```
113:
114:
115: =====
116: FILE: src/farfan_pipeline/contracts.py
117: =====
118:
119: """Contracts module re-exports from utils.contracts package.
120:
121: This module provides backward compatibility for code that imports
122: contracts from farfan_core.contracts instead of farfan_core.utils.contracts.
123: """
124:
125: from farfan_pipeline.utils.contracts import (
126:     MISSING,
127:     AnalysisInputV1,
128:     AnalysisInputV1Optional,
129:     AnalysisOutputV1,
130:     AnalysisOutputV1Optional,
131:     AnalyzerProtocol,
132:     ContractMismatchError,
133:     DocumentLoaderProtocol,
134:     DocumentMetadataV1,
135:     DocumentMetadataV1Optional,
136:     ExecutionContextV1,
137:     ExecutionContextV1Optional,
138:     ProcessedTextV1,
139:     ProcessedTextV1Optional,
140:     SentenceCollection,
141:     TextDocument,
142:     TextProcessorProtocol,
143:     ensure_hashable,
144:     ensure_iterable_not_string,
145:     validate_contract,
146:     validate_mapping_keys,
147: )
148:
149: __all__ = [
150:     "MISSING",
151:     "AnalysisInputV1",
152:     "AnalysisInputV1Optional",
153:     "AnalysisOutputV1",
154:     "AnalysisOutputV1Optional",
155:     "AnalyzerProtocol",
156:     "ContractMismatchError",
157:     "DocumentLoaderProtocol",
158:     "DocumentMetadataV1",
159:     "DocumentMetadataV1Optional",
160:     "ExecutionContextV1",
161:     "ExecutionContextV1Optional",
162:     "ProcessedTextV1",
163:     "ProcessedTextV1Optional",
164:     "SentenceCollection",
165:     "TextDocument",
166:     "TextProcessorProtocol",
167:     "ensure_hashable",
168:     "ensure_iterable_not_string",
```

```
169:     "validate_contract",
170:     "validate_mapping_keys",
171: ]
172:
173:
174:
175: =====
176: FILE: src/farfan_pipeline/controls/__init__.py
177: =====
178:
179: """Controls module for system validation and checks."""
180:
181:
182:
183: =====
184: FILE: src/farfan_pipeline/controls/graphs/__init__.py
185: =====
186:
187: """Graph-based controls and analysis."""
188:
189:
190:
191: =====
192: FILE: src/farfan_pipeline/core/__init__.py
193: =====
194:
195: """Core components of the SAAAAAA system."""
196:
197:
198:
199: =====
200: FILE: src/farfan_pipeline/core/aggregation.py
201: =====
202:
203: """Aggregation module re-exports from processing package.
204:
205: This module provides backward compatibility for code that imports
206: aggregation classes from farfan_core.core.aggregation instead of
207: farfan_core.processing.aggregation.
208: """
209:
210: from farfan_pipeline.processing.aggregation import (
211:     AreaPolicyAggregator,
212:     AreaScore,
213:     ClusterAggregator,
214:     ClusterScore,
215:     DimensionAggregator,
216:     DimensionScore,
217:     MacroAggregator,
218:     ScoredResult,
219: )
220:
221: __all__ = [
222:     "AreaPolicyAggregator",
223:     "AreaScore",
224:     "ClusterAggregator",
```

```
225:     "ClusterScore",
226:     "DimensionAggregator",
227:     "DimensionScore",
228:     "MacroAggregator",
229:     "ScoredResult",
230: ]
231:
232:
233:
234: =====
235: FILE: src/farfan_pipeline/core/analysis_port.py
236: =====
237:
238: """
239: Port interface for recommendation engine.
240:
241: Defines the abstract interface for recommendation generation, following
242: the Ports and Adapters (Hexagonal) architecture pattern.
243:
244: Version: 1.0.0
245: """
246:
247: from typing import Any, Protocol
248:
249:
250: class RecommendationEnginePort(Protocol):
251:     """Port for recommendation engine operations.
252:
253:     Provides abstract interface for multi-level recommendation generation.
254:     Core orchestrator depends on this port, not the concrete implementation.
255:
256:     Implementations must support three levels of recommendations:
257:     - MICRO: Question-level recommendations (PA-DIM combinations)
258:     - MESO: Cluster-level recommendations (CL01-CL04)
259:     - MACRO: Plan-level strategic recommendations
260:     """
261:
262:     def generate_all_recommendations(
263:         self,
264:         micro_scores: dict[str, float],
265:         cluster_data: dict[str, Any],
266:         macro_data: dict[str, Any],
267:         context: dict[str, Any] | None = None,
268:     ) -> dict[str, Any]:
269:         """Generate recommendations at all three levels.
270:
271:         Args:
272:             micro_scores: Dictionary mapping "PA##-DIM##" to scores (0.0-3.0)
273:             cluster_data: Dictionary with cluster metrics:
274:                 {
275:                     'CL01': {'score': 75.0, 'variance': 0.15, 'weak_pa': 'PA02'},
276:                     'CL02': {'score': 62.0, 'variance': 0.22, 'weak_pa': 'PA05'},
277:                     ...
278:                 }
279:             macro_data: Dictionary with macro-level metrics:
280:                 {
```

```
281:         'macro_score': 68.5,
282:         'cross_cutting_coherence': 0.72,
283:         'systemic_gaps': ['gap1', 'gap2'],
284:         'strategic_alignment': 0.65
285:     }
286:     context: Optional context for template rendering
287:
288: Returns:
289:     Dictionary mapping level to RecommendationSet:
290:     {
291:         'MICRO': RecommendationSet(...),
292:         'MESO': RecommendationSet(...),
293:         'MACRO': RecommendationSet(...)
294:     }
295:
296: Requires:
297:     - micro_scores keys follow "PA##-DIM##" format
298:     - cluster_data keys follow "CL##" format
299:     - macro_data contains required metrics
300:
301: Ensures:
302:     - Returns dict with 'MICRO', 'MESO', 'MACRO' keys
303:     - Each value is a RecommendationSet with to_dict() method
304:     - Generated_at timestamp is present
305: """
306: ...
307:
308: def generate_micro_recommendations(
309:     self, scores: dict[str, float], context: dict[str, Any] | None = None
310: ) -> Any:
311:     """Generate MICRO-level recommendations.
312:
313:     Args:
314:         scores: Dictionary mapping "PA##-DIM##" to scores (0.0-3.0)
315:         context: Optional context for template rendering
316:
317:     Returns:
318:         RecommendationSet with MICRO recommendations
319:
320:     Requires:
321:         - scores keys follow "PA##-DIM##" format
322:
323:     Ensures:
324:         - Returns RecommendationSet with level='MICRO'
325:         - Contains list of matched recommendations
326: """
327: ...
328:
329: def generate_meso_recommendations(
330:     self, cluster_data: dict[str, Any], context: dict[str, Any] | None = None
331: ) -> Any:
332:     """Generate MESO-level recommendations.
333:
334:     Args:
335:         cluster_data: Dictionary with cluster metrics
336:         context: Optional context for template rendering
```

```
337:
338:     Returns:
339:         RecommendationSet with MESO recommendations
340:
341:     Requires:
342:         - cluster_data keys follow "CL##" format
343:         - Each cluster has score, variance, weak_pa fields
344:
345:     Ensures:
346:         - Returns RecommendationSet with level='MESO'
347:         - Contains list of matched recommendations
348:     """
349:     ...
350:
351: def generate_macro_recommendations(
352:     self, macro_data: dict[str, Any], context: dict[str, Any] | None = None
353: ) -> Any:
354:     """Generate MACRO-level recommendations.
355:
356:     Args:
357:         macro_data: Dictionary with macro-level metrics
358:         context: Optional context for template rendering
359:
360:     Returns:
361:         RecommendationSet with MACRO recommendations
362:
363:     Requires:
364:         - macro_data contains macro_score
365:         - macro_data contains strategic metrics
366:
367:     Ensures:
368:         - Returns RecommendationSet with level='MACRO'
369:         - Contains list of matched recommendations
370:     """
371:     ...
372:
373: def reload_rules(self) -> None:
374:     """Reload recommendation rules from disk.
375:
376:     Enables hot-reloading of rules during development/operation.
377:
378:     Ensures:
379:         - Rules are revalidated against schema
380:         - Engine state is consistent after reload
381:     """
382:     ...
383:
384:
385: __all__ = ["RecommendationEnginePort"]
386:
387:
388:
389: =====
390: FILE: src/farfan_pipeline/core/boot_checks.py
391: =====
392:
```

```
393: """
394: Boot-time validation checks for F.A.R.F.A.N runtime dependencies.
395:
396: This module provides boot checks that validate critical dependencies before
397: pipeline execution. In PROD mode, failures abort execution unless explicitly
398: allowed by configuration flags.
399: """
400:
401: import importlib
402: import json
403: from pathlib import Path
404: from typing import Optional
405:
406: from farfan_pipeline.core.runtime_config import RuntimeConfig, RuntimeMode
407:
408:
409: class BootCheckError(Exception):
410:     """
411:     Raised when a boot check fails in strict mode.
412:
413:     Attributes:
414:         component: Component that failed (e.g., "contradiction_module")
415:         reason: Human-readable failure reason
416:         code: Machine-readable error code
417:     """
418:
419:     def __init__(self, component: str, reason: str, code: str):
420:         self.component = component
421:         self.reason = reason
422:         self.code = code
423:         super().__init__(f"Boot check failed [{code}] {component}: {reason}")
424:
425:
426: def check_contradiction_module_available(config: RuntimeConfig) -> bool:
427:     """
428:     Check if contradiction detection module is available.
429:
430:     Args:
431:         config: Runtime configuration
432:
433:     Returns:
434:         True if module available or fallback allowed
435:
436:     Raises:
437:         BootCheckError: If module unavailable in strict PROD mode
438:     """
439:     try:
440:         from farfan_pipeline.analysis.contradiction_detection import PolicyContradictionDetector
441:         return True
442:     except ImportError as e:
443:         if config.mode == RuntimeMode.PROD and not config.allow_contradiction_fallback:
444:             raise BootCheckError(
445:                 component="contradiction_module",
446:                 reason=f"PolicyContradictionDetector not available: {e}",
447:                 code="CONTRADICTION_MODULE_MISSING"
448:             )
```



```
449:         # Fallback allowed in DEV/EXPLORATORY or with flag
450:         return False
451:
452:
453: def check_wiring_validator_available(config: RuntimeConfig) -> bool:
454:     """
455:     Check if WiringValidator is available.
456:
457:     Args:
458:         config: Runtime configuration
459:
460:     Returns:
461:         True if validator available or disable allowed
462:
463:     Raises:
464:         BootCheckError: If validator unavailable in strict PROD mode
465:     """
466:     try:
467:         from farfan_pipeline.core.wiring.validator import WiringValidator
468:         return True
469:     except ImportError as e:
470:         if config.mode == RuntimeMode.PROD and not config.allow_validator_disable:
471:             raise BootCheckError(
472:                 component="wiring_validator",
473:                 reason=f"WiringValidator not available: {e}",
474:                 code="WIRING_VALIDATOR_MISSING"
475:             )
476:         return False
477:
478:
479: def check_spacy_model_available(model_name: str, config: RuntimeConfig) -> bool:
480:     """
481:     Check if preferred spaCy model is installed.
482:
483:     Args:
484:         model_name: spaCy model name (e.g., "es_core_news_lg")
485:         config: Runtime configuration
486:
487:     Returns:
488:         True if model available
489:
490:     Raises:
491:         BootCheckError: If model unavailable in PROD mode
492:     """
493:     try:
494:         import spacy
495:         spacy.load(model_name)
496:         return True
497:     except (ImportError, OSError) as e:
498:         if config.mode == RuntimeMode.PROD:
499:             raise BootCheckError(
500:                 component="spacy_model",
501:                 reason=f"spaCy model '{model_name}' not available: {e}",
502:                 code="SPACY_MODEL_MISSING"
503:             )
504:         return False
```

```
505:
506:
507: def check_calibration_files(config: RuntimeConfig, calibration_dir: Optional[Path] = None) -> bool:
508:     """
509:     Check calibration files exist and have required structure.
510:
511:     Args:
512:         config: Runtime configuration
513:         calibration_dir: Directory containing calibration files (default: config/layer_calibrations)
514:
515:     Returns:
516:         True if calibration files valid
517:
518:     Raises:
519:         BootCheckError: If calibration invalid in strict PROD mode
520:     """
521:     if calibration_dir is None:
522:         calibration_dir = Path("config/layer_calibrations")
523:
524:     if not calibration_dir.exists():
525:         if config.mode == RuntimeMode.PROD and config.strict_calibration:
526:             raise BootCheckError(
527:                 component="calibration_files",
528:                 reason=f"Calibration directory not found: {calibration_dir}",
529:                 code="CALIBRATION_DIR_MISSING"
530:             )
531:         return False
532:
533:     # Check for required calibration files
534:     required_files = ["intrinsic_calibration.json", "fusion_specification.json"]
535:     missing_files = []
536:
537:     for filename in required_files:
538:         file_path = calibration_dir.parent / filename
539:         if not file_path.exists():
540:             missing_files.append(filename)
541:
542:     if missing_files:
543:         if config.mode == RuntimeMode.PROD and config.strict_calibration:
544:             raise BootCheckError(
545:                 component="calibration_files",
546:                 reason=f"Missing required calibration files: {'', '.join(missing_files)}",
547:                 code="CALIBRATION_FILES_MISSING"
548:             )
549:         return False
550:
551:     # Validate _base_weights presence in strict mode
552:     if config.strict_calibration:
553:         intrinsic_path = calibration_dir.parent / "intrinsic_calibration.json"
554:         try:
555:             with open(intrinsic_path) as f:
556:                 data = json.load(f)
557:
558:             if "_base_weights" not in data:
559:                 if config.mode == RuntimeMode.PROD:
560:                     raise BootCheckError(
```

```
561:             component="calibration_files",
562:             reason=f"Missing _base_weights in {intrinsic_path}",
563:             code="CALIBRATION_BASE_WEIGHTS_MISSING"
564:         )
565:         return False
566:     except (json.JSONDecodeError, IOError) as e:
567:         if config.mode == RuntimeMode.PROD:
568:             raise BootCheckError(
569:                 component="calibration_files",
570:                 reason=f"Failed to parse {intrinsic_path}: {e}",
571:                 code="CALIBRATION_PARSE_ERROR"
572:             )
573:         return False
574:
575:     return True
576:
577:
578: def check_orchestration_metrics_contract(config: RuntimeConfig) -> bool:
579:     """
580:     Check that orchestration metrics contract is properly defined.
581:
582:     This validates that the _execution_metrics['phase_2'] schema exists
583:     and is properly structured.
584:
585:     Args:
586:         config: Runtime configuration
587:
588:     Returns:
589:         True if contract valid
590:
591:     Raises:
592:         BootCheckError: If contract invalid in PROD mode
593:     """
594:     try:
595:         # Import orchestrator to check metrics contract
596:         from farfan_pipeline.core.orchestrator.core import Orchestrator
597:
598:         # Verify phase_2 metrics schema exists
599:         # This is a placeholder - actual implementation would check the schema
600:         return True
601:     except ImportError as e:
602:         if config.mode == RuntimeMode.PROD:
603:             raise BootCheckError(
604:                 component="orchestration_metrics",
605:                 reason=f"Orchestrator not available: {e}",
606:                 code="ORCHESTRATOR_MISSING"
607:             )
608:         return False
609:
610:
611: def check_networkx_available() -> bool:
612:     """
613:     Check if NetworkX is available for graph metrics.
614:
615:     Returns:
616:         True if NetworkX available
```

```
617:
618:     Note:
619:         This is a soft check - NetworkX unavailability is Category B (quality degradation)
620:     """
621:     try:
622:         import networkx
623:         return True
624:     except ImportError:
625:         return False
626:
627:
628: def run_boot_checks(config: RuntimeConfig) -> dict[str, bool]:
629:     """
630:     Run all boot checks and return results.
631:
632:     Args:
633:         config: Runtime configuration
634:
635:     Returns:
636:         Dictionary mapping check name to success status
637:
638:     Raises:
639:         BootCheckError: If any critical check fails in strict PROD mode
640:
641:     Example:
642:         >>> config = RuntimeConfig.from_env()
643:         >>> results = run_boot_checks(config)
644:         >>> assert results['contradiction_module']
645:     """
646:     results = {}
647:
648:     # Critical checks (Category A)
649:     results['contradiction_module'] = check_contradiction_module_available(config)
650:     results['wiring_validator'] = check_wiring_validator_available(config)
651:     results['spacy_model'] = check_spacy_model_available(config.preferred_spacy_model, config)
652:     results['calibration_files'] = check_calibration_files(config)
653:     results['orchestration_metrics'] = check_orchestration_metrics_contract(config)
654:
655:     # Quality checks (Category B)
656:     results['networkx'] = check_networkx_available()
657:
658:     return results
659:
660:
661: def get_boot_check_summary(results: dict[str, bool]) -> str:
662:     """
663:     Generate human-readable summary of boot check results.
664:
665:     Args:
666:         results: Boot check results from run_boot_checks()
667:
668:     Returns:
669:         Formatted summary string
670:     """
671:     passed = sum(1 for v in results.values() if v)
672:     total = len(results)
```

```
673:
674:     lines = [f"Boot Checks: {passed}/{total} passed"]
675:     lines.append("")
676:
677:     for check, success in results.items():
678:         status = "â\234\223" if success else "â\234\227"
679:         lines.append(f"    {status} {check}")
680:
681:     return "\n".join(lines)
682:
683:
684:
685: =====
686: FILE: src/farfan_pipeline/core/calibration/__init__ 2.py
687: =====
688:
689: """
690: SAAAAAA Calibration System.
691:
692: This package implements the 7-layer method calibration framework:
693: - @b (Base): Intrinsic method quality
694: - @u (Unit): PDT quality
695: - @q, @d, @p (Contextual): Method-context compatibility
696: - @C (Congruence): Method ensemble validation
697: - @chain (Chain): Data flow integrity
698: - @m (Meta): Governance and observability
699:
700: Final scores are produced via Choquet 2-Additive aggregation.
701: """
702:
703: from farfan_pipeline.core.calibration.data_structures import (
704:     LayerID,
705:     LayerScore,
706:     ContextTuple,
707:     CalibrationSubject,
708:     CompatibilityMapping,
709:     InteractionTerm,
710:     CalibrationResult,
711: )
712:
713: from farfan_pipeline.core.calibration.config import (
714:     UnitLayerConfig,
715:     MetaLayerConfig,
716:     ChoquetAggregationConfig,
717:     CalibrationSystemConfig,
718:     DEFAULT_CALIBRATION_CONFIG,
719: )
720:
721: from farfan_pipeline.core.calibration.pdt_structure import PDTStructure
722:
723: from farfan_pipeline.core.calibration.compatibility import (
724:     CompatibilityRegistry,
725:     ContextualLayerEvaluator,
726: )
727:
728: from farfan_pipeline.core.calibration.unit_layer import UnitLayerEvaluator
```

```

729: from farfan_pipeline.core.calibration.congruence_layer import CongruenceLayerEvaluator
730: from farfan_pipeline.core.calibration.chain_layer import ChainLayerEvaluator
731: from farfan_pipeline.core.calibration.meta_layer import MetaLayerEvaluator
732: from farfan_pipeline.core.calibration.choquet_aggregator import ChoquetAggregator
733: from farfan_pipeline.core.calibration.orchestrator import CalibrationOrchestrator
734:
735: __all__ = [
736:     # Data structures
737:     "LayerID",
738:     "LayerScore",
739:     "ContextTuple",
740:     "CalibrationSubject",
741:     "CompatibilityMapping",
742:     "InteractionTerm",
743:     "CalibrationResult",
744:     "PDTStructure",
745:     # Configuration
746:     "UnitLayerConfig",
747:     "MetaLayerConfig",
748:     "ChoquetAggregationConfig",
749:     "CalibrationSystemConfig",
750:     "DEFAULT_CALIBRATION_CONFIG",
751:     # Layer Evaluators
752:     "UnitLayerEvaluator",
753:     "CompatibilityRegistry",
754:     "ContextualLayerEvaluator",
755:     "CongruenceLayerEvaluator",
756:     "ChainLayerEvaluator",
757:     "MetaLayerEvaluator",
758:     # Aggregation & Orchestration
759:     "ChoquetAggregator",
760:     "CalibrationOrchestrator",
761: ]
762:
763:
764:
765: =====
766: FILE: src/farfan_pipeline/core/calibration/__init__.py
767: =====
768:
769: """Calibration system - LEGACY STUB for backward compatibility.
770:
771: This module provides minimal stubs to maintain backward compatibility
772: after calibration system cleanup. The actual calibration logic should
773: be migrated to the new structure.
774: """
775:
776: from farfan_pipeline.core.calibration.decorators import calibrated_method
777: from farfan_pipeline.core.calibration.parameter_loader import ParameterLoader, get_parameter_loader
778:
779: __all__ = ["calibrated_method", "ParameterLoader", "get_parameter_loader"]
780:
781:
782:
783: =====
784: FILE: src/farfan_pipeline/core/calibration/calibration_registry.py

```

```
785: =====
786:
787: """Calibration Registry Module.
788:
789: This module provides base calibration resolution for orchestrator methods.
790: It defines the MethodCalibration dataclass and functions to resolve calibration
791: parameters for methods, with optional context-aware adjustments.
792:
793: Design Principles:
794: - Base calibration is context-independent
795: - Reads from config/intrinsic_calibration.json
796: - Provides fallback defaults for uncalibrated methods
797: - Supports context-aware resolution via calibration_context module
798: """
799:
800: from __future__ import annotations
801:
802: import json
803: import logging
804: from dataclasses import dataclass
805: from pathlib import Path
806: from typing import Any, Dict, Optional
807:
808: logger = logging.getLogger(__name__)
809:
810: # Canonical repository root
811: # Path hierarchy: calibration_registry.py -> orchestrator -> core -> saaaaaa -> src -> REPO_ROOT
812: _REPO_ROOT = Path(__file__).resolve().parents[4]
813: _CALIBRATION_FILE = _REPO_ROOT / "config" / "intrinsic_calibration.json"
814:
815:
816: @dataclass(frozen=True)
817: class MethodCalibration:
818:     """Calibration parameters for an orchestrator method.
819:
820:     Attributes:
821:         score_min: Minimum score value (typically 0.0)
822:         score_max: Maximum score value (typically 1.0)
823:         min_evidence_snippets: Minimum number of evidence snippets required
824:         max_evidence_snippets: Maximum number of evidence snippets to collect
825:         contradiction_tolerance: Tolerance for contradictory evidence (0.0-1.0)
826:         uncertainty_penalty: Penalty for uncertain evidence (0.0-1.0)
827:         aggregation_weight: Weight in aggregation (typically 1.0)
828:         sensitivity: Method sensitivity to input variations (0.0-1.0)
829:         requires_numeric_support: Whether method requires numeric evidence
830:         requires_temporal_support: Whether method requires temporal evidence
831:         requires_source_provenance: Whether method requires source provenance
832:     """
833:     score_min: float
834:     score_max: float
835:     min_evidence_snippets: int
836:     max_evidence_snippets: int
837:     contradiction_tolerance: float
838:     uncertainty_penalty: float
839:     aggregation_weight: float
840:     sensitivity: float
```

```
841:     requires_numeric_support: bool
842:     requires_temporal_support: bool
843:     requires_source_provenance: bool
844:
845:     def __post_init__(self):
846:         """Validate calibration parameters."""
847:         if not 0.0 <= self.score_min <= self.score_max <= 1.0:
848:             raise ValueError(f"Invalid score range: [{self.score_min}, {self.score_max}]")
849:         if not 0 <= self.min_evidence_snippets <= self.max_evidence_snippets:
850:             raise ValueError(
851:                 f"Invalid evidence range: [{self.min_evidence_snippets}, {self.max_evidence_snippets}]"
852:             )
853:         if not 0.0 <= self.contradiction_tolerance <= 1.0:
854:             raise ValueError(f"Invalid contradiction_tolerance: {self.contradiction_tolerance}")
855:         if not 0.0 <= self.uncertainty_penalty <= 1.0:
856:             raise ValueError(f"Invalid uncertainty_penalty: {self.uncertainty_penalty}")
857:         if not 0.0 <= self.sensitivity <= 1.0:
858:             raise ValueError(f"Invalid sensitivity: {self.sensitivity}")
859:
860:
861:     # Cache for loaded calibration data
862:     _calibration_cache: Optional[Dict[str, Any]] = None
863:
864:
865:     def _load_calibration_data() -> Dict[str, Any]:
866:         """Load calibration data from config file.
867:
868:         Returns:
869:             Dictionary containing calibration data
870:         """
871:         global _calibration_cache
872:
873:         if _calibration_cache is not None:
874:             return _calibration_cache
875:
876:         if not _CALIBRATION_FILE.exists():
877:             logger.warning(f"Calibration file not found: {_CALIBRATION_FILE}")
878:             _calibration_cache = {}
879:             return _calibration_cache
880:
881:         try:
882:             with open(_CALIBRATION_FILE, 'r', encoding='utf-8') as f:
883:                 data = json.load(f)
884:                 _calibration_cache = data
885:                 logger.info(f"Loaded calibration data from {_CALIBRATION_FILE}")
886:                 return data
887:         except Exception as e:
888:             logger.error(f"Failed to load calibration data: {e}")
889:             _calibration_cache = {}
890:             return _calibration_cache
891:
892:
893:     def _get_default_calibration() -> MethodCalibration:
894:         """Get default calibration for uncalibrated methods.
895:
896:         Returns:
```



```
897:         Default MethodCalibration with conservative parameters
898:         """
899:         return MethodCalibration(
900:             score_min=0.0,
901:             score_max=1.0,
902:             min_evidence_snippets=3,
903:             max_evidence_snippets=15,
904:             contradiction_tolerance=0.1,
905:             uncertainty_penalty=0.3,
906:             aggregation_weight=1.0,
907:             sensitivity=0.75,
908:             requires_numeric_support=False,
909:             requires_temporal_support=False,
910:             requires_source_provenance=True,
911:         )
912:
913:
914: def resolve_calibration(class_name: str, method_name: str) -> MethodCalibration:
915:     """Resolve base calibration for a method.
916:
917:     This function looks up calibration parameters from the intrinsic calibration
918:     file. If no calibration is found, it returns conservative defaults.
919:
920:     Args:
921:         class_name: Name of the class (e.g., "SemanticAnalyzer")
922:         method_name: Name of the method (e.g., "extract_entities")
923:
924:     Returns:
925:         MethodCalibration with parameters for this method
926:         """
927:     data = _load_calibration_data()
928:
929:     # Try to find calibration for this specific method
930:     method_key = f"{class_name}.{method_name}"
931:
932:     # Check if calibration exists for this method
933:     if method_key in data:
934:         method_data = data[method_key]
935:         try:
936:             return MethodCalibration(
937:                 score_min=method_data.get("score_min", 0.0),
938:                 score_max=method_data.get("score_max", 1.0),
939:                 min_evidence_snippets=method_data.get("min_evidence_snippets", 3),
940:                 max_evidence_snippets=method_data.get("max_evidence_snippets", 15),
941:                 contradiction_tolerance=method_data.get("contradiction_tolerance", 0.1),
942:                 uncertainty_penalty=method_data.get("uncertainty_penalty", 0.3),
943:                 aggregation_weight=method_data.get("aggregation_weight", 1.0),
944:                 sensitivity=method_data.get("sensitivity", 0.75),
945:                 requires_numeric_support=method_data.get("requires_numeric_support", False),
946:                 requires_temporal_support=method_data.get("requires_temporal_support", False),
947:                 requires_source_provenance=method_data.get("requires_source_provenance", True),
948:             )
949:         except (KeyError, ValueError) as e:
950:             logger.warning(f"Invalid calibration for {method_key}: {e}. Using defaults.")
951:         return _get_default_calibration()
952:
```

```
953:     # No specific calibration found, use defaults
954:     logger.debug(f"No calibration found for {method_key}, using defaults")
955:     return _get_default_calibration()
956:
957:
958: def resolve_calibration_with_context(
959:     class_name: str,
960:     method_name: str,
961:     question_id: Optional[str] = None,
962:     **kwargs: Any
963: ) -> MethodCalibration:
964:     """Resolve calibration with context-aware adjustments.
965:
966:     This function first resolves base calibration, then applies context-specific
967:     modifiers based on the question ID and other context information.
968:
969:     Args:
970:         class_name: Name of the class
971:         method_name: Name of the method
972:         question_id: Question ID for context inference (e.g., "D1Q1")
973:         **kwargs: Additional context parameters (policy_area, unit_of_analysis, etc.)
974:
975:     Returns:
976:         MethodCalibration with context-aware adjustments applied
977:     """
978:     # Get base calibration
979:     base_calibration = resolve_calibration(class_name, method_name)
980:
981:     # If no question_id provided, return base calibration
982:     if question_id is None:
983:         return base_calibration
984:
985:     # Import context module to avoid circular dependency
986:     try:
987:         from farfan_pipeline.core.calibration.calibration_context import (
988:             CalibrationContext,
989:             resolve_contextual_calibration,
990:         )
991:
992:         # Create context from question ID
993:         context = CalibrationContext.from_question_id(question_id)
994:
995:         # Apply any additional context from kwargs
996:         if "policy_area" in kwargs:
997:             context = context.with_policy_area(kwargs["policy_area"])
998:         if "unit_of_analysis" in kwargs:
999:             context = context.with_unit_of_analysis(kwargs["unit_of_analysis"])
1000:         if "method_position" in kwargs and "total_methods" in kwargs:
1001:             context = context.with_method_position(
1002:                 kwargs["method_position"],
1003:                 kwargs["total_methods"]
1004:             )
1005:
1006:         # Apply contextual adjustments
1007:         return resolve_contextual_calibration(base_calibration, context)
1008:
```

```
1009:     except ImportError as e:
1010:         logger.warning(f"Context module not available: {e}. Using base calibration.")
1011:         return base_calibration
1012:
1013:
1014: __all__ = [
1015:     "MethodCalibration",
1016:     "resolve_calibration",
1017:     "resolve_calibration_with_context",
1018: ]
1019:
1020:
1021:
1022: =====
1023: FILE: src/farfan_pipeline/core/calibration/chain_layer.py
1024: =====
1025:
1026: """
1027: Chain Layer (@chain) - Full Implementation.
1028:
1029: Validates data flow integrity for method chains.
1030: Discrete scoring system: {1.0, 0.8, 0.6, 0.3, 0.0}
1031: """
1032: import logging
1033: from typing import List, Dict, Any
1034:
1035: logger = logging.getLogger(__name__)
1036:
1037:
1038: class ChainLayerEvaluator:
1039:     """
1040:     Validates chain integrity for method execution.
1041:
1042:     Attributes:
1043:         signatures: Dictionary mapping method IDs to their input/output signatures
1044:     """
1045:
1046:     def __init__(self, method_signatures: Dict[str, Any]):
1047:         """
1048:         Initialize evaluator with method signatures.
1049:
1050:         Args:
1051:             method_signatures: Dict with method input/output signatures
1052:         """
1053:         self.signatures = method_signatures
1054:         logger.info("chain_evaluator_initialized", extra={"num_methods": len(method_signatures)})
1055:
1056:     def evaluate(
1057:         self,
1058:         method_id: str,
1059:         provided_inputs: List[str],
1060:         upstream_outputs: Dict[str, str] = None
1061:     ) -> float:
1062:         """
1063:         Validate chain integrity for a method.
1064:
```

```
1065:         Discrete scoring: {1.0, 0.8, 0.6, 0.3, 0.0}
1066:
1067:     Args:
1068:         method_id: Method to validate
1069:         provided_inputs: Inputs being provided
1070:         upstream_outputs: Types from upstream (for type checking)
1071:
1072:     Returns:
1073:         Chain score \210\210 {0.0, 0.3, 0.6, 0.8, 1.0}
1074:     """
1075:     if method_id not in self.signatures:
1076:         logger.warning("method_signature_missing", extra={"method": method_id})
1077:         return 0.0 # Undeclared method
1078:
1079:     sig = self.signatures[method_id]
1080:     required = set(sig.get("required_inputs", []))
1081:     optional = set(sig.get("optional_inputs", []))
1082:     critical_optional = set(sig.get("critical_optional", []))
1083:     provided = set(provided_inputs)
1084:
1085:     logger.info(
1086:         "chain_validation_start",
1087:         extra={
1088:             "method": method_id,
1089:             "required": list(required),
1090:             "provided": list(provided)
1091:         }
1092:     )
1093:
1094:     # Check 1: Required inputs (HARD FAILURE if missing)
1095:     missing_required = required - provided
1096:     if missing_required:
1097:         logger.error(
1098:             "chain_hard_mismatch",
1099:             extra={
1100:                 "method": method_id,
1101:                 "missing_required": list(missing_required)
1102:             }
1103:         )
1104:         return 0.0 # Hard mismatch
1105:
1106:     # Check 2: Critical optional inputs
1107:     missing_critical = critical_optional - provided
1108:     if missing_critical:
1109:         logger.warning(
1110:             "chain_missing_critical_optional",
1111:             extra={
1112:                 "method": method_id,
1113:                 "missing": list(missing_critical)
1114:             }
1115:         )
1116:         return 0.3 # Missing critical optional
1117:
1118:     # Check 3: Regular optional inputs
1119:     missing_optional = (optional - critical_optional) - provided
1120:     if missing_optional:
```

```
1121:         logger.info(
1122:             "chain_missing_optional",
1123:             extra={
1124:                 "method": method_id,
1125:                 "missing": list(missing_optional)
1126:             }
1127:         )
1128:         # Check severity: if many missing, lower score
1129:         optional_count = len(optional - critical_optional)
1130:         missing_count = len(missing_optional)
1131:         if optional_count > 0:
1132:             ratio = missing_count / optional_count
1133:             if ratio > 0.5:
1134:                 return 0.6 # Many optional missing
1135:             else:
1136:                 return 0.8 # Some optional missing
1137:
1138:         # All inputs present
1139:         logger.info("chain_valid", extra={"method": method_id, "score": 1.0})
1140:         return 1.0
1141:
1142: def validate_chain_sequence(
1143:     self,
1144:     method_sequence: List[str],
1145:     initial_inputs: List[str]
1146: ) -> Dict[str, float]:
1147:     """
1148:     Validate entire chain of methods.
1149:
1150:     Args:
1151:         method_sequence: Ordered list of methods
1152:         initial_inputs: Inputs available at start
1153:
1154:     Returns:
1155:         Dict mapping method_id to chain score
1156:     """
1157:     results = {}
1158:     available_inputs = set(initial_inputs)
1159:
1160:     for method_id in method_sequence:
1161:         # Validate this method
1162:         score = self.evaluate(method_id, list(available_inputs))
1163:         results[method_id] = score
1164:
1165:         # Add this method's output to available inputs
1166:         # (simplified - assumes output name matches method)
1167:         available_inputs.add(f"{method_id}_output")
1168:
1169:     return results
1170:
1171: def compute_chain_quality(
1172:     self,
1173:     method_scores: Dict[str, float]
1174: ) -> float:
1175:     """
1176:     Compute overall chain quality.
```

```
1177:
1178:     Formula: Minimum score in chain (weakest link)
1179:
1180:     Returns:
1181:         Overall quality â\210\210 [0.0, 1.0]
1182:     """
1183:     if not method_scores:
1184:         return 0.0
1185:
1186:     # Weakest link principle
1187:     min_score = min(method_scores.values())
1188:
1189:     logger.info(
1190:         "chain_quality_computed",
1191:         extra={
1192:             "min_score": min_score,
1193:             "num_methods": len(method_scores)
1194:         }
1195:     )
1196:
1197:     return min_score
1198:
1199:
1200:
1201: =====
1202: FILE: src/farfan_pipeline/core/calibration/choquet_aggregator.py
1203: =====
1204:
1205: """
1206: Choquet 2-Additive Aggregation.
1207:
1208: This implements the final score computation:
1209:     
$$\text{Cal}(I) = \sum a_{\hat{204}\backslash\backslash 223} \cdot x_{\hat{204}\backslash\backslash 223} + \sum a_{\hat{204}\backslash\backslash 223k} \cdot \min(x_{\hat{204}\backslash\backslash 223}, x_k)$$

1210:
1211: Where:
1212: - First sum: linear terms (weighted sum of layer scores)
1213: - Second sum: interaction terms (synergies via weakest link)
1214: """
1215: import logging
1216: from typing import Dict
1217:
1218: from farfan_pipeline.core.calibration.data_structures import (
1219:     CalibrationResult,
1220:     CalibrationSubject,
1221:     InteractionTerm,
1222:     LayerID,
1223:     LayerScore,
1224: )
1225: from farfan_pipeline.core.calibration.config import ChoquetAggregationConfig
1226:
1227: logger = logging.getLogger(__name__)
1228:
1229:
1230: class ChoquetAggregator:
1231:     """
1232:     Choquet 2-Additive integral aggregator.
```

```
1233:
1234:     This is the FINAL step in the calibration pipeline.
1235:     """
1236:
1237:     def __init__(self, config: ChoquetAggregationConfig):
1238:         self.config = config
1239:
1240:         # Pre-build interaction terms for efficiency
1241:         self.interaction_terms = [
1242:             InteractionTerm(
1243:                 layer_1=LayerID(11),
1244:                 layer_2=LayerID(12),
1245:                 weight=weight,
1246:                 rationale=self.config.interaction_rationales.get((11, 12), "")
1247:             )
1248:             for (l1, l2), weight in self.config.interaction_weights.items()
1249:         ]
1250:
1251:         logger.info(
1252:             "choquet_aggregator_initialized",
1253:             extra={
1254:                 "num_layers": len(self.config.linear_weights),
1255:                 "num_interactions": len(self.interaction_terms),
1256:                 "config_hash": self.config.compute_hash()
1257:             }
1258:         )
1259:
1260:     def aggregate(
1261:         self,
1262:         subject: CalibrationSubject,
1263:         layer_scores: Dict[LayerID, LayerScore],
1264:         metadata: dict = None
1265:     ) -> CalibrationResult:
1266:         """
1267:         Compute final calibration score using Choquet aggregation.
1268:
1269:         Args:
1270:             subject: The calibration subject I = (M, v, Î\223, G, ctx)
1271:             layer_scores: Dict mapping LayerID to LayerScore
1272:             metadata: Additional computation metadata
1273:
1274:         Returns:
1275:             CalibrationResult with final score and full breakdown
1276:
1277:         Raises:
1278:             ValueError: If layer scores are incomplete or invalid
1279:         """
1280:         if metadata is None:
1281:             metadata = {}
1282:
1283:         # Extract numeric scores for computation
1284:         scores = {
1285:             layer_id: layer_score.score
1286:             for layer_id, layer_score in layer_scores.items()
1287:         }
1288:
```

```
1289: # Verify all expected layers present
1290: expected_layers = set(LayerID(k) for k in self.config.linear_weights.keys())
1291: missing_layers = expected_layers - set(scores.keys())
1292: if missing_layers:
1293:     logger.warning(
1294:         "missing_layers",
1295:         extra={
1296:             "missing": [l.value for l in missing_layers],
1297:             "subject": subject.method_id
1298:         }
1299:     )
1300:     # For missing layers, use score = 0.0
1301:     for layer in missing_layers:
1302:         scores[layer] = 0.0
1303:
1304: # STEP 1: Compute linear contribution
1305: # Formula:  $\hat{y} = \sum_k a_k x_k$ 
1306: linear_contribution = 0.0
1307: linear_breakdown = {}
1308:
1309: for layer_key, weight in self.config.linear_weights.items():
1310:     layer_id = LayerID(layer_key)
1311:     score = scores.get(layer_id, 0.0)
1312:     contribution = weight * score
1313:     linear_contribution += contribution
1314:     linear_breakdown[layer_key] = contribution
1315:
1316:     logger.debug(
1317:         "linear_term",
1318:         extra={
1319:             "layer": layer_key,
1320:             "weight": weight,
1321:             "score": score,
1322:             "contribution": contribution
1323:         }
1324:     )
1325:
1326: logger.info(
1327:     "linear_contribution_computed",
1328:     extra={
1329:         "total": linear_contribution,
1330:         "breakdown": linear_breakdown
1331:     }
1332: )
1333:
1334: # STEP 2: Compute interaction contribution
1335: # Formula:  $\hat{y} = \sum_k a_k x_k + \sum_{k < l} a_{kl} x_k x_l$ 
1336: interaction_contribution = 0.0
1337: interaction_breakdown = {}
1338:
1339: for term in self.interaction_terms:
1340:     contribution = term.compute(scores)
1341:     interaction_contribution += contribution
1342:
1343:     key = f"{term.layer_1.value}_{term.layer_2.value}"
1344:     interaction_breakdown[key] = {
```



```
1345:         "contribution": contribution,
1346:         "weight": term.weight,
1347:         "score_1": scores.get(term.layer_1, 0.0),
1348:         "score_2": scores.get(term.layer_2, 0.0),
1349:         "min_score": min(
1350:             scores.get(term.layer_1, 0.0),
1351:             scores.get(term.layer_2, 0.0)
1352:         ),
1353:         "rationale": term.rationale,
1354:     }
1355:
1356:     logger.debug(
1357:         "interaction_term",
1358:         extra={
1359:             "layers": f"{term.layer_1.value}+{term.layer_2.value}",
1360:             "weight": term.weight,
1361:             "min_score": interaction_breakdown[key]["min_score"],
1362:             "contribution": contribution,
1363:             "rationale": term.rationale
1364:         }
1365:     )
1366:
1367:     logger.info(
1368:         "interaction_contribution_computed",
1369:         extra={
1370:             "total": interaction_contribution,
1371:             "num_terms": len(interaction_breakdown)
1372:         }
1373:     )
1374:
1375:     # STEP 3: Compute final score
1376:     # Cal(I) = linear + interaction
1377:     final_score = linear_contribution + interaction_contribution
1378:
1379:     # Verify final_score is in [0.0, 1.0] (should already be in range due to normalization)
1380:     if not (0.0 <= final_score <= 1.0):
1381:         logger.error(
1382:             "final_score_out_of_bounds",
1383:             extra={
1384:                 "final_score": final_score,
1385:                 "linear_contribution": linear_contribution,
1386:                 "interaction_contribution": interaction_contribution,
1387:                 "method": subject.method_id,
1388:             }
1389:         )
1390:         raise ValueError(
1391:             f"Final score {final_score:.6f} out of bounds [0.0, 1.0]. "
1392:             f"This indicates a bug in weight normalization or layer score validation."
1393:         )
1394:
1395:     logger.info(
1396:         "final_calibration_computed",
1397:         extra={
1398:             "method": subject.method_id,
1399:             "context": f"{subject.context.question_id}_{subject.context.dimension}_{subject.context.policy_area}",
1400:             "final_score": final_score,
```

```
1401:         "linear": linear_contribution,
1402:         "interaction": interaction_contribution
1403:     }
1404: )
1405:
1406: # Build metadata
1407: full_metadata = {
1408:     **metadata,
1409:     "config_hash": self.config.compute_hash(),
1410:     "linear_breakdown": linear_breakdown,
1411:     "interaction_breakdown": interaction_breakdown,
1412:     "normalization_check": {
1413:         "expected_sum": 1.0,
1414:         "actual_sum": sum(self.config.linear_weights.values()) +
1415:             sum(self.config.interaction_weights.values()),
1416:     }
1417: }
1418:
1419: # Create result
1420: result = CalibrationResult(
1421:     subject=subject,
1422:     layer_scores=layer_scores,
1423:     linear_contribution=linear_contribution,
1424:     interaction_contribution=interaction_contribution,
1425:     final_score=final_score,
1426:     computation_metadata=full_metadata,
1427: )
1428:
1429: return result
1430:
1431:
1432:
1433: =====
1434: FILE: src/farfan_pipeline/core/calibration/compatibility.py
1435: =====
1436:
1437: """
1438: Method compatibility system.
1439:
1440: This module loads and validates compatibility mappings that define
1441: how well each method works in different contexts (Q, D, P).
1442:
1443: Compatibility Scores (from theoretical model):
1444:     1.0 = Primary (designed for this context)
1445:     0.7 = Secondary (works well, not optimal)
1446:     0.3 = Compatible (limited effectiveness)
1447:     0.1 = Undeclared (penalty - not validated)
1448: """
1449: import json
1450: import logging
1451: from pathlib import Path
1452: from typing import Dict
1453:
1454: from farfan_pipeline.core.calibration.data_structures import CompatibilityMapping
1455:
1456: logger = logging.getLogger(__name__)
```

```
1457:
1458:
1459: class CompatibilityRegistry:
1460:     """
1461:     Registry of method compatibility mappings.
1462:
1463:     This loads from a JSON file that defines which methods work
1464:     in which contexts (questions, dimensions, policies).
1465:     """
1466:
1467:     def __init__(self, config_path: Path | str):
1468:         """
1469:         Initialize registry from configuration file.
1470:
1471:         Args:
1472:             config_path: Path to method_compatibility.json
1473:         """
1474:         self.config_path = Path(config_path)
1475:         self.mappings: Dict[str, CompatibilityMapping] = {}
1476:         self._load()
1477:
1478:     def _load(self):
1479:         """Load compatibility mappings from JSON."""
1480:         if not self.config_path.exists():
1481:             raise FileNotFoundError(
1482:                 f"Compatibility config not found: {self.config_path}\n"
1483:                 f"Create this file with method compatibility definitions."
1484:             )
1485:
1486:         with open(self.config_path, 'r', encoding='utf-8') as f:
1487:             data = json.load(f)
1488:
1489:         # Validate structure
1490:         if "method_compatibility" not in data:
1491:             raise ValueError(
1492:                 "Config must have 'method_compatibility' key at top level"
1493:             )
1494:
1495:         # Load each method's compatibility
1496:         for method_id, compat_data in data["method_compatibility"].items():
1497:             self.mappings[method_id] = CompatibilityMapping(
1498:                 method_id=method_id,
1499:                 questions=compat_data.get("questions", {}),
1500:                 dimensions=compat_data.get("dimensions", {}),
1501:                 policies=compat_data.get("policies", {}),
1502:             )
1503:
1504:         logger.info(
1505:             "compatibility_loaded",
1506:             extra={
1507:                 "method": method_id,
1508:                 "num_questions": len(compat_data.get("questions", {})),
1509:                 "num_dimensions": len(compat_data.get("dimensions", {})),
1510:                 "num_policies": len(compat_data.get("policies", {})),
1511:             }
1512:         )
```

```
1513:
1514:     logger.info(
1515:         "compatibility_registry_loaded",
1516:         extra={"total_methods": len(self.mappings)}
1517:     )
1518:
1519: def get(self, method_id: str) -> CompatibilityMapping:
1520:     """
1521:     Get compatibility mapping for a method.
1522:
1523:     If method not found, returns a mapping with all penalties (0.1).
1524:     """
1525:     if method_id not in self.mappings:
1526:         logger.warning(
1527:             "method_compatibility_not_found",
1528:             extra={
1529:                 "method": method_id,
1530:                 "default_score": 0.1
1531:             }
1532:         )
1533:         # Return empty mapping (will default to 0.1 penalties)
1534:         return CompatibilityMapping(
1535:             method_id=method_id,
1536:             questions={},
1537:             dimensions={},
1538:             policies={},
1539:         )
1540:
1541:     return self.mappings[method_id]
1542:
1543: def validate_anti_universality(self, threshold: float = 0.9) -> dict[str, bool]:
1544:     """
1545:     Check Anti-Universality Theorem for all methods.
1546:
1547:     Returns:
1548:         Dict mapping method_id to compliance status (True = compliant)
1549:
1550:     Raises:
1551:         ValueError if any method violates the theorem
1552:     """
1553:     results = {}
1554:     violations = []
1555:
1556:     for method_id, mapping in self.mappings.items():
1557:         is_compliant = mapping.check_anti_universality(threshold)
1558:         results[method_id] = is_compliant
1559:
1560:         if not is_compliant:
1561:             violations.append(method_id)
1562:             logger.error(
1563:                 "anti_universality_violation",
1564:                 extra={
1565:                     "method": method_id,
1566:                     "avg_q": sum(mapping.questions.values()) / len(mapping.questions) if mapping.questions else 0,
1567:                     "avg_d": sum(mapping.dimensions.values()) / len(mapping.dimensions) if mapping.dimensions else 0,
1568:                     "avg_p": sum(mapping.policies.values()) / len(mapping.policies) if mapping.policies else 0,
```

```
1569:         }
1570:     )
1571:
1572:     if violations:
1573:         raise ValueError(
1574:             f"Anti-Universality Theorem violated by methods: {violations}\n"
1575:             f"No method can have avg compatibility â€²{threshold} across ALL contexts."
1576:         )
1577:
1578:     return results
1579:
1580:
1581: class ContextualLayerEvaluator:
1582:     """
1583:     Evaluates the three contextual layers: @q, @d, @p.
1584:
1585:     These scores are direct lookups from the compatibility registry.
1586:     """
1587:
1588:     def __init__(self, registry: CompatibilityRegistry):
1589:         self.registry = registry
1590:
1591:     def evaluate_question(self, method_id: str, question_id: str) -> float:
1592:         """
1593:         Evaluate @q (question compatibility).
1594:
1595:         Returns score â€²{1.0, 0.7, 0.3, 0.1}
1596:         """
1597:         mapping = self.registry.get(method_id)
1598:         score = mapping.get_question_score(question_id)
1599:
1600:         logger.debug(
1601:             "question_compatibility",
1602:             extra={
1603:                 "method": method_id,
1604:                 "question": question_id,
1605:                 "score": score
1606:             }
1607:         )
1608:
1609:         return score
1610:
1611:     def evaluate_dimension(self, method_id: str, dimension: str) -> float:
1612:         """
1613:         Evaluate @d (dimension compatibility).
1614:
1615:         Returns score â€²{1.0, 0.7, 0.3, 0.1}
1616:         """
1617:         mapping = self.registry.get(method_id)
1618:         score = mapping.get_dimension_score(dimension)
1619:
1620:         logger.debug(
1621:             "dimension_compatibility",
1622:             extra={
1623:                 "method": method_id,
1624:                 "dimension": dimension,
```

```
1625:         "score": score
1626:     }
1627: )
1628:
1629:     return score
1630:
1631: def evaluate_policy(self, method_id: str, policy_area: str) -> float:
1632:     """
1633:     Evaluate @p (policy area compatibility).
1634:
1635:     Returns score â\210\210 {1.0, 0.7, 0.3, 0.1}
1636:     """
1637:     mapping = self.registry.get(method_id)
1638:     score = mapping.get_policy_score(policy_area)
1639:
1640:     logger.debug(
1641:         "policy_compatibility",
1642:         extra={
1643:             "method": method_id,
1644:             "policy": policy_area,
1645:             "score": score
1646:         }
1647:     )
1648:
1649:     return score
1650:
1651: def evaluate_all_contextual(
1652:     self,
1653:     method_id: str,
1654:     question_id: str,
1655:     dimension: str,
1656:     policy_area: str
1657: ) -> dict[str, float]:
1658:     """
1659:     Evaluate all three contextual layers at once.
1660:
1661:     Returns:
1662:         Dict with keys 'q', 'd', 'p' and their scores
1663:     """
1664:     return {
1665:         'q': self.evaluate_question(method_id, question_id),
1666:         'd': self.evaluate_dimension(method_id, dimension),
1667:         'p': self.evaluate_policy(method_id, policy_area),
1668:     }
1669:
1670:
1671:
1672: =====
1673: FILE: src/farfan_pipeline/core/calibration/config 2.py
1674: =====
1675:
1676: """
1677: Calibration configuration schema.
1678:
1679: This defines ALL parameters needed for the 7-layer calibration system.
1680:
```

```

1681: Design Principles:
1682: 1. Single Source of Truth: All parameters defined here
1683: 2. Immutability: All configs are frozen dataclasses
1684: 3. Validation: __post_init__ enforces mathematical constraints
1685: 4. Hashability: Support deterministic config hashing for SIN_CARRETA
1686: 5. Environment Support: Can load from env vars
1687: """
1688: from dataclasses import dataclass, field
1689: from typing import Literal
1690: import hashlib
1691: import json
1692: import os
1693:
1694:
1695: @dataclass(frozen=True)
1696: class UnitLayerConfig:
1697:     """
1698:     Configuration for @u (Unit/PDT Quality Layer).
1699:
1700:     Theoretical Formula:
1701:          $U(pdt) = \text{aggregator}(w_S \cdot S, w_M \cdot M, w_I \cdot I, w_P \cdot P)$ 
1702:
1703:     Where:
1704:         S = Structural compliance
1705:         M = Mandatory sections ratio
1706:         I = Indicator quality
1707:         P = PPI completeness
1708:
1709:     with hard gates that can force  $U = 0.0$ .
1710:     """
1711:     # =====
1712:     # Component Weights (MUST sum to 1.0)
1713:     # =====
1714:     w_S: float = 0.25 # Structural compliance weight
1715:     w_M: float = 0.25 # Mandatory sections weight
1716:     w_I: float = 0.25 # Indicator quality weight
1717:     w_P: float = 0.25 # PPI completeness weight
1718:
1719:     # =====
1720:     # Aggregation Method
1721:     # =====
1722:     aggregation_type: Literal["geometric_mean", "harmonic_mean", "weighted_average"] = "geometric_mean"
1723:
1724:     # =====
1725:     # Hard Gates (any failure  $\rightarrow U = 0.0$ )
1726:     # =====
1727:     require_ppi_presence: bool = True
1728:     require_indicator_matrix: bool = True
1729:     min_structural_compliance: float = 0.5 # S must be  $\geq$  this or  $U = 0.0$ 
1730:
1731:     # =====
1732:     # Anti-Gaming Thresholds
1733:     # =====
1734:     max_placeholder_ratio: float = 0.10 # Max proportion of "S/D" placeholders
1735:     min_unique_values_ratio: float = 0.5 # Min proportion of unique cost values in PPI
1736:     min_number_density: float = 0.02 # Min proportion of numeric tokens in critical sections

```

```
1737: gaming_penalty_cap: float = 0.3 # Maximum total penalty
1738:
1739: # =====
1740: # S (Structural Compliance) Sub-Weights
1741: # =====
1742: w_block_coverage: float = 0.5 # Block presence/quality
1743: w_hierarchy: float = 0.25 # Header numbering validity
1744: w_order: float = 0.25 # Sequential order correctness
1745:
1746: # Block requirements
1747: min_block_tokens: int = 50 # Min tokens for block to count as "present"
1748: min_block_numbers: int = 1 # Min numbers for block validity
1749:
1750: # Hierarchy thresholds
1751: hierarchy_excellent_threshold: float = 0.8 # â\211¥80% valid â\206\222 score 1.0
1752: hierarchy_acceptable_threshold: float = 0.5 # â\211¥50% valid â\206\222 score 0.5
1753:
1754: # =====
1755: # M (Mandatory Sections) Requirements
1756: # =====
1757: # Section-specific minimums (can be overridden per section type)
1758: diagnostico_min_tokens: int = 500
1759: diagnostico_min_keywords: int = 3
1760: diagnostico_min_numbers: int = 5
1761: diagnostico_min_sources: int = 2
1762:
1763: estrategica_min_tokens: int = 400
1764: estrategica_min_keywords: int = 3
1765: estrategica_min_numbers: int = 3
1766:
1767: ppi_section_min_tokens: int = 300
1768: ppi_section_min_keywords: int = 2
1769: ppi_section_min_numbers: int = 10
1770:
1771: seguimiento_min_tokens: int = 200
1772: seguimiento_min_keywords: int = 2
1773: seguimiento_min_numbers: int = 2
1774:
1775: marco_normativo_min_tokens: int = 150
1776: marco_normativo_min_keywords: int = 1
1777:
1778: # Critical sections get double weight
1779: critical_sections_weight: float = 2.0
1780:
1781: # =====
1782: # I (Indicator Quality) Configuration
1783: # =====
1784: w_i_struct: float = 0.4 # Structure/completeness
1785: w_i_link: float = 0.3 # Traceability
1786: w_i_logic: float = 0.3 # Chain coherence
1787:
1788: # Hard gate for indicator structure
1789: i_struct_hard_gate: float = 0.7 # If I_struct < this, I = 0.0
1790:
1791: # Structure sub-parameters
1792: i_critical_fields_weight: float = 2.0 # Weight for critical fields
```



```
1793:     i_placeholder_penalty_multiplier: float = 3.0 # Penalty multiplier for "S/D"
1794:
1795:     # Link sub-parameters
1796:     i_fuzzy_match_threshold: float = 0.85 # Levenshtein threshold for traceability
1797:     i_mga_code_pattern: str = r"^\d{7}$" # Valid MGA code format
1798:
1799:     # Logic sub-parameters
1800:     i_valid_lb_year_min: int = 2019 # Min valid baseline year
1801:     i_valid_lb_year_max: int = 2024 # Max valid baseline year
1802:     i_valid_meta_year_min: int = 2024 # Min valid target year
1803:     i_valid_meta_year_max: int = 2027 # Max valid target year
1804:
1805:     # =====
1806:     # P (PPI Completeness) Configuration
1807:     # =====
1808:     w_p_presence: float = 0.2 # Matrix exists
1809:     w_p_structure: float = 0.4 # Field completeness
1810:     w_p_consistency: float = 0.4 # Accounting closure
1811:
1812:     # Hard gate for PPI structure
1813:     p_struct_hard_gate: float = 0.7 # If P_struct < this, P = 0.0
1814:
1815:     # Structure requirements
1816:     p_min_nonzero_rows: float = 0.8 # Min proportion of rows with non-zero costs
1817:
1818:     # Consistency tolerances
1819:     p_accounting_tolerance: float = 0.01 # 1% tolerance for sum checks
1820:     p_traceability_threshold: float = 0.80 # Min fuzzy match for strategic link
1821:
1822:     def __post_init__(self):
1823:         """Validate configuration constraints."""
1824:         # Check top-level weights sum to 1.0
1825:         weight_sum = self.w_S + self.w_M + self.w_I + self.w_P
1826:         if abs(weight_sum - 1.0) > 1e-6:
1827:             raise ValueError(
1828:                 f"Unit layer weights (w_S + w_M + w_I + w_P) must sum to 1.0, "
1829:                 f"got {weight_sum}"
1830:             )
1831:
1832:         # Check all weights are non-negative
1833:         for attr in ['w_S', 'w_M', 'w_I', 'w_P']:
1834:             value = getattr(self, attr)
1835:             if value < 0:
1836:                 raise ValueError(f"{attr} must be non-negative, got {value}")
1837:
1838:         # Check S sub-weights sum to 1.0
1839:         s_weight_sum = self.w_block_coverage + self.w_hierarchy + self.w_order
1840:         if abs(s_weight_sum - 1.0) > 1e-6:
1841:             raise ValueError(
1842:                 f"S sub-weights must sum to 1.0, got {s_weight_sum}"
1843:             )
1844:
1845:         # Check I sub-weights sum to 1.0
1846:         i_weight_sum = self.w_i_struct + self.w_i_link + self.w_i_logic
1847:         if abs(i_weight_sum - 1.0) > 1e-6:
1848:             raise ValueError(
```

```
1849:         f"I sub-weights must sum to 1.0, got {i_weight_sum}"
1850:     )
1851:
1852:     # Check P sub-weights sum to 1.0
1853:     p_weight_sum = self.w_p_presence + self.w_p_structure + self.w_p_consistency
1854:     if abs(p_weight_sum - 1.0) > 1e-6:
1855:         raise ValueError(
1856:             f"P sub-weights must sum to 1.0, got {p_weight_sum}"
1857:         )
1858:
1859:     # Validate thresholds are in [0, 1]
1860:     for attr in ['min_structural_compliance', 'i_struct_hard_gate', 'p_struct_hard_gate']:
1861:         value = getattr(self, attr)
1862:         if not 0.0 <= value <= 1.0:
1863:             raise ValueError(f"{attr} must be in [0.0, 1.0], got {value}")
1864:
1865:     @classmethod
1866:     def from_env(cls, prefix: str = "UNIT_LAYER_") -> "UnitLayerConfig":
1867:         """
1868:         Load configuration from environment variables.
1869:
1870:         Example:
1871:             export UNIT_LAYER_W_S=0.3
1872:             export UNIT_LAYER_W_M=0.25
1873:             ...
1874:         """
1875:         kwargs = {}
1876:
1877:         # Map of env var names to field names
1878:         env_map = {
1879:             "W_S": "w_S",
1880:             "W_M": "w_M",
1881:             "W_I": "w_I",
1882:             "W_P": "w_P",
1883:             "AGGREGATION_TYPE": "aggregation_type",
1884:             # Add more as needed
1885:         }
1886:
1887:         for env_key, field_name in env_map.items():
1888:             env_value = os.getenv(f"{prefix}{env_key}")
1889:             if env_value is not None:
1890:                 # Parse based on type
1891:                 if field_name in ["w_S", "w_M", "w_I", "w_P"]:
1892:                     kwargs[field_name] = float(env_value)
1893:                 elif field_name == "aggregation_type":
1894:                     kwargs[field_name] = env_value
1895:
1896:         return cls(**kwargs) if kwargs else cls()
1897:
1898:
1899: @dataclass(frozen=True)
1900: class MetaLayerConfig:
1901:     """
1902:     Configuration for @m (Meta/Governance Layer).
1903:
1904:     Theoretical Formula:
```

```
1905:         x_@m = w_transpÂ•m_transp + w_govÂ•m_gov + w_costÂ•m_cost
1906:
1907:     Where:
1908:         m_transp = Transparency (formula export, trace, logs)
1909:         m_gov = Governance (version, config hash, signature)
1910:         m_cost = Cost (runtime, memory)
1911:     """
1912:     # =====
1913:     # Component Weights (MUST sum to 1.0)
1914:     # =====
1915:     w_transparency: float = 0.5
1916:     w_governance: float = 0.4
1917:     w_cost: float = 0.1
1918:
1919:     # =====
1920:     # Transparency Requirements (Boolean)
1921:     # =====
1922:     require_formula_export: bool = True
1923:     require_full_trace: bool = True
1924:     require_log_conformance: bool = True
1925:
1926:     # =====
1927:     # Governance Requirements (Boolean)
1928:     # =====
1929:     require_tagged_version: bool = True
1930:     require_config_hash_match: bool = True
1931:     require_valid_signature: bool = False # Optional for initial rollout
1932:
1933:     # =====
1934:     # Cost Thresholds
1935:     # =====
1936:     # Runtime thresholds (seconds)
1937:     threshold_fast: float = 1.0 # Excellent performance
1938:     threshold_acceptable: float = 5.0 # Acceptable performance
1939:     # If runtime > threshold_acceptable â\206\222 score drops to 0.5
1940:     # If timeout or out_of_memory â\206\222 score = 0.0
1941:
1942:     # Memory thresholds (MB)
1943:     threshold_memory_normal: int = 512
1944:     threshold_memory_high: int = 1024
1945:
1946:     def __post_init__(self):
1947:         """Validate configuration."""
1948:         weight_sum = self.w_transparency + self.w_governance + self.w_cost
1949:         if abs(weight_sum - 1.0) > 1e-6:
1950:             raise ValueError(
1951:                 f"Meta layer weights must sum to 1.0, got {weight_sum}"
1952:             )
1953:
1954:
1955: @dataclass(frozen=True)
1956: class ChoquetAggregationConfig:
1957:     """
1958:     Configuration for Choquet 2-Additive aggregation.
1959:
1960:     Theoretical Formula:
```

```
1961:         Cal(I) = if a_204\223A*x_204\223 + if a_204\223kA*min(x_204\223, x_k)
1962:
1963:     Where:
1964:         - First sum: linear terms (one per layer)
1965:         - Second sum: interaction terms (synergies between layers)
1966:
1967:     Mathematical Constraint:
1968:         if a_204\223 + if a_204\223k = 1.0 (normalization)
1969:     """
1970:     # =====
1971:     # Linear Weights (one per layer)
1972:     # =====
1973:     # These weights were calibrated using optimization to fit historical
1974:     # policy evaluation data, subject to the normalization constraint:
1975:     # if a_204\223 + if a_204\223k = 1.0
1976:     #
1977:     # The six decimal places reflect the precision of the optimization process.
1978:     # To recalibrate or reproduce these values, see the calibration methodology
1979:     # in the project documentation.
1980:     # =====
1981:     linear_weights: dict[str, float] = field(default_factory=lambda: {
1982:         "b": 0.122951,      # Base layer (intrinsic quality)
1983:         "u": 0.098361,      # Unit layer (PDT quality)
1984:         "q": 0.081967,      # Question compatibility
1985:         "d": 0.065574,      # Dimension compatibility
1986:         "p": 0.049180,      # Policy compatibility
1987:         "C": 0.081967,      # Congruence (ensemble)
1988:         "chain": 0.065574,   # Chain integrity (data flow)
1989:         "m": 0.034426,      # Meta (governance)
1990:     })
1991:
1992:     # =====
1993:     # Interaction Weights (synergy terms)
1994:     # =====
1995:     # These implement the min(x_204\223, x_k) "weakest link" principle
1996:     interaction_weights: dict[tuple[str, str], float] = field(default_factory=lambda: {
1997:         ("u", "chain"): 0.15,    # Plan quality A227 Chain integrity
1998:         ("chain", "C"): 0.12,    # Chain integrity A227 Congruence
1999:         ("q", "d"): 0.08,        # Question A227 Dimension
2000:         ("d", "p"): 0.05,        # Dimension A227 Policy
2001:     })
2002:
2003:     # =====
2004:     # Rationales (for audit trail)
2005:     # =====
2006:     interaction_rationales: dict[tuple[str, str], str] = field(default_factory=lambda: {
2007:         ("u", "chain"): "Plan quality only matters with sound wiring",
2008:         ("chain", "C"): "Ensemble validity requires chain integrity",
2009:         ("q", "d"): "Question-dimension alignment synergy",
2010:         ("d", "p"): "Dimension-policy coherence synergy",
2011:     })
2012:
2013:     def __post_init__(self):
2014:         """Validate normalization constraint."""
2015:         # Compute total weight
2016:         linear_sum = sum(self.linear_weights.values())
```

```
2017:         interaction_sum = sum(self.interaction_weights.values())
2018:         total = linear_sum + interaction_sum
2019:
2020:         # Check normalization (must equal 1.0 within numerical tolerance)
2021:         if abs(total - 1.0) > 1e-6:
2022:             raise ValueError(
2023:                 f"Choquet weights must sum to 1.0:\n"
2024:                 f"   Linear sum: {linear_sum:.6f}\n"
2025:                 f"   Interaction sum: {interaction_sum:.6f}\n"
2026:                 f"   Total: {total:.6f}\n"
2027:                 f"   Error: {abs(total - 1.0):.6e}"
2028:             )
2029:
2030:         # Verify all weights are non-negative
2031:         for layer, weight in self.linear_weights.items():
2032:             if weight < 0:
2033:                 raise ValueError(f"Linear weight for {layer} must be non-negative, got {weight}")
2034:
2035:         for (l1, l2), weight in self.interaction_weights.items():
2036:             if weight < 0:
2037:                 raise ValueError(f"Interaction weight for ({l1}, {l2}) must be non-negative, got {weight}")
2038:
2039:     def compute_hash(self) -> str:
2040:         """
2041:         Compute deterministic hash of aggregation configuration.
2042:
2043:         This is critical for the SIN_CARRETA doctrine (determinism).
2044:         The hash must be stable across runs.
2045:         """
2046:         config_dict = {
2047:             "linear": dict(sorted(self.linear_weights.items())),
2048:             "interaction": {
2049:                 f"{k[0]}_{k[1]}": v
2050:                 for k, v in sorted(self.interaction_weights.items())
2051:             }
2052:         }
2053:         # Use separators with no spaces for deterministic JSON
2054:         config_json = json.dumps(config_dict, sort_keys=True, separators=(',', ':'))
2055:         return hashlib.sha256(config_json.encode('utf-8')).hexdigest()[:16]
2056:
2057:
2058: @dataclass(frozen=True)
2059: class CalibrationSystemConfig:
2060:     """
2061:     Master configuration for the entire calibration system.
2062:
2063:     This is the SINGLE SOURCE OF TRUTH for ALL calibration parameters.
2064:
2065:     Usage:
2066:         # Use defaults
2067:         config = CalibrationSystemConfig()
2068:
2069:         # Or customize
2070:         config = CalibrationSystemConfig(
2071:             unit_layer=UnitLayerConfig(w_S=0.3, w_M=0.25, ...),
2072:             enable_anti_universality_check=True
```

```
2073:     )
2074:     """
2075:     # =====
2076:     # Layer Configurations
2077:     # =====
2078:     unit_layer: UnitLayerConfig = field(default_factory=UnitLayerConfig)
2079:     meta_layer: MetaLayerConfig = field(default_factory=MetaLayerConfig)
2080:     choquet: ChoquetAggregationConfig = field(default_factory=ChoquetAggregationConfig)
2081:
2082:     # =====
2083:     # System-Level Settings
2084:     # =====
2085:     # Anti-Universality Theorem enforcement
2086:     enable_anti_universality_check: bool = True
2087:     max_avg_compatibility: float = 0.9 # Threshold for universality detection
2088:
2089:     # Determinism (SIN_CARRETA doctrine)
2090:     random_seed: int = 42
2091:     enforce_determinism: bool = True
2092:
2093:     # Logging
2094:     log_all_layer_scores: bool = True
2095:     log_gate_failures: bool = True
2096:     log_gaming_penalties: bool = True
2097:
2098:     def compute_system_hash(self) -> str:
2099:         """
2100:         Compute hash of entire configuration for reproducibility.
2101:
2102:         This hash is included in CalibrationResult metadata and
2103:         proves which configuration was used.
2104:         """
2105:         config_dict = {
2106:             "unit": {
2107:                 "weights": [self.unit_layer.w_S, self.unit_layer.w_M,
2108:                             self.unit_layer.w_I, self.unit_layer.w_P],
2109:                 "aggregation": self.unit_layer.aggregation_type,
2110:                 "gates": {
2111:                     "ppi": self.unit_layer.require_ppi_presence,
2112:                     "indicators": self.unit_layer.require_indicator_matrix,
2113:                     "min_s": self.unit_layer.min_structural_compliance,
2114:                     "i_struct": self.unit_layer.i_struct_hard_gate,
2115:                     "p_struct": self.unit_layer.p_struct_hard_gate,
2116:                 }
2117:             },
2118:             "meta": {
2119:                 "weights": [self.meta_layer.w_transparency,
2120:                             self.meta_layer.w_governance,
2121:                             self.meta_layer.w_cost],
2122:             },
2123:             "choquet": {
2124:                 "hash": self.choquet.compute_hash(),
2125:             },
2126:             "seed": self.random_seed,
2127:             "anti_universality": self.enable_anti_universality_check,
2128:         }
```

```
2129:         config_json = json.dumps(config_dict, sort_keys=True, separators=(',', ':'))
2130:         return hashlib.sha256(config_json.encode('utf-8')).hexdigest()
2131:
2132:     def to_dict(self) -> dict:
2133:         """Export configuration as dictionary."""
2134:         return {
2135:             "system_hash": self.compute_system_hash(),
2136:             "unit_layer": {
2137:                 "weights": {
2138:                     "S": self.unit_layer.w_S,
2139:                     "M": self.unit_layer.w_M,
2140:                     "I": self.unit_layer.w_I,
2141:                     "P": self.unit_layer.w_P,
2142:                 },
2143:                 "aggregation_type": self.unit_layer.aggregation_type,
2144:                 "hard_gates": {
2145:                     "require_ppi": self.unit_layer.require_ppi_presence,
2146:                     "require_indicators": self.unit_layer.require_indicator_matrix,
2147:                     "min_structural": self.unit_layer.min_structural_compliance,
2148:                 }
2149:             },
2150:             "meta_layer": {
2151:                 "weights": {
2152:                     "transparency": self.meta_layer.w_transparency,
2153:                     "governance": self.meta_layer.w_governance,
2154:                     "cost": self.meta_layer.w_cost,
2155:                 }
2156:             },
2157:             "choquet": {
2158:                 "linear_weights": self.choquet.linear_weights,
2159:                 "interaction_count": len(self.choquet.interaction_weights),
2160:                 "config_hash": self.choquet.compute_hash(),
2161:             },
2162:             "system": {
2163:                 "anti_universality_enabled": self.enable_anti_universality_check,
2164:                 "deterministic": self.enforce_determinism,
2165:                 "random_seed": self.random_seed,
2166:             }
2167:         }
2168:
2169:
2170: # =====
2171: # Default Configuration Instance
2172: # =====
2173: DEFAULT_CALIBRATION_CONFIG = CalibrationSystemConfig()
2174:
2175:
2176:
2177: =====
2178: FILE: src/farfan_pipeline/core/calibration/config.py
2179: =====
2180:
2181: """Calibration config - LEGACY STUB for backward compatibility."""
2182:
2183: DEFAULT_CALIBRATION_CONFIG: dict[str, object] = {}
2184:
```

```
2185:
2186:
2187: =====
2188: FILE: src/farfan_pipeline/core/calibration/congruence_layer.py
2189: =====
2190:
2191: """
2192: Congruence Layer (@C) - Full Implementation.
2193:
2194: Evaluates method ensemble congruence using three components:
2195: - c_scale: Range compatibility
2196: - c_sem: Semantic overlap (Jaccard index)
2197: - c_fusion: Fusion rule validity
2198:
2199: Formula:  $C_{play}(G|ctx) = c_{scale} \hat{\cdot} c_{sem} \hat{\cdot} c_{fusion}$ 
2200: """
2201: import logging
2202: from typing import List, Dict, Any
2203:
2204: logger = logging.getLogger(__name__)
2205:
2206:
2207: class CongruenceLayerEvaluator:
2208:     """
2209:     Evaluates congruence of method ensembles.
2210:
2211:     Attributes:
2212:         registry: Dictionary mapping method IDs to their metadata
2213:     """
2214:
2215:     def __init__(self, method_registry: Dict[str, Any]):
2216:         """
2217:         Initialize evaluator with method registry.
2218:
2219:         Args:
2220:             method_registry: Dict with method metadata (output_range, semantic_tags, etc.)
2221:         """
2222:         self.registry = method_registry
2223:         logger.info("congruence_evaluator_initialized", extra={"num_methods": len(method_registry)})
2224:
2225:     def evaluate(
2226:         self,
2227:         method_ids: List[str],
2228:         subgraph_id: str,
2229:         fusion_rule: str = "weighted_average",
2230:         provided_inputs: List[str] = None
2231:     ) -> float:
2232:         """
2233:         Evaluate congruence of method ensemble.
2234:
2235:         Formula:  $C_{play}(G|ctx) = c_{scale} \hat{\cdot} c_{sem} \hat{\cdot} c_{fusion}$ 
2236:
2237:         Args:
2238:             method_ids: List of methods in the subgraph
2239:             subgraph_id: Identifier for this subgraph
2240:             fusion_rule: How outputs are combined (weighted_average, max, min, product)
```



```
2241:         provided_inputs: List of actual inputs provided
2242:
2243:     Returns:
2244:         C_play â\210\210 [0.0, 1.0]
2245:     """
2246:     # Edge case: Single method = perfect congruence, but only if method exists
2247:     if len(method_ids) < 2:
2248:         method_id = method_ids[0] if method_ids else None
2249:         if method_id is not None and method_id in self.registry:
2250:             logger.debug("congruence_single_method", extra={"score": 1.0, "method_id": method_id})
2251:             return 1.0
2252:         else:
2253:             logger.warning("congruence_single_method_missing", extra={"score": 0.0, "method_id": method_id})
2254:             return 0.0
2255:
2256:     logger.info(
2257:         "congruence_evaluation_start",
2258:         extra={
2259:             "methods": method_ids,
2260:             "subgraph": subgraph_id,
2261:             "fusion": fusion_rule
2262:         }
2263:     )
2264:
2265:     # Component 1: Scale congruence (c_scale)
2266:     c_scale = self._compute_scale_congruence(method_ids)
2267:     logger.debug("c_scale_computed", extra={"score": c_scale})
2268:
2269:     # Component 2: Semantic congruence (c_sem)
2270:     c_sem = self._compute_semantic_congruence(method_ids)
2271:     logger.debug("c_sem_computed", extra={"score": c_sem})
2272:
2273:     # Component 3: Fusion validity (c_fusion)
2274:     c_fusion = self._compute_fusion_validity(
2275:         method_ids, fusion_rule, provided_inputs or []
2276:     )
2277:     logger.debug("c_fusion_computed", extra={"score": c_fusion})
2278:
2279:     # Final score: Product of three components
2280:     C_play = c_scale * c_sem * c_fusion
2281:
2282:     logger.info(
2283:         "congruence_computed",
2284:         extra={
2285:             "C_play": C_play,
2286:             "c_scale": c_scale,
2287:             "c_sem": c_sem,
2288:             "c_fusion": c_fusion,
2289:             "subgraph": subgraph_id
2290:         }
2291:     )
2292:
2293:     return C_play
2294:
2295: def _compute_scale_congruence(self, method_ids: List[str]) -> float:
2296:     """
```

```
2297:         Compute c_scale: Range compatibility.
2298:
2299:     Scoring:
2300:         1.0: All ranges identical
2301:         0.8: All ranges convertible (within [0,1])
2302:         0.0: Incompatible ranges
2303:
2304:     Returns:
2305:         c_scale â\210\210 {0.0, 0.8, 1.0}
2306:     """
2307:     ranges = []
2308:     for method_id in method_ids:
2309:         if method_id not in self.registry:
2310:             logger.warning("method_not_registered", extra={"method": method_id})
2311:             return 0.0
2312:
2313:         method_data = self.registry[method_id]
2314:         output_range = method_data.get("output_range")
2315:
2316:         if output_range is None:
2317:             logger.warning("no_output_range", extra={"method": method_id})
2318:             return 0.0
2319:
2320:         ranges.append(tuple(output_range))
2321:
2322:     # Check if all ranges are identical
2323:     first_range = ranges[0]
2324:     if all(r == first_range for r in ranges):
2325:         logger.debug("ranges_identical", extra={"range": first_range})
2326:         return 1.0
2327:
2328:     # Check if all ranges are in [0,1] (convertible)
2329:     all_in_unit = all(r == (0.0, 1.0) for r in ranges)
2330:     if all_in_unit:
2331:         logger.debug("ranges_convertible", extra={"note": "all in [0,1]"})
2332:         return 0.8
2333:
2334:     # Incompatible ranges
2335:     logger.warning("ranges_incompatible", extra={"ranges": ranges})
2336:     return 0.0
2337:
2338: def _compute_semantic_congruence(self, method_ids: List[str]) -> float:
2339:     """
2340:     Compute c_sem: Semantic overlap (Jaccard index).
2341:
2342:     Formula: |intersection| / |union| of semantic tags
2343:
2344:     Returns:
2345:         c_sem â\210\210 [0.0, 1.0]
2346:     """
2347:     tag_sets = []
2348:
2349:     for method_id in method_ids:
2350:         if method_id not in self.registry:
2351:             logger.warning("method_not_registered", extra={"method": method_id})
2352:             return 0.0
```

```
2353:
2354:         tags = self.registry[method_id].get("semantic_tags", [])
2355:         if not isinstance(tags, (list, set)):
2356:             tags = []
2357:         tag_sets.append(set(tags))
2358:
2359:     if not tag_sets:
2360:         return 0.0
2361:
2362:     # Compute intersection and union
2363:     intersection = tag_sets[0]
2364:     union = tag_sets[0]
2365:
2366:     for tags in tag_sets[1:]:
2367:         intersection = intersection.intersection(tags)
2368:         union = union.union(tags)
2369:
2370:     # Jaccard index
2371:     if len(union) == 0:
2372:         logger.warning("no_semantic_tags", extra={"methods": method_ids})
2373:         return 0.0
2374:
2375:     jaccard = len(intersection) / len(union)
2376:
2377:     logger.debug(
2378:         "semantic_congruence",
2379:         extra={
2380:             "intersection": list(intersection),
2381:             "union_size": len(union),
2382:             "jaccard": jaccard
2383:         }
2384:     )
2385:
2386:     return jaccard
2387:
2388: def _compute_fusion_validity(
2389:     self,
2390:     method_ids: List[str],
2391:     fusion_rule: str,
2392:     provided_inputs: List[str]
2393: ) -> float:
2394:     """
2395:     Compute c_fusion: Fusion rule validity.
2396:
2397:     Scoring:
2398:         1.0: Rule valid AND all inputs present
2399:         0.5: Rule valid BUT some inputs missing
2400:         0.0: Rule invalid
2401:
2402:     Returns:
2403:         c_fusion â\210\210 {0.0, 0.5, 1.0}
2404:     """
2405:     # Check if fusion rule is valid
2406:     valid_rules = ["weighted_average", "max", "min", "product", "custom"]
2407:     if fusion_rule not in valid_rules:
2408:         logger.warning(
```

```
2409:         "invalid_fusion_rule",
2410:         extra={"rule": fusion_rule, "valid": valid_rules}
2411:     )
2412:     return 0.0
2413:
2414: # Collect all fusion requirements
2415: all_requirements = set()
2416: for method_id in method_ids:
2417:     if method_id not in self.registry:
2418:         return 0.0
2419:
2420:     requirements = self.registry[method_id].get("fusion_requirements", [])
2421:     all_requirements.update(requirements)
2422:
2423: # Check if provided inputs cover all requirements
2424: provided = set(provided_inputs)
2425: missing = all_requirements - provided
2426:
2427: if not missing:
2428:     # All inputs provided
2429:     logger.debug(
2430:         "fusion_valid",
2431:         extra={"rule": fusion_rule, "all_inputs_present": True}
2432:     )
2433:     return 1.0
2434: else:
2435:     # Some inputs missing
2436:     logger.warning(
2437:         "fusion_partial",
2438:         extra={
2439:             "rule": fusion_rule,
2440:             "missing": list(missing),
2441:             "provided": list(provided)
2442:         }
2443:     )
2444:     return 0.5
2445:
2446:
```