

SIMATS ENGINEERING ASSESSMENT TOOL 1

COURSE NAME: CSA07 COURSE CODE: Computer Networks

COURSE OUTCOME COVERED

CO1: Apply the functions of OSI layer in enabling reliable data transmission across networks. (BL2, BL3)

Assessment Tool Weightage: 40%

Annexure A

SHORT ANSWER TEST

Description about the assessment tool:

Short-answer questions effectively measure conceptual understanding, logical reasoning, and the ability to apply theoretical knowledge without requiring lengthy descriptive responses. This assessment method is also efficient for evaluating multiple OSI-related concepts within a limited time while ensuring objective and consistent evaluation.

Code of Conduct:

I A. Althaf (192521257) (Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.

I understand that any violation of academic integrity rules will result in disciplinary action.

A. Althaf
Signature of the student:

Criteria	Weightage	Q1 10marks	Q2 10marks	Q3 10marks	Q4 10marks
Understanding of Concepts	25%	2	2	2	2
Explanation	25%	2	2	2	✓
Application	20%	2	2	2	2
Organization	15%	1	1	1	1
Accuracy	10%	1	1	1	1
Clarity	5%				

Total Marks 32 /40

[Signature]
Signature of the Faculty

Short Answer Test

1. A company needs to transfer a **150 MB** design file from a client computer to a remote server over a network with a bandwidth of **50 Mbps**. The Transport Layer divides the file into **1500-byte segments**, while the Data Link Layer encapsulates each segment into frames by adding **40 bytes of header and trailer**. Calculate the total number of segments and frames transmitted, the total transmission overhead introduced by the Data Link Layer, and estimate the total transmission time (ignoring propagation delay). Explain how the Transport and Data Link layers ensure reliable communication.
2. A Transport Layer protocol uses a **sliding window size of 6 frames**. Each frame carries **1024 bytes** of user data. If the sender transmits **48 frames**, calculate the number of transmission windows required. If one frame in every window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.
3. A **12,000-byte** IP packet is transmitted through a router where the Maximum Transmission Unit (MTU) is **1500 bytes**. Assuming each fragment requires a **20-byte IP header**, calculate the total number of fragments created and the total header overhead introduced. Explain how the Network Layer ensures successful delivery of fragmented packets to the destination.
4. A Transport Layer protocol uses a **sliding window size of 6 frames**. Each frame carries **1024 bytes** of user data. If the sender transmits **48 frames**, calculate the number of transmission windows required. If one frame in every window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.

5. A multimedia application transfers a **600 MB** video file. The Session Layer inserts a synchronization checkpoint after every **60 MB** of transmitted data. During transmission, a failure occurs after **390 MB** has been transferred. Determine the number of checkpoints created before failure and calculate the amount of data that must be retransmitted after recovery. Explain the importance of synchronization in the Session Layer.

6. Before transmission, the Presentation Layer compresses a **900 MB** file by **40%**. The compressed data is encrypted, adding **5%** overhead to the compressed size. Calculate the compressed file size, the encrypted file size, and the total percentage reduction compared to the original file. Explain how the Presentation Layer improves transmission efficiency and security.

7. An FTP application transfers **3 GB** of data over a network with an effective throughput of **120 Mbps**. The Application Layer divides the data into requests of **3 MB** each. Calculate the total number of requests generated and estimate the total transmission time in seconds. Discuss how the Application Layer provides reliable services to users.

8. A packet experiences the following processing delays at different OSI layers: Application Layer = **4 ms**, Transport Layer = **3 ms**, Network Layer = **5 ms**, Data Link Layer = **2 ms**, and Physical Layer = **1 ms**. The propagation delay is **18 ms**, and the transmission delay is **12 ms**. Calculate the total end-to-end delay experienced by the packet and explain how each layer contributes to the communication process.

9. A network transfers **80 MB** of useful data using frames of **1600 bytes**, where each frame contains **80 bytes** of protocol overhead added by different OSI layers. Calculate the total number of frames required, the total overhead

transmitted, and the transmission efficiency as a percentage. Explain how protocol overhead affects network performance.

10. A hospital transfers a patient's medical record of **240 MB** through an IoT-enabled healthcare network. The Presentation Layer compresses the data by **30%**, the Transport Layer divides the compressed data into **1400-byte segments**, and the Data Link Layer adds **60 bytes** of overhead to each frame. Calculate the compressed file size, the total number of segments transmitted, the total protocol overhead introduced, and the final amount of data transmitted across the Physical Layer. Explain how multiple OSI layers work together to ensure secure and reliable communication.

RUBRICS FOR CALCULATION

Criteria	Weightage	Level 4 – Exemplary	Level 3 – Proficient	Level 2 – Developing	Level 1 – Beginning
Understanding of Concepts	25%	Demonstrates a thorough, accurate understanding of concepts	Good understanding with minor gaps	Basic understanding with some misconceptions	Poor understanding; major misconceptions
Explanation	25%	Detailed, well-explained answers with relevant examples	Clear explanation with adequate details	Limited explanation; lacks depth	Poor or unclear explanation
Application	20%	Effectively applies concepts with strong analytical ability	Applies concepts with minor errors	Limited application with weak analysis	No application or incorrect analysis
Organization	15%	Well-structured answers with logical flow and coherence	Organized with minor issues in flow	Basic structure, lacks clarity	Poor organization, incoherent answers
Accuracy	10%	Completely accurate and	Mostly accurate with minor	Partially correct with	Incorrect answers with

		covers all required points	omissions	missing points	major gaps
Clarity	5%	Clear, neat, professional presentation	Understandable with minor issues	Limited clarity, readability issues	Poorly written, difficult to understand

Co 1 - AT - 1

Short Answers Test

Name : A. Althaf

Reg.no : 192521257

course : Computer Networks

code : CNA 0707

File Transfer using Transport and Data link layers.

Given:

File Size = 150 MB

Bandwidth = 50 mbps

Segment size = 1500 bytes

Data Link header + trailer = 40 bytes

Step 1: Convert file size into bytes.

Using, 1 MB = 1,000,000 bytes

$$150 \times 1,000,000 = 150,000,000 \text{ bytes.}$$

Step 2: Number of segments:

$$\frac{150,000,000}{1500} = 100,000 \text{ segments.}$$

no. of frame = 100,000

Step 3: Total Data link overhead.

Each frame adds 40 bytes.

$$100,000 \times 40 = 4,000,000 \text{ bytes. Total} = 4 \text{ MB}$$

Step 4: Total data transmitted

$$150,000,000 + 4,000,000 = 154,000,000 \text{ bytes.}$$

Convert to bits:

$$154,000,000 \times 8 = 1,232,000,000 \text{ bits.}$$

Step 5: Transmission time:

Bandwidth = 50 mbps

$$\frac{1,232,000,000}{50,000,000} = 24.64 \text{ seconds.}$$

Answer

segments = 100,000

frames = 100,000

Data Link overhead = 4,000,000 bytes (4 MB)

Transmission time = 24.64 seconds.

Reliability

Transport layer.

- segments the data
- uses sequence number
- Detects missing segment
- retransmits lost segments
- provides flow and error

Data link layer

- Adds frame headers/trailers.
- Detects transmission errors using CRC
- Ensures reliable communication between adjacent devices.

Sliding window protocol

Given

Sliding window size = 6 frames

Frame size = 1024 bytes

Total frames = 48

Step 1: Number of windows

$$\frac{48}{6} = 8 \text{ windows}$$

Step 2: Retransmissions

one frame is lost in every window

$$8 \times 1 = 8$$

Answer

- Transmission window = 8
- Retransmission = 8 frames

Flow Control

Flow control prevents the sending data faster than the receiver can process it.

it :

- Prevents buffer overflow
- Improves network efficiency
- Reduce packet loss

- Reduces packet loss
- Maintain smooth communication
- Ensures reliable data transfer.

3)

IP Fragmentation in the Network Layer

Given:

IP packet size = 12,000 bytes

Maximum Transmission Unit (MTU) = 1500 bytes

IP header size = 20 bytes.

Step 1: Calculate the data carried by each fragment.
Each fragment.

Data carried by each fragment.

$$1500 - 20 = 1480 \text{ bytes}$$

Step 2: Number of fragments.

$$\frac{12,000}{1480} = 8.11$$

Round up: Total fragment = 9

Step 3: Header overhead

Each fragment needs a 20-byte header.

$$9 \times 20 = 180 \text{ bytes.}$$

Answer

- Fragments created = 9
- Header overhead = 180 bytes

Network layer function.

The Layers are:

- Fragments packets according to MTU
- Assigns identification numbers.
- uses fragment offsets.
- sets the more fragment (MF) flag.
- uses routing protocols to deliver packets successfully.

4) "sliding window protocol"

Given

- window size = 6 frames
- frame size = 1024 bytes
- Total frames = 48

Step 1 : Number of windows

$$\frac{48}{6} = 8$$

Step 2: Retransmissions

one lost frame in each window

$$8 \times 1 = 8$$

Answer

- Transmission windows = 8
- Retransmissions = 8 frames

Flow control.

Flow control:

- Matches sender speed with receiver speed.
- Prevent congestion.
- Avoids buffer overflow.
- Improves throughput.
- Ensures reliable and efficient communication.