

Package

August 2, 2019

Type Package

Title Loads Shapefiles of Official Spatial Data Sets of Brazil

Version 1.0

Date 2019-07-28

URL <https://github.com/ipeaGIT/geobr>

BugReports <https://github.com/ipeaGIT/geobr/issues>

Description Easy access to shapefiles of the Brazilian Institute of Geography and Statistics (IBGE) <<https://www.ibge.gov.br/>> and other official spatial data sets of Brazil as 'sf' objects in R. The package includes a wide range of geographic datasets available at various geographic scales and for various years.

License MIT + file LICENSE

Encoding UTF-8

LazyData TRUE

Depends R (>= 3.4.0)

Suggests ggplot2,
mapview,
knitr,
rio,
rmarkdown

Imports dplyr,
httr,
readr,
sf,
utils

RoxygenNote 6.1.1

VignetteBuilder knitr

R topics documented:

geobr	2
grid_state_correspondence_table	2
read_census_tract	3
read_country	4
read_health_facilities	4

read_meso_region	5
read_micro_region	6
read_municipality	7
read_region	8
read_state	8
read_statistical_grid	9
read_weighting_area	10

Index	12
--------------	-----------

geobr	geobr package
-------	---------------

Description

Easy access to shapefiles of the Brazilian Institute of Geography and Statistics (IBGE) and other official spatial data sets of Brazil

Details

See the README on [CRAN](#) or [GitHub](#)

grid_state_correspondence_table	<i>A correspondence table indicating what quadrants of IBGE's statistical grid intersect with each Brazilian state</i>
---------------------------------	--

Description

Built-in dataset

- code_uf: IBGE code of State (2-digit, numeric)
- name_state: Title-case name of state (character)
- code_grid: Unique code of each quadrant of IBGE's statistical grid

Usage

```
data(grid_state_correspondence_table)
```

Format

A data frame sf with 139 rows and 3 columns

Details

correspondence table indicating what quadrants of IBGE's statistical grid intersect with each Brazilian state

Note

Last updated 2019-06-17

read_census_tract	<i>Download shape files of census tracts of the Brazilian Population Census (Only years 2000 and 2010 are currently available).</i>
-------------------	---

Description

Download shape files of census tracts of the Brazilian Population Census (Only years 2000 and 2010 are currently available).

Usage

```
read_census_tract(code_tract, year = NULL, zone = "urban")
```

Arguments

code_tract	The 7-digit code of a Municipality. If the two-digit code or a two-letter upper-case abbreviation of a state is passed, (e.g. 33 or "RJ") the function will load all census tracts of that state. If code_tract="all", all census tracts of the country are loaded.
year	Year of the data (defaults to 2010)
zone	"urban" or "rural" census tracts come in separate files in the year 2000 (defaults to "urban")

See Also

Other general area functions: [read_country](#), [read_meso_region](#), [read_micro_region](#), [read_municipality](#), [read_region](#), [read_state](#), [read_statistical_grid](#), [read_weighting_area](#)

Examples

```
library(geobr)

# Read rural census tracts for years before 2007
c <- read_census_tract(code_tract=5201108, year=2000, zone="rural")

# Read all census tracts of a state at a given year
c <- read_census_tract(code_tract=53, year=2010); # or
c <- read_census_tract(code_tract="DF", year=2010)
plot(c)

# Read all census tracts of a municipality at a given year
c <- read_census_tract(code_tract=5201108, year=2010)
plot(c)

# Read all census tracts of the country at a given year
c <- read_census_tract(code_tract="all", year=2010)
```

read_country	<i>Download shape file of Brazil as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)</i>
--------------	---

Description

Download shape file of Brazil as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)

Usage

```
read_country(year = NULL)
```

Arguments

year	Year of the data (defaults to 2010)
------	-------------------------------------

See Also

Other general area functions: [read_census_tract](#), [read_meso_region](#), [read_micro_region](#), [read_municipality](#), [read_region](#), [read_state](#), [read_statistical_grid](#), [read_weighting_area](#)

Examples

```
library(geobr)

# Read specific year
br <- read_country(year=2018)
```

read_health_facilities	<i>Download geolocated data of health facilities as an sf object.</i>
------------------------	---

Description

Data comes from the National Registry of Healthcare facilities (Cadastro Nacional de Estabelecimentos de Saúde - CNES), originally collected by the Brazilian Ministry of Health. The date of the last data update is registered in the database in the columns 'date_update' and 'year_update'. These data uses Geodetic reference system "SIRGAS2000" and CRS(4674). The coordinates of each facility was obtained by CNES and validated by means of space operations. These operations verify if the point is in the municipality, considering a radius of 5,000 meters. When the coordinate is not correct, further searches are done in other systems of the Ministry of Health and in web services like Google Maps . Finally, if the coordinates have been correctly obtained in this process, the coordinates of the municipal head office are used. The final source used is registered in the database in a specific column 'data_source'. Periodically the coordinates are revised with the objective of improving the quality of the data. More information available at <http://dados.gov.br/dataset/cnes>

Usage

```
read_health_facilities(code)
```

Arguments

code The 7-digit code of a municipality. If the two-digit code or a two-letter abbreviation of a state is passed, (e.g. 33 or "RJ") the function will load all healthcare facilities of that state. If code="all", all facilities of the country are loaded.

Examples

```
library(geobr)

# Read the health facilities of state 11
h <- read_health_facilities(code=11)

# Read the health facilities of state "AM"
h <- read_health_facilities(code="AM")

# Read all health facilities of the country
h <- read_health_facilities(code="all")
```

read_meso_region	<i>Download shape files of meso region as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)</i>
------------------	---

Description

Download shape files of meso region as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)

Usage

```
read_meso_region(code_meso, year = NULL)
```

Arguments

code_meso The 4-digit code of a meso region. If the two-digit code or a two-letter uppercase abbreviation of a state is passed, (e.g. 33 or "RJ") the function will load all meso regions of that state. If code_meso="all", all meso regions of the country are loaded.

year Year of the data (defaults to 2010)

See Also

Other general area functions: [read_census_tract](#), [read_country](#), [read_micro_region](#), [read_municipality](#), [read_region](#), [read_state](#), [read_statistical_grid](#), [read_weighting_area](#)

Examples

```
library(geobr)

# Read specific meso region at a given year
meso <- read_meso_region(code_meso=3301, year=2018)

# Read all meso regions of a state at a given year
meso <- read_meso_region(code_meso=12, year=2017)
meso <- read_meso_region(code_meso="AM", year=2000)

# Read all meso regions of the country at a given year
meso <- read_meso_region(code_meso="all", year=2010)
```

read_micro_region	<i>Download shape files of micro region as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)</i>
-------------------	--

Description

Download shape files of micro region as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)

Usage

```
read_micro_region(code_micro, year = NULL)
```

Arguments

code_micro	5-digit code of a micro region. If the two-digit code or a two-letter uppercase abbreviation of a state is passed, (e.g. 33 or "RJ") the function will load all micro regions of that state. If code_micro="all", all micro regions of the country are loaded.
year	Year of the data (defaults to 2010)

See Also

Other general area functions: [read_census_tract](#), [read_country](#), [read_meso_region](#), [read_municipality](#), [read_region](#), [read_state](#), [read_statistical_grid](#), [read_weighting_area](#)

Examples

```
library(geobr)

# Read an specific micro region a given year
micro <- read_micro_region(code_micro=11008, year=2018)
```

```
# Read micro regions of a state at a given year
micro <- read_micro_region(code_micro=12, year=2017)
micro <- read_micro_region(code_meso="AM", year=2000)

# Read all micro regions at a given year
micro <- read_micro_region(code_micro="all", year=2010)
```

read_municipality	<i>Download shape files of Brazilian municipalities as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)</i>
-------------------	--

Description

Download shape files of Brazilian municipalities as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)

Usage

```
read_municipality(code_muni, year = NULL)
```

Arguments

code_muni	The 7-digit code of a municipality. If the two-digit code or a two-letter uppercase abbreviation of a state is passed, (e.g. 33 or "RJ") the function will load all municipalities of that state. If code_muni="all", all municipalities of the country will be loaded.
year	Year of the data (defaults to 2010)

See Also

Other general area functions: [read_census_tract](#), [read_country](#), [read_meso_region](#), [read_micro_region](#), [read_region](#), [read_state](#), [read_statistical_grid](#), [read_weighting_area](#)

Examples

```
library(geobr)

# Read specific municipality at a given year
mun <- read_municipality(code_muni=1200179, year=2017)

# Read all municipalities of a state at a given year
mun <- read_municipality(code_muni=33, year=2010)
mun <- read_municipality(code_muni="RJ", year=2010)

# Read all municipalities of the country at a given year
mun <- read_municipality(code_muni="all", year=2018)
```

read_region	<i>Download shape file of Brazil Regions as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)</i>
-------------	---

Description

Download shape file of Brazil Regions as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)

Usage

```
read_region(year = NULL)
```

Arguments

year	Year of the data (defaults to 2010)
------	-------------------------------------

See Also

Other general area functions: [read_census_tract](#), [read_country](#), [read_meso_region](#), [read_micro_region](#), [read_municipality](#), [read_state](#), [read_statistical_grid](#), [read_weighting_area](#)

Examples

```
library(geobr)

# Read specific year
reg <- read_region(year=2018)
```

read_state	<i>Download shape files of Brazilian states as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)</i>
------------	--

Description

Download shape files of Brazilian states as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)

Usage

```
read_state(code_state, year = NULL)
```


Arguments

`code_state` The two-digit code of a state or a two-letter uppercase abbreviation (e.g. 33 or "RJ"). If `code_state="all"`, all states will be loaded.

`year` Year of the data (defaults to 2010)

See Also

Other general area functions: [read_census_tract](#), [read_country](#), [read_meso_region](#), [read_micro_region](#), [read_municipality](#), [read_region](#), [read_statistical_grid](#), [read_weighting_area](#)

Examples

```
library(geobr)

# Read specific state at a given year
uf <- read_state(code_state=12, year=2017)

# Read specific state at a given year
uf <- read_state(code_state="SC", year=2000)

# Read all states at a given year
ufs <- read_state(code_state="all", year=2010)
```

`read_statistical_grid` *Download shape files of IBGE's statistical grid (200 x 200 meters) as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)*

Description

Download shape files of IBGE's statistical grid (200 x 200 meters) as sf objects. Data at scale 1:250,000, using Geodetic reference system "SIRGAS2000" and CRS(4674)

Usage

```
read_statistical_grid(code_grid, year = NULL)
```

Arguments

`code_grid` The 7-digit code of a grid quadrant If the two-letter abbreviation of a state is used, the function will load all grid quadrants that intersect with that state. If `code_grid="all"`, the grid of the whole country will be loaded.

`year` Year of the data (defaults to 2010). The only year available thus far is 2010.

See Also

Other general area functions: [read_census_tract](#), [read_country](#), [read_meso_region](#), [read_micro_region](#), [read_municipality](#), [read_region](#), [read_state](#), [read_weighting_area](#)

Examples

```
library(geobr)

# Read specific municipality at a given year
grid <- read_statistical_grid(code_grid = 45, year=2010)

# Read all municipalities of a state at a given year
state_grid <- read_statistical_grid(code_grid = "RJ")
```

read_weighting_area	<i>Download shape files of Census Weighting Areas (area de ponderação) of the Brazilian Population Census. Only 2010 data is currently available.</i>
---------------------	---

Description

Download shape files of Census Weighting Areas (area de ponderação) of the Brazilian Population Census. Only 2010 data is currently available.

Usage

```
read_weighting_area(code_weighting, year = NULL)
```

Arguments

code_weighting	The 7-digit code of a Municipality. If the two-digit code or a two-letter upper-case abbreviation of a state is passed, (e.g. 33 or "RJ") the function will load all weighting areas of that state. If code_weighting="all", all weighting areas of the country are loaded.
year	Year of the data (defaults to 2010)

See Also

Other general area functions: [read_census_tract](#), [read_country](#), [read_meso_region](#), [read_micro_region](#), [read_municipality](#), [read_region](#), [read_state](#), [read_statistical_grid](#)

Examples

```
library(geobr)

# Read specific weighting area at a given year
w <- read_weighting_area(code_weighting=5201108005004, year=2010)

# Read all weighting areas of a state at a given year
w <- read_weighting_area(code_weighting=53, year=2010); # or
w <- read_weighting_area(code_weighting="DF", year=2010)
plot(w)
```

```
# Read all weighting areas of a municipality at a given year
w <- read_weighting_area(code_weighting=5201108, year=2010)
plot(w)

# Read all weighting areas of the country at a given year
w <- read_weighting_area(code_weighting="all", year=2010)
```

Index

*Topic **datasets**

grid_state_correspondence_table, [2](#)

geobr, [2](#)

geobr-package (geobr), [2](#)

grid_state_correspondence_table, [2](#)

read_census_tract, [3](#), [4–10](#)

read_country, [3](#), [4](#), [5–10](#)

read_health_facilities, [4](#)

read_meso_region, [3](#), [4](#), [5](#), [6–10](#)

read_micro_region, [3–5](#), [6](#), [7–10](#)

read_municipality, [3–6](#), [7](#), [8–10](#)

read_region, [3–7](#), [8](#), [9](#), [10](#)

read_state, [3–8](#), [8](#), [9](#), [10](#)

read_statistical_grid, [3–9](#), [9](#), [10](#)

read_weighting_area, [3–9](#), [10](#)