

Overview

The 12v 2200mAh rechargeable lithium ion battery from Wattnine is designed to provide high energy density for low-rate applications.

Features

- · High energy density.
- · Equipped with Smart Battery Management System.
- · Low self-discharge rate.
- · Long cycle life.
- · Excellent safty & performance.



DC Male Female Charging/Discharging Connector





Battery Specification:

Nominal Characteristics		
Nominal Voltage /V	11.1V	
Nominal Capacity /Ah (25°C, 0.2C)	≈2200mAh	
Operating Voltage Range	9.2V-12.8V	
Pack Characteristics		
Design	3S1P	
Cell type/ Chemistry	18650/ NMC	
Mechanical Characteristics		
Weight	153 gms	
Dimensions (LxWxH)	56 x 22 x 68 mm	
Charging/Discharging Connector	DC Male Female Connector	
Charging Characteristics		
Charge Voltage	12.8V	
Max. Continues Charge Current	1.1A	
Charging Duration	≈120Mins	
Discharging Characteristics		
Max Voltage	12.8V	
Min Voltage	9.2V	
Max. Continues Discharge Current	2.2A	

Page:1/2 www.wattnine.in







BMS - Battery Management System:

Prote	ction	Range	Units
Over Charge	Trigger Voltage	4.25	V
	Release Voltage	4.05	V
	Delay Time	80	ms
Over Discharge	Trigger Voltage	2.40	V
	Release Voltage	3.0	V
	Delay Time	40	ms
Over Current	Trigger Current	7	А
	Delay Time	40	ms
Balancing Function	NA		
Short Circuit	Delay	500	μs
	Manual Reset	Connect Power Source to Reset	
Thermal Protection	High Temperature	NA	
	Low Temperature	NA	

Page:2/2 www.wattnine.in