

Register file structure : regfile_xgs_athena.pdf

Created by imaval on 2020/05/27 14:00:26

Register file CRC32 : 0x36EA9D6F

1. Main Parameters

Register file endianness: little endian

Address bus width: 11 bits

Data bus width: 32 bits

2. Memory Map

Section name	Address(es) / Address Ranges	Register name	Access Type
SYSTEM	0x000	TAG	R
	0x004	VERSION	R
	0x008	CAPABILITY	R
	0x00C	SCRATCHPAD	RW
DMA	0x070	CTRL	RW
	0x078	FSTART	RW
	0x07C	FSTART_HIGH	RW
	0x080	FSTART_G	RW
	0x084	FSTART_G_HIGH	RW
	0x088	FSTART_R	RW
	0x08C	FSTART_R_HIGH	RW
	0x090	LINE_PITCH	RW
	0x094	LINE_SIZE	RW
	0x098	CSC	RW
ACQ	0x100	GRAB_CTRL	RW
	0x108	GRAB_STAT	R
	0x110	READOUT_CFG1	RW
	0x114	READOUT_CFG_FRAME_LINE	RW
	0x118	READOUT_CFG2	R
	0x120	READOUT_CFG3	RW
	0x124	READOUT_CFG4	RW
	0x128	EXP_CTRL1	RW
	0x130	EXP_CTRL2	RW
	0x138	EXP_CTRL3	RW
	0x140	TRIGGER_DELAY	RW
	0x148	STROBE_CTRL1	RW
	0x150	STROBE_CTRL2	RW
	0x158	ACQ_SER_CTRL	RW
	0x160	ACQ_SER_ADDDATA	RW
	0x168	ACQ_SER_STAT	R
	0x190	SENSOR_CTRL	RW

Section name	Address(es) / Address Ranges	Register name	Access Type
	0x198	SENSOR_STAT	R
	0x19C	SENSOR_SUBSAMPLING	RW
	0x1A4	SENSOR_GAIN_ANA	RW
	0x1A8	SENSOR_ROI_Y_START	RW
	0x1AC	SENSOR_ROI_Y_SIZE	RW
	0x1B0	SENSOR_ROI2_Y_START	RW
	0x1B4	SENSOR_ROI2_Y_SIZE	RW
	0x1B8	SENSOR_M_LINES	RW
	0x1BC	SENSOR_DP_GR	RW
	0x1C0	SENSOR_DP_GB	RW
	0x1C4	SENSOR_DP_R	RW
	0x1C8	SENSOR_DP_B	RW
	0x1CC	SENSOR_X_SIZE	RW
	0x1D0	SENSOR_X_START	RW
	0x1D4	SENSOR_X_END	RW
	0x1E0	DEBUG_PINS	RW
	0x1E8	TRIGGER_MISSED	RW
	0x1F0	SENSOR_FPS	R
	0x2A0	DEBUG	RW
	0x2A8	DEBUG_CNTR1	R
	0x2B8	EXP_FOT	RW
	0x2C0	ACQ_SFNC	RW
HISPI	0x400	CTRL	RW
	0x404	STATUS	R
	0x408	IDELAYCTRL_STATUSES	R
	0x40C	IDLE_CHARACTER	RW
	0x410, 0x414, ... ,0x424	LANE_DECODER_STATUSES (5:0)	RW
	0x428, 0x42C, ... ,0x43C	TAP_HISTOGRAM (5:0)	R
	0x440, 0x444, 0x448	LANE_PACKER_STATUSES (2:0)	RW
	0x44C	DEBUG	RW

3. Registers definition

Section: SYSTEM

Address Range: [0x000 - 0x00C]

TAG

Address: section "SYSTEM" base address + 0x000

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
VALUE(23:16)							
15	14	13	12	11	10	9	8
VALUE(15:8)							
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (23:0) <i>STATIC</i>	Tag identifier	
Value at Reset:	0x58544d	
Possible Values:	0x58544D	MTX ASCII string

Address: section "SYSTEM" base address + 0x004

Description:

Revisions

1.3.x : First functional revision with a single list of multiple Ethernet frames

1.4.x : Second revision. Implements multiple list of frames

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
MAJOR(7:0)							
15	14	13	12	11	10	9	8
MINOR(7:0)							
7	6	5	4	3	2	1	0
HW(7:0)							

MAJOR (7:0)	
<i>STATIC</i>	
Value at Reset:	0x0

MINOR (7:0)	
<i>STATIC</i>	
Value at Reset:	0x1

HW (7:0)	
<i>STATIC</i>	
Value at Reset:	0x0

Address: section "SYSTEM" base address + 0x008

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved							
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (7:0)	
STATIC	
Value at Reset:	0x0

Address: section "SYSTEM" base address + 0x00C

31	30	29	28	27	26	25	24
VALUE(31:24)							
23	22	21	20	19	18	17	16
VALUE(23:16)							
15	14	13	12	11	10	9	8
VALUE(15:8)							
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (31:0)	
RW	
Value at Reset:	0x0

Section: DMA

Address Range: [0x070 - 0x0A4]

CTRL

Initial Grab Address Register

Address: section "DMA" base address + 0x000

Description:
Initial Grab Address LOW 32 bits

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved							
7	6	5	4	3	2	1	0
Reserved							GRAB_QUEUE_EN

GRAB_QUEUE_EN RW		
Value at Reset:	0x0	
Possible Values:	0x0	
	0x1	

Address: section "DMA" base address + 0x008

Description:

Initial Grab Address LOW 32 bits

31	30	29	28	27	26	25	24
VALUE(31:24)							
23	22	21	20	19	18	17	16
VALUE(23:16)							
15	14	13	12	11	10	9	8
VALUE(15:8)							
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (31:0)	Initial GRAB ADDRESS Register	
<i>RW</i>	This is the address in the host ram where the grab engine will start writing pixel data.	
Value at Reset:	0x0	
Possible Values:	Any Value	

Address: section "DMA" base address + 0x00C

Description:

Initial Grab Address HI 32 bits

31	30	29	28	27	26	25	24
VALUE(31:24)							
23	22	21	20	19	18	17	16
VALUE(23:16)							
15	14	13	12	11	10	9	8
VALUE(15:8)							
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (31:0)	Initial GRAB ADDRESS Register High	
<i>RW</i>	This is the high 32 bits of the 64-bit addresses in the host ram where the grab engine will start writing pixel data.	
Value at Reset:	0x0	
Possible Values:	Any Value	

Address: section "DMA" base address + 0x010

Description:

Grab Address LOW 32 bits for the Green plane. Only used when grabbing in Planar mode.

31	30	29	28	27	26	25	24
VALUE(31:24)							
23	22	21	20	19	18	17	16
VALUE(23:16)							
15	14	13	12	11	10	9	8
VALUE(15:8)							
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (31:0)	GRAb ADDRess Register	
<i>RW</i>	This is the address in the host ram where the grab engine will start writing pixel data.	
Value at Reset:	0x0	
Possible Values:	Any Value	

Address: section "DMA" base address + 0x014

Description:

Green Grab Address HIGH 32 bits

31	30	29	28	27	26	25	24
VALUE(31:24)							
23	22	21	20	19	18	17	16
VALUE(23:16)							
15	14	13	12	11	10	9	8
VALUE(15:8)							
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (31:0) <i>RW</i>	GRAb ADDRess Register High	
	This is the high part of the 64-bit addresses in the host ram where the grab engine will start writing pixel data.	
Value at Reset:	0x0	
Possible Values:	Any Value	Any value

Address: section "DMA" base address + 0x018

Description:

Grab Address LOW 32 bits for the Red plane. Only used when grabbing in Planar mode.

31	30	29	28	27	26	25	24
VALUE(31:24)							
23	22	21	20	19	18	17	16
VALUE(23:16)							
15	14	13	12	11	10	9	8
VALUE(15:8)							
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (31:0)	GRAb ADDRess Register	
<i>RW</i>	This is the address in the host ram where the grab engine will start writing pixel data.	
Value at Reset:	0x0	
Possible Values:	Any Value	Any value

Address: section "DMA" base address + 0x01C

Description:

Red Grab Address HIGH 32 bits

31	30	29	28	27	26	25	24
VALUE(31:24)							
23	22	21	20	19	18	17	16
VALUE(23:16)							
15	14	13	12	11	10	9	8
VALUE(15:8)							
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (31:0) <i>RW</i>	GRAb ADDRess Register High	
	This is the high part of the 64-bit addresses in the host ram where the grab engine will start writing pixel data.	
Value at Reset:	0x0	
Possible Values:	Any Value	Any value

Address: section "DMA" base address + 0x020

Description:
Grab Line Pitch Register

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
VALUE(15:8)							
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (15:0)	Grab LinePitch
RW	This is the line pitch when writing in ram. It is measured in bytes, not pixels.
Value at Reset:	0x0

Address: section "DMA" base address + 0x024

Description:

Host Line Size Register.

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved		VALUE(13:8)					
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (13:0) <i>RW</i>	Host Line size	
	<p>This is the line size when writing in host ram. It is measured in bytes, not pixels. If this register is higher than the actual data provided by the sensor, stray data will be written into host memory. If this register is lower than the data provided by the sensor, image data will be cropped at the end of the line.</p> <p>For backward compatibility, the value of 0 indicates that the FPGA should auto-compute the line sized based on data provided by the sensor interface.</p>	
Value at Reset:	0x0	
Possible Values:	0x1 - 0x3FFF	Written line size in host frame.
	0x0	Auto-compute line size from sensor data.

Address: section "DMA" base address + 0x028

31	30	29	28	27	26	25	24
Reserved					COLOR_SPACE(2:0)		
23	22	21	20	19	18	17	16
DUP_LAST_LINE	Reserved						
15	14	13	12	11	10	9	8
Reserved						REVERSE_Y	REVERSE_X
7	6	5	4	3	2	1	0
Reserved							

COLOR_SPACE (2:0)		
<i>RW</i>	Output color space used to transfer data to the DMA engine.	
Value at Reset:	0x0	
Possible Values:	0x0	Reserved for Mono sensor operation
	0x1	BGR32
	0x2	YUV 4:2:2 in full range
	0x3	Planar 8-bits
	0x4	Reserved for Y only with color sensor
	0x5	RAW color pixels (8bpp or 10bpp selected with MONO10 registor)

DUP_LAST_LINE		
<i>RW</i>	This field is used to enable the duplicate last line feature. When turned on, the datapath will regenerate the last line when it receives the end of frame marker from the acquisition section. The goal of this feature is to compensate for the lost line during the Bayer demosaic processing.	
Value at Reset:	0x0	
Possible Values:	0x0	normal processing
	0x1	last line is duplicated

REVERSE_Y	REVERSE Y	
<i>RW</i>	Reverse readout	
Value at Reset:	0x0	
Possible Values:	0x0	Bottom to top readout
	0x1	Top to bottom readout

REVERSE_X		
<i>RW</i>		
Value at Reset:	0x0	

Section: ACQ

Address Range: [0x100 - 0x2CC]

GRAB_CTRL

GRAB ConTRoL Register

Address: section "ACQ" base address + 0x000

Description:

Grag Control Register

31	30	29	28	27	26	25	24
RESET_GRAB	Reserved	GRAB_ROI2_EN	ABORT_GRAB	Reserved			
23	22	21	20	19	18	17	16
Reserved							TRIGGER_O VERLAP_BUFn
15	14	13	12	11	10	9	8
TRIGGER_O VERLAP	TRIGGER_ACT(2:0)			Reserved	TRIGGER_SRC(2:0)		
7	6	5	4	3	2	1	0
Reserved			GRAB_SS	Reserved		BUFFER_ID	GRAB_CMD

RESET_GRAB <i>RW</i>		
	This register resets the entire python_ctrl.	
Value at Reset:	0x0	
Possible Values:	0x0	Reset not active
	0x1	Reset active

GRAB_ROI2_EN <i>RW</i>		
	Enable the second ROI on the frame (KNS). This register is not DB. 1) No Y overlap is allowed 2) Xsize must be the same for the two ROI for the moment(DMA constraint). 3) EOF and SOF in between the two in-frame ROIs will be masked to the DMA. The DMA will see one frame, with the two ROI inside.	
Value at Reset:	0x0	
Possible Values:	0x0	Dual ROI disable
	0x1	Dual ROI enable

ABORT_GRAB <i>WO/AutoClr</i>	ABORT GRAB	
	This is the grab Abort signal, it will reset all the grab queued.	
Possible Values:	0x0	Normal operation
	0x1	Reset Grab

TRIGGER_OVERLAP_BUF Fn <i>RW</i>		
	NOT FULLY VALIDATED. DON'T USE. SET IT TO '0'.	
Value at Reset:	0x0	
Possible Values:	0x0	Buffer the trigger received during the dead window in PET mode and execute
	0x1	The trigger will be ignored during dead window in PET mode.

TRIGGER_OVERLAP <i>RW</i>		
	This field enables the trigger overlap. In this mode the exposure and the readout of the sensor can be done in parallel for higher framerates.	
Value at Reset:	0x1	
Possible Values:	0x0	Trigger Overlap disable
	0x1	Trigger Overlap enable (default)

TRIGGER_ACT (2:0) <i>RW</i>	TRIGGER ACTivation	
	<p>This is the trigger activation . This register selects the activation of the trigger when the trigger source is set to Hardware Snapshot mode . This register is Double Buffered, so the trigger activation may change from one grab command to another.</p> <p>In activation Level HI/LO with EXPOSURE_MODE register set to Timed, the camera will be triggered in continuous way if the level of the external trigger remains at the LEVEL programmed in this register.</p> <p>In activation Level HI/LO with EXPOSURE_MODE register set to Trigger Width, the Exposure time will be set by the level of the trigger input. The FPGA exposure regsiters will be ignored. The Dual and Triple slope are not supported in the mode.</p>	
Value at Reset:	0x0	
Possible Values:	0x0	Rising edge
	0x1	Falling edge
	0x2	Rising or Falling edge
	0x3	Level HI
	0x4	Level LO
	0x5	RESERVED
	0x6	RESERVED
	0x7	RESERVED

TRIGGER_SRC (2:0) <i>RW</i>	TRIGGER SouRCe	
	<p>This is the trigger source. This register selects the source of the grab trigger. This register is Double Buffered, so the trigger source may change from one grab command to another. TRIGGER_SRC(1) may be seen as a TRIGGER_STATE by the software driver.</p>	
Value at Reset:	0x0	
Possible Values:	0x0	RESERVED
	0x1	Immediate mode (Continuous)
	0x2	Hardware Snapshot mode
	0x3	Software Snapshot mode
	0x4	SFNC mode (auto trig)

GRAB_SS <i>WO/AutoClr</i>	GRAB Software Snapshot	
	This is the software snapshot register when the trigger source selected is Software Snapshot mode.	
Possible Values:	0x0	Idle
	0x1	Start a grab

BUFFER_ID <i>RW</i>		
	This is the ID of the DMA parameters to associate with this grab command.	
Value at Reset:	0x0	

GRAB_CMD <i>WO/AutoClr</i>	GRAB CoMmanD	
	<p>This is MIL GRAB command.</p> <p>When the trigger source is set to Immediate mode(Continuous), an exposure sequence will be automatically executed. When the trigger source is set to Software Snapshot mode or Hardware Snapshot mode, GRAB_CMD will act as an ARM.</p> <p>The GRAB_CMD will take around 13 clks to record the grab parameters to the SPI fifo. The GRAB_CMD_DONE register may be read to avoid fifo corruption before sending another Grab command instruction.</p>	
Possible Values:	0x0	Idle
	0x1	Start grab command

GRAB_STAT

Address: section "ACQ" base address + 0x008

31	30	29	28	27	26	25	24
GRAB_CMD_DONE	ABORT_PET	ABORT_DELAI	ABORT_DONE	Reserved		TRIGGER_RDY	
23	22	21	20	19	18	17	16
Reserved	ABORT_MNGR_STAT(2:0)			TRIG_MNGR_STAT(3:0)			
15	14	13	12	11	10	9	8
Reserved	TIMER_MNGR_STAT(2:0)			GRAB_MNGR_STAT(3:0)			
7	6	5	4	3	2	1	0
Reserved	GRAB_FOT	GRAB_READOUT	GRAB_EXPOSURE	Reserved	GRAB_PENDING	GRAB_ACTIVE	GRAB_IDLE

GRAB_CMD_DONE <i>RO</i>	GRAB CoMmanD DONE						
	The GRAB_CMD will take around 13 clks to reccord the grab parametters to the SPI fifo. This register may be readed to avoid fifo corruption before sending another Grab command instruction.						
Possible Values:	0x0		Grab Command in process				
	0x1		Grab command idle				

ABORT_PET <i>RO</i>	ABORT during PET						
	This is the ABORT PET flag. It is set to '1' when an abort is detected in the PETengin phase of the trigger. It is set back to '0' when ABORT_DONE is set to '1'.						
Possible Values:	0x0		Abort in PET Phase idle				
	0x1		Abort in PET Phase active				

ABORT_DELAI <i>RO</i>							
	This is the ABORT DELAI flag. It is set to '1' when an abort is detected in the delai phase of the trigger. It is set back to '0' when ABORT_DONE is set to '1'.						
Possible Values:	0x0		Abort in Delai Phase idle				
	0x1		Abort in Delai Phase active				

ABORT_DONE <i>RO</i>	ABORT is DONE						
	This read-only field indicates the RESET_GRAB command status. If 0, an abort sequence is executing.						
Possible Values:	0x0		Abort sequence not finished yet				
	0x1		Abort DONE, or not started (reset value)				

TRIGGER_RDY <i>RO</i>							

ABORT_MNGR_STAT (2:0) <i>RO</i>							
	DEBUG ABORT MANAGER STATE MACHINE						

TRIG_MNGR_STAT (3:0)	
<i>RO</i>	DEBUG TRIGGER MANAGER STATE MACHINE

TIMER_MNGR_STAT (2:0)	
<i>RO</i>	DEBUG TIMER MANAGER STATE MACHINE

GRAB_MNGR_STAT (3:0)	
<i>RO</i>	DEBUG GRAB MANAGER STATE MACHINE

GRAB_FOT	GRAB Field Overhead Time	
<i>RO</i>	This is the sensor FOT (Field Overhead Time).	
Possible Values:	0x0	Not in FOT
	0x1	In FOT

GRAB_READOUT		
<i>RO</i>	This is the sensor readout status. It goes to '1' on the SO_FOT and goes to '0' when the datapath decoder decodes the end of frame.	

GRAB_EXPOSURE		
<i>RO</i>	This is the sensor integration status	
Possible Values:	0x0	Idle
	0x1	Integrating

GRAB_PENDING		
<i>RO</i>	Grab pending status. When this register is set to one, a second grab command is queued in the fpga.	
Possible Values:	0x0	No grab pending
	0x1	Grab pending

GRAB_ACTIVE		
<i>RO</i>	Grab active status. When this register is set to one, at least one grab command has been received.	

GRAB_IDLE		
<i>RO</i>	GRAB IDLE status. When this register is set to '1', The grab engin is in idle state.	
Possible Values:	0x0	Grab is in process
	0x1	Grab is Idle

READOUT_CFG1

Address: section "ACQ" base address + 0x010

31	30	29	28	27	26	25	24
Reserved			FOT_LENGTH_LINE(4:0)				
23	22	21	20	19	18	17	16
Reserved							EO_FOT_SEL
15	14	13	12	11	10	9	8
FOT_LENGTH(15:8)							
7	6	5	4	3	2	1	0
FOT_LENGTH(7:0)							

FOT_LENGTH_LINE (4:0)	Frame Overhead Time LENGTH LINE	
<i>RW</i>	This is the length of the Frame Overhead Time in line_time unit.	
Value at Reset:	0x0	
Possible Values:	Any Value	Any 16 bit value

EO_FOT_SEL		
<i>RW</i>	This selector selects who will generate the EO_FOT in the controller. When select 0, the EO_FOT is the falling edge detection of the monitor FOT. When select 1, the EO_FOT will be generated inside the controller with programmed FOT_LENGTH.	
Value at Reset:	0x0	

FOT_LENGTH (15:0)	Frame Overhead Time LENGTH	
<i>RW</i>	This is the length of the Frame Overhead Time. This register is defined as number of lines. It is used when EO_FOT_SEL is set to 1.	
Value at Reset:	0x0	
Possible Values:	Any Value	Any 16 bit value

READOUT_CFG_FRAME_LINE

Address: section "ACQ" base address + 0x014

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
DUMMY_LINES(7:0)							
15	14	13	12	11	10	9	8
Reserved				CURR_FRAME_LINES(12:8)			
7	6	5	4	3	2	1	0
CURR_FRAME_LINES(7:0)							

DUMMY_LINES (7:0)	
<i>RW</i>	Number of lines to add in the readout (to debug XGS)
Value at Reset:	0x0

CURR_FRAME_LINES (12:0)	
<i>RO</i>	Current number of lines in the readout calculated by the XGS controller (without FOT).

READOUT_CFG2

Address: section "ACQ" base address + 0x018

31	30	29	28	27	26	25	24
Reserved			READOUT_LENGTH(28:24)				
23	22	21	20	19	18	17	16
READOUT_LENGTH(23:16)							
15	14	13	12	11	10	9	8
READOUT_LENGTH(15:8)							
7	6	5	4	3	2	1	0
READOUT_LENGTH(7:0)							

READOUT_LENGTH (28:0) RO		
	This is the readout length register. This register is calculated by the FPGA in the IRIS4 projectand gives the readout lenght without the FOT. This register will depend on the ROI, and Subsampling mode. It is used in the PET engin calculations. In Sys_Clock domain.	
Possible Values:	Any Value	Any 24 bits value

READOUT_CFG3

Address: section "ACQ" base address + 0x020

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							KEEP_OUT_TRIG_ENA
15	14	13	12	11	10	9	8
LINE_TIME(15:8)							
7	6	5	4	3	2	1	0
LINE_TIME(7:0)							

KEEP_OUT_TRIG_ENA <i>RW</i>	KEEPOUT zone TRIGger ENable. When this register is enabled, then the trigger output will be synchronized with the line_int(monitor2) signal from the XGS sensor. To configure this keep out zone, use register READOUT_CFG4.
Value at Reset:	0x0

LINE_TIME (15:0) <i>RW</i>	LINE TIME This register definel the length of one line of the sensor. It includes blanking and valid time . Line Time Unit is SENSOR Clock Cycles
Value at Reset:	0x16e
Possible Values:	Any Value between 1 and 255

READOUT_CFG4

Address: section "ACQ" base address + 0x024

31	30	29	28	27	26	25	24
KEEP_OUT_TRIG_END(15:8)							
23	22	21	20	19	18	17	16
KEEP_OUT_TRIG_END(7:0)							
15	14	13	12	11	10	9	8
KEEP_OUT_TRIG_START(15:8)							
7	6	5	4	3	2	1	0
KEEP_OUT_TRIG_START(7:0)							

KEEP_OUT_TRIG_END (15:0)	
<i>RW</i>	During the line time, this register indicates the end of the trigger keep-out zone.
Value at Reset:	0x16d

KEEP_OUT_TRIG_START (15:0)	
<i>RW</i>	During the line time, this register indicates the start of the trigger keep-out zone.
Value at Reset:	0x16e

EXP_CTRL1

Address: section "ACQ" base address + 0x028

31	30	29	28	27	26	25	24
Reserved			EXPOSURE_lev_MODE	EXPOSURE_SS(27:24)			
23	22	21	20	19	18	17	16
EXPOSURE_SS(23:16)							
15	14	13	12	11	10	9	8
EXPOSURE_SS(15:8)							
7	6	5	4	3	2	1	0
EXPOSURE_SS(7:0)							

EXPOSURE_LEV_MODE	EXPOSURE LEVel MODE	
<i>RW</i>	This is the exposure level mode selector. When selecting the TRIGGER ACTIVATION = Level Mode, this register selects the exposure method used. When this register is set to '0' the timed mode is selected; Register EXPOSURE_SS is used for the exposure time. When this register is set to '1' the external trigger width is used for the exposure time.	
Value at Reset:	0x0	
Possible Values:	0x0	Timed Mode
	0x1	Trigger Width

EXPOSURE_SS (27:0)	EXPOSURE Single Slope	
<i>RW</i>	This is the total exposure time in single/dual/triple slope mode.	
	This register is double buffered.	
Value at Reset:	0x0	
Possible Values:	Any Value	Any 28 bits value

EXP_CTRL2

Address: section "ACQ" base address + 0x030

31	30	29	28	27	26	25	24
Reserved				EXPOSURE_DS(27:24)			
23	22	21	20	19	18	17	16
EXPOSURE_DS(23:16)							
15	14	13	12	11	10	9	8
EXPOSURE_DS(15:8)							
7	6	5	4	3	2	1	0
EXPOSURE_DS(7:0)							

EXPOSURE_DS (27:0) <i>RW</i>	EXPOSURE Dual	
	This is a new 3d profiler feature We will be able to program upto 3 diferent exposure times (using unused multiSlope registers) Then we will be able to sequence those exposure times . Selection is made with input exposure_select.	
Value at Reset:	0x0	
Possible Values:	Any Value	Any 28 bits value

EXP_CTRL3

Address: section "ACQ" base address + 0x038

31	30	29	28	27	26	25	24
Reserved				EXPOSURE_TS(27:24)			
23	22	21	20	19	18	17	16
EXPOSURE_TS(23:16)							
15	14	13	12	11	10	9	8
EXPOSURE_TS(15:8)							
7	6	5	4	3	2	1	0
EXPOSURE_TS(7:0)							

EXPOSURE_TS (27:0) <i>RW</i>	EXPOSURE Tripple						
	This is a new 3d profiler feature We will be able to program upto 3 diferent exposure times (using unused multiSlope registers) Then we will be able to sequence those exposure times . Selection is made with input exposure_select.						
Value at Reset:	0x0						
Possible Values:	Any Value			Any 28 bits value			

TRIGGER_DELAY

Address: section "ACQ" base address + 0x040

31	30	29	28	27	26	25	24
Reserved				TRIGGER_DELAY(27:24)			
23	22	21	20	19	18	17	16
TRIGGER_DELAY(23:16)							
15	14	13	12	11	10	9	8
TRIGGER_DELAY(15:8)							
7	6	5	4	3	2	1	0
TRIGGER_DELAY(7:0)							

TRIGGER_DELAY (27:0) <i>RW</i>	TRIGGER_DELAY	
	This is the trigger delay. This trigger delay can be applied to HW(Only edge mode), SW and Continuous mode.	
	In HW level mode, the trigger cannot be delayed, since the level time represents the exposure time.	
	This register is double buffered	
Value at Reset:	0x0	
Possible Values:	Any Value	Any 28 bits value

STROBE_CTRL1

Address: section "ACQ" base address + 0x048

31	30	29	28	27	26	25	24
STROBE_E	Reserved		STROBE_PO L	STROBE_START(27:24)			
23	22	21	20	19	18	17	16
STROBE_START(23:16)							
15	14	13	12	11	10	9	8
STROBE_START(15:8)							
7	6	5	4	3	2	1	0
STROBE_START(7:0)							

STROBE_E <i>RW</i>	STROBE Enable	
	This register enables the strobe logic.	
	For Nexis 3 systems, to enable STROBE_A signal, STROBE_E and STROBE_A_EN must be enabled. For Nexis 3 systems, to enable STROBE_B signal, STROBE_E and STROBE_B_EN must be enabled.	
	For Nexis 3 systems, STROBE_A and STROBE B can be activated at the same time, in this case the two strobes will be the same as they share the same programming.	
	This register is double buffered	
Value at Reset:	0x0	
Possible Values:	0x0	Strobe disabled
	0x1	Strobe enabled

STROBE_POL <i>RW</i>	STROBE POLarity	
	This is the strobe polarity at the pin of the FPGA only for GTR systems.	
	For NEXIS3 systems use register ANPUT\IO\IO_OUT_POL\OUTx_POL	
	This register is not double buffered.	
Value at Reset:	0x0	
Possible Values:	0x0	Active high strobe
	0x1	Active low strobe

STROBE_START (27:0) <i>RW</i>	STROBE START	
	This is the strobe start location. This location depends on the Strobe Mode used.	
	In Strobe Mode='0', the start of the strobe is situated during the exposure time. In Strobe Mode='1', the start of the strobe is situated during the trigger delay.	
	This register is double buffered	
Value at Reset:	0x0	
Possible Values:	Any Value	Any 28 bits value

STROBE_CTRL2

Address: section "ACQ" base address + 0x050

31	30	29	28	27	26	25	24
STROBE_MO DE	Reserved	STROBE_B_ EN	STROBE_A_ EN	STROBE_END(27:24)			
23	22	21	20	19	18	17	16
STROBE_END(23:16)							
15	14	13	12	11	10	9	8
STROBE_END(15:8)							
7	6	5	4	3	2	1	0
STROBE_END(7:0)							

STROBE_MODE <i>RW</i>	STROBE MODE	
	This register selects the location of the Strobe Start.	
	When this register is set to 0, the STROBE_START register is located during the exposure timer.	
	When this register is set to 1, the STROBE_START register is located during the trigger delay timer.	
	In HW level mode the strobe mode must be set to STROBE MODE=0 since the trigger cannot be delayed.	
	This register is double buffered	
Value at Reset:	0x0	
Possible Values:	0x0	Strobe start during exposure
	0x1	Strobe start during trigger delay

STROBE_B_EN <i>RW</i>	STROBE phase B ENable	
	This field enables the generation of STROBE_B signal, for a NEXIS 3 system.	
	This register is double buffered to support back2back mode in nexis systems.	
Value at Reset:	0x0	
Possible Values:	0x0	Enable Strobe B
	0x1	Disable Strobe B

STROBE_A_EN <i>RW</i>	STROBE phase A ENable	
	This field enables the generation of STROBE_A signal(Default strobe), for a NEXIS 3 system.	
	This register is double buffered to support back2back mode in nexis systems.	
Value at Reset:	0x1	
Possible Values:	0x0	Enable Strobe A (default strobe)
	0x1	Disable Strobe A

STROBE_END (27:0) <i>RW</i>	STROBE END	
	This is the strobe end location. This location does not depend on the Strobe Mode used.	
	This register is double buffered	
Value at Reset:	0xffffffff	
Possible Values:	Any Value	Any 28 bits value

Address: section "ACQ" base address + 0x058

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							SER_RWn
15	14	13	12	11	10	9	8
Reserved						SER_CMD(1:0)	
7	6	5	4	3	2	1	0
Reserved			SER_RF_SS	Reserved			SER_WF_SS

SER_RWn	SERial Read/Writen	
<i>RW</i>	This register configures the type of the serial access to the CMOS sensor	
Value at Reset:	0x1	
Possible Values:	0x0	Write access
	0x1	Read access

SER_CMD (1:0)	SERial CoMmand	
<i>RW</i>	This is the type of command sent to the serial fifo.	
	To access the Sensor, write SER_WF_SS=1 with SER_CMD=0x0, with the parametters: SER_WRn, SER_ADD(8:0) and SER_DAT(15:0).	
	To insert a timer between fifo commands, write SER_WF_SS=1 with SER_CMD=0x1, with the parameter: SER_DAT(15:0). The value of the timer inserted is calculated with the following formula: $\text{Timer} = \text{SER_DAT}(15:0) * 1024 * \text{SYS_PERIOD}$, SYS_PERIOD is 1/62.5mhz. The granularity of the timer is 16.384us	
	To insert a Stop separator command, write SER_WF_SS=1 with SER_CMD=0x3. When the read logic encounter this command, it will stop read from the fifo until a new SER_RF_SS is received.	
Value at Reset:	0x0	
Possible Values:	0x0	CMOS sensor access COMMAND
	0x1	Insert timer COMMAND
	0x2	STOP separator COMMAND
	0x3	RESERVED

SER_RF_SS	SERial Read Fifo SnapShot	
<i>WO/AutoClr</i>	This is the read fifo snapshot. When the read fifo logic receives this snapshot, it will read all the fifo comands until a STOP separator command is read or Empty fifo is detected.	
Possible Values:	0x0	Idle
	0x1	Start Read FIFO

SER_WF_SS	SERial Write Fifo SnapShot	
<i>WO/AutoClr</i>	When the system toggle this bit, the address, data and command are wrote to the command fifo. This fifo can contain the entire dcf, so the driver will not need to pool the status bit. This is a auto reset bit register, so after the driver write one, the bit will be auto reset to 0. To start the FIFO read logic write '1' to regsiter SER_RF_SS.	
Possible Values:	0x0	Idle
	0x1	Write a command to the FIFO

Address: section "ACQ" base address + 0x060

31	30	29	28	27	26	25	24
SER_DAT(15:8)							
23	22	21	20	19	18	17	16
SER_DAT(7:0)							
15	14	13	12	11	10	9	8
Reserved	SER_ADD(14:8)						
7	6	5	4	3	2	1	0
SER_ADD(7:0)							

SER_DAT (15:0)	SERial interface DATA	
<i>RW</i>	This is the write data to be send to the CMOS sensor by the serial interface, or the config data to a TIMER command or to a POWER sequence command. See register SER_CMD.	
Value at Reset:	0x0	
Possible Values:	Any Value	Any 16 bits value

SER_ADD (14:0)	SERial interface ADDRESS	
<i>RW</i>	This is the read/write address of the register in the CMOS sensor.	
Value at Reset:	0x0	
Possible Values:	Any Value	Any 9 bits value

Address: section "ACQ" base address + 0x068

31	30	29	28	27	26	25	24
Reserved							SER_FIFO_EMPTY
23	22	21	20	19	18	17	16
Reserved							SER_BUSY
15	14	13	12	11	10	9	8
SER_DAT_R(15:8)							
7	6	5	4	3	2	1	0
SER_DAT_R(7:0)							

SER_FIFO_EMPTY	SERial FIFO EMPTY	
<i>RO</i>	This is the EMPTY flag of the xilinx fifo, when '1' there are no pending operations in the fifo.	

SER_BUSY	SERial BUSY	
<i>RO</i>	This is the BUSY status of the FIFO read logic. The flag will be set to '1' when the SER_RF_SS is set to '1'. It will be reseted to '0' when the read logic will decode a STOP separator command or when the FIFO will be empty.	
Possible Values:	0x0	FIFO read logic is idle
	0x1	FIFO read logic is running

SER_DAT_R (15:0)	SERial interface DATa Read	
<i>RO</i>	This is the data read from CMOS sensor.	
Possible Values:	Any Value	Any 16 bits value

Address: section "ACQ" base address + 0x090

31	30	29	28	27	26	25	24
Reserved							SENSOR_REFRESH_TEMP
23	22	21	20	19	18	17	16
Reserved							SENSOR_POWERDOWN
15	14	13	12	11	10	9	8
Reserved							SENSOR_COLOR
7	6	5	4	3	2	1	0
Reserved			SENSOR_REGISTER_UPDATE	Reserved		SENSOR_REGISTER_SETN	SENSOR_POWERUP

SENSOR_REFRESH_TEMP <i>WO/AutoClr</i>	SENSOR REFRESH TEMPerature						
	This register starts a sensor temperature read on the serial interface of the Python sensor. The temperature value readed will be available on field SENSOR_TEMP when field SENSOR_TEMP_VALID is set to '1'. [Pas utilise pour le moment dans IRIS4]						
Possible Values:	0x0	Idle					
	0x1	Starts a Temperature read on Python SPI interface					

SENSOR_POWERDOWN <i>WO/AutoClr</i>							
	After a PowerUp sequence(SESOR_POWERUP_DONE=1), successfull or not, this register can reset the clock oscillator and enable the reset to the sensor. This power down don't do power sequencing.						

SENSOR_COLOR <i>RW</i>	SENSOR COLOR						
	This register informs the datapath logic that a color sensor is used. This information is needed for the remapper logic.						
Value at Reset:	0x0						
Possible Values:	0x0	Monochrome sensor					
	0x1	Color sensor					

SENSOR_REG_UPDATE <i>RW</i>	SENSOR REGister UPDATE						
	By setting this bit to 1, the SENSOR CONTROLLER WILL UPDATE the programed CMOS sensor registers at the beginning of each grab.						
Value at Reset:	0x1						
Possible Values:	0x0	Do not update registers					
	0x1	Update registers					

SENSOR_RESETN	SENSOR RESET Not	
<i>RW</i>	After a successfull PowerUP sequence, writing this field to '0' reset the Python CMOS sensor.	
Value at Reset:	0x1	
Possible Values:	0x0	Reset the sensor after a successfull powerUP
	0x1	Nothing

SENSOR_POWERUP		
<i>WO/AutoClr</i>	This register Enables the clk oscillator and removes the reset from the sensor.	
Possible Values:	0x0	idle
	0x1	Start the power sequence

Address: section "ACQ" base address + 0x098

31	30	29	28	27	26	25	24
SENSOR_TEMP(7:0)							
23	22	21	20	19	18	17	16
SENSOR_TEMP_VALID	Reserved						SENSOR_POWERDOWN
15	14	13	12	11	10	9	8
Reserved		SENSOR_RESETN	SENSOR_OSC_EN	Reserved		SENSOR_VCC_PG	
7	6	5	4	3	2	1	0
Reserved						SENSOR_POWERUP_STATUS	SENSOR_POWERUP_DONE

SENSOR_TEMP (7:0) <i>RO</i>							
	This register gives the Temperature of the Python sensor after a SENSOR_REFRESH_TEMP snapshot. The field SENSOR_TEMP_VALID indicates when the SENSOR_TEMP value is valid.						
	[Pas utilise pour le moment dans IRIS4]						
Possible Values:	Any Value						

SENSOR_TEMP_VALID <i>RO</i>	SENSOR TEMPerature VALID						
	This field indicates that the field SENSOR_TEMP have valid temperature after a SENSOR_REFRESH_TEMP snapshot.						
	[Pas utilise pour le moment dans IRIS4]						
Possible Values:	0x0	SENSOR_TEMPERATURE register is not valid					
	0x1	SENSOR_TEMPERATURE register is valid					

SENSOR_POWERDOWN <i>RO</i>							
	This field indicates that the sensor is in powerdown state.						
Possible Values:	0x0	Not in powerdown state					
	0x1	Powerdown					

SENSOR_RESETN <i>RO</i>	SENSOR RESET N						
	This is the sensor RESETN status.						
Possible Values:	0x0	In reset state					
	0x1	Not in reset					

SENSOR_OSC_EN <i>RO</i>	SENSOR OSCILLATOR ENable						
	This is the sensor oscillator enable status.						
Possible Values:	0x0	Disable					
	0x1	Enable					

SENSOR_VCC_PG <i>RO</i>	SENSOR supply VCC Power Good	
	This is the VCC Power Good status (generated by external HW).	
	[TO BE DELETED, waiting for ON SEMI INFORMATION]	
Possible Values:	0x0	Disable
	0x1	Enable

SENSOR_POWERUP_STAT <i>RO</i>		
	When a powerup sequence is finish, this register indicates the result of the POWERUP sequence.	
Possible Values:	0x0	PowerUp sequence fail
	0x1	PowerUp sequence success

SENSOR_POWERUP_DONE <i>RO</i>		
	This register indicates that the POWERUP sequence is finish. Read register SENSOR_POWERUP_STAT to see the result.	
Possible Values:	0x0	PowerUp sequence not started
	0x1	PowerUp sequence finish

SENSOR SUBSAMPLING

Address: section "ACQ" base address + 0x09C

Description:

SENSOR ADDRESS

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
reserved1(11:4)							
7	6	5	4	3	2	1	0
reserved1(3:0)				ACTIVE_SUBSAMPLING_Y	reserved0	M_SUBSAMPLING_Y	SUBSAMPLING_X

reserved1 (11:0)	
<i>STATIC</i>	
Value at Reset:	0x0

ACTIVE_SUBSAMPLING_Y	
<i>RW</i>	Subsampling (Row) for ROI Configurations
Value at Reset:	0x0
Possible Values:	0x0
	0x1

reserved0	
<i>STATIC</i>	
Value at Reset:	0x0
Possible Values:	0x0 Idle
	0x1 Enable

M_SUBSAMPLING_Y	
<i>RW</i>	Subsampling (Row) for M Region
Value at Reset:	0x0
Possible Values:	0x0
	0x1

SUBSAMPLING_X	
<i>RW</i>	Readout in Column Subsampling Mode
Value at Reset:	0x0
Possible Values:	0x0
	0x1

SENSOR_GAIN_ANA

Address: section "ACQ" base address + 0x0A4

Description:

SENSOR ADDRESS 204 DEC

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
reserved1(4:0)				ANALOG_GAIN(2:0)			
7	6	5	4	3	2	1	0
reserved0(7:0)							

reserved1 (4:0)	
<i>STATIC</i>	
Value at Reset:	0x0

ANALOG_GAIN (2:0)	
<i>RW</i>	
Value at Reset:	0x1
Possible Values:	0x11x
	0x32x
	0x74x

reserved0 (7:0)	
<i>STATIC</i>	
Value at Reset:	0x0

SENSOR ROI_Y_START

Address: section "ACQ" base address + 0x0A8

Description:
SENSOR ADDRESS

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
reserved(5:0)						Y_START(9:8)	
7	6	5	4	3	2	1	0
Y_START(7:0)							

reserved (5:0)	
STATIC	
Value at Reset:	0x0

Y_START (9:0)	Y START
RW	Y Start in Kernel size (Kernel is 4 lines)
Value at Reset:	0x0

SENSOR ROI_Y_SIZE

Address: section "ACQ" base address + 0x0AC

Description:
SENSOR ADDRESS

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
reserved(5:0)						Y_SIZE(9:8)	
7	6	5	4	3	2	1	0
Y_SIZE(7:0)							

reserved (5:0)	
STATIC	
Value at Reset:	0x0

Y_SIZE (9:0)	Y SIZE
RW	Y SIZE in Kernel size (Kernel is 4 lines)
Value at Reset:	0x302

SENSOR ROI2_Y_START

Address: section "ACQ" base address + 0x0B0

Description:
SENSOR ADDRESS

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
reserved(5:0)						Y_START(9:8)	
7	6	5	4	3	2	1	0
Y_START(7:0)							

reserved (5:0)	
STATIC	
Value at Reset:	0x0

Y_START (9:0)	Y START
RW	Y Start in Kernel size (Kernel is 4 lines)
Value at Reset:	0x0

SENSOR ROI2_Y_SIZE

Address: section "ACQ" base address + 0x0B4

Description:
SENSOR ADDRESS

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
reserved(5:0)						Y_SIZE(9:8)	
7	6	5	4	3	2	1	0
Y_SIZE(7:0)							

reserved (5:0)	
STATIC	
Value at Reset:	0x0

Y_SIZE (9:0)	Y SIZE
RW	Y SIZE in Kernel size (Kernel is 4 lines)
Value at Reset:	0x302

SENSOR M LINES

Address: section "ACQ" base address + 0x0B8

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved	M_SUPPRESSED(4:0)					M_LINES_SENSOR(9:8)	
7	6	5	4	3	2	1	0
M_LINES_SENSOR(7:0)							

M_SUPPRESSED (4:0)	
<i>RW</i>	Suppress the Readout of Initial Lines in the M Region
Value at Reset:	0x0

M_LINES_SENSOR (9:0)	
<i>RW</i>	Number of Lines to Readout from M Region in Context 0 Unit is #lines Total number of Black lines = M_LINES Total number of Black lines transfered as valid Black lines= M_LINES-M_SUPRESSED
Value at Reset:	0x8

SENSOR DP GR

Address: section "ACQ" base address + 0x0BC

Description:

Sensor Analog data pedestal for Gr pixels (Black offset)

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
reserved(3:0)				DP_OFFSET_GR(11:8)			
7	6	5	4	3	2	1	0
DP_OFFSET_GR(7:0)							

reserved (3:0)	
<i>STATIC</i>	
Value at Reset:	0x0

DP_OFFSET_GR (11:0)	
<i>RW</i>	Sensor Analog data pedestal for Gr pixels (Black offset)
Value at Reset:	0x100

SENSOR DP_GB

Address: section "ACQ" base address + 0x0C0

Description:

Sensor Analog data pedestal for Gb pixels (Black offset)

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
reserved(3:0)				DP_OFFSET_GB(11:8)			
7	6	5	4	3	2	1	0
DP_OFFSET_GB(7:0)							

reserved (3:0)	
<i>STATIC</i>	
Value at Reset:	0x0

DP_OFFSET_GB (11:0)	
<i>RW</i>	Sensor Analog data pedestal for Gb pixels (Black offset)
Value at Reset:	0x100

SENSOR DP R

Address: section "ACQ" base address + 0x0C4

Description:

Sensor Analog data pedestal for R pixels (Black offset)

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
reserved(3:0)				DP_OFFSET_R(11:8)			
7	6	5	4	3	2	1	0
DP_OFFSET_R(7:0)							

reserved (3:0)	
<i>STATIC</i>	
Value at Reset:	0x0

DP_OFFSET_R (11:0)	
<i>RW</i>	Sensor Analog data pedestal for R pixels (Black offset)
Value at Reset:	0x100

SENSOR DP B

Address: section "ACQ" base address + 0x0C8

Description:

Sensor Analog data pedestal for B pixels (Black offset)

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
reserved(3:0)				DP_OFFSET_B(11:8)			
7	6	5	4	3	2	1	0
DP_OFFSET_B(7:0)							

reserved (3:0)	
<i>STATIC</i>	
Value at Reset:	0x0

DP_OFFSET_B (11:0)	
<i>RW</i>	Sensor Analog data pedestal for B pixels (Black offset)
Value at Reset:	0x100

SENSOR X SIZE

Address: section "ACQ" base address + 0x0CC

Description:

SENSOR X SIZE

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved				SENSOR_X_SIZE(12:8)			
7	6	5	4	3	2	1	0
SENSOR_X_SIZE(7:0)							

SENSOR_X_SIZE (12:0)	
<i>RW</i>	<p>SENSOR X SIZE is the complete X size of the sensor defined in number of pixels. It includes dummy pixels, black reference pixels, interpolation pixels and valid pixels. The sensor X size differs between XGS family members and configurations. The dcf will load the X size. It is defined as 1-based number.</p> <p>For XGS12000, the value is 4176 (0x1050)</p>
Value at Reset:	0x1050

SENSOR_X_START

Address: section "ACQ" base address + 0x0D0

Description:

SENSOR_X_START

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved				SENSOR_X_START(12:8)			
7	6	5	4	3	2	1	0
SENSOR_X_START(7:0)							

SENSOR_X_START (12:0)	
<i>RW</i>	<p>This register defines the position of the first horizontal valid pixel (including dummy pixels, black reference pixels and interpolation pixels). The location of the first X valid pixel differs between XGS family members and configurations. The dcf will load the location of the X start. It is defined as 1-based number</p> <p>For XGS12000, in a monochrome sensor the x start is 36 (0x24). For XGS12000, in a color sensor the x start is 32 (0x22). (For BAYER correction)</p>
Value at Reset:	0x24

SENSOR_X_END

Address: section "ACQ" base address + 0x0D4

Description:

SENSOR_X_ORIGIN location (X Start)

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved				SENSOR_X_END(12:8)			
7	6	5	4	3	2	1	0
SENSOR_X_END(7:0)							

SENSOR_X_END (12:0)	
<i>RW</i>	<p>This register defines the position of the last horizontal valid pixel (including initial dummy pixels, black reference pixels and interpolation pixels). The location of the last X valid pixel differs between XGS family members and configurations. The dcf will load the location of the X end. It is defined as 1-based number</p> <p>For XGS12000, in a monochrome sensor the x end is 4132 (0x1024). For XGS12000, in a color sensor the x end is 4136 (0x1028). (For BAYER correction)</p>
Value at Reset:	0x1023

DEBUG PINS

Address: section "ACQ" base address + 0x0E0

31	30	29	28	27	26	25	24
Reserved				Debug3_sel(4:0)			
23	22	21	20	19	18	17	16
Reserved				Debug2_sel(4:0)			
15	14	13	12	11	10	9	8
Reserved				Debug1_sel(4:0)			
7	6	5	4	3	2	1	0
Reserved				Debug0_sel(4:0)			

Debug3_sel (4:0) <i>RW</i>	
	<pre> debug_vector(0x0) <= python_monitor0; debug_vector(0x1) <= python_monitor1; debug_vector(0x2) <= grab_mgr_trig_rdy; debug_vector(0x3) <= curr_trig0; debug_vector(0x4) <= strobe; debug_vector(0x5) <= python_exposure; debug_vector(0x6) <= FOT; debug_vector(0x7) <= readout; debug_vector(0x8) <= readout_stateD; debug_vector(0x9) <= ext_trig; debug_vector(0xa) <= REGFILE.ACQ.GRAB_CTRL.GRAB_CMD; debug_vector(0xb) <= REGFILE.ACQ.GRAB_CTRL.GRAB_SS; debug_vector(0xc) <= grab_mgr_trig; debug_vector(0xd) <= grab_mgr_trig_rdy; debug_vector(0xe) <= grab_pending; debug_vector(0xf) <= grab_active; debug_vector(0x10) <= DEC_DATA_EN; debug_vector(0x11) <= DEC_SOL; debug_vector(0x12) <= DEC_SOF; debug_vector(0x13) <= DEC_EOL; debug_vector(0x14) <= DEC_EOF; debug_vector(0x15) <= DEC_CRC; debug_vector(0x16) <= DEC_TRAIN; debug_vector(0x17) <= fpnprnu_corr_sof; debug_vector(0x18) <= fpnprnu_corr_sol; debug_vector(0x19) <= fpnprnu_corr_data_val; debug_vector(0x1a) <= fpnprnu_corr_eol; debug_vector(0x1b) <= fpnprnu_corr_eof; debug_vector(0x1c) <= python_ssn_int; debug_vector(0x1d) <= debug_lvds(0); debug_vector(0x1e) <= debug_lvds(1); debug_vector(0x1f) <= 'Z'; </pre>
Value at Reset:	0x1f

Debug2_sel (4:0) <i>RW</i>	<pre> debug_vector(0x0) <= python_monitor0; debug_vector(0x1) <= python_monitor1; debug_vector(0x2) <= grab_mngr_trig_rdy; debug_vector(0x3) <= curr_trig0; debug_vector(0x4) <= strobe; debug_vector(0x5) <= python_exposure; debug_vector(0x6) <= FOT; debug_vector(0x7) <= readout; debug_vector(0x8) <= readout_stateD; debug_vector(0x9) <= ext_trig; debug_vector(0xa) <= REGFILE.ACQ.GRAB_CTRL.GRAB_CMD; debug_vector(0xb) <= REGFILE.ACQ.GRAB_CTRL.GRAB_SS; debug_vector(0xc) <= grab_mngr_trig; debug_vector(0xd) <= grab_mngr_trig_rdy; debug_vector(0xe) <= grab_pending; debug_vector(0xf) <= grab_active; debug_vector(0x10) <= DEC_DATA_EN; debug_vector(0x11) <= DEC_SOL; debug_vector(0x12) <= DEC_SOF; debug_vector(0x13) <= DEC_EOL; debug_vector(0x14) <= DEC_EOF; debug_vector(0x15) <= DEC_CRC; debug_vector(0x16) <= DEC_TRAIN; debug_vector(0x17) <= fpnprnu_corr_sof; debug_vector(0x18) <= fpnprnu_corr_sol; debug_vector(0x19) <= fpnprnu_corr_data_val; debug_vector(0x1a) <= fpnprnu_corr_eol; debug_vector(0x1b) <= fpnprnu_corr_eof; debug_vector(0x1c) <= python_ssn_int; debug_vector(0x1d) <= debug_lvds(0); debug_vector(0x1e) <= debug_lvds(1); debug_vector(0x1f) <= 'Z'; </pre>
Value at Reset:	0x1f

Debug1_sel (4:0) <i>RW</i>	<pre> debug_vector(0x0) <= python_monitor0; debug_vector(0x1) <= python_monitor1; debug_vector(0x2) <= grab_mngr_trig_rdy; debug_vector(0x3) <= curr_trig0; debug_vector(0x4) <= strobe; debug_vector(0x5) <= python_exposure; debug_vector(0x6) <= FOT; debug_vector(0x7) <= readout; debug_vector(0x8) <= readout_stateD; debug_vector(0x9) <= ext_trig; debug_vector(0xa) <= REGFILE.ACQ.GRAB_CTRL.GRAB_CMD; debug_vector(0xb) <= REGFILE.ACQ.GRAB_CTRL.GRAB_SS; debug_vector(0xc) <= grab_mngr_trig; debug_vector(0xd) <= grab_mngr_trig_rdy; debug_vector(0xe) <= grab_pending; debug_vector(0xf) <= grab_active; debug_vector(0x10) <= DEC_DATA_EN; debug_vector(0x11) <= DEC_SOL; debug_vector(0x12) <= DEC_SOF; debug_vector(0x13) <= DEC_EOL; debug_vector(0x14) <= DEC_EOF; debug_vector(0x15) <= DEC_CRC; debug_vector(0x16) <= DEC_TRAIN; debug_vector(0x17) <= fpnprnu_corr_sof; debug_vector(0x18) <= fpnprnu_corr_sol; debug_vector(0x19) <= fpnprnu_corr_data_val; debug_vector(0x1a) <= fpnprnu_corr_eol; debug_vector(0x1b) <= fpnprnu_corr_eof; debug_vector(0x1c) <= python_ssn_int; debug_vector(0x1d) <= debug_lvds(0); debug_vector(0x1e) <= debug_lvds(1); debug_vector(0x1f) <= 'Z'; </pre>
Value at Reset:	0x1f

Debug0_sel (4:0) RW	<pre> debug_vector(0x0) <= python_monitor0; debug_vector(0x1) <= python_monitor1; debug_vector(0x2) <= grab_mngr_trig_rdy; debug_vector(0x3) <= curr_trig0; debug_vector(0x4) <= strobe; debug_vector(0x5) <= python_exposure; debug_vector(0x6) <= FOT; debug_vector(0x7) <= readout; debug_vector(0x8) <= readout_stateD; debug_vector(0x9) <= ext_trig; debug_vector(0xa) <= REGFILE.ACQ.GRAB_CTRL.GRAB_CMD; debug_vector(0xb) <= REGFILE.ACQ.GRAB_CTRL.GRAB_SS; debug_vector(0xc) <= grab_mngr_trig; debug_vector(0xd) <= grab_mngr_trig_rdy; debug_vector(0xe) <= grab_pending; debug_vector(0xf) <= grab_active; debug_vector(0x10) <= DEC_DATA_EN; debug_vector(0x11) <= DEC_SOL; debug_vector(0x12) <= DEC_SOF; debug_vector(0x13) <= DEC_EOL; debug_vector(0x14) <= DEC_EOF; debug_vector(0x15) <= DEC_CRC; debug_vector(0x16) <= DEC_TRAIN; debug_vector(0x17) <= fpnprnu_corr_sof; debug_vector(0x18) <= fpnprnu_corr_sol; debug_vector(0x19) <= fpnprnu_corr_data_val; debug_vector(0x1a) <= fpnprnu_corr_eol; debug_vector(0x1b) <= fpnprnu_corr_eof; debug_vector(0x1c) <= python_ssn_int; debug_vector(0x1d) <= debug_lvds(0); debug_vector(0x1e) <= debug_lvds(1); debug_vector(0x1f) <= 'Z'; </pre>
Value at Reset:	0x1f

TRIGGER_MISSED

Address: section "ACQ" base address + 0x0E8

31	30	29	28	27	26	25	24
Reserved			TRIGGER_MISSED_RST	Reserved			
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
TRIGGER_MISSED_CNTR(15:8)							
7	6	5	4	3	2	1	0
TRIGGER_MISSED_CNTR(7:0)							

TRIGGER_MISSED_RST	TRIGGER MISSED ReSeT	
WO/AutoClr	This is the trigger missed reset.	
Possible Values:	0x1	Reset the Trigger counter reset

TRIGGER_MISSED_CNTR (15:0)	TRIGGER MISSED CouNTeR	
RO	This is the number of trigger missed detected.	
Possible Values:	Any Value	

SENSOR_FPS

Address: section "ACQ" base address + 0x0F0

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
SENSOR_FPS(15:8)							
7	6	5	4	3	2	1	0
SENSOR_FPS(7:0)							

SENSOR_FPS (15:0) RO	SENSOR Frame Per Second
	This is the number of frames received in 1 second interval. This register can count up to 64k frame/s. This counter counts on SO_FOT event.

DEBUG

Address: section "ACQ" base address + 0x1A0

31	30	29	28	27	26	25	24
FPGA_7c706	Reserved			DEBUG_RST_CNTR	Reserved		
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved							
7	6	5	4	3	2	1	0
Reserved					LED_TEST_COLOR(1:0)		LED_TEST

FPGA_7c706 <i>RO</i>							
	This field indicates that the FPGA is compiled for a Xilinx 7C706 Evaluation Board for use with Xcelerator sensor board.						
Possible Values:	0x0	Artix fpga					
	0x1	Zynq fpga					

DEBUG_RST_CNTR <i>RW</i>							
	This register clears the debug cnts						
Value at Reset:	0x1						
Possible Values:	0x0						
	0x1	Reset counters					

LED_TEST_COLOR (1:0) <i>RW</i>							
Value at Reset:	0x0						
Possible Values:	0x0	The LED is OFF					
	0x1	The LED is GREEN					
	0x2	The LED is RED					
	0x3	The LED is ORANGE					

LED_TEST <i>RW</i>							
	This register will put the LED status in test mode. The test mode is controlled by LED_TEST_COLOR						
Value at Reset:	0x0						
Possible Values:	0x0	The LED is in user mode.					
	0x1	The LED is in test mode.					

DEBUG_CNTR1

Address: section "ACQ" base address + 0x1A8

31	30	29	28	27	26	25	24
Reserved				SENSOR_FRAME_DURATION(27:24)			
23	22	21	20	19	18	17	16
SENSOR_FRAME_DURATION(23:16)							
15	14	13	12	11	10	9	8
SENSOR_FRAME_DURATION(15:8)							
7	6	5	4	3	2	1	0
SENSOR_FRAME_DURATION(7:0)							

SENSOR_FRAME_DURATION (27:0) <i>RO</i>							
	This is the time between the last 2 EOF received(in sys clock domain). This register can count up to 4.29 seconds. It can be used to predict sensor framerate or to verify sync between 3D profiler heads. This feature is enabled by setting register regfile.ACQ.DEBUG.DEBUG_RST_CNTR to 0.						
Possible Values:	Any Value			Any 28 bits value			

EXP_FOT

Address: section "ACQ" base address + 0x1B8

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							EXP_FOT
15	14	13	12	11	10	9	8
Reserved				EXP_FOT_TIME(11:8)			
7	6	5	4	3	2	1	0
EXP_FOT_TIME(7:0)							

EXP_FOT <i>RW</i>	EXPosure during FOT	
	When set to '1' this register, the output exposure and strobe signals will take into account the exposure in the FOT of the frame. This timing must be programmed in register EXP_FOT_TIME. This timing must be calculated from the OnSemi setting files .	
Value at Reset:	0x1	
Possible Values:	0x0	Disable exposure during FOT in output exposure signal and Strobe
	0x1	Enable exposure during FOT in output exposure signal and Strobe

EXP_FOT_TIME (11:0) <i>RW</i>	EXPosure during FOT TIME	
	This is the time of the exposure during the FOT. This timing must be calculated from the OnSemi setting files . From DCF v1.2, for all LVDS modes : P5000 & P2000 EXP_FOT=40.666us, program value 0x9ee P1300 & P500 & P300 EXP_FOT=27.333us, program value 0x6ac	
Value at Reset:	0x9ee	

ACQ_SFNC

Address: section "ACQ" base address + 0x1C0

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved							
7	6	5	4	3	2	1	0
Reserved							RELOAD_GRAB_PARAMS

RELOAD_GRAB_PARAMS		
<i>RW</i>	This register is not used for the moment. It may be used in the future to reload the exposure time	
Value at Reset:	0x1	
Possible Values:	0x0	
	0x1	

Address Range: [0x400 - 0x44C]

CTRL

Address: section "HISPI" base address + 0x000

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved							
7	6	5	4	3	2	1	0
Reserved			SW_CLR_ID ELAYCTRL	SW_CLR_HIS PI	SW_CALIB_S ERDES	ENABLE_DA TA_PATH	ENABLE_HIS PI

SW_CLR_IDELAYCTRL	Reset the Xilinx macro IDELAYCTRL		
<i>RW</i>			
Value at Reset:	0x0		
Possible Values:	0x0	No effect	
	0x1	Reset IDELAYCTRL	

SW_CLR_HISPI			
<i>RW</i>			
Value at Reset:	0x0		

SW_CALIB_SERDES	Initiate the SERDES TAP calibration		
<i>WO/AutoClr</i>			
Possible Values:	0x0	No effect	
	0x1	Initiate the calibration	

ENABLE_DATA_PATH			
<i>RW</i>			
Value at Reset:	0x0		

ENABLE_HISPI			
<i>RW</i>			
Value at Reset:	0x0		

Address: section "HISPI" base address + 0x004

31	30	29	28	27	26	25	24
FSM(3:0)				Reserved			
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved							
7	6	5	4	3	2	1	0
Reserved				PHY_BIT_LOCKED_ERROR	FIFO_ERROR	CALIBRATION_ERROR	CALIBRATION_DONE

FSM (3:0)	HISPI finite state machine status	
<i>RO</i>		
Possible Values:	0x0	S_DISABLED
	0x1	S_IDLE
	0x2	S_RESET_PHY
	0x3	S_INIT
	0x4	S_START_CALIBRATION
	0x5	S_CALIBRATE
	0x6	S_PACK
	0x7	S_FLUSH_PACKER
	0x8	S_SOF
	0x9	S_EOF
	0xA	S_SOL
	0xB	S_EOL
	0xC	Reserved
	0xD	Reserved
	0xE	FSM error (Unknown state)
	0xF	S_DONE

PHY_BIT_LOCKED_ERROR	
<i>RO</i>	

FIFO_ERROR	Calibration active
<i>RO</i>	

CALIBRATION_ERROR	Calibration active
<i>RO</i>	

CALIBRATION_DONE	Calibration active
<i>RO</i>	

IDELAYCTRL_STATUS

Address: section "HISPI" base address + 0x008

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved							
7	6	5	4	3	2	1	0
Reserved							PLL_LOCKED

PLL_LOCKED RO	IDELAYCTRL PLL locked	
Possible Values:	0x0	IDELAYCTRL PLL unlocked
	0x1	IDELAYCTRL PLL locked

IDLE CHARACTER

Address: section "HISPI" base address + 0x00C

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved				VALUE(11:8)			
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (11:0)		
RW		
Value at Reset:	0x3A6	
Possible Values:	Any Value	

LANE_DECODER_STATUS (5:0)

Address: section "HISPI" base address + 0x010 + (index * 0x4)

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved	PHY_SYNC_ERROR	PHY_BIT_LOCKED_ERROR	PHY_BIT_LOCKED	Reserved			CALIBRATION_TAP_VALUE(4)
7	6	5	4	3	2	1	0
CALIBRATION_TAP_VALUE(3:0)				CALIBRATION_ERROR	CALIBRATION_DONE	FIFO_UNDRUN	FIFO_OVERFLOW

PHY_SYNC_ERROR <i>RW2C</i>							
Value at Reset:	0x0						
Possible Values:	0x0			Pixel bit boundaries unlocked			
	0x1			Pixel bit boundaries locked			

PHY_BIT_LOCKED_ERROR <i>RW2C</i>							
Value at Reset:	0x0						
Possible Values:	0x0			Pixel bit boundaries unlocked			
	0x1			Pixel bit boundaries locked			

PHY_BIT_LOCKED <i>RO</i>							
Possible Values:	0x0			Pixel bit boundaries unlocked			
	0x1			Pixel bit boundaries locked			

CALIBRATION_TAP_VALUE (4:0) <i>RO</i>							

CALIBRATION_ERROR <i>RW2C</i>							
Value at Reset:	0x0						

CALIBRATION_DONE <i>RO</i>							

FIFO_UNDERRUN <i>RW2C</i>	
Value at Reset:	0x0

FIFO_OVERRUN <i>RW2C</i>	
Value at Reset:	0x0

TAP HISTOGRAM (5:0)

Address: section "HISPI" base address + 0x028 + (index * 0x4)

31	30	29	28	27	26	25	24
VALUE(31:24)							
23	22	21	20	19	18	17	16
VALUE(23:16)							
15	14	13	12	11	10	9	8
VALUE(15:8)							
7	6	5	4	3	2	1	0
VALUE(7:0)							

VALUE (31:0)	
RO	

LANE PACKER STATUS (2:0)

Address: section "HISPI" base address + 0x040 + (index * 0x4)

31	30	29	28	27	26	25	24
Reserved							
23	22	21	20	19	18	17	16
Reserved							
15	14	13	12	11	10	9	8
Reserved							
7	6	5	4	3	2	1	0
Reserved						FIFO_UNDE RRUN	FIFO_OVERR UN

FIFO_UNDERRUN RW2C	
Value at Reset:	0x0

FIFO_OVERRUN RW2C	
Value at Reset:	0x0

DEBUG

Address: section "HISPI" base address + 0x04C

31	30	29	28	27	26	25	24
MANUAL_C ALIB_EN	LOAD_TAPS	TAP_LANE_5(4:0)				TAP_LANE_4 (4)	
23	22	21	20	19	18	17	16
TAP_LANE_4(3:0)				TAP_LANE_3(4:1)			
15	14	13	12	11	10	9	8
TAP_LANE_3 (0)	TAP_LANE_2(4:0)				TAP_LANE_1(4:3)		
7	6	5	4	3	2	1	0
TAP_LANE_1(2:0)			TAP_LANE_0(4:0)				

MANUAL_CALIB_EN <i>RW</i>	
Value at Reset:	0x0

LOAD_TAPS <i>WO/AutoClr</i>	

TAP_LANE_5 (4:0) <i>RW</i>	
Value at Reset:	0x0

TAP_LANE_4 (4:0) <i>RW</i>	
Value at Reset:	0x0

TAP_LANE_3 (4:0) <i>RW</i>	
Value at Reset:	0x0

TAP_LANE_2 (4:0) <i>RW</i>	
Value at Reset:	0x0

TAP_LANE_1 (4:0) <i>RW</i>	
Value at Reset:	0x0

TAP_LANE_0 (4:0) <i>RW</i>	
Value at Reset:	0x0