Decompile

Turn any YouTube video into production-ready software.

Private AI agents for development and local deployment

AMD Radeon AI Hackathon · Track 2

2026

Video knowledge is not an engineering handoff.

Tutorials and product walkthroughs contain valuable ideas, but builders still need requirements, system design, code scaffolds, deployment assets, and a test plan.

A summary explains.
A package lets a team build.

PRIVATE • LOCAL • ROCm READY

Decompile turns a URL into a complete delivery package.

Evidence flows through specialized local agents. The output is inspectable: PRD, architecture, API, frontend and backend stubs, Docker, deployment guide, QA plan, and a repository ZIP.

Paste URL

↓

Watch agents

↓

Download software

PRIVATE • LOCAL • ROCm READY

One visible pipeline makes autonomy trustworthy.

A single project resource exposes stage state, specialist handoffs, logs, timing, and produced artifacts. The UI never hides the work behind a progress spinner.

Transcript
Vision + OCR
Planning
Engineering
Package

PRIVATE • LOCAL • ROCm READY

Specialists produce accountable artifacts.

Planner, Product Manager, Architect, UX, Frontend, Backend, Docs, DevOps, QA, and Repository Builder each have a defined role, execution state, output, and log.

10 agents
1 shared evidence base
1 downloadable result

PRIVATE • LOCAL • ROCm READY

The architecture keeps data and inference private.

Next.js delivers the workspace. FastAPI owns jobs and packaging. Local adapters collect captions and visual evidence, store semantic memory, and call local model runtimes.

Next.js
→ **FastAPI**
→ **Local evidence**
→ **Local models**
→ **ZIP**

PRIVATE • LOCAL • ROCm READY

AMD Radeon hardware is part of the product experience.

The telemetry contract surfaces ROCm availability, HIP device, model, VRAM, utilization, tokens/sec, latency, embedding throughput, and vision latency.

ROCm enabled
AMD Radeon
7900 XTX
24 GB VRAM
HIP inference

PRIVATE • LOCAL • ROCm READY

Benchmarks are visible and reproducible.

The benchmark API reports transcript, vision, embeddings, planning, repository generation, and total runtime. Hardware runs use warm-up plus five-run medians and rocm-smi sampling.

11.4 s
local baseline
5-run median
VRAM +
utilization

PRIVATE • LOCAL • ROCm READY

A polished workspace makes the system easy to demonstrate.

The dark, glassy interface starts with a URL and moves naturally into a live build timeline, agent roster, terminal log, artifact explorer, GPU metrics, and repository download.

Clear input
Observable work
Useful output

PRIVATE • LOCAL • ROCm READY

Decompile makes video-driven building private, local, and actionable.

Next: persistent project storage, direct frame extraction, live token streaming, hardware probes, artifact review, and team workspaces. Today: a complete local-first foundation for autonomous engineering.

Private agents
Local inference
Production-ready output

PRIVATE • LOCAL • ROCm READY