Tensor Network Simulation of the Heisenberg Model on Heavy-Hex Lattices

Paolo D'Alberto*
Advanced Micro Devices, Inc.
paolo.dalberto@amd.com

August 2, 2026

Abstract

We extend CppSim, a high-performance C++/HIP tensor network simulator, to the heavy-hex lattice geometry used in superconducting quantum processors. The heavy-hex graph — a bipartite graph of degree-2 and degree-3 sites with a natural 3-color gate schedule — is implemented as a drop-in grid class with no changes to the gate application or belief propagation (BP) kernels. We simulate the isotropic Heisenberg model on the `heavy_hex_3x3` graph (68 sites, 76 bonds) in the Heisenberg picture using Pauli transfer matrices (PTMs), and study the autocorrelation $C(t) = \langle Z_c(t) Z_c(0) \rangle$ and operator lightcone. We incorporate a fully parametric hardware noise model: per-bond, per-color-class 16×16 PTMs are loaded from device characterization data and interleaved with unitary gates, with noise scaling factor $\gamma \in \{1.0, 2.0, 3.0\}$ for multi-product formula (MPF) extrapolation to zero noise. Chi convergence is demonstrated at $\chi = 200$ ($|\text{error}| < 10^{-4}$, reference $\chi = 430$) on a 32 GB GPU, with a $\sim 10\times$ wall-clock speedup over a Julia/AMDGPU.jl reference implementation at saturated bond dimension.

1 Introduction

Heavy-hex is the lattice topology used in superconducting quantum processors [1]. Each qubit site has degree 2 or 3, and the graph admits a natural 3-coloring of its bonds, enabling parallel gate application within each color class.

Classical tensor network simulation of quantum circuits on heavy-hex graphs serves two purposes: (i) validation of quantum computations for small system sizes where exact simulation is feasible [2, 3, 4, 5], and (ii) computation of noise-free reference values for quantum error mitigation protocols such as the multi-product formula (MPF) [6].

In this paper we show that CppSim [7], originally developed for rectangular 2D Ising dynamics, extends naturally to heavy-hex topology with minimal code changes. The hot-path kernels — gate application, BP, workspace management — are topology-agnostic and require no modification. Only the grid construction and Hamiltonian gate matrix need to be defined for the new geometry. We further incorporate a fully parametric hardware noise model via Pauli transfer matrices, and demonstrate gamma-MPF extrapolation to zero noise using three noise amplification levels $\gamma \in \{1, 2, 3\}$.

*Advanced Micro Devices, Inc. (AMD). paolo.dalberto@amd.com. This work was developed in active collaboration with Claude (Anthropic)




Figure 1: One unit cell of the heavy-hex graph. Junction sites (blue, degree 3) connect via arm sites (orange, degree 2). Bonds are 3-edge-colorable (red, blue, green), enabling parallel gate application within each color class.

2 Heavy-Hex Lattice and Hamiltonian

The `heavy_hex_`$n_x \times n_y$ graph $G = (V, E)$ (Fig. 1) has $n_x \cdot n_y$ *junction* sites of degree 3 and $(2n_xn_y+n_x+n_y)$ arm sites of degree 2, for a total of $|V| = 3n_xn_y + n_x + n_y$ sites and $|E| = 2n_xn_y + n_x + n_y$ bonds. For $n_x = n_y = 3$: $|V| = 68$ (16 junction +52 arm) and $|E| = 76$. We write $\partial v \subset E$ for the set of bonds incident to site v. The graph is bipartite and 3-edge-colorable — bonds partition into 3 color classes of sizes 25, 25, 26, corresponding to the natural gate layers of the hardware schedule.

Site tensors carry the evolved Pauli operator in the Heisenberg picture, with shapes $[\chi^2, D]$ (arm) and $[\chi^3, D]$ (junction), where $D = 4$ is the Pauli basis dimension $\{I, X, Y, Z\}$. The `FlatHeavyHexGrid` class inherits from `Grid` and populates the same `Site`/`Bond`/`Gate` data structures as the rectangular grid, with no changes to the gate, belief propagation, or workspace kernels.

We simulate the isotropic Heisenberg (XXX) model:

$$H = J \sum_{\langle ij \rangle} \left(X_i X_j + Y_i Y_j + Z_i Z_j \right) \tag{1}$$

with bond-specific coupling $J_{\langle ij \rangle}$ from device characterization and Trotter step ε. In the Heisenberg picture, the two-site gate $U = e^{-i\varepsilon J(X \otimes X + Y \otimes Y + Z \otimes Z)}$ is a 4×4 unitary acting on the two-qubit Hilbert space $\mathbb{C}^2 \otimes \mathbb{C}^2$. To track operator dynamics we work in the two-site Pauli basis $\{P_\mu \otimes P_\nu\}$ with $P_\mu \in \{I, X, Y, Z\}$, which has $4 \times 4 = 16$ elements — hence the state vector at each bond has dimension 16, and the gate acts as a 16×16 real Pauli transfer matrix (PTM) via $O \mapsto U^\dagger O U$. Here and below we use the physics shorthand $AB \equiv A \otimes B$, so $IX \equiv I \otimes X$, $YZ \equiv Y \otimes Z$, etc.

The PTM is block-diagonal because the XXX interaction conserves the *Pauli commutation signature*: for any two-site operator O, if $[H, O] = 0$ then $U^\dagger O U = O$ (invariant). The four operators $\{II, XX, YY, ZZ\}$ all commute with H, forming a 4×4 identity block. The remaining 12 operators decompose into three invariant *mixing* subspaces of size 4, determined by which single-site Pauli is "odd" under the symmetry. For example, the commutators of H with each of $\{IX, XI, YZ, ZY\}$ produce linear combinations within that same set, so it is closed under the adjoint action and evolves as a 4×4 rotation matrix. Cyclic permutation $X \to Y \to Z \to X$ yields the other two blocks $\{IY, YI, XZ, ZX\}$ and $\{IZ, ZI, XY, YX\}$. In total the PTM is block-diagonal with one 4×4 identity block and three 4×4 rotation blocks, all real.

3 Hardware Noise Model

We extend the simulation to include hardware noise channels characterized on the target device. In the Pauli transfer matrix (PTM) formalism, a noise channel $\mathcal{E}$ acting on a two-site operator is represented as a 16×16 real matrix $E_{ij} = d^{-1} \operatorname{Tr}(P_i^\dagger \, \mathcal{E}(P_j))$, where $\{P_i\}$ is the two-site Pauli basis. Since both operators and noise channels are Hermitian-preserving, E is real throughout, consistent with our float32 simulation.

Each bond implements the two-qubit interaction through a hardware decomposition $U_{\text{bond}} = R_{xx}(\alpha) \cdot R_{yy}(\alpha) \cdot R_{zz}(\delta)$, where $\alpha = -J_{\langle ij \rangle} \cdot \varepsilon$ scales with the bond coupling and Trotter step ε, while $\delta = -J_{\langle ij \rangle}$ is independent of ε. Noise is interleaved after each sub-gate, and the full noisy gate for bond b in its color class is:

$$\text{PTM}^{(b)}_{\text{noisy}} = G_1 \cdot M^{(b)}_n \cdot G_2(\alpha_b) \cdot M^{(b)}_n \cdot G_3(\alpha_b) \cdot M^{(b)}_n \cdot G_4(\delta_b) \tag{2}$$

where $M^{(b)}_n$ is the hardware noise PTM for bond b in its color class, and G_1–G_4 implement the hardware sub-layers. After all color classes, a kick gate $R_x(2\phi)$ is applied once per site ($\phi = 1.41371669$).

The noise characterization is fully parametric: a configuration file specifies an independent 16×16 PTM for each (bond, color class) pair and noise scaling factor $\gamma \in \{1.0, 2.0, 3.0\}$ ($\gamma = 1.0$: hardware noise as measured; $\gamma = 2.0, 3.0$: amplified for MPF extrapolation). This single composed PTM is pre-computed per bond at build time, so runtime applies exactly one matrix–vector product per bond per Trotter step — the same cost as the noiseless simulation.

4 Autocorrelation and Chi Convergence

We initialize the Heisenberg-picture operator as Z at a single center site (site 13, a degree-3 junction at the graph midpoint) and I elsewhere. The autocorrelation $C(t) = \langle Z_c(t) Z_c(0) \rangle$ is computed via the Bethe approximation [2, 8] after each Trotter step. We study convergence with respect to the bond dimension χ by running nine simulations with $\chi \in \{50, 100, 150, 200, 250, 300, 350, 400, 430\}$ over 30 Trotter steps at Trotter step $\varepsilon = 0.25$ and cutoff 10^{-4}.




Figure 2: Autocorrelation $C(t) = \langle Z_c(t) Z_c(0) \rangle$ for $\chi = 50, 100, 150, 200, 250, 300, 350, 400, 430$ over 30 Trotter steps at $\varepsilon = 0.25$. The oscillatory behaviour is a genuine quantum recurrence of the XXX model on the finite heavy-hex graph. Curves for $\chi \geq 150$ are visually indistinguishable, indicating convergence.

Figure 2 shows $C(t)$ for $\chi = 50, 100, 150, 200, 250, 300, 350, 400, 430$ over 30 Trotter steps. The result converges to $\lesssim 10^{-4}$ at $\chi = 150$ and to 3×10^{-6} at $\chi = 400$ (reference $\chi = 430$), indicating that $\chi_{\max} = 200$ is sufficient for $|\text{error}| < 10^{-4}$ on this graph at 10 cycles.

The non-monotonic behaviour of $C(t)$ — a decrease followed by partial recovery — is a genuine quantum recurrence of the XXX model on the degree-3 lattice, confirmed by its independence from χ.

To put the MPF results of Section 6 in perspective: the gamma-MPF simulations use $\varepsilon = 0.1$, so 10 Trotter cycles correspond to physical time $T = 10 \times 0.1 = 1.0$, which maps to only 4 steps on the axis of Figure 2 (where $\varepsilon = 0.25$). The MPF operates entirely within the initial decay regime, well before the quantum recurrence sets in around step 10.

Figure 7 shows the non-identity Pauli weight $n(v, t)$ at each site for 20 cycles. The operator spreads radially outward from the center junction, following the 3-fold symmetry of the hexagonal lattice. The wavefront reaches the boundary sites by cycle 17, defining the computational window within which the simulation is exact regardless of χ truncation at the boundary.




Figure 3: Lightcone frontier analysis at $\chi = 70$, cutoff $= 10^{-3}$, $\varepsilon = 0.10$. *Left*: maximum non-identity Pauli weight $n(v, t)$ per distance shell (BFS distance from site 13) vs Trotter cycle — the spreading wavefront is visible as a propagating bright ridge. *Right*: frontier distance (furthest active shell, threshold 10^{-4}) vs cycle, with linear fit $v_{\text{hop}} = 0.244$ hops/cycle. The plateau at distance 6 (cycle 12) reflects χ truncation, consistent with the physical boundary at distance 3 hops giving ~ 12 faithful cycles.

$\chi_{\max}$	cutoff δ	v_{hop} (hops/cycle)	Notes
70	2×10^{-3}	0.419	artifact: χ saturates too early
70	10^{-3}	0.232	
70	5×10^{-4}	0.259	
70	2×10^{-4}	0.244	
200	10^{-3}	0.232	χ not bottleneck
200	5×10^{-4}	0.259	χ not bottleneck

Table 1: Lightcone frontier velocity v_{hop} sweep over $(\chi_{\max}, \delta)$ for the `heavy_hex_3x3` graph, $\varepsilon = 0.10$, $J = 1$, 20 cycles. Velocity converges to $v_{\text{hop}} = 0.245 \pm 0.015$ hops/cycle for $\delta \leq 10^{-3}$, independent of $\chi_{\max}$ — confirming that $\chi = 70$, $\delta^* = 10^{-3}$ is the faithful operating point.

Lightcone frontier calibration. The non-identity Pauli weight $n(v,t)$ provides a direct probe of the operator lightcone: site v is inside the lightcone at time t if $n(v,t) > 0$. We define the *frontier* as the maximum graph distance from the center at which $n(v,t) > \epsilon_{\text{th}}$ (threshold $\epsilon_{\text{th}} = 10^{-4}$). Figure 7 shows the frontier advancing approximately linearly, with a fitted velocity of $v_{\text{hop}} \approx 0.245$ hops/cycle at $\varepsilon = 0.10$ — corresponding to $v = v_{\text{hop}}/\varepsilon = 2.45$ hops per unit time.

We use the frontier velocity to calibrate the simulation parameters. A sweep over bond dimension $\chi \in \{70, 200\}$ and cutoff $\delta \in \{2 \times 10^{-3}, 10^{-3}, 5 \times 10^{-4}, 2 \times 10^{-4}\}$ reveals two key findings. First, v_{hop} converges to 0.245 ± 0.015 hops/cycle for $\delta \leq 10^{-3}$ — the *faithful cutoff* $\delta^* \approx 10^{-3}$. Second, increasing χ from 70 to 200 at fixed cutoff produces no change in v_{hop}, confirming that $\chi = 70$ is sufficient at δ^*.

The frontier plateaus at graph distance 6 by cycle 12, after which χ truncation prevents further tracking. The physical boundary of the `heavy_hex_3x3` graph (perimeter arm sites with a single junction neighbor) lies 3 hops from the center site, giving a faithful regime of $3/v_{\text{hop}} \approx 12$ cycles — consistent with the observed plateau. The full graph diameter (14 hops) would require ~ 57 cycles at $v_{\text{hop}} = 0.245$, accessible on a larger graph. Our 10-cycle MPF simulations lie within the faithful regime: cycles 1–10 are physically meaningful, and χ truncation effects become visible only after cycle 12.

5 Performance

We report wall-clock times on a 32 GB GPU using Householder QR decomposition (QR) and float32 arithmetic. All timings are per Trotter cycle at saturated bond dimension.

Table 2: Wall-clock time per cycle. GPU runs: χ capped at 430, float32, Householder QR, cutoff=10^{-4}. CPU: float64, no χ cap (grows freely to χ_{CPU}). Julia: GPU, noiseless evolution time only. '—': not measured.

Cycle	$\chi_{\max}$	CPU (s)	χ_{CPU}	Julia (s)	CppSim (s)	Speedup
2	14	9	14	29	0.1	290×
4	60	15	58	29	0.5	58×
6	165	201	202	38	1.9	20×
7	278	978	364	65	4.4	15×
8	430	4,393	637	132	12.3	11×
9	430	—	—	251	25.2	10×
10	430	—	—	418	46.9	9×

All runs saturate at their χ cap by cycle 7–9. The dominant cost is the Householder QR decomposition ($\mathcal{O}(mn^2)$ where $m = \chi^2 D$ for degree-3 sites), scaling approximately as χ^3. Table 1 compares wall-clock times at $\chi = 430$, cutoff=10^{-4}. Julia times report autocorrelation evolution only. At saturated bond dimension (cycles 8–10), CppSim achieves a consistent $\sim$10× speedup. At saturated bond dimension ($\chi = 430$, cycles 8–10), CppSim achieves a $\sim$10× speedup over the Julia/AMDGPU.jl reference implementation on the same GPU. Both use Householder QR and float32 arithmetic. The speedup arises from: (i) zero GPU memory allocation during simulation (pre-allocated workspace), (ii) direct HIP/rocBLAS calls without framework dispatch overhead, and (iii) on-device `pseudo_sqrt` kernel eliminating CPU–GPU transfers.

6 Multi-Product Formula Application

The gamma-MPF uses three noisy states at noise scaling factors $\gamma \in \{1.0, 2.0, 3.0\}$ with fixed Trotter step $\varepsilon = 0.1$, extrapolating to $\gamma = 0$ to recover the noise-free signal. The MPF extrapolation requires coefficients $\{c_i\}$ such that $C_{\text{mpf}}(t) = \sum_i c_i C_n(\gamma_i, t) \approx C_{\text{nl}}(t)$, with constraint $\sum_i c_i = 1$.




Figure 4: MPF error $|C_{\text{mpf}}(t) - C_{\text{nl}}(t)|$ (log scale) for gamma-MPF with $\chi = 200$, $\varepsilon = 0.1$, 20 Trotter cycles. Left: $|C_{\text{mpf}}(t)|$ vs $|C_{\text{nl}}|$ reference (dashed). Right: error comparison — poor man's MPF (red, correlation matrix) outperforms polynomial extrapolation (blue) by 2–3 orders of magnitude up to cycle 12. Band shows variation across all χ/cutoff values.

Rather than computing quantum inner products $\langle\psi_i|\psi_j\rangle$ (which requires solving a gauge-dependent cross-state contraction problem), we construct the coefficient matrix directly from the observable time series. We define the correlation matrix:

$$A_{ij} = \sum_t C_n(\gamma_i, t)\, C_n(\gamma_j, t), \qquad B_i = \sum_t C_n(\gamma_i, t)\, C_{\text{nl}}(t) \tag{3}$$

and solve $\min_{\mathbf{c}} \|A\mathbf{c} - \mathbf{B}\|^2$ subject to $\sum_i c_i = 1$. This *poor man's MPF* is gauge-invariant — it depends only on the autocorrelation $C(t)$, a physical observable — and requires no additional computation beyond the Trotter evolution already performed.

This formulation is also a natural scaffold for the full quantum inner product MPF: replacing A_{ij} with $\langle\psi_i|\psi_j\rangle$ recovers the complete formulation used in [6]. Below we describe the algorithm and block structure for computing these inner products efficiently on GPU.

Quantum inner product via double-layer belief propagation

The inner product between two Heisenberg-picture operator states $|\psi_a\rangle$ and $|\psi_b\rangle$ — both living on the heavy-hex graph as tensor networks with bond dimension χ — is computed by contracting a *double-layer* tensor network. At each site v, the single-layer site tensor $\psi_v[\mathbf{i}, d]$ (bond indices $\mathbf{i}$, Pauli index $d \in \{I, X, Y, Z\}$) becomes:

$$T_v[\mathbf{i}_a, \mathbf{i}_b] \;=\; \sum_{d=1}^{D} \psi_a[v, \mathbf{i}_a, d]\; \psi_b[v, \mathbf{i}_b, d] \tag{4}$$

where $\mathbf{i}_a$ and $\mathbf{i}_b$ are *independent* bond indices for the two layers: $i_{a,k} \in [0, \chi_{a,k})$ is determined by the bond dimension of $|\psi_a\rangle$, and $i_{b,k} \in [0, \chi_{b,k})$ by that of $|\psi_b\rangle$. These may differ — for cross-overlaps between the noiseless and noisy states, $\chi_{a,k} \neq \chi_{b,k}$ in general. Each bond $e \in E$ carries a $\chi_{a,e} \times \chi_{b,e}$ message matrix $M_e[i_a, i_b]$, and the inner product follows from the Bethe partition function:

$$\langle \psi_a | \psi_b \rangle \;\approx\; \frac{\prod_{v \in V} a_v}{\prod_{e \in E} z_e}, \qquad a_v = \sum_{\mathbf{i}_a, \mathbf{i}_b} T_v \prod_{e \in \partial v} M_e, \quad z_e = \sum_{i_a, i_b} M_e^{\rightarrow}[i_a, i_b]\, M_e^{\leftarrow}[i_a, i_b] \tag{5}$$

which is the BP approximation (exact on trees, approximate on the loopy graph G).

Message update without building T_v. Each bond e carries *two* directed messages: $M_e^{\rightarrow}[i_a, i_b]$ flowing from site a to site b, and $M_e^{\leftarrow}[i_a, i_b]$ in the reverse direction. Both are $\chi_{a,e} \times \chi_{b,e}$ matrices coupling the bond index of $|\psi_a\rangle$ to that of $|\psi_b\rangle$.

Initialization. Before any BP sweep, the messages are warm-started from the single-layer BP messages already computed during the Trotter step:

$$M_e^{(0)}[i_a,\, i_b] \;=\; \left|m_e^{(a)}[i_a]\right| \cdot \left|m_e^{(b)}[i_b]\right| \tag{6}$$

where $m_e^{(a)}$ and $m_e^{(b)}$ are the diagonal entries of the converged single-layer BP messages for $|\psi_a\rangle$ and $|\psi_b\rangle$ respectively. This rank-1 warm-start — a Kronecker product of the two single-layer diagonals — places BP in a good basin of attraction at zero additional cost. After convergence, M_e evolves to a general matrix of rank up to $\min(\chi_{a,e}, \chi_{b,e}, D)$.

Update rule. Constructing T_v explicitly costs $O(\chi^{2\deg})$ — for degree-3 junction sites this is $O(\chi^6)$, which is intractable at $\chi \gtrsim 10$. Instead, we contract M into ψ *before* forming the outer product, giving $O(\chi^3 D)$ per message update.

Consider a degree-2 (arm) site v with bonds k_0 and k_1. To update the outgoing message on bond k_0, we use only the *incoming* message from the other bond k_1 — BP never uses the current message of a bond to update itself. The update proceeds in two steps:

$$\phi_a[i_{a,0},\, j_{b,1},\, d] = \sum_{i_{a,1}} \psi_a[v,\, i_{a,0},\, i_{a,1},\, d] \cdot M_{k_1}[i_{a,1},\, j_{b,1}] \tag{7}$$

$$M_{k_0}^{\text{new}}[i_{a,0},\, i_{b,0}] = \sum_{j_{b,1},\, d} \phi_a[i_{a,0},\, j_{b,1},\, d] \cdot \psi_b[v,\, i_{b,0},\, j_{b,1},\, d] \tag{8}$$

Here $i_{a,k}$ denotes the bond-k index of state $|\psi_a\rangle$ and $j_{b,k}$ that of state $|\psi_b\rangle$ (e.g. $i_{a,0} \in [0, \chi_{a,0})$ for bond k_0 in $|\psi_a\rangle$, $j_{b,1} \in [0, \chi_{b,1})$ for bond k_1 in $|\psi_b\rangle$). Equation (7) absorbs the incoming message M_{k_1} into ψ_a by summing over $i_{a,1}$, producing an intermediate tensor ϕ_a of shape $[\chi_{a,0}, \chi_{b,1}, D]$. Equation (8) pairs ϕ_a with ψ_b by summing over the shared index $j_{b,1}$ and the Pauli index d, yielding the new outgoing message $M_{k_0}^{\text{new}}$ of shape $[\chi_{a,0}, \chi_{b,0}]$. The symmetric update for $M_{k_1}^{\text{new}}$ follows by swapping $k_0 \leftrightarrow k_1$. For degree-3 (junction) sites, two sequential contractions of the form (7) absorb the two incoming messages before the final step (8), keeping the cost at $O(\chi^3 D)$ throughout.

Matrix formulation. Both the message update and the Bethe PF reduce to standard matrix multiplications. We use the shorthand $\tilde{\Psi}_a \in \mathbb{R}^{\chi_{a,0} \times \chi_{a,1} D}$ for the site tensor $\psi_a[v, i_{a,0}, i_{a,1}, d]$ reshaped by treating the last bond index and Pauli index $d \in \{I, X, Y, Z\}$ jointly.

Degree-2 site (arm node, bonds k_0 and k_1; updating $M_{k_0}^{\text{new}}$ using incoming M_{k_1}):

$$\Phi_a = \tilde{\Psi}_a \cdot (M_{k_1} \otimes I_D) \;\in\; \mathbb{R}^{\chi_{a,0} \times \chi_{b,1} D} \quad \text{(GEMM, batched over } D\text{)} \tag{9}$$

$$M_{k_0}^{\text{new}} = \Phi_a \cdot \tilde{\Psi}_b^{\top} \;\in\; \mathbb{R}^{\chi_{a,0} \times \chi_{b,0}} \quad (D \text{ sequential GEMMs}) \tag{10}$$

Degree-3 site (junction, bonds k_0, k_1, k_2; updating $M_{k_0}^{\text{new}}$ using incoming M_{k_1} and M_{k_2}): same structure applied twice before the final step:

$$\Phi_a^{(1)} = \tilde{\Psi}_a^{[k_2]} \cdot (M_{k_2} \otimes I_D) \ \in \ \mathbb{R}^{\chi_{a,0}\chi_{a,1} \times \chi_{b,2} D} \tag{11}$$

$$\Phi_a^{(2)} = \Phi_a^{(1)[k_1]} \cdot (M_{k_1} \otimes I_D) \ \in \ \mathbb{R}^{\chi_{a,0} \times \chi_{b,1}\chi_{b,2} D} \tag{12}$$

$$M_{k_0}^{\text{new}} = \Phi_a^{(2)} \cdot \tilde{\Psi}_b^{\top} \ \in \ \mathbb{R}^{\chi_{a,0} \times \chi_{b,0}} \tag{13}$$

where $[\,\cdot\,]$ denotes a reshape placing that bond index outermost. Total cost: $O(\chi^3 D)$ for both degree-2 and degree-3. The formulation above was derived by formalising the implemented and validated GPU code (`test_blf_sgemm.cpp`); the equations describe exactly what the kernels compute.

Bethe partition function. The vertex and edge factors in (5) are computed by the same GEMM chain applied to *all* bonds:

$$a_v = \langle M_{k_0},\ \Phi_a^{\text{full}} \cdot (\tilde{\Psi}_b^{\text{full}})^{\top} \rangle_F \tag{14}$$

$$z_e = \langle M_e^{\rightarrow},\ M_e^{\leftarrow} \rangle_F \tag{15}$$

where $\langle \cdot, \cdot \rangle_F$ is the Frobenius inner product (one `sdot` call per bond). The Bethe PF costs the same as one message update per site — $O(\chi^3 D)$.

Two-GPU pipeline and timing. The 9 inner product pairs (A_{ij} and B_i) are independent and launched as concurrent streams on GPU 1, while GPU 0 runs the four-state Trotter step. The total cycle time is $t_{\text{cycle}} = \max(t_{\text{Trotter}}, t_{\text{IP}})$ (Fig. 4). Table 2 shows the measured breakdown: Trotter dominates from cycle 3 onward, so inner products add zero wall-clock overhead for the remainder of the simulation. At $\chi = 250$ (cycle 10): $t_{\text{Trotter}} \approx 80\,\text{s}$, $t_{\text{IP}} \approx 11\,\text{s}$ — inner products are 7× faster than Trotter. Compared to the Julia reference at 350 s per cycle, CppSim achieves a 4× improvement at the same bond dimension.




Figure 5: Per-cycle timing at $\chi_{\max} = 250$, 10 cycles. *Left*: MPF extrapolation — noiseless C_{nl} (black), poor man's MPF (red), inner product MPF (blue). *Right*: wall-clock breakdown. Black: total cycle time $t_{\text{cycle}} = \max(t_{\text{Trotter}}, t_{\text{IP}})$. Red: pure Trotter time (4 states, GPU 0). Blue: IP wall-clock (9 pairs, parallel streams, GPU 1). Green dashed: P2P upload overhead. Crossover at cycle 2–3: IP bottleneck early ($\chi \lesssim 41$), Trotter dominates thereafter.

Cycle	χ	t_{cycle} (s)	t_{Trotter} (s)	t_{IP} (s)
2	18	0.89	0.39	0.89
3	41	1.31	1.31	1.26
5	108	5.69	5.69	3.81
7	214	18.44	18.44	5.39
10	250	79.68	70.48	11.00

Table 3: Per-cycle wall-clock times at $\chi_{\max} = 250$, 10 cycles. $t_{\text{cycle}} = \max(t_{\text{Trotter}}, t_{\text{IP}})$. t_{Trotter}: GPU 0 Trotter time (4 states sequential). t_{IP}: GPU 1 wall-clock for all 9 inner products (parallel streams). Trotter dominates from cycle 3 — inner products add zero overhead.

Validation of inner product MPF. The inner product MPF (Fig. 4, left) exhibits a *consistent systematic bias*: the extrapolated curve follows the correct oscillation shape and recurrence structure of $C_{\text{nl}}(t)$, displaced by a roughly constant amplitude offset. This behaviour distinguishes a correct implementation with a gauge-dependent approximation error from a broken one — random scatter would indicate algorithmic failure. The double-layer BP on the loopy heavy-hex graph approximates the exact contraction, and the QR gauge introduces a reproducible bias in the Bethe partition function. The consistent bias confirms that the $O(\chi^3 D)$ GEMM-based inner product pipeline is correct; improving accuracy requires a better gauge (e.g. symmetric gauge) or loop corrections, not algorithmic changes.

Rank-1 message approximation. The double-layer message $M_k[i_{a,k}, i_{b,k}]$ couples bond k of state $|\psi_a\rangle$ to bond k of state $|\psi_b\rangle$. Note that the bond indices $i_{a,k}$ and $i_{b,k}$ belong to *different* states — the Kronecker product is across layers, not across bonds. If M_k is approximated as rank-1:

$$M_k[i_{a,k}, i_{b,k}] \;\approx\; u_k[i_{a,k}] \cdot v_k[i_{b,k}] \tag{16}$$

the two layers decouple completely. Each contraction in (7) separates into independent single-layer operations — $O(\chi^2 D)$ each — identical in structure to the autocorrelation computation (which is the special case $\chi_b = 1$, $v_k \equiv 1$). On a tree this rank-1 approximation is exact when messages have converged. On the loopy heavy-hex graph it is an additional approximation on top of BP, but the error is bounded by the same loop-correction terms that make plain BP approximate. The rank-1 vectors u_k, v_k are updated each sweep via the leading singular vectors of the full message matrix (16), extracted by power iteration at $O(\chi^2)$ cost. This approximation reduces the inner product cost to $O(\chi^2 D)$ per message update — the same order as autocorrelation — and is the natural next step toward a production GPU implementation.

Symmetric gauge: diagonal messages. The strongest simplification arises in the *symmetric gauge*, where the converged single-layer BP messages are absorbed into the site tensors as $\psi_a^{\surd} \leftarrow \sqrt{M_e}\,\psi_a$ for each incident bond. After this absorption the effective single-layer messages are identity, and the warm-start (6) gives $M_e^{(0)} = I$ — a diagonal matrix. Assuming BP converges back to diagonal matrices (which is forced to be true on a tree, and is an excellent approximation on the heavy-hex graph when the gauge is well-chosen), the message product in the vertex factor a_v is non-zero only when $i_{a,k} = i_{b,k}$ for every bond $k \in \partial v$. The double sum over $(\mathbf{i}_a, \mathbf{i}_b)$ collapses to a single sum:

$$a_v \;\approx\; \sum_{\mathbf{i},\,d} \psi_a^{\surd}[v, \mathbf{i}, d] \cdot \psi_b^{\surd}[v, \mathbf{i}, d], \tag{17}$$

which costs $O(\chi^{\deg} D)$ — identical to the autocorrelation evaluation. No BP sweeps are required and the $\chi \times \chi$ message matrices never appear explicitly. Implementing this gauge change on GPU 1 before the

Bethe PF evaluation would reduce the inner product cost from $O(\chi^3 D)$ to $O(\chi D)$, making the inner product pipeline faster than Trotter at all bond dimensions.




Figure 6: MPF error $|C_{\text{mpf}}(t) - C_{\text{nl}}(t)|$ vs cycle for $\chi_{\max} \in \{50, 100, 150, 200, 250\}$ and cutoff $\in \{2 \times 10^{-2}, 10^{-2}, 2 \times 10^{-3}, 10^{-3}, 10^{-4}\}$. Solid lines: poor man's MPF. Dashed lines: inner product MPF. *Poor man's MPF* shows significant variation across chi and cutoff — it genuinely improves with tighter approximation. *Inner product MPF* curves cluster tightly regardless of chi or cutoff — the error is gauge-limited, not compute-limited. Both methods show error growth at $\chi = 250$ cycle 10 where chi saturates and truncation error accumulates — a physics limit, not an MPF artifact.

The polynomial extrapolation is a Taylor approximation in γ, valid when the noise perturbation is small. As cycles accumulate, the noise effect grows and higher-order terms become significant, causing the polynomial fit to diverge. The poor man's MPF (correlation matrix) exploits the full temporal structure of the signal and outperforms the polynomial by 2–3 orders of magnitude up to cycle 12 (Fig. 3). The full 10-cycle gamma-MPF computation at $\chi = 70$ completes in under 5 s on a 32 GB GPU.

7 Conclusion

Our design maintains the original idea of being topology-agnostic: gate and belief propagation kernels require no modification; only a new grid class and Hamiltonian gate matrix are needed for the new geometry. To showcase different physics, we incorporate a fully parametric hardware noise model: each bond carries an independent 16×16 Pauli transfer matrix per color class, loaded from device characterization data and reduced into a single matrix–vector product per bond — at no additional runtime cost over the noiseless case. This approach captures bond interactions without assumptions on computation order, and is mathematically equivalent to sequential gate application.

Our goal is to provide a framework where physics can be expressed directly for GPU, maintaining the intuitive formulation of the Julia/AMDGPU.jl reference [5] while explicitly exploiting parallelism and performance. For quantum error mitigation via the gamma multi-product formula [6], CppSim completes 20 Trotter cycles in a fraction of the time of current implementations, enabling fast and systematic exploration of the parameter space.

The inner product quantities $F_{ij} = \langle\langle O|\Lambda_{\lambda_i}^T \Lambda_{\lambda_j}|O\rangle\rangle$ computed here are the central classical component of Lindblad Multiproduct Formula workflows [**?**, **?**], which combine two-dimensional tensor networks with loop-corrected belief propagation [8] and quantum hardware measurements to perform error mitigation on the heavy-hex lattice.

Future work proceeds along four interconnected directions. First, *loop corrections* to belief propagation [8]: plain BP on the loopy heavy-hex graph introduces a gauge-dependent bias in the Bethe partition




Figure 7: Pareto frontier: mean error (cycles 3–10) vs total compute time for all 25 (chi, cutoff) combinations. Filled markers: poor man's MPF. Open markers: inner product MPF. Shape encodes $\chi_{\max}$; color encodes cutoff. *The Pareto frontier is entirely dominated by poor man's MPF* — no inner product point achieves competitive accuracy at any compute budget. Poor man's MPF achieves mean error $\sim 3 \times 10^{-4}$ across the full compute range; inner product MPF stays at $\sim 5 \times 10^{-2}$, two orders of magnitude worse. The inner product points are vertically flat (insensitive to chi/cutoff), confirming that the error is set by the QR gauge approximation bias, not by approximation quality.

function; loop corrections make the inner product matrix F_{ij} better conditioned and bring it closer to the exact contraction. Second, the *symmetric gauge* for inner products: absorbing $\sqrt{M_e}$ into the site tensors makes the double-layer messages diagonal, collapsing the $O(\chi^3 D)$ GEMM chain to an $O(\chi D)$ dot product — identical in cost to autocorrelation — without any BP sweeps. This is essential for extension to degree-4 sites (rectangular 2D grids), where the current QR-gauge inner product cost is $\sim 450\times$ the Trotter cost. Third, *bond dimension extrapolation*: computing $F_{ij}(\chi)$ at multiple bond dimensions and extrapolating to $\epsilon_\chi \to 0$ via $\langle O \rangle = a \log(1 - \epsilon_\chi) + b$ provides both a calibrated estimate and a systematic error bar — replacing empirical chi convergence with a physically motivated criterion. Fourth, *ergodic amplification* as an alternative to noise amplification: perturbing the Hamiltonian parameter ε (ergodicity) rather than the noise rates γ gives smoother, better-conditioned coefficients and avoids the sampling overhead of probabilistic error amplification. We are also interested in extending the Pauli weight lightcone $n(v, t)$ to the noisy setting and applying the MPF correction spatially — recovering the noiseless lightcone frontier from noisy measurements, site by site.




Figure 8: Non-identity Pauli weight $n(v,t)$ at each site of the heavy_hex_3x3 graph over 20 Trotter steps, initialised at site 13 (mid-graph degree-3 junction). The operator spreads radially outward with 3-fold hexagonal symmetry, reaching the graph boundary by cycle $\sim$17. Color scale is per-panel normalized.

References

[1] C. Chamberland, G. Zhu, T. J. Yoder, J. B. Hertzberg, and A. W. Cross. Topological and subsystem codes on low-degree graphs with flag qubits. *PRX Quantum*, 2:030345, 2021.

[2] J. Tindall and M. Fishman. Gauging tensor networks with belief propagation. *SciPost Physics*, 15:222, 2023.

[3] J. Tindall, M. Fishman, E. M. Stoudenmire, and D. Sels. Efficient tensor network simulation of IBM's eagle kicked ising experiment. *PRX Quantum*, 5:010308, 2024.

[4] J. Tindall, A. Mello, M. Fishman, M. Stoudenmire, and D. Sels. Dynamics of disordered quantum systems with two- and three-dimensional tensor networks, 2025.

[5] M. S. Rudolph and J. Tindall. Simulating and sampling from quantum circuits with 2d tensor networks, 2025.

[6] G. H. Low, V. Kliuchnikov, and N. Wiebe. Well-conditioned multi-product formulas for hardware-friendly Hamiltonian simulation, 2019.

[7] Paolo D'Alberto. Gpu-first heisenberg-picture tensor network dynamics for the 2d transverse-field ising model, 2026.

[8] G. Evenbly, N. Pancotti, A. Milsted, J. Gray, and G. K.-L. Chan. Loop series expansions for tensor networks. *Physical Review Research*, 8:013245, 2026.